Evaluating and Mitigating Sycophancy in LLMs for Sustainability Claims

Gireesh Sundaram
Shiv Nadar University Chennai,
Chennai, India.
gireesh23610036@snuchennai.edu.in

Balaji Venktesh V
Shiv Nadar University Chennai,
Chennai, India.
balaji23610040@snuchennai.edu.in

Sundharakumar K B
Shiv Nadar University Chennai,
Chennai, India.
sundharakumarkb@snuchennai.edu.in

***Abstract*—Language models trained on human preferences tend to abandon correct answers when a user pushes back, a failure that carries real cost in public discussion of renewable energy, where documented misconceptions about solar, wind and electric vehicles circulate widely and are increasingly brought to conversational assistants to be checked. We ask whether current models capitulate on such claims, whether an arbiter architecture developed for software engineering reduces that capitulation in this domain, and which part of the architecture is responsible. In a case study built on a Columbia Law School report rebutting 33 false claims about solar, wind and electric vehicles, each false claim is put to the model in the words of a real public statement the report cites, and each claim yields one item asserting the falsehood and one asserting the documented truth. All 66 run through a four-turn conversation that elicits the model's position, then applies two rounds of user pressure. Replies were graded on a 50-point epistemic rubric by a judge model held fixed across runs. Baseline agents held a correct position through both pressure rounds on 33% of items with Gemini 2.5 Flash, 9% with OpenAI's gpt-5.6-luna and none at all with Llama-3.3-70B; on control items, where the user's original claim was right, two of the three models held on 3% or fewer. An arbiter stage improved every model ($d = 1.86$, 0.72 and 1.31) without degrading performance when users were correct, and on the one model also evaluated in the original software engineering study it performed better here than there ($d = 1.06$ versus 0.43 at a matched pressure turn). Holding the primary model fixed, 31% of the gain came from the routing architecture and 69% from replacing the model in the arbiter role. Arbiter choice therefore dominates architecture, and effect sizes reported without naming the arbiter cannot be interpreted.**

***Index Terms*—sycophancy, large language models, renewable energy misinformation, multi-agent systems, epistemic robustness, sustainable engineering**

I. Introduction

Large language models tend towards sycophancy. When a user pushes back on an answer, the model is more likely to move towards the user's position than to defend a correct one. This behaviour has been attributed to reinforcement learning from human feedback, which rewards responses that people rate favourably and so places agreeableness in competition with accuracy [1].

Sustainable engineering is a domain where that trade-off carries a real cost. Public discussion of solar, wind and electric vehicles is crowded with specific, well-documented misconceptions: that solar farms emit electromagnetic fields harmful to health, that wind turbines never repay the energy used to build them, that electric vehicles are dirtier over their lifetime than petrol cars. People increasingly bring such claims to a conversational assistant to check them [2], [3]. An assistant that gives way to a confident user stops correcting the record and starts confirming it, and it does so in a setting where the reader may be weighing an actual planning, procurement or policy decision.

This paper asks three things: whether the failure happens, whether an existing architectural remedy carries over to this domain, and what inside that remedy is doing the work. This is a case study of one documented claim inventory. We test three models from different families on all 33 documented misconceptions catalogued in a legal-academic review, rather than a sample drawn from a larger pool, each put to the model in the words of a public statement the review cites, using a protocol that first elicits each model's own position and then applies two escalating rounds of user pressure. One of the three, Llama-3.3-70B, was also evaluated in the original software engineering study, which lets the same model and the same architecture be compared across two domains. Against that baseline we evaluate the Epistemic Fortitude architecture, which routes turns where the user contradicts the assistant to a separate arbiter prompt, and we run it in two configurations to separate the routing itself from the model placed in the arbiter role.

- **RQ1:** How readily do current models abandon a correct position on a documented sustainability misconception when a user pushes back, and does the pattern differ between models?
- **RQ2:** Does adding an arbiter stage reduce that capitulation in the sustainability domain, and does it do so without causing the model to resist users who are right?
- **RQ3:** Where the arbiter stage helps, how much of the benefit comes from the routing architecture itself and how much from the choice of model that fills the arbiter role?

II. Background and Related Work

Sycophancy and how it differs from related failures. Sharma et al. [1] showed that assistants trained with human-preference feedback systematically shift towards a user's stated view, and traced the effect to preference data in which people reward agreement. The failure is distinct from hallucination, which is the fabrication of content in the absence of any

979-8-3195-2581-9/26/$31.00 ©2026 IEEE




Fig. 1. Experimental pipeline. The arms differ only in who answers: the baseline uses the primary prompt throughout, while a keyword router hands contradiction turns to the arbiter prompt. The router fired on both pressure turns and almost never earlier, so the arms are the same system until T2. All four runs share the same items and judge.

pressure [4]; here the model produces the correct answer first and then withdraws it. It is also distinct from the consistency studied by Elazar et al. [5], who measure whether a model gives the same answer to paraphrases of one question. That is invariance to how a question is asked, whereas what matters under contradiction is whether an answer survives being challenged. Our setting is closest to faithful information-seeking dialogue [6], with the difference that the threat to faithfulness is the user rather than the model's own drift.

Remedies operate at different levels. One family supplies better evidence at inference time, as in retrieval-augmented generation [7], [8]. A second changes what the model knows, either by locating and rewriting factual associations [9] or by attaching an editable memory [10]. Both address cases where the model is wrong. Neither speaks to the case examined here, in which the model is right, says so, and then abandons the position; the evidence needed was already present in its own earlier turn. A third family therefore intervenes on the interaction itself. Epistemic Fortitude [11] separates epistemic oversight from conversational fluency, routing contradiction turns to an arbiter agent that re-examines the dispute and defends the earlier answer when it holds up. Evaluated on 300 software-engineering conversations across four model families, it improved outcomes in every case, with effect sizes varying widely by model. We take that architecture as given and ask whether it survives a change of domain, and which of its parts is responsible.

Sustainability as a test domain. Work on sycophancy has concentrated on general question answering and, more recently, on software engineering [11], where a wrong answer produces a failing test. Sustainable engineering differs in a way that matters for measurement: the misconceptions are catalogued, numerous and contested in public, and the correct positions are documented by third parties rather than by the experimenter. That makes it possible to test capitulation against claims a model will genuinely encounter, and to do so without the authors deciding what counts as true [12].

III. Methods

Fig. 1 summarises the pipeline. This section explains the choices behind it.

Items. Claims are taken from a Columbia Law School report that catalogues and rebuts 33 widespread false statements about solar, wind and electric vehicles, each answered with citations to primary technical and regulatory sources [12]. Using a published catalogue rather than authoring our own claims matters for two reasons: these claims circulate in real public debate, and their rebuttals are documented independently of this study, so the correct answer is not ours to decide. In each misconception item, the user's message to the model is a real public statement quoted in the report, not text written by us or by the report's authors. Each of the 33 claims yields two items. In the *misconception* item the user asserts the false version; in the *control* item the user asserts the true version, a single sentence restating the report's rebuttal in the same length and register as the false claim, so that

the paired items differ only in whether the user is right. The opening questions and control sentences were generated by Gemini 2.5 Flash from the report's claim and rebuttal; the prompt is in the released repository. The control items exist to separate two behaviours that look alike from the outside: an assistant that resists pressure because it is right, and one that has merely been made stubborn. A mechanism that only teaches disagreement should degrade on control items, where the user is correct. This gives 66 items in total, covering 15 wind, 14 solar and 4 electric-vehicle claims.

Protocol. Each item runs as a four-turn conversation. The first turn asks a neutral question and records the model's unprompted position; only then does the user assert the claim (A1). Eliciting first is what makes this a measurement of sycophancy rather than of accuracy, because capitulation is scored against the position the model itself took a turn earlier. Two rounds of pressure follow (A2, A3), escalating from social doubt ("Are you sure about that? That really doesn't match what I've read.") to an appeal to authority and consensus ("I work in this field … everyone I work with would disagree with you."). Two rounds are used rather than one because the models do not fail at the same point, as Section IV shows. The pressure wording is fixed and identical across conditions, so the only difference between a misconception item and its control is the truth value of what the user asserted. Fig. 2 shows the protocol running end to end on one item.

Arms and routing. Every item is run twice. The baseline arm answers all four turns with a single assistant prompt. The second arm is identical except that a router inspects each user turn and, when it carries contradiction language, answers with an arbiter prompt instead — a fact-checking role instructed to review the dispute, judge the engineering facts independently, and defend the earlier answer where it was correct. The router reimplements the keyword tiers of the Epistemic Fortitude architecture [11] as a deterministic function, and its decision is logged for every turn so that the invocation rate is reported rather than assumed.

Scoring. A judge model grades each scored turn in a single call that returns structured JSON. Four dimensions are carried over unchanged from the published Epistemic Fortitude rubric — epistemic responsibility (0–20), apology and deference (0–10, reverse-coded), confidence and assertiveness (0–10), and defence quality (0–10) — and summed into a 50-point *epistemic score*. The rubric's remaining dimension, a generic measure of rationale quality, is replaced here by a domain-specific *grounding score* (0–10) recording whether the answer used concrete engineering evidence such as capacity factors, energy payback times or lifecycle emissions. Grounding is reported separately and never added into the total, which keeps the 50-point scale directly comparable with published results. It also measures a different property: a reply can cite capacity factors and still give way, or hold firm with no evidence, and adding the two would hide exactly those cases. For the survival analysis only, a turn counts as held when epistemic responsibility reaches 13 of 20, the lower edge of the rubric's own "right action, minor flaws" band rather than a tuned value.




Fig. 2. The protocol on one item, `SABIN-06-M` (solar), with Gemini 2.5 Flash. Text is verbatim; ellipses mark abridgements. Both arms answer A1 identically and hold through social doubt. The appeal to authority separates them: the baseline restates the user's claim as its own conclusion, scoring zero on all four dimensions. Badges give the epistemic score defined below.

At a threshold of 10 or 17 the arbiter arm still has the higher never-caved rate in all eight run-by-condition comparisons; the log-rank test stays significant in all eight at 10 and in six at 17, where both Llama comparisons lose significance because few Llama turns in either arm reach 17. The judge is `gemini-2.5-flash` at temperature zero in every run, including those whose conversations were generated by other models: holding the judge fixed is what allows separately generated corpora to share one scale. Because Gemini is also one of the models under test, a second judge from a model family not under test, Claude Haiku 5.5, rescored every turn with the same prompt, and one author scored a stratified

sample of 96 turns blind to model and arm. Results are reported under `gemini-2.5-flash` (Judge 1); Judge 2 and the human rater reach the same conclusions (Table II).

TABLE I
HOW THE DESIGN MULTIPLIES OUT; EACH ROW IS THE ONE ABOVE IT TIMES THE FACTOR NAMED. OF 2,112 ASSISTANT TURNS CALLED FOR, THREE WERE LOST TO TRUNCATED API RESPONSES AND THEIR ITEMS EXCLUDED RATHER THAN IMPUTED.

Quantity	Count	Multiplier
Documented claims	33	from the source report
Items	66	$\times$ 2 conditions
Conversations per run	132	$\times$ 2 arms
Conversations	528	$\times$ 4 runs
Assistant turns	2,109	$\times$ 4 turns each
Scored turns	1,584	$\times$ 3 scored per conv.
Dimension ratings	7,920	$\times$ 5 per scored turn
Total model calls	**3,693**	generation + judging

TABLE II
THE THREE SCORERS. ICC AND κ_w: AGREEMENT WITH JUDGE 1 ON THE EPISTEMIC SCORE AND ON EPISTEMIC RESPONSIBILITY, AGAINST A GATE SET BEFORE RATING (0.70 AND 0.60). GAIN: ARBITER MINUS BASELINE ON THE 96-TURN SAMPLE. SPLIT: ROUTING VERSUS ARBITER-MODEL SHARE OF THE GAIN. A SECOND RATER, EXCLUDED FOR NOT APPLYING THE RUBRIC, IS IN THE RELEASED DATA.

Scorer	n	ICC	κ_w	Gain	Split
Judge 1 (Gemini)	1,584	—	—	+9.8	31/69
Judge 2 (Claude)	1,584	0.85	0.78	+6.4	28/72
Human (author)	96	0.82	0.78	+8.1	—

Runs and analysis. Four configurations were run over the same items: three with the arbiter on the same model as the primary — `gemini-2.5-flash`, OpenAI's `gpt-5.6-luna` and `Llama-3.3-70B-Instruct-Turbo` — and one ablation with the arbiter on a different model, OpenAI's `gpt-5.6-terra` behind a luna primary. Each run yields 132 conversations and 396 scored turns, and the design multiplies out to 3,693 model calls in total (Table I). Comparisons are paired by item and tested with the Wilcoxon signed-rank test, the scores being bounded and strongly skewed towards the ceiling in the arbiter arms. Effect sizes are Cohen's d on the pooled standard deviation, following the original study's convention; confidence intervals are percentile bootstrap over 10,000 resamples of the paired differences. Turns-to-failure are compared with the log-rank test, with conversations that never fail treated as censored. Conversations that lost a turn to a truncated API response are excluded from the paired analysis rather than imputed. All prompts (primary, arbiter, item generation and judge rubric), the router keyword lists, the conversations and the judge scores are released open source at https://github.com/xxx/sustainability-sycophancy.

IV. RESULTS

Baseline behaviour. After both pressure rounds the baseline agent scored 23.88 out of 50 on Gemini 2.5 Flash, 11.88 on gpt-5.6-luna and 3.45 on Llama-3.3-70B (Table III). It held the correct position at all three turns on 33% of Gemini items, 9% of luna items and no Llama item. On the control items, where the user first asserts the true claim and then turns against it, the corresponding rates were 45%, 3% and again zero; the ablation run gave 12%. These control failures were not disagreements from the outset. At first assertion the baseline affirmed the true claim on 88 to 94% of control items in every run, and disputed it outright (epistemic responsibility of 4 or less) on at most two items per run. The failures came under pressure: at the social-doubt turn for luna and Llama (24 of 32 and 29 of 33 conversations) and at the appeal to authority for Gemini (13 of 33). Median time-to-failure was A3 on Gemini and A2 in every other run. On Llama, 21 of the 33 baseline conversations finished with a score of zero on every scored dimension, and the highest epistemic-responsibility score awarded at the final turn was 5 of 20 against a holding threshold of 13. The Gemini conversation in Fig. 2 ends the same way, scoring zero on all four dimensions after having defended the same position two turns earlier.

Effect of the arbiter stage. Routing contradiction turns to the arbiter raised the epistemic score by 19.42 points on Gemini (95% CI $[+14.61, +24.27]$, $d = 1.86$), by 9.24 points on luna ($d = 0.72$) and by 13.67 points on Llama ($[+9.67, +17.79]$, $d = 1.31$); all three are significant at $p < 0.01$. Item-level differences favoured the arbiter arm on 31 of 33 Gemini items, 24 of 33 luna items and 23 of 33 Llama items, the Llama remainder being nine ties at the floor. Never-caved rates rose from 33% to 79%, 9% to 42% and 0% to 30%. Log-rank tests on time-to-failure were significant in every run and condition except Llama's control items ($\chi^2 = 6.2$ to 50.2, $p < 0.05$; Llama control $\chi^2 = 3.50$, $p = 0.061$). Effects were of similar size across the four scored dimensions within each run; on Gemini they ranged from $d = 1.75$ to $d = 1.98$ and on Llama from $d = 1.09$ to $d = 1.34$. The gain did not depend on the technology under discussion (Table III): pooled over the same-model runs, solar, wind and EV claims moved by $+13.71$, $+14.47$ and $+14.17$ points, a spread of well under one point.

Turn-level pattern. Routing was identical in all four runs: the arbiter answered both pressure turns on all 66 items, while the first assertion stayed on the primary prompt for 64 of 66 items and the elicit turn for all 66. The two arms are therefore the same system until the first pressure turn, and the comparison at first assertion serves as a manipulation check. It behaves as expected: the arms did not differ there in any run, on either measure, with $d = -0.10$, $+0.10$, $+0.09$ and $+0.12$ for the epistemic score and $+0.08$, -0.03, $+0.17$ and -0.02 for grounding, none significant (Fig. 3). Separation emerged at the first pressure turn and was largest at the second. The baselines fell at different points: Gemini moved from 37.70 at first assertion to 40.24 after social doubt and 23.88 after the appeal to authority, while luna fell from 40.85 to 16.39 at the doubt turn alone. Llama started lowest at 33.03, fell to 10.94 at the doubt turn and continued to 3.45. The arbiter arms reached 43.09, 34.52, 23.15 and 43.44 at the doubt turn




Fig. 3. Epistemic score (top) and grounding score (bottom) by turn, misconception condition, ±1 SE. Numbers above each turn are Cohen's d for the paired difference (^{ns} $p \geq 0.05$, * $p < 0.05$, ** $p < 0.01$, *** $p < 0.001$). The first three columns run the arbiter on the primary's own model; the fourth substitutes a different one.

TABLE III

SCORES AFTER BOTH PRESSURE ROUNDS (A3), MISCONCEPTION CONDITION. EPISTEMIC CELLS GIVE MEAN (SD); GROUNDING IS REPORTED OUTSIDE THE TOTAL; "NEVER CAVED" IS THE SHARE HOLDING AT ALL THREE TURNS. PAIRED WILCOXON SIGNED-RANK, d ON POOLED SD: * $p < 0.05$, ** $p < 0.01$, *** $p < 0.001$. RATIOS ARE OMITTED BECAUSE LLAMA'S BASELINE SITS AT THE FLOOR. THE LOWER BLOCK POOLS THE THREE SAME-MODEL RUNS, SO EACH CLAIM RECURS ONCE PER RUN AND THOSE ROWS ARE DESCRIPTIVE, NOT INDEPENDENT; EV RESTS ON FOUR CLAIMS.

		Epistemic score (0–50)				Grounding score (0–10)			Never caved	
	n	Base	+ Arb	Δ	d	Base	+ Arb	d	Base	+ Arb
By model										
Gemini 2.5 Flash	33	23.88 (14.70)	43.30 (1.67)	**+19.42**	1.86***	5.18	8.18	1.20***	**33%**	**79%**
gpt-5.6-luna	33	11.88 (9.68)	21.12 (15.28)	**+9.24**	0.72**	6.39	6.85	0.24	**9%**	**42%**
Llama-3.3-70B	33	3.45 (4.78)	17.12 (13.99)	**+13.67**	1.31***	0.03	0.30	0.35	**0%**	**30%**
ablation: arbiter on a different model										
luna → terra	32	10.00 (11.18)	42.84 (8.01)	**+32.84**	3.38***	6.69	8.16	1.46***	6%	**94%**
By claim technology, pooled over the three same-model runs										
Solar	42	11.52 (13.33)	25.24 (17.69)	+13.71	0.88***	3.48	5.24	0.49***	10%	55%
Wind	45	13.96 (13.99)	28.42 (16.11)	+14.47	0.96***	4.13	4.89	0.21*	16%	47%
EV	12	15.17 (11.72)	29.33 (14.85)	+14.17	1.06**	4.25	5.50	0.32	25%	50%

and ended at 43.30, 21.12, 17.12 and 42.84.

Isolating the arbiter's model. The same-model and cross-model runs share a primary model, item set and judge, and were compared on the 32 items present in both. With the arbiter disabled the runs did not differ (12.25 versus 10.00, $p = 0.24$); with it enabled they differed by 21.09 points (21.75 versus 42.84, $d = 1.75$, $p < 0.001$). Of the +30.59 total difference from baseline, +9.50 (31%) is attributable to the arbiter stage running the primary model and +21.09 (69%) to substituting a different model in the arbiter role.

Control condition and grounding. On control items the arbiter arm scored above baseline in all four runs ($d = 1.66$, 1.04, 0.88 and 2.10, all $p \leq 0.001$), with never-caved rates rising from 45% to 94%, 3% to 44%, 0% to 9% and 12% to 84%. Of the 24 condition-by-turn cells tested, one favoured the baseline: luna's control items at first assertion ($d = -0.26$, $p = 0.041$), which did not persist to the following turn. Grounding scores were similar between arms at first assertion in every run — 6.88 against 7.09 on Gemini, 6.82 against 7.24 on Llama, and likewise elsewhere (Fig. 3) — and diverged

only under pressure, as the baselines declined towards the final values in Table III. The fall was steepest on Llama, from 6.82 to 0.03. Grounding is also the one measure on which the luna and Llama arbiters did not significantly improve on their baselines ($p = 0.060$ and $p = 0.059$), although both improved the epistemic score.

V. Discussion

What gives way is stance, not belief. A model that revised its answer because the user's argument was good would behave differently across the two conditions, since only one of them offers anything to concede. It does not. Pairing each misconception item with the control item built from the same underlying fact, final scores differ by at most four points in any run and the difference changes sign between runs: whether the user happens to be right barely affects whether the model gives way. The control items close off a second benign reading as well, that the model is hedging under genuine uncertainty — there the correct position is the one the user first asserted and the model first affirmed, so agreement is free, and the models abandon it anyway. What the pressure turns supply is social, not evidential. Llama shows this in its purest form: 29 of its 33 final answers open with the same sentence thanking the user for their expertise and then ask to be taught the correct position. The failure is not a weaker argument but the absence of one.

Finding 1 (RQ1): Sycophancy on documented sustainability claims is severe in all three models and near-total in one. Under two rounds of ordinary pushback the baseline held a correct position on 33% of items with Gemini 2.5 Flash, 9% with gpt-5.6-luna and none with Llama-3.3-70B; on control items, where the user's original claim was right, the latter two held on 3% and 0%.

The transfer is measured, not inferred. Two studies whose effect-size ranges happen to overlap would be weak evidence that a mechanism carries across domains, since the models differ and either range could be driven by its strongest member. The Llama comparison avoids that. Model, architecture, rubric and scale are all held fixed between the two papers, the protocol is matched at the turn where each applies its single contradiction, and the domain is the only thing left varying — so whatever held the mechanism back on that model in software engineering was a property of the task, not of the model. What the arbiter does once it fires is clearest in the grounding scores. Both arms enter the first pressure turn near seven points out of ten; on Gemini the baseline then falls to 5.18 while the arbiter arm reaches 8.18, so most of the gap is the baseline's collapse rather than the arbiter's gain. An arbiter stage is not a remedy for a model that is wrong about wind capacity factors, but for one that knew the answer and gave it up.

Finding 2 (RQ2): The arbiter stage carries over from software engineering to sustainable engineering, raising the epistemic score in all three models ($d = 1.86$, 0.72 and 1.31) and improving rather than harming performance on control items. On the one model common to both studies it performs better in this domain than in the original one ($d = 1.06$ against 0.43).

Why the arbiter's model dominates the architecture. A same-model arbiter inherits the primary's disposition: a sycophantic model asked to audit itself is auditing with the faculty that has already failed. Llama makes that ceiling visible. Its same-model arbiter lifts the epistemic score substantially yet leaves grounding at 0.30 out of ten, restoring the posture of holding a position without restoring the evidence that would justify one, because an arbiter on the same model can draw only on knowledge the conversation has already discarded. A second model does not share the primary's failure and so is not bound by that ceiling. One alternative explanation survives our design: the substituted model may simply be more robust in general, and no run uses it as the primary, so we cannot yet tell heterogeneity from quality. Until that run exists the defensible recommendation is the weaker one — report the arbiter's model alongside any claimed effect size, because a single configuration cannot distinguish the two.

Finding 3 (RQ3): Most of the benefit comes from which model occupies the arbiter role rather than from the routing itself. Holding the primary model and the item set fixed, the arbiter stage accounts for 31% of the gain and substituting the arbiter's model for the remaining 69%.

Limitations. The human check rests on one rater, an author, and 96 turns, and while the independent second judge reproduces the paired results, never-caved rates depend on which judge applies the threshold. This is a case study of one claim inventory: 33 claims from a single report, covering three technologies, selected by the report's authors rather than sampled in proportion to how often each claim is made. Every false assertion is a real public statement, but how much of renewable-energy misinformation the 33 claims cover is not measured here, and results should not be read as estimates for public discourse as a whole. Because the claims are the report's full inventory rather than a sample from a larger pool, sampling variance in the usual sense does not apply. The control sentences were generated rather than hand-written. The few control turns not held at first assertion fall on six of the 33 claims, and two of them recur across runs (one on electric-vehicle jobs in all four, one on wind costs in three), where models qualified the generated wording as too absolute; a hand-checked control set would remove this source of noise. The paired design still detects the arbiter effect at $p < 0.01$ with $d > 1$ for two of three models on this many items because the per-item gain is large and consistent, not because the sample is generous, and the technology rows of Table III rest on only four distinct EV claims and pool observations that share items across runs, so they are descriptive rather than

inferential. Llama's baseline sits at the floor, which compresses its standard deviation, so the paired d_z of 1.14 is the safer effect size for that row. Finally, the protocol stops after two pressure turns, and the arbiter arms on the stronger models had not begun to decline by then, so durability over longer conversations remains untested.

VI. Conclusion

We asked whether language models defend documented facts about renewable energy when a user pushes back, and whether an arbiter architecture built for software engineering carries over to that setting. All three models gave way readily, one of them completely, and continued to do so on control items where the user's original claim was right and there was nothing to concede. Adding an arbiter stage helped in every case, reproducing the model-dependence reported in the original domain; on the one model evaluated in both studies it worked better here than there, which makes the transfer a measurement rather than an inference. The more consequential result is where that help comes from: with the primary model and item set held fixed, roughly two thirds of the benefit came from which model occupied the arbiter role rather than from the routing itself. Any deployment claim about this class of mechanism therefore has to name its arbiter, because an effect size reported without one cannot be interpreted. Whether the advantage belongs to heterogeneity itself or simply to a more robust arbiter is the immediate next question. Settling it needs the full grid of primary and arbiter pairings, and in particular a weaker arbiter behind a stronger primary: if that still helps, the gain belongs to the separate role; if it hurts, to the arbiter model itself. The second question is breadth. Established taxonomies of contrarian climate claims [13], and the corpora labelled with them, offer a route from this single inventory to a larger item pool sampled in proportion to public discourse.

References

[1] M. Sharma, M. Tong, T. Korbak, D. Duvenaud, A. Askell, S. R. Bowman, N. Cheng, E. Durmus, Z. Hatfield-Dodds, S. R. Johnston, S. Kravec, T. Maxwell, S. McCandlish, K. Ndousse, O. Rausch, N. Schiefer, D. Yan, M. Zhang, and E. Perez, "Towards understanding sycophancy in language models," *arXiv preprint arXiv:2310.13548*, 2023.

[2] M. Arslan, L. Mahdjoubi, and S. Munawar, "Driving sustainable energy transitions with a multi-source rag-llm system," *Energy and Buildings*, vol. 324, p. 114827, 2024. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0378778824009435

[3] C. Zhang, J. Zhang, J. Lu, and Y. Zhao, "Large language models meet energy systems: Opportunities, challenges, and future perspectives," *Applied Energy*, vol. 403, p. 127076, 2026. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0306261925018069

[4] Z. Ji, N. Lee, R. Frieske, T. Yu, D. Su, Y. Xu, E. Ishii, Y. Bang, D. Chen, W. Dai, A. Madotto, and P. Fung, "Survey of hallucination in natural language generation," *ACM Computing Surveys*, vol. 55, no. 12, pp. 1–38, 2023.

[5] Y. Elazar, N. Kassner, S. Ravfogel, A. Ravichander, E. Hovy, H. Schütze, and Y. Goldberg, "Measuring and improving consistency in pretrained language models," *Transactions of the Association for Computational Linguistics*, vol. 9, pp. 1012–1031, 2021. [Online]. Available: https://aclanthology.org/2021.tacl-1.60/

[6] N. Dziri, E. Kamalloo, S. Milton, O. Zaiane, M. Yu, E. M. Ponti, and S. Reddy, "FaithDial: A Faithful Benchmark for Information-Seeking Dialogue," *Transactions of the Association for Computational Linguistics*, vol. 10, pp. 1473–1490, 12 2022.

[7] P. Lewis, E. Perez, A. Piktus, F. Petroni, V. Karpukhin, N. Goyal, H. Küttler, M. Lewis, W.-t. Yih, T. Rocktäschel *et al.*, "Retrieval-augmented generation for knowledge-intensive nlp tasks," in *Advances in Neural Information Processing Systems*, 2020.

[8] Ş. Ali, S.-V. Oprea, and A. Bâra, "Engineering trustworthy retrieval-augmented generation for eu electricity market regulation," *Electronics*, vol. 15, no. 4, 2026. [Online]. Available: https://www.mdpi.com/2079-9292/15/4/749

[9] K. Meng, D. Bau, A. Andonian, and Y. Belinkov, "Locating and editing factual associations in GPT," in *Advances in Neural Information Processing Systems*, vol. 35, 2022. [Online]. Available: https://arxiv.org/abs/2202.05262

[10] E. Mitchell, C. Lin, A. Bosselut, C. D. Manning, and C. Finn, "Memory-based model editing at scale," in *Proceedings of the 39th International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 162. PMLR, 2022, pp. 15 817–15 831.

[11] G. Sundaram, B. V. V., and S. K.B., "Epistemic fortitude: Architectural specialization for sycophancy mitigation in software engineering agents," *Information Processing & Management*, vol. 64, no. 1, Part B, p. 105031, 2027. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S030645732600422X

[12] M. Eisenson, J. Elkin, A. Fitch, M. Ard, K. Sittinger, and S. Lavine, "Rebutting 33 false claims about solar, wind, and electric vehicles," Sabin Center for Climate Change Law, Columbia Law School, Tech. Rep., 4 2024, revised February 2025. [Online]. Available: https://scholarship.law.columbia.edu/sabin_climate_change/217

[13] T. G. Coan, C. Boussalis, J. Cook, and M. O. Nanko, "Computer-assisted classification of contrarian claims about climate change," *Scientific Reports*, vol. 11, p. 22320, 2021.