

Topside / In Vehicle Connector Pinout

SubConn Connector	Pin Role	SubConn Pin No.	Wire Base Color	Wire Stripe Color	Topside Interface Connector
MCIL8F	Main Power V+ 1 (VIN1)	1	Black		Bare Lead or 2 pin connector (Microfit 3.0)
MCIL8F	Main Power V+ 2 (VIN2)	2	White		Bare Lead or 2 pin connector (Microfit 3.0)
MCIL8F	Main Power GND (VIN-)	3	Red		Bare Lead or 2 pin connector (Microfit 3.0)
MCIL8F	Arduino RX (Swapped from downstream TX)	4	Green		To DB9 Serial > RS232 to USB converter > Computer
MCIL8F	Arduino TX (swapped from downstream RX)	5	Orange		To DB9 Serial > RS232 to USB converter > Computer
MCIL8F	RGA RX (Swapped from downstream TX)	6	Blue		To DB9 Serial with 'fake-handshake' null modem > RS232 to USB converter > Computer
MCIL8F	RGA TX (Swapped from downstream RX)	7	White	Black	To DB9 Serial with 'fake-handshake' null modem > RS232 to USB converter > Computer
MCIL8F	Communication GND (shared)	8	Red	Black	Bare Lead or 2 pin connector (Microfit 3.0)