Hal25

setup and Configure a LAN

Sotup and Configure a LAN (Local vorea Network) wing a smith and etternt Cables is your lab.

what is LAN?

A Local Area Notwork (LAN) My to a natural that connected desires with a limited onen such as an office hilling, school or home. It curales unto share revouves, irelading data, printers round want terner NAJ - Erosa tireti to premote collaboration out transfor ifornation between wars, such as computers, computers, estudies e thing.

How to vetup a LAN?

Step 1: Plan and design on appropriate network toplogy taking into account hetwork requirements and equipment location. step 2: You can toke A Computer , a existed with a 16 or 24 posts with is sufficient for networks of their sizes allow

Step 3: Consect you computers: the hatwark the estimate calles when the street calle which is as simple as property are set of the streets attempts. Calles into your computer attempts. and the other end into retrook de de la companya della companya de la companya della companya del

Step 4: Serign IP address to your PCs I happen to the elect computer as Administration on as evener.

2. Olik retrock and interest correction 3. Right dick Loral Area Constint theret

PCI -IP addres: 10.1.1.1 subsit mark 255.0.0.0

PC2-IP address: 10.1.1.2 Juliet mark 255.0.0.0

PC3 - IP addres: 10.1-1.3 subset mosk 255.0.0.0

R4 - IP addres: 10.1.1.4 subst mark 259-0.0.0

devilestip 5-12/2/2/2012 decit Switch to access the swinth is the suiterface, you will need to consider the suiterface of the suiter and suiterface of the suiter and suiterface of the suiter and suiterface of the suiterface 279 Logista the sitesforiet got? to By Configure Staric sitting. 4. Assign IP oddses as 10.1.1.15 Step 7: Select a folder of to prepartion of the order it with everyone or the Jame LAN. step 8: Tay to acress the shored follow trouted att for retugner rette made tolder 8:14:01 ments to 90- 879 concerts too time + hd-obs ments so so - 1 8-0.0.80 alroy []

