AMRITA
VISHWA VIDYAPEETHAM
DEEMED TO BE UNIVERSITY

22AIE204
COMPUTER NETWORKS

NETWORK LAYER

- Routing Vs Forwarding
- IP Fragmentation
- DHCP
- NAT

Network layer

- transport segment from sending to receiving host
- on sending side encapsulates segments into datagrams
- on receiving side, delivers segments to transport layer
- network layer protocols in *every* host, router
- router examines header fields in all IP datagrams passing through it



Two key network-layer functions

- *forwarding:* move packets from router's input to appropriate router output
- *routing:* determine route taken by packets from source to dest.
  - *routing algorithms*

analogy:

- *routing:* process of planning trip from source to dest
- *forwarding:* process of getting through single interchange

Interplay between routing and forwarding



routing algorithm determines end-end-path through network

forwarding table determines local forwarding at this router

Chapter 4: outline

4.1 introduction

4.2 virtual circuit and datagram networks

4.3 what's inside a router

4.4 IP: Internet Protocol
- datagram format
- IPv4 addressing
- ICMP
- IPv6

4.5 routing algorithms
- link state
- distance vector
- hierarchical routing

4.6 routing in the Internet
- RIP
- OSPF
- BGP

4.7 broadcast and multicast routing

Connection, connection-less service

- *datagram* network provides network-layer *connectionless* service
- *virtual-circuit* network provides network-layer *connection* service
- analogous to TCP/UDP connecton-oriented / connectionless transport-layer services, but:
  - *service:* host-to-host
  - *no choice:* network provides one or the other
  - *implementation:* in network core

Virtual circuits: signaling protocols

used to setup, maintain teardown VC
used in ATM, frame-relay, X.25
not used in today's Internet



Datagram networks

no call setup at network layer

routers: no state about end-to-end connections

- no network-level concept of "connection"

packets forwarded using destination host address



Datagram forwarding table



4 billion IP addresses, so rather than list individual destination address list *range* of addresses (aggregate table entries)

Datagram forwarding table

Destination Address Range	Link Interface
11001000 00010111 00010000 00000000 through 11001000 00010111 00010111 11111111	0
11001000 00010111 00011000 00000000 through 11001000 00010111 00011000 11111111	1
11001000 00010111 00011001 00000000 through 11001000 00010111 00011111 11111111	2
otherwise	3

Q: but what happens if ranges don't divide up so nicely?

Longest prefix matching

longest prefix matching

when looking for forwarding table entry for given destination address, use *longest* address prefix that matches destination address.

Destination Address Range	Link interface
11001000 00010111 00010*** *********	0
11001000 00010111 00011000 *********	1
11001000 00010111 00011*** *********	2
otherwise	3

examples:

DA: 11001000 00010111 00010110 10100001 which interface?

DA: 11001000 00010111 00011000 10101010 which interface?

Chapter 4: outline

4.1 introduction

4.2 virtual circuit and datagram networks

4.3 what's inside a router

4.4 IP: Internet Protocol
- datagram format
- IPv4 addressing
- ICMP
- IPv6

4.5 routing algorithms
- link state
- distance vector
- hierarchical routing

4.6 routing in the Internet
- RIP
- OSPF
- BGP

4.7 broadcast and multicast routing

Router architecture overview

two key router functions:

- run routing algorithms/protocol (RIP, OSPF, BGP)
- *forwarding* datagrams from incoming to outgoing link



Chapter 4: outline

4.1 introduction

4.2 virtual circuit and datagram networks

4.3 what's inside a router

4.4 IP: Internet Protocol

- datagram format
- IPv4 addressing
- ICMP
- IPv6

4.5 routing algorithms

- link state
- distance vector
- hierarchical routing

4.6 routing in the Internet

- RIP
- OSPF
- BGP

4.7 broadcast and multicast routing

The Internet network layer

host, router network layer functions:



IP Datagram Format



how much overhead?

- 20 bytes of TCP
- 20 bytes of IP
- = 40 bytes + app layer overhead

IP fragmentation, reassembly

- network links have MTU (max.transfer size) - largest possible link-level frame
  - different link types, different MTUs
- large IP datagram divided ("fragmented") within net
  - one datagram becomes several datagrams
  - "reassembled" only at final destination
  - IP header bits used to identify, order related fragments



IP fragmentation, reassembly

example:

- 4000 byte datagram
- MTU = 1500 bytes



Chapter 4: outline

4.1 introduction

4.2 virtual circuit and datagram networks

4.3 what's inside a router

4.4 IP: Internet Protocol
- datagram format
- IPv4 addressing
- ICMP

4.5 routing algorithms
- link state
- distance vector
- hierarchical routing

4.6 routing in the Internet
- RIP
- OSPF
- BGP

4.7 broadcast and multicast routing

IP addressing: introduction

IP address: 32-bit identifier for host, router *interface*

interface: connection between host/router and physical link

- router's typically have multiple interfaces
- host typically has one or two interfaces (e.g., wired Ethernet, wireless 802.11)

IP addresses associated with each interface



$$223.1.1.1 = \underbrace{11011111}_{223}\ \underbrace{00000001}_{1}\ \underbrace{00000001}_{1}\ \underbrace{00000001}_{1}$$

IP addressing: introduction

Q: how are interfaces actually connected?

A: we'll learn about that in chapter 5, 6.



A: wired Ethernet interfaces connected by Ethernet switches

A: wireless WiFi interfaces connected by WiFi base station

For now: don't need to worry about how one interface is connected to another (with no intervening router)

Subnets

IP address:

- subnet part - high order bits
- host part - low order bits

what's a subnet ?

- device interfaces with same subnet part of IP address
- can physically reach each other *without intervening router*



network consisting of 3 subnets

Subnets

recipe

❖to determine the subnets, detach each interface from its host or router, creating islands of isolated networks

❖each isolated network is called a *subnet*



subnet mask: /24

Subnets

how many?



IP addressing: CIDR

CIDR: Classless InterDomain Routing

- subnet portion of address of arbitrary length
- address format: a.b.c.d/x, where x is # bits in subnet portion of address

subnet part	host part
11001000 00010111 0001000	0 00000000

200.23.16.0/23

IP addresses: how to get one?

Q: How does a *host* get IP address?

- hard-coded by system admin in a file
  - Windows: control-panel->network->configuration->tcp/ip->properties
  - UNIX: /etc/rc.config
- DHCP: Dynamic Host Configuration Protocol: dynamically get address from as server
  - "plug-and-play"

DHCP: Dynamic Host Configuration Protocol

goal: allow host to *dynamically* obtain its IP address from network server when it joins network

- can renew its lease on address in use
- allows reuse of addresses (only hold address while connected/"on")
- support for mobile users who want to join network (more shortly)

DHCP overview:

- host broadcasts "DHCP discover" msg [optional]
- DHCP server responds with "DHCP offer" msg [optional]
- host requests IP address: "DHCP request" msg
- DHCP server sends address: "DHCP ack" msg

DHCP client-server scenario



arriving DHCP client needs address in this network

Broadcast

Limited Broadcasting:-

1) In Limited Broadcasting data reaches from source to all the host in a same network.

2) Here source will send message to all the host connected to it

3) Since message covers all host so destination Address would be 255.255.255.255

Directed Broadcast:-

1) When host in one network sends message to all host in another network

2) Here source 11.1.2.3 sends data to all the hosts of another network 20.0.0.0

3) Since network is different so we need to tell about network so directed broadcast address is 20.255.255.255





DHCP client-server scenario



NAT: network address translation

NAT: all devices in local network share just one IPv4 address as far as outside world is concerned



all datagrams *leaving* local network have *same* source NAT IP address: 138.76.29.7, but *different* source port numbers

datagrams with source or destination in this network have 10.0.0/24 address for source, destination (as usual)

NAT: network address translation

- all devices in local network have 32-bit addresses in a "private" IP address space (10/8, 172.16/12, 192.168/16 prefixes) that can only be used in local network
- advantages:
  - just one IP address needed from provider ISP for *all* devices
  - can change addresses of host in local network without notifying outside world
  - can change ISP without changing addresses of devices in local network
  - security: devices inside local net not directly addressable, visible by outside world

NAT: network address translation

implementation: NAT router must (transparently):

- outgoing datagrams: replace (source IP address, port #) of every outgoing datagram to (NAT IP address, new port #)
  - remote clients/servers will respond using (NAT IP address, new port #) as destination address
- remember (in NAT translation table) every (source IP address, port #) to (NAT IP address, new port #) translation pair
- incoming datagrams: replace (NAT IP address, new port #) in destination fields of every incoming datagram with corresponding (source IP address, port #) stored in NAT table

NAT: network address translation

2: NAT router changes datagram source address from 10.0.0.1, 3345 to 138.76.29.7, 5001, updates table

NAT translation table

WAN side addr	LAN side addr
138.76.29.7, 5001	10.0.0.1, 3345
……	……



1: host 10.0.0.1 sends datagram to 128.119.40.186, 80

3: reply arrives, destination address: 138.76.29.7, 5001

Namah Shivaya