

Loading pre-trained openAI weights

↳ using openAI openly shared weights 768

Parameter Dictionary keys:

① wte: Token Embeddings

② wpe: Positional Embeddings

③ Blocks:

* Attention layers in transformer block:

↳ transformer/h0/atten/c-atten/w } similarly for $h_1, h_2, \dots, h_{12}$
↳ transformer/h0/atten/c-atten/b } Q, K, V

Dictionary mappings

* Feed forward neural network weights in transformer block

↳ transformer/h0/mlp/c-fc/w } similarly for $h_1, h_2, \dots, h_{12}$
↳ transformer/h0/mlp/c-fc/b }

transformer/h0/mlp/c-proj/w } similarly for $h_1, h_2, \dots, h_{12}$
transformer/h0/mlp/c-proj/b }

* Output projection layer in transformer block

transformer/h0/atten/c-proj/w } similarly for $h_1, h_2, \dots, h_{12}$

* Layer normalization:

Layer 1 } transformer/h0/lh-1/g → layer norm scale } similarly for $h_1, h_2, \dots, h_{12}$
transformer/h0/lh-1/b → layer norm shift }

Layer 2 } transformer/h0/lh-2/g → layer norm scale }
transformer/h0/lh-2/b → layer norm shift }

④ g: Final norm scale

⑤ b: Final norm shift

params["b"]

params["g"]