

CV 2 exercise 1



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Summer Semester 2019
Group 8

Problem 1 Probabilities and Statistics (13 Points)

1. 1 Point

x	y	example x	example y
discrete	discrete	exam grade	exam duration
continuous	discrete	location	number of bathtubducks in sight
continuous	continuous	velocity while driving	acceleration while driving

2. 2 Points

with the chainrule we can extend as follows:

$$p(v, w, x, y, z) = p(w, x, y, z)p(v|w, x, y, z) \quad (1)$$

$$p(v, w, x, y, z) = p(x, y, z)p(w|x, y, z)p(v|w, x, y, z) \quad (2)$$

$$p(v, w, x, y, z) = p(y, z)p(x|y, z)p(w|x, y, z)p(v|w, x, y, z) \quad (3)$$

$$p(v, w, x, y, z) = p(z)p(y|z)p(y, z)p(x|y, z)p(w|x, y, z)p(v|w, x, y, z) \quad (4)$$

$$(5)$$

as equation (2) is already the answer we are looking for.

3. 3 Points

$$\begin{aligned} p(w, x) &= \int \int p(w, x, y, z) dy dz \\ &= \int \int p(w)p(y|z)p(z|x, w)p(x) dy dz \\ &= p(x)p(w) \int \int \frac{p(y, z)}{p(z)} \frac{p(z, x, w)}{p(x, w)} dy dz \\ &= p(x)p(w) \int \left(\int \frac{p(y, z)}{p(z)} dy \right) \frac{p(z, x, w)}{p(x, w)} dz \\ &= p(x)p(w) \int \frac{p(z)}{p(z)} \frac{p(z, x, w)}{p(x, w)} dz \\ &= p(x)p(w) \int \frac{p(z, x, w)}{p(x, w)} dz \\ &= p(x)p(w) \frac{p(x, w)}{p(x, w)} \\ &= p(x)p(w) \end{aligned}$$

4. 3 Points

$$\begin{aligned} E[(x - \mu)^2] &= E[x^2 - 2x\mu + \mu^2] \\ &= E[x^2] + E[-2x\mu] + E[\mu^2] \\ &= E[x^2] - 2\mu E[x] + \mu\mu & |E[x] = \mu \\ &= E[x^2] - 2E[x]E[x] + E[x]E[x] \\ &= E[x^2] - E[x]E[x] \end{aligned}$$

5. 4 Points

Lets call the choice of door 1 D , therefore the probability that the prize is behind door 1 is $p(D) = \frac{1}{3}$ and the probability that the prize is not behind door 1 is $p(notD) = 1 - p(D) = \frac{2}{3}$.

Now the event R takes place, in which the game host reveals one Door with no prize behind it. Therefore we have the conditional probabilities $p(R|D) = 1$ and $p(R|notD) = \frac{2}{3}$.

We now want to know what the probability that the prize is behind door 1 is $p(D|R)$.

Given Bayes rule and that $p(R)$ can be factorized as $p(R|D)p(D) + p(R|notD)p(notD)$:

$$p(D|R) = \frac{p(R|D)p(D)}{p(R)} = \frac{p(R|D)p(D)}{p(R|D)p(D) + p(R|notD)p(notD)}$$

We plug in our probabilities for each case:

$$p(D|R) = \frac{1 \cdot \frac{1}{3}}{1 \cdot \frac{1}{3} + 1 \cdot \frac{2}{3}} = \frac{1}{3}$$

Therefore the probability behind the door $p(D_2)$, which the game show host didn't chose is

$$p(D_2) = 1 - p(D|R) = \frac{2}{3}$$

, which shows us that we should switch to the door 2. This is only true aslong the gameshow host choses the door the way he does.

Problem 2 Modeling (5 Points)

1. 1 Point

We assume conditional independence of the pixels in the Image I^1 with the pixels that are produced from I^0 with translation that has been done at each pixel by the $d(\text{disparity})$. Therefore we make an assumption that we have brightness or color constancy and no occlusions, if they are not fulfilled then this does not be valid.

2. 1 Point

Gaussian distributions are light tailed, due to this they are very sensitive to outliers, they give large penalty or really low probability to outliers. These outliers are caused by occlusions, shading, shadows, gain control from camera etc. In order to deal with those problems we should choose robust likelihood instead of Gaussian.

As we know that the influence is proportional to the derivative of the error function then we have by derivative of squared Gaussian a linear function, it means that the further away the outliers is the bigger is the influence on the Estimate. In the other hand we take absolute value function that corresponds the Laplacian distribution, by taking the derivative of the absolute value function scaled by σ . So Influence of a outlier does not increase the further it is away. The influence on any point on Estimate is the same no matter where the point is. It is more robust than Gaussian but of course with its issues.

3. 2 Points

The pairwise MRF prior only which pairwise relations are more likely and which are not, therefore we can not directly express relations between three or more Disparity values. This independence assumption of our pairwise model gives us a disparity value of all 4 direct neighbours and is therefore not dependent on any other disparity value despite those 4. We can not get more information about a disparity value than knowing the value of its 4 neighbours gives us. Therefore d_1 and d_3 are not independent given d_2 because connections in the MRF model a undirected dependency and knowing d_3 would give us information about d_1 .

4. 1 Point

Kronecker delta used in Potts Model assign high compatibility when the disparities in the two neighbor pixels are the same and if they are different a lower compatibility, no matter how different they are. We could use a function which has its maximum at 1 when a and b are the same. Further we could penalize bigger difference more than smaller ones. A function which does this is:

$$\delta = \frac{1}{1 + |a - b|_2}$$

5. 1 Point

As we have learnt, in likelihood function are compared only single pixel values, and with help of MRF prior are modelled dependencies between nearby pixels based on the disparity values. This helps us to conclude that dependencies between pixels are not constrained to a region.

Problem 4 Stereo Likelihood (10 Points)

3. 1

For the likelihood we need multiply the probability of each pixel. If we now assume a Gaussian and we are sampling for an almost optimal case. We could assume the following equation:

$$\max \mathcal{N}(0, 1)^{384 \cdot 288} \approx 0.4^{384 \cdot 288} \approx 0$$

For the negative log likelihood we would not multiply numbers $|n| < 1$ and herefore again something signifcant bigger than 0.

6. 1

We calculate the negative log likelihoods for the Gaussian and Laplacian without the scaling term and compute the increasing factor from 0% noise. Both Models are not really robust, but the Laplacian seems to be less effected by outliers than the Gaussian.

noise	Gaussian	Factor	noise	Laplacian	Factor
0%	88.97	1	0%	1236.49	1
12%	622.75	7	12%	3882.1	3.14
25%	1208.51	13.58	25%	6775.24	5.48