

```
//Search.java
//Creating a search interface
import java.rmi.*;

public interface Search extends Remote
{
    //Declaring the method prototype
    public String query(String search) throws
    RemoteException;
}

//SearchQuery.java
import java.rmi.*;
import java.rmi.server.*;

public class SearchQuery extends RemoteObject
implements Search
{
    //Implementation of query interface
    public String query(String search)
    throws RemoteException{
        String result;
        if(search.equals("Reflection in java"))
            result="Found";
        else
            result="Not Found";
        return result;
    }
}

//Server.java
import java.net.*;
import java.io.*;

public class Server
{
    private Socket
```

```

socket=null;

private ServerSocket server =null;
private DataInputStream in =null;

//constructor with port
public Server(int port)
{
//start server and wait for connection
try
{
server= new ServerSocket(port);
System.out.println("Sevrer started");
System.out.println("Waiting for client");socket=server.accept();
System.out.println("Cliebt accepeted");
// i/p from clinet
in=new DataInputStream(new BufferedInputStream(socket.getInputStream()));
String line="";
//read msg from client until'over' is sent
while(!line.equals("Over"))
{
try
{
line=in.readUTF();
System.out.println(line);
}
catch(IOException i)
{
System.out.println(i);
}
}
System.out.println("Closing Connnection");
//close connection
socket.close();

```

```

in.close();
}
catch(IOException i)
{
System.out.println(i);
}
}

public static void main(String args[])
{
Server server =new Server(5000);
}
}

//Client.java
import java.io.*;
import java.net.*;

public class Client{
private Socket socket = null;
private BufferedReader d = null;
private InputStream input = null;
private DataOutputStream out = null;
public Client(String address, int port)
{
try{
socket = new Socket(address, port);
System.out.println("Connected");
System.out.println("Done with 1st program of DS");
d = new BufferedReader(new InputStreamReader(System.in));
out = new DataOutputStream(
socket.getOutputStream());
}
catch(UnknownHostException u)
{

```

```
System.out.println(u);
return;
}
catch(IOException i )
{
System.out.println(i);
return;
}
String line = "";
while(!line.equals("Over"))
{
try{
line = d.readLine();
out.writeUTF(line);
}
catch(IOException i )
{
System.out.println(i);
}
}
try{
input.close();
out.close();
socket.close();
}
catch(IOException i)
{
System.out.println(i);
}
}
public static void main(String args[])
{
```

```
Client client = new Client("127.0.0.1", 5000);  
}  
}
```

COMMANDS:

Terminal 1

```
javac Search.java
```

```
javac SearchQuery.java
```

```
rmic SearchQuery
```

```
rmiregistry &
```

```
javac Server.java
```

```
java Server
```

Terminal 2

```
javac Client.java
```

```
java Client
```