Amplitude Modulated Voltage Source   vam


Figure 1: Independent Voltage Source Element.

Form: `vam:⟨instance name⟩` n_1 n_2 `⟨parameter list⟩`

  n_1 is the positive element node,
  n_2 is the negative element node.

Parameters:

Parameter	Type	Default value	Required?
oc: Offset Constant (Dimensionless)	DOUBLE	0	no
sa: Signal amplitude (V)	DOUBLE	0	no
fcarrier: Carrier frequency (Hz)	DOUBLE	0	no
fmod: modulation frequency(Hz)	DOUBLE	0	no
td: Time Delay (seconds)	DOUBLE	0	no

Example:
```
vam:vsignal 8 0 oc=1 sa=10 fcarrier=1K fmod=100 td=1m
vam:v2 8 0 oc=1 sa=10 fcarrier=100 fmod=1K td=1m
```

Description:
The waveform for this source is

$$v = saoc + \sin[2.\pi.fmod.(t - td)]sin[2.\pi.fcarrier.(t - td)] \tag{1}$$

Notes:
This is the `V` element in the SPICE compatible netlist.

Version:
2002.05.01

Credits:

Name	Affiliation	Date	Links
Satish Uppathil	NC State University	May 2002	**NC STATE UNIVERSITY**
uvs@ieee.org			www.ncsu.edu