

MATERIAL SAFETY DATA SHEET

HIND PLAST SUPER M	
1. IDENTIFICATION OF THE SUBSTANCE/MANUFACTURING COMPANY	
Product name	Hind Plast Super M
Chemical Name	Super Plasticiser.
Supplier	HINDCON CHEMICALS LIMITED
Registered Office	Works
62B, Bruanfeld Row, 1st Floor, Kolkata-700027 Ph. No.:- 033 2449 0835/39. Fax:- 033 2449 0849	Baniyara, P.O. Begari, Jalan complex, Gate No – 3 Howrah 711411.
2. HAZARDS IDENTIFICATION	
Human health hazards	Prolonged or repeated exposure may be irritating to skin, eyes and mucous membranes
3. FIRST-AID MEASURES	
Inhalation	Fresh air
Ingestion	Wash out mouth with water. Drink water.
Skin contact	Wash properly with soap and water.
Eye contact	Wash out with plenty of water with the eyelid held wide open. If condition persists, consult an eye specialist.
Other Information	In case of accident or if you feel unwell, seek medical advice immediately. Bring safety data sheet. Never give anything by mouth to an unconscious person
4. FIREFIGHTING MEASURES	
Fire & Explosion Hazards	Non flammable & Non explosive.
Suitable extinguishing media	Dry chemical, alcohol-resistant foam, Water spray, carbon dioxide.
Hazardous thermal	Carbon monoxide, carbon dioxide, & (de)composition products sulphur oxides.
5. ACCIDENTAL RELEASE MEASURES	
Personal precautions	Avoid contact with skin and eyes.
Environmental precautions	Avoid release to the environment. In the event of major spillage immediately contact the fire brigade and police

6. EXPOSURE CONTROLS/PERSONAL PROTECTION

a) Engineering measures	Use only in well-ventilated areas.
b) Hygiene measures	Wash hands after working with the product. When using do not eat, drink or smoke.
c) Personal protective equipment	
Hands	Suitable gloves are recommended.
Eyes	Safety goggles or face shield is recommended.
Other protective equipment	Eye wash facility

7. HANDLING AND STORAGE

Storage	Store between the following temperatures 0-30°C. The product should be used within twelve (12) month from the date of delivery.
Recommended Packaging	25, 50, 120, 225 kgs in HDPE container.

8. PHYSICAL AND CHEMICAL PROPERTIES

Aspect	Light Brown
Form	Liquid
Specific Gravity	1.02 to 1.26 at 27°C
pH	>6
Chloride	0.02% (Max)
Permeability to water as per IS: 2645-2003	Much below the limit of the standard.
Compatibility	With all grades of cement

9. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Hazardous reactions	Not reactive
Hazardous decomposition	Will not occur.

10. TOXICOLOGICAL INFORMATION

Skin contact	Prolonged or repeated skin contact (may result in allergic eczema (Redness, blistering)).
Eye contact	May cause redness and sting
Sensitization	The product contains a very small amount of formaldehyde, which may cause sensitization by skin contact

11. OTHER INFORMATION

This safety data sheet is based on **Hindcon Chemicals Limited** present knowledge and experience, and is intended to serve as a guide for safe handling of the product regarding to health and environmental aspects. The above-mentioned data relates to the specified material designated herein and does not relate to use in combination with any other material and any process. It is subject to revision as additional knowledge is gained.