

MATERIAL SAFETY DATA SHEET

HIND PAVER COAT		
1. IDENTIFICATION OF THE SUBSTANCE/MANUFACTURING COMPANY		
Product name	Hind Paver Coat	
Chemical Name	Solvent based acrylic clear glossy concrete surface sealer/coating.	
Supplier	HINDCON CHEMICALS LIMITED	
Registered Office	Works	
62B, Bruanfeld Row, 1st Floor, Kolkata-700027 Ph. No.:- 033 2449 0835/39. Fax:- 033 2449 0849	Baniyara, P.O. Begari, Jalan complex, Gate No – 3 Howrah 711411.	
2. HAZARDS IDENTIFICATION		
Main hazards	Classified to be harmful. R10 Flammable, R 20/21 Harmful by inhalation and in contact with skin. R 38 Irritating to skin.	
3. COMPOSITION/INFORMATION ON INGREDIENTS		
Ingredient	CAS Number	% (w/w)
Xylene	1330-20-7	Trade Secret
Acrylic Polymer	X	Trade Secret
4. FIRST-AID MEASURES		
Inhalation	Plenty of Fresh air to be provided. Seek medical advice if symptoms persist.	
Ingestion	Wash out mouth with water and allow the victim to drink plenty of water. Do not induce vomiting. Seek medical attention.	
Skin contact	Wash affected area with soap and water.	
Eye contact	Wash out with plenty of water with the eyelid held wide open. If condition persists, consult an eye specialist.	
5. FIRE FIGHTING MEASURES		
Fire & Explosion Hazards	Flammable.	
Suitable extinguishing media	Foam, carbon di-oxide, fire extinguishing dry powder.	
Unsuitable extinguishing media for safety reason.	Water jet.	

Protective Equipment	Wear self contained respiratory protective device.
6. ACCIDENTAL RELEASE MEASURES	
Personal Precautions	Wear relevant PPE.
Environmental Protection	Do not allow to enter sewer, surface or ground water.
Cleaning up	Absorb with liquid binding material (sand, diatomite, acid binders, sawdust & universal binders. Dispose contaminated waste according to item 13.
7. EXPOSURE CONTROLS/PERSONAL PROTECTION	
Exposure Limit Values OES	Short Term Value – 442 mg/m ³ , 100 ppm Long Term Value – 221 mg/m ³ , 50 ppm
a) Respiratory Protection	Adequate ventilation should be arranged to maintain solvent concentrations below limit at work place. Respiratory protection to be arranged if there is a risk of exposure to high vapor concentrations.
b) Personal protective equipment	
Skin & Hands protection	Suitable gloves are recommended.
Eyes	Safety goggles or face shield is recommended.
Other protective equipment	Eye wash facility
8. HANDLING AND STORAGE	
Handling	Ensure good ventilation/exhaustion at the workplace.
Storage Recommendations:	Must be stored in tightly sealed containers.
Fire and Explosion protection	Keep away from sources of ignition. Do not smoke. Protect against electrostatic charges.
9. PHYSICAL AND CHEMICAL PROPERTIES	
Colour	Pale Brown/Transparent
Form	Liquid
Odour	Characteristic
pH	Not applicable
Viscosity	Dynamic at 20°C < 0.61 m Pas
Solubility in Water	0.2g/l
Vapour Pressure	50 mbar @ 25°C
Flash Point	30°C
Boiling point	137 -143° C
Density	. 0.87g/cm @ 20°C
10. STABILITY AND REACTIVITY	
Dangerous decomposition products	Carbon monoxide and carbon dioxide. Poisonous gases/vapors.
Dangerous reactions	Reacts with strong oxidizing agents

11. TOXICOLOGICAL INFORMATION

LD/LC50 values relevant for classification

Oral LD50	4300mg/kg (Rat)
Dermal LD50	2000mg/kg (Rabbit)
Primary Irritant effect	Irritant to skin and mucous membrane.

12. ECOLOGICAL INFORMATION

Aquatic Toxicity	LC 50 (96u) 165ppm (daphnia)
Environmental Fate:	Insoluble in Water, Non-Biodegradable, Water hazard class 2 (German regulation)

13. DISPOSAL INFORMATION

Waste Disposal:	Must not be disposed of together with household waste. Do not allow product to reach sewage system. Unclean packaging must be disposed of in accordance with official regulations.
-----------------	--

14. TRANSPORTATION INFORMATION

Transport	ADR/RID class: 3 flammable liquids Danger Code : 30 UN Number : 1307 Packaging Group : III Hazard label : 3 Description of goods: Solvent based acrylic sealer/coating
Marine Transport	IMDG class: 3 UN Number : 1307 Packaging Group : III Label : 3 Shipping Name : Solvent based acrylic sealer/coating EMS Number : F-E, S-D
Air Transport	ICAO/IATA class: 3 UN/ID Number : 1307 Packaging Group : III Label : 3 Shipping Name : Solvent based acrylic sealer/coating

15. REGULATORY INFORMATION

(Classification – Xn Harmful) Risk Phrases

10	Flammable
20/21	Harmful by inhalation and by contact with skin.
38	Irritating to skin

16. OTHER INFORMATION	Recommended uses and restrictions follow technical data sheet for detailed information.
------------------------------	---

DISCLAIMER OF LIABILITY

This safety data sheet is based on **Hindcon Chemicals Limited** present knowledge and experience, and is intended to serve as a guide for safe handling of the product regarding to health and environmental aspects. The above-mentioned data relates to the specified material designated. The information mentioned in this MSDS is based on present knowledge and obtained from sources which we believe are reliable. However, the information provided is intended to serve as a guide for safe handling of the product regarding to health and environmental aspects. The above-mentioned data relates to the specified material designated. We are not responsible and disclaim liability for loss, damage or expense incurred arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

