

MATERIAL SAFETY DATA SHEET

HIND SELFLOOR 1000				
1. IDENTIFICATION OF THE SUBSTANCE/MANUFACTURING COMPANY				
Product name		Hind Selfloor 1000 (Comp A – Resin & Component B Hardener)		
Chemical Name		Epoxy Self Levelling Floor Topping System		
Supplier		HINDCON CHEMICALS LIMITED		
Registered Office		Works		
62B, Braunfeld Row, 1st Floor, Kolkata-700027 Ph. No:- 033 2449 0835/39. Fax:- 033 2449 0849		Baniyara, P.O. Begari, Jalan complex, Gate No – 3 Howrah 711411. Mouza Narendrapur, P.O-Munsirhat, G.P-Shankarhati- II , P.S-Jagatballavpur, Dist: Howrah, Pin: 711410		
2. HAZARD IDENTIFICATION				
Inhalation		Exposure to vapour at high concentrations may cause irritation of nose, throat and respiratory track.		
Ingestion		Irritation of mouth, throat, digestive track, nausea, gastro, intestinal irritation and central nervous system depression.		
Skin Contact		Repeated or prolonged contact may produce defatting of ski leading to irritation and dermatitis.		
Eye Contact		Liquid or mist can cause irritation.		
Risk Phrases		R 10 Flammable R20/21/22-Harmful by inhalation, on contact with skin and if swallowed. R 38 -Irritating to skin		
3. COMPOSITION/INFORMATION ON INGREDIENTS				
	Substance	Form	HSN CODE	CAS NO.
	Resin	Liquid Epoxy Resin	39073010	25068-38-6
	Hardener	Polyamine	29212990	1761-71-3
Nature		Non-Flammable		
Freezing Point		NotApplicable		
Flash Point		Above 100°C		
4. FIRST-AID MEASURES				
Inhalation		Move victim to fresh air and in well ventilated space. Seek medical advice.		
Ingestion		Do not induce victim to vomiting until directed by medical personnel. Unconscious person should not be given anything by mouth. Loosen tight clothing, belt, collar and tie. Medical assistance to be arranged if symptoms are noticed.		
Skin contact		Wash properly with soap and plenty of water for at 10-15 minutes and remove contaminated clothing, shoes and seek medical advice.		

Eye contact	If victim is wearing contact lenses, remove it and immediately flush eyes with clean water for 15 minutes with eyelids kept wide open. Cold water is to be used with applying any eye ointment. Seek Medical attention.
Other Information	In case of accident or if you feel unwell, seek medical advice immediately. Bring safety data sheet.
5. FIRE FIGHTING MEASURES	
Extinguishing media	Foam , Dry extinguishing powder.
Unsuitable extinguishing media	Do not use water jet.
Special hazards of product	Toxic gases are released in a fire.
Protective Equipment for fire fighting	Wear self-contained breathing apparatus.
6. ACCIDENTAL RELEASE MEASURES	
Personal precautions	Avoid contact with skin and eyes. Personal protective equipment: • Appropriate gloves. • Safety glasses. • Suitable protective clothing.
Environmental precautions	Do not discharge into drains/rivers.
Spillages	Wipe it with saw dust. For neutralization use a mixture of IPA, water and Liquid Ammonia.
7. EXPOSURE CONTROLS/PERSONAL PROTECTION	
a) Engineering measures	Use only in well-ventilated areas under normal use conditions. Keep the container tightly closed when not in use.
b) Personal Protective Equipment	
Hands	Suitable gloves (AS2161 Type) are recommended.
Eyes	Safety goggles or face shield is recommended.
Respiratory protection	Respiratory protection required in insufficiently ventilated working areas and during spraying
Other protective equipment	Eye wash facility. Use barrier creams to protect skin from contact with the product.
8. HANDLING AND STORAGE	
Precautions for safe handling	Store between in a cool, dry and well ventilated place. The container should be tightly closed and kept away from all sources of heat and ignition.
Other precautions	Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.
9. PHYSICAL AND CHEMICAL PROPERTIES	
Physical state	Liquid
Odor	Strong
Colour	Resin: Transparent Hardener : Clear Transparent
Solubility in water	Not soluble
Solubility in aliphatic solvents	Limited solubility
Solubility in aromatic solvents	Unlimited solubility
Relative Density (Mixed Material)	1.1 to 1.18
Vapor Pressure	0.01kPa

10. STABILITY AND REACTIVITY	
Stability	Stable under normal conditions and room temperature for 12 months.
Conditions to be avoided	Temperatures below 0°C and above 50°C.
Materials to be avoided	Water and strong oxidizing agents.
Hazardous decomposition products	On pyrolysis, releases: oxides of carbon, acid smoke and irritating fumes.
11. TOXICOLOGICAL INFORMATION	
Repeated and prolonged skin contact may lead to defatting and irritation of skin. Inhalation of solvent vapours in higher concentrations may lead to nausea, headache, drowsiness and dizziness. Eye contact with the product may lead to irritation. In the case of swallowing with subsequent vomiting, aspiration of the lungs can occur which can lead to chemical pneumonia or asphyxiation.	
12. ECOLOGICAL INFORMATION	
Do not allow to enter soil, waterways or waste water drains/canals.	
13. DISPOSAL INFORMATION	
Disposal are to be done in accordance with Local Governmental rules and regulations. Unused Product: Disposal to be done through authorized waste agency and dumped at licensed site. Used/ Contaminated Product: Same as unused product. Packaging: May be solvent cleaned and recycled.	
14. TRANSPORT INFORMATION	
Proper Shipping Name: Epoxy Polyamine.	
Shipping Name (Sea Transport)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
IMDG Code	LIQUID, N.O.S.
UN Number	2735,3082
Dangerous goods class	8,9
Packaging Instruction	P001
Packing Group	III (Chemicals)
15. REGULATORY INFORMATION	
• Harmful by Inhalation and in contact with skin. • Irritating to Skin. • May cause long term adverse effects in the aquatic environment. • Keep away from food, drink and animal feeding stuffs. • When using do not eat, drink or smoke. • Avoid contact with skin. • In case of contact with eyes, rinse immediately with plenty of water and seek medical advise. • Use only in well ventilated areas. • If swallowed do not induce vomiting, seek medical advice immediately.	
16. OTHER HEALTH & SAFETY INFORMATION	
Recommended uses & restrictions	If is product is re-formulated, re-distributed for sale to others, details for hazards and methods for safe handling must be circulated to the customers. Customers must ensure that the product is suitable for use of their own purpose. It is the customers obligation to ensure that a suitable and safe assessment of the risks created by a work activity using the product is undertaken before use. All product are meant for industrial use only.

DISCLAIMER OF LIABILITY

This safety data sheet is based on **Hindcon Chemicals Limited** present knowledge and experience, and is intended to serve as a guide for safe handling of the product regarding to health and environmental aspects. The above-mentioned data relates to the specified material designated. The information mentioned in this MSDS is based on present knowledge and obtained from sources which we believe are reliable. However, the information provided is intended to serve as a guide for safe handling of the product regarding to health and environmental aspects. The above-mentioned data relates to the specified material designated. We are not responsible and disclaim liability for loss, damage or expense incurred arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

