

HIND BITKOTE (CT)

SOLVENT BASED COAL TAR PRIMER FOR CONCRETE SURFACES/RUNWAYS



DESCRIPTION

Hind Bitkote (CT) is a solvent based Coal Tar primer which is applied to seal the pores in surfaces such as concrete and improves adhesion of Coal Tar based sealing compound to the substrate.

USES

Hind Bitkote (CT) is used as a primer for application on floor joints, expansion joints in runways and other concrete surfaces which allows establishing a perfect bonding prior to pouring of Coal Tar based Sealing compounds.

ADVANTAGES

- Easy to Apply
- Excellent bonding of Coal Tar Sealing compound and concrete surface.
- Economical and cost effective.

APPLICATION

It has to be ensured the concrete is cured for at least seven days. The concrete surface should be cleaned properly and free from dust, sand and all foreign particles by air jetting / brooming. **Hind Bitkote (CT)** should be stirred thoroughly to get an uniform consistency & homogeneity. Application to be done on dry substrate by means of brush, roller or spray at the rate of **0.3 Ltr/m²** and allowed to dry for **24 hrs**. It is advised not to apply when temperature is less than 50 C or during foggy conditions.

PROPERTIES

Aspect	Black Coating
Drying Time	24 hours at 25°C.
Application Temperature	5°C to 50°C
Coverage (m ² /L)	0.30
Specific Gravity	1.0 - 1.1
Flash Point, ACC	50°C Min.
Water Content	0.20 Max.

HIND BITKOTE (CT)

SOLVENT BASED COAL TAR PRIMER FOR CONCRETE SURFACES/RUNWAYS

PACKING

Available in 20 Litre Container.

HANDLING PRECAUTIONS

Hind Bitkote (CT) is non-toxic and ingestion must be avoided. Use goggles, masks and hand gloves during application. Clean hands with warm soap water after a single apply.



IMPORTANT NOTICE :

Hindcon Chemicals maintains a team of technically trained professionals to provide full support to your problems in construction, and recommend the correct product to suite your specific requirements. Our authorized applicators can attend your site for application of the products. The content of the Technical datasheet are for general information and guideline. The result shown here are generated from our laboratory or from our site experiences.

Quality of our products are maintained as per ISO9001:2008 recommendations and continuous researches. The behaviour can change as per the prevailing conditions at the time of applications. Since **HINDCON CHEMICALS LIMITED** has no control over the use to which the users may put the material, it does not claim or warrant that in the user's particular circumstances, the result that the user will obtain from the product will be the same as those described in this communication or that the user will find the information or recommendations complete, accurate or useful. The client must test and ascertain the safety and fitness for the product for use. The right to change the properties of the products is reserved with us. The proprietary rights of third parties must be observed. All orders are accepted subject to the terms of sale and delivery. Users must always refer to the most recent issue of the latest Data Sheet for the product concerned, copies of which will be supplied on request.



✉ contactus@hindcon.com
☎ +91 33 24490839, 9830599113
☎ +91 33 24490849
📍 Kolkata, West Bengal, India

VISIT OUR WEBSITE

