

NAME

sysinfo – returns information on overall system statistics

SYNOPSIS

```
#include <sys/sysinfo.h>
```

```
int sysinfo(struct sysinfo *info);
```

DESCRIPTION

Until Linux 2.3.16, **sysinfo()** used to return information in the following structure:

```
struct sysinfo {
    long uptime;           /* Seconds since boot */
    unsigned long loads[3]; /* 1, 5, and 15 minute load averages */
    unsigned long totalram; /* Total usable main memory size */
    unsigned long freeram;  /* Available memory size */
    unsigned long sharedram; /* Amount of shared memory */
    unsigned long bufferram; /* Memory used by buffers */
    unsigned long totalswap; /* Total swap space size */
    unsigned long freeswap; /* swap space still available */
    unsigned short procs;   /* Number of current processes */
    char _f[22];           /* Pads structure to 64 bytes */
};
```

and the sizes were given in bytes.

Since Linux 2.3.23 (i386), 2.3.48 (all architectures) the structure is:

```
struct sysinfo {
    long uptime;           /* Seconds since boot */
    unsigned long loads[3]; /* 1, 5, and 15 minute load averages */
    unsigned long totalram; /* Total usable main memory size */
    unsigned long freeram;  /* Available memory size */
    unsigned long sharedram; /* Amount of shared memory */
    unsigned long bufferram; /* Memory used by buffers */
    unsigned long totalswap; /* Total swap space size */
    unsigned long freeswap; /* swap space still available */
    unsigned short procs;   /* Number of current processes */
    unsigned long totalhigh; /* Total high memory size */
    unsigned long freehigh; /* Available high memory size */
    unsigned int mem_unit;  /* Memory unit size in bytes */
    char _f[20-2*sizeof(long)-sizeof(int)]; /* Padding for libc5 */
};
```

and the sizes are given as multiples of *mem_unit* bytes.

sysinfo() provides a simple way of getting overall system statistics. This is more portable than reading */dev/kmem*.

RETURN VALUE

On success, zero is returned. On error, *-1* is returned, and *errno* is set appropriately.

ERRORS**EFAULT**

pointer to *struct sysinfo* is invalid

CONFORMING TO

This function is Linux-specific, and should not be used in programs intended to be portable.

The Linux kernel has a **sysinfo()** system call since 0.98.pl6. Linux libc contains a **sysinfo()** routine since 5.3.5, and glibc has one since 1.90.

SEE ALSO

proc(5)

COLOPHON

This page is part of release 3.22 of the Linux *man-pages* project. A description of the project, and information about reporting bugs, can be found at <http://www.kernel.org/doc/man-pages/>.