

NAME

posixoptions – optional parts of the POSIX standard

DESCRIPTION

The POSIX standard (the information below is from POSIX.1-2001) describes a set of behaviors and interfaces for a compliant system. However, many interfaces are optional and there are feature test macros to test the availability of interfaces at compile time, and functions **sysconf**(3), **fpathconf**(3), **pathconf**(3), **confstr**(3) to do this at run time. From shell scripts one can use **getconf**(1). For more detail, see **sysconf**(3).

We give the name of the POSIX abbreviation, the option, the name of the **sysconf**() parameter used to inquire about the option, and possibly a very short description. Much more precise detail can be found in the POSIX standard itself, versions of which can nowadays be accessed freely on the web.

ADV - _POSIX_ADVISORY_INFO - _SC_ADVISORY_INFO

The following advisory functions are present:

```
posix_fadvise(),
posix_fallocate(),
posix_memalign(),
posix_madvise().
```

AIO - _POSIX_ASYNCHRONOUS_IO - _SC_ASYNCHRONOUS_IO

The header `<aio.h>` is present. The following functions are present:

```
aio_cancel(),
aio_error(),
aio_fsync(),
aio_read(),
aio_return(),
aio_suspend(),
aio_write(),
lio_listio().
```

BAR - _POSIX_BARRIERS - _SC_BARRIERS

This option implies the **_POSIX_THREADS** and **_POSIX_THREAD_SAFE_FUNCTIONS** options.

The following functions are present:

```
pthread_barrier_destroy(),
pthread_barrier_init(),
pthread_barrier_wait(),
pthread_barrierattr_destroy(),
pthread_barrierattr_init().
```

--- - POSIX_CHOWN_RESTRICTED

If this option is in effect (as it always is under POSIX.1-2001) then only root may change the owner of a file, and non-root can only set the group of a file to one of the groups it belongs to. This affects the functions *chown*(), *fchown*().

CS - _POSIX_CLOCK_SELECTION - _SC_CLOCK_SELECTION

This option implies the **_POSIX_TIMERS** option. The following functions are present:

```
pthread_condattr_getclock(),
pthread_condattr_setclock(),
clock_nanosleep().
```

If **CLOCK_REALTIME** is changed by the function *clock_settime*(), then this affects all timers set for an absolute time.

CPT - _POSIX_CPUTIME - _SC_CPUTIME

The clockID `CLOCK_PROCESS_CPUTIME_ID` is supported. The initial value of this clock is 0 for each process. This option implies the `_POSIX_TIMERS` option. The function `clock_getcpuclockid()` is present.

--- - _POSIX_FILE_LOCKING - _SC_FILE_LOCKING

This option has been deleted. Not in final XPG6.

FSC - _POSIX_FSYNC - _SC_FSYNC

The function `fsync()` is present.

IP6 - _POSIX_IPV6 - _SC_IPV6

Internet Protocol Version 6 is supported.

--- - _POSIX_JOB_CONTROL - _SC_JOB_CONTROL

If this option is in effect (as it always is under POSIX.1-2001) then the system implements POSIX-style job control, and the following functions are present:

```
setpgid(),
tcdrain(),
tcflush(),
tcgetpgrp(),
tcsendbreak(),
tcsetattr(),
tcsetpgrp().
```

MF - _POSIX_MAPPED_FILES - _SC_MAPPED_FILES

Shared memory is supported. The include file `<sys/mman.h>` is present. The following functions are present: `mmap()`, `msync()`, `munmap()`.

ML - _POSIX_MEMLOCK - _SC_MEMLOCK

Shared memory can be locked into core. The functions `mlockall()`, `munlockall()` are present.

MR/MLR - _POSIX_MEMLOCK_RANGE - _SC_MEMLOCK_RANGE

More precisely, ranges can be locked into core. The functions `mlock()`, `munlock()` are present.

MPR - _POSIX_MEMORY_PROTECTION - _SC_MEMORY_PROTECTION

The function `mprotect()` is present.

MSG - _POSIX_MESSAGE_PASSING - _SC_MESSAGE_PASSING

The include file `<mqueue.h>` is present. The following functions are present:

```
mq_close(),
mq_getattr(),
mq_notify(),
mq_open(),
mq_receive(),
mq_send(),
mq_setattr(),
mq_unlink().
```

MON - _POSIX_MONOTONIC_CLOCK - _SC_MONOTONIC_CLOCK

`CLOCK_MONOTONIC` is supported. This option implies the `_POSIX_TIMERS` option. Affected functions are

```
aio_suspend(),
clock_getres(),
clock_gettime(),
clock_settime(),
timer_create().
```

--- - _POSIX_MULTI_PROCESS - _SC_MULTI_PROCESS

This option has been deleted. Not in final XPG6.

--- - _POSIX_NO_TRUNC

If this option is in effect (as it always is under POSIX.1-2001) then pathname components longer than **NAME_MAX** are not truncated, but give an error. This property may be dependent on the path prefix of the component.

PIO - _POSIX_PRIORITIZED_IO - _SC_PRIORITIZED_IO

This option says that one can specify priorities for asynchronous I/O. This affects the functions

aio_read(),
aio_write().

PS - _POSIX_PRIORITY_SCHEDULING - _SC_PRIORITY_SCHEDULING

The include file *<sched.h>* is present. The following functions are present:

sched_get_priority_max(),
sched_get_priority_min(),
sched_getparam(),
sched_getscheduler(),
sched_rr_get_interval(),
sched_setparam(),
sched_setscheduler(),
sched_yield().

If also **_POSIX_SPAWN** is in effect, then the following functions are present:

posix_spawnattr_getschedparam(),
posix_spawnattr_getschedpolicy(),
posix_spawnattr_setschedparam(),
posix_spawnattr_setschedpolicy().

RS - _POSIX_RAW_SOCKETS

Raw sockets are supported. Affected functions are *getsockopt()*, *setsockopt()*.

--- - _POSIX_READER_WRITER_LOCKS - _SC_READER_WRITER_LOCKS

This option implies the **_POSIX_THREADS** option. Conversely, under POSIX.1-2001 the **_POSIX_THREADS** option implies this option.

The following functions are present:

pthread_rwlock_destroy(),
pthread_rwlock_init(),
pthread_rwlock_rdlock(),
pthread_rwlock_tryrdlock(),
pthread_rwlock_trywrlock(),
pthread_rwlock_unlock(),
pthread_rwlock_wrlock(),
pthread_rwlockattr_destroy(),
pthread_rwlockattr_init().

RTS - _POSIX_REALTIME_SIGNALS - _SC_REALTIME_SIGNALS

Realtime signals are supported. The following functions are present:

sigqueue(),
sigtimedwait(),
sigwaitinfo().

--- - _POSIX_REGEX - _SC_REGEX

If this option is in effect (as it always is under POSIX.1-2001) then POSIX regular expressions are supported and the following functions are present:

```
regcomp(),
regerror(),
regexexec(),
regfree().
```

--- - _POSIX_SAVED_IDS - _SC_SAVED_IDS

If this option is in effect (as it always is under POSIX.1-2001) then a process has a saved set-user-ID and a saved set-group-ID. Affected functions are

```
exec(),
kill(),
seteuid(),
setegid(),
setgid(),
setuid().
```

SEM - _POSIX_SEMAPHORES - _SC_SEMAPHORES

The include file `<semaphore.h>` is present. The following functions are present:

```
sem_close(),
sem_destroy(),
sem_getvalue(),
sem_init(),
sem_open(),
sem_post(),
sem_trywait(),
sem_unlink(),
sem_wait().
```

SHM - _POSIX_SHARED_MEMORY_OBJECTS - _SC_SHARED_MEMORY_OBJECTS

The following functions are present:

```
mmap(),
munmap(),
shm_open(),
shm_unlink().
```

--- - _POSIX_SHELL - _SC_SHELL

If this option is in effect (as it always is under POSIX.1-2001), the function `system()` is present.

SPN - _POSIX_SPAWN - _SC_SPAWN

This option describes support for process creation in a context where it is difficult or impossible to use `fork()`, for example, because no MMU is present. If **_POSIX_SPAWN** is in effect, then the include file `<spawn.h>` and the following functions are present:

```
posix_spawn(),
posix_spawn_file_actions_addclose(),
posix_spawn_file_actions_adddup2(),
posix_spawn_file_actions_addopen(),
posix_spawn_file_actions_destroy(),
posix_spawn_file_actions_init(),
posix_spawnattr_destroy(),
posix_spawnattr_getsigdefault(),
```

```

posix_spawnattr_getflags(),
posix_spawnattr_getpgroup(),
posix_spawnattr_getsigmask(),
posix_spawnattr_init(),
posix_spawnattr_setsigdefault(),
posix_spawnattr_setflags(),
posix_spawnattr_setpgroup(),
posix_spawnattr_setsigmask(),
posix_spawnnp().

```

If also **_POSIX_PRIORITY_SCHEDULING** is in effect, then the following functions are present:

```

posix_spawnattr_getschedparam(),
posix_spawnattr_getschedpolicy(),
posix_spawnattr_setschedparam(),
posix_spawnattr_setschedpolicy().

```

SPI - _POSIX_SPIN_LOCKS - _SC_SPIN_LOCKS

This option implies the **_POSIX_THREADS** and **_POSIX_THREAD_SAFE_FUNCTIONS** options. The following functions are present:

```

pthread_spin_destroy(),
pthread_spin_init(),
pthread_spin_lock(),
pthread_spin_trylock(),
pthread_spin_unlock().

```

SS - _POSIX_SPORADIC_SERVER - _SC_SPORADIC_SERVER

The scheduling policy **SCHED_SPORADIC** is supported. This option implies the **_POSIX_PRIORITY_SCHEDULING** option. Affected functions are

```

sched_setparam(),
sched_setscheduler().

```

SIO - _POSIX_SYNCHRONIZED_IO - _SC_SYNCHRONIZED_IO

Affected functions are *open()*, *msync()*, *fsync()*, *fdatasync()*.

TSA - _POSIX_THREAD_ATTR_STACKADDR - _SC_THREAD_ATTR_STACKADDR

Affected functions are

```

pthread_attr_getstack(),
pthread_attr_getstackaddr(),
pthread_attr_setstack(),
pthread_attr_setstackaddr().

```

TSS - _POSIX_THREAD_ATTR_STACKSIZE - _SC_THREAD_ATTR_STACKSIZE

Affected functions are

```

pthread_attr_getstack(),
pthread_attr_getstacksize(),
pthread_attr_setstack(),
pthread_attr_setstacksize().

```

TCT - _POSIX_THREAD_CPUTIME - _SC_THREAD_CPUTIME

The clockID **CLOCK_THREAD_CPUTIME_ID** is supported. This option implies the **_POSIX_TIMERS** option. Affected functions are

```

pthread_getcpuclockid(),
clock_getres(),

```

clock_gettime(),
clock_settime(),
timer_create().

TPI - _POSIX_THREAD_PRIO_INHERIT - _SC_THREAD_PRIO_INHERIT

Affected functions are

pthread_mutexattr_getprotocol(),
pthread_mutexattr_setprotocol().

TPP - _POSIX_THREAD_PRIO_PROTECT - _SC_THREAD_PRIO_PROTECT

Affected functions are

pthread_mutex_getprioceiling(),
pthread_mutex_setprioceiling(),
pthread_mutexattr_getprioceiling(),
pthread_mutexattr_getprotocol(),
pthread_mutexattr_setprioceiling(),
pthread_mutexattr_setprotocol().

TPS - _POSIX_THREAD_PRIORITY_SCHEDULING - _SC_THREAD_PRIORITY_SCHEDULING

If this option is in effect, the different threads inside a process can run with different priorities and/or different schedulers. Affected functions are

pthread_attr_getinheritsched(),
pthread_attr_getschedpolicy(),
pthread_attr_getscope(),
pthread_attr_setinheritsched(),
pthread_attr_setschedpolicy(),
pthread_attr_setscope(),
pthread_getschedparam(),
pthread_setschedparam(),
pthread_setschedprio().

TSH - _POSIX_THREAD_PROCESS_SHARED - _SC_THREAD_PROCESS_SHARED

Affected functions are

pthread_barrierattr_getpshared(),
pthread_barrierattr_setpshared(),
pthread_condattr_getpshared(),
pthread_condattr_setpshared(),
pthread_mutexattr_getpshared(),
pthread_mutexattr_setpshared(),
pthread_rwlockattr_getpshared(),
pthread_rwlockattr_setpshared().

TSF - _POSIX_THREAD_SAFE_FUNCTIONS - _SC_THREAD_SAFE_FUNCTIONS

Affected functions are

readdir_r(),
getgrgid_r(),
getgrnam_r(),
getpwnam_r(),
getpwuid_r(),
flockfile(),
ftrylockfile(),
funlockfile(),

```

getc_unlocked(),
getchar_unlocked(),
putc_unlocked(),
putchar_unlocked(),
rand_r(),
strerror_r(),
strtok_r(),
asctime_r(),
ctime_r(),
gmtime_r(),
localtime_r().

```

TSP - _POSIX_THREAD_SPORADIC_SERVER - _SC_THREAD_SPORADIC_SERVER

This option implies the **_POSIX_THREAD_PRIORITY_SCHEDULING** option. Affected functions are

```

sched_getparam(),
sched_setparam(),
sched_setscheduler().

```

THR - _POSIX_THREADS - _SC_THREADS

Basic support for POSIX threads is available. The following functions are present:

```

pthread_atfork(),
pthread_attr_destroy(),
pthread_attr_getdetachstate(),
pthread_attr_getschedparam(),
pthread_attr_init(),
pthread_attr_setdetachstate(),
pthread_attr_setschedparam(),
pthread_cancel(),
pthread_cleanup_push(),
pthread_cleanup_pop(),
pthread_cond_broadcast(),
pthread_cond_destroy(),
pthread_cond_init(),
pthread_cond_signal(),
pthread_cond_timedwait(),
pthread_cond_wait(),
pthread_condattr_destroy(),
pthread_condattr_init(),
pthread_create(),
pthread_detach(),
pthread_equal(),
pthread_exit(),
pthread_getspecific(),
pthread_join(),
pthread_key_create(),
pthread_key_delete(),
pthread_mutex_destroy(),
pthread_mutex_init(),
pthread_mutex_lock(),
pthread_mutex_trylock(),
pthread_mutex_unlock(),
pthread_mutexattr_destroy(),
pthread_mutexattr_init(),
pthread_once(),

```

```

pthread_rwlock_destroy(),
pthread_rwlock_init(),
pthread_rwlock_rdlock(),
pthread_rwlock_tryrdlock(),
pthread_rwlock_trywrlock(),
pthread_rwlock_unlock(),
pthread_rwlock_wrlock(),
pthread_rwlockattr_destroy(),
pthread_rwlockattr_init(),
pthread_self(),
pthread_setcancelstate(),
pthread_setcanceltype(),
pthread_setspecific(),
pthread_testcancel().

```

TMO - _POSIX_TIMEOUTS - _SC_TIMEOUTS

The following functions are present:

```

mq_timedreceive(),
mq_timedsend(),
pthread_mutex_timedlock(),
pthread_rwlock_timedrdlock(),
pthread_rwlock_timedwrlock(),
sem_timedwait(),
posix_trace_timedgetnext_event().

```

TMR - _POSIX_TIMERS - _SC_TIMERS

The following functions are present:

```

clock_getres(),
clock_gettime(),
clock_settime(),
nanosleep(),
timer_create(),
timer_delete(),
timer_gettime(),
timer_getoverrun(),
timer_settime().

```

TRC - _POSIX_TRACE - _SC_TRACE

POSIX tracing is available. The following functions are present:

```

posix_trace_attr_destroy(),
posix_trace_attr_getclockres(),
posix_trace_attr_getcreatetime(),
posix_trace_attr_getgenversion(),
posix_trace_attr_getmaxdatasize(),
posix_trace_attr_getmaxsystemevents(),
posix_trace_attr_getmaxuserevents(),
posix_trace_attr_getname(),
posix_trace_attr_getstreamfullpolicy(),
posix_trace_attr_getstreamsize(),
posix_trace_attr_init(),
posix_trace_attr_setmaxdatasize(),
posix_trace_attr_setname(),
posix_trace_attr_setstreamsize(),

```



```

posix_trace_attr_setstreamfullpolicy(),
posix_trace_clear(),
posix_trace_create(),
posix_trace_event(),
posix_trace_eventid_equal(),
posix_trace_eventid_get_name(),
posix_trace_eventid_open(),
posix_trace_eventtypelist_getnext_id(),
posix_trace_eventtypelist_rewind(),
posix_trace_flush(),
posix_trace_get_attr(),
posix_trace_get_status(),
posix_trace_getnext_event(),
posix_trace_shutdown(),
posix_trace_start(),
posix_trace_stop(),
posix_trace_trygetnext_event().

```

TEF - _POSIX_TRACE_EVENT_FILTER - _SC_TRACE_EVENT_FILTER

This option implies the **_POSIX_TRACE** option. The following functions are present:

```

posix_trace_eventset_add(),
posix_trace_eventset_del(),
posix_trace_eventset_empty(),
posix_trace_eventset_fill(),
posix_trace_eventset_ismember(),
posix_trace_get_filter(),
posix_trace_set_filter(),
posix_trace_trid_eventid_open().

```

TRI - _POSIX_TRACE_INHERIT - _SC_TRACE_INHERIT

Tracing children of the traced process is supported. This option implies the **_POSIX_TRACE** option. The following functions are present:

```

posix_trace_attr_getinherited(),
posix_trace_attr_setinherited().

```

TRL - _POSIX_TRACE_LOG - _SC_TRACE_LOG

This option implies the **_POSIX_TRACE** option. The following functions are present:

```

posix_trace_attr_getlogfullpolicy(),
posix_trace_attr_getlogsize(),
posix_trace_attr_setlogfullpolicy(),
posix_trace_attr_setlogsize(),
posix_trace_close(),
posix_trace_create_withlog(),
posix_trace_open(),
posix_trace_rewind().

```

TYM - _POSIX_TYPED_MEMORY_OBJECTS - _SC_TYPED_MEMORY_OBJECT

The following functions are present:

```

posix_mem_offset(),
posix_typed_mem_get_info(),
posix_typed_mem_open().

```

--- - _POSIX_VDISABLE

Always present (probably 0). Value to set a changeable special control character to indicate that it is disabled.

XOPEN EXTENSIONS

_XOPEN_CRYPT, _XOPEN_LEGACY, _XOPEN_REALTIME, _XOPEN_REALTIME_THREADS, _XOPEN_UNIX.

SEE ALSO

sysconf(3), standards(7)

COLOPHON

This page is part of release 3.22 of the Linux *man-pages* project. A description of the project, and information about reporting bugs, can be found at <http://www.kernel.org/doc/man-pages/>.