

NAME

feature_test_macros – feature test macros

SYNOPSIS

```
#include <features.h>
```

DESCRIPTION

Feature test macros allow the programmer to control the definitions that are exposed by system header files when a program is compiled. This can be useful for creating portable applications, by preventing non-standard definitions from being exposed. Other macros can be used to expose non-standard definitions that are not exposed by default. The precise effects of each of the feature test macros described below can be ascertained by inspecting the *<features.h>* header file.

In order to be effective, a feature test macro *must be defined before including any header files*. This can either be done in the compilation command (*cc -DMACRO=value*) or by defining the macro within the source code before including any headers.

Specification of feature test macro requirements in manual pages

When a function requires that a feature test macro is defined, the manual page SYNOPSIS typically includes a note of the following form (this example from the **chmod(2)** manual page):

```
#include <sys/stat.h>
```

```
int chmod(const char *path, mode_t mode);
int fchmod(int fd, mode_t mode);
```

Feature Test Macro Requirements for glibc (see **feature_test_macros(7)**):

```
fchmod(): _BSD_SOURCE || _XOPEN_SOURCE >= 500
```

The `||` means that in order to obtain the declaration of **fchmod(2)** from *<sys/stat.h>*, *either* of the following macro definitions must be made before including any header files:

```
#define _BSD_SOURCE
#define _XOPEN_SOURCE 500 /* or any value > 500 */
```

Alternatively, equivalent definitions can be included in the compilation command:

```
cc -D_BSD_SOURCE
cc -D_XOPEN_SOURCE=500 # Or any value > 500
```

Note that, as described below, **some feature test macros are defined by default**, so that it may not always be necessary to explicitly specify the feature test macro(s) shown in the SYNOPSIS.

In a few cases, manual pages use a shorthand for expressing the feature test macro requirements (this example from **readahead(2)**):

```
#define _GNU_SOURCE
#include <fcntl.h>
```

```
ssize_t readahead(int fd, off64_t *offset, size_t count);
```

This format is employed in cases where only a single feature test macro can be used to expose the function declaration, and that macro is not defined by default.

Feature test macros understood by glibc

The following paragraphs explain how feature test macros are handled in Linux glibc 2.x, *x* > 0.

Linux glibc understands the following feature test macros:

__STRICT_ANSI__

ISO Standard C. This macro is implicitly defined by **gcc**(1) when invoked with, for example, the *-std=c99* or *-ansi* flag.

_POSIX_C_SOURCE

Defining this macro causes header files to expose definitions as follows:

- The value 1 exposes definitions conforming to POSIX.1-1990 and ISO C (1990).
- The value 2 or greater additionally exposes definitions for POSIX.2-1992.
- The value 199309L or greater additionally exposes definitions for POSIX.1b (real-time extensions).
- The value 199506L or greater additionally exposes definitions for POSIX.1c (threads).
- (Since glibc 2.3.3) The value 200112L or greater exposes definitions corresponding to the POSIX.1-2001 base specification (excluding the XSI extension).
- (Since glibc 2.10) The value 200809L or greater exposes definitions corresponding to the POSIX.1-2008 base specification (excluding the XSI extension).

_POSIX_SOURCE

Defining this obsolete macro with any value is equivalent to defining **_POSIX_C_SOURCE** with the value 1.

_XOPEN_SOURCE

Defining this macro causes header files to expose definitions as follows:

- Defining with any value exposes definitions conforming to POSIX.1, POSIX.2, and XPG4.
- The value 500 or greater additionally exposes definitions for SUSv2 (UNIX 98).
- (Since glibc 2.2) The value 600 or greater additionally exposes definitions for SUSv3 (UNIX 03; i.e., the POSIX.1-2001 base specification plus the XSI extension) and C99 definitions.
- (Since glibc 2.10) The value 700 or greater additionally exposes definitions for SUSv4 (i.e., the POSIX.1-2008 base specification plus the XSI extension).

_XOPEN_SOURCE_EXTENDED

If this macro is defined, and **_XOPEN_SOURCE** is defined, then expose definitions corresponding to the XPG4v2 (SUSv1) UNIX extensions (UNIX 95). This macro is also implicitly defined if **_XOPEN_SOURCE** is defined with a value of 500 or more.

_ISOC99_SOURCE

Exposes C99 extensions to ISO C (1990). This macro is recognized since glibc 2.1.3; earlier glibc 2.1.x versions recognized an equivalent macro named **_ISOC9X_SOURCE** (because the C99 standard had not then been finalized). Although the use of the latter macro is obsolete, glibc continues to recognize it for backwards compatibility.

_LARGEFILE64_SOURCE

Expose definitions for the alternative API specified by the LFS (Large File Summit) as a "transitional extension" to the Single UNIX Specification. (See <http://opengroup.org/platform/lfs.html>.) The alternative API consists of a set of new objects (i.e., functions and types) whose names are suffixed with "64" (e.g., *off64_t* versus *off_t*, ***lseek64()*** versus ***lseek()***, etc.). New programs should not employ this interface; instead ***_FILE_OFFSET_BITS=64*** should be employed.

_FILE_OFFSET_BITS

Defining this macro with the value 64 automatically converts references to 32-bit functions and data types related to file I/O and file system operations into references to their 64-bit counterparts. This is useful for performing I/O on large files (> 2 Gigabytes) on 32-bit systems. (Defining this macro permits correctly written programs to use large files with only a recompilation being required.) 64-bit systems naturally permit file sizes greater than 2 Gigabytes, and on those systems this macro has no effect.

_BSD_SOURCE

Defining this macro with any value causes header files to expose BSD-derived definitions. Defining this macro also causes BSD definitions to be preferred in some situations where standards conflict, unless one or more of **_SVID_SOURCE**, **_POSIX_SOURCE**, **_POSIX_C_SOURCE**, **_XOPEN_SOURCE**, **_XOPEN_SOURCE_EXTENDED**, or **_GNU_SOURCE** is defined, in which case BSD definitions are disfavored.

_SVID_SOURCE

Defining this macro with any value causes header files to expose System V-derived definitions. (SVID == System V Interface Definition; see **standards(7)**.)

_ATFILE_SOURCE (since glibc 2.4)

Defining this macro with any value causes header files to expose declarations of a range of functions with the suffix "at"; see **openat(2)**.

_GNU_SOURCE

Defining this macro (with any value) is equivalent to defining **_BSD_SOURCE**, **_SVID_SOURCE**, **_ATFILE_SOURCE**, **_LARGEFILE64_SOURCE**, **_ISOC99_SOURCE**, **_XOPEN_SOURCE_EXTENDED**, **_POSIX_SOURCE**, **_POSIX_C_SOURCE** with the value 200809L (200112L in glibc versions before 2.10; 199506L in glibc versions before 2.5; 199309L in glibc versions before 2.1) and **_XOPEN_SOURCE** with the value 700 (600 in glibc versions before 2.10; 500 in glibc versions before 2.2). In addition, various GNU-specific extensions are also exposed. Where standards conflict, BSD definitions are disfavored.

_REENTRANT

Defining this macro exposes definitions of certain reentrant functions. For multithreaded programs, use *cc -pthread* instead.

_THREAD_SAFE

Synonym for **_REENTRANT**, provided for compatibility with some other implementations.

_FORTIFY_SOURCE (since glibc 2.3.4)

Defining this macro causes some lightweight checks to be performed to detect some buffer overflow errors when employing various string and memory manipulation functions. Not all buffer overflows are detected, just some common cases. In the current implementation checks are added for calls to **memcpy(3)**, **mempcpy(3)**, **memmove(3)**, **memset(3)**, **stpcpy(3)**, **strcpy(3)**, **strncpy(3)**, **strcat(3)**, **strncat(3)**, **sprintf(3)**, **snprintf(3)**, **vsprintf(3)**, **vsnprintf(3)**, and **gets(3)**. If **_FORTIFY_SOURCE** is set to 1, with compiler optimization level 1 (*gcc -O1*) and above, checks that shouldn't change the behavior of conforming programs are performed. With **_FORTIFY_SOURCE** set to 2 some more checking is added, but some conforming programs might fail. Some of the checks can be performed at compile time, and result in compiler warnings; other checks take place at run time, and result in a run-time error if the check fails. Use of this macro requires compiler support, available with **gcc(1)** since version 4.0.

Default definitions, implicit definitions, and combining definitions

If no feature test macros are explicitly defined, then the following feature test macros are defined by default: **_BSD_SOURCE**, **_SVID_SOURCE**, **_POSIX_SOURCE**, and **_POSIX_C_SOURCE=200909L** (200112L in glibc versions before 2.10; 199506L in glibc versions before 2.4; 199309L in glibc versions before 2.1).

If any of **__STRICT_ANSI__**, **_ISOC99_SOURCE**, **_POSIX_SOURCE**, **_POSIX_C_SOURCE**, **_XOPEN_SOURCE**, **_XOPEN_SOURCE_EXTENDED**, **_BSD_SOURCE**, or **_SVID_SOURCE** is explicitly defined, then **_BSD_SOURCE**, and **_SVID_SOURCE** are not defined by default.

If **_POSIX_SOURCE** and **_POSIX_C_SOURCE** are not explicitly defined, and either **__STRICT_ANSI__** is not defined or **_XOPEN_SOURCE** is defined with a value of 500 or more, then

* **_POSIX_SOURCE** is defined with the value 1; and

* **_POSIX_C_SOURCE** is defined with one of the following values:

- 2, if **XOPEN_SOURCE** is defined with a value less than 500;
- 199506L, if **XOPEN_SOURCE** is defined with a value greater than or equal to 500 and less than 600; or
- (since glibc 2.4) 200112L, if **XOPEN_SOURCE** is defined with a value greater than or equal to 600 and less than 700.
- (Since glibc 2.10) 200809L, if **XOPEN_SOURCE** is defined with a value greater than or equal to 700.
- Older versions of glibc do not know about the values 200112L and 200809L for **_POSIX_C_SOURCE**, and the setting of this macro will depend on the glibc version.
- If **XOPEN_SOURCE** is undefined, then the setting of **_POSIX_C_SOURCE** depends on the glibc version: 199506L, in glibc versions before 2.4; 200112L, in glibc 2.4 to 2.9; and 200809L, since glibc 2.10.

Multiple macros can be defined; the results are additive.

CONFORMING TO

POSIX.1 specifies **_POSIX_C_SOURCE**, **_POSIX_SOURCE**, and **_XOPEN_SOURCE**. **_XOPEN_SOURCE_EXTENDED** was specified by XPG4v2 (aka SUSv1).

_FILE_OFFSET_BITS is not specified by any standard, but is employed on some other implementations.

_BSD_SOURCE, **_SVID_SOURCE**, **_ATFILE_SOURCE**, **_GNU_SOURCE**, **_FORTIFY_SOURCE**, **_REENTRANT**, and **_THREAD_SAFE** are specific to Linux (glibc).

NOTES

<features.h> is a Linux/glibc-specific header file. Other systems have an analogous file, but typically with a different name. This header file is automatically included by other header files as required: it is not necessary to explicitly include it in order to employ feature test macros.

According to which of the above feature test macros are defined, *<features.h>* internally defines various other macros that are checked by other glibc header files. These macros have names prefixed by two underscores (e.g., **__USE_MISC**). Programs should *never* define these macros directly: instead, the appropriate feature test macro(s) from the list above should be employed.

EXAMPLE

The program below can be used to explore how the various feature test macros are set depending on the glibc version and what feature test macros are explicitly set. The following shell session, on a system with glibc 2.10, shows some examples of what we would see:

```
$ cc ftm.c
$ ./a.out
_POSIX_SOURCE defined
_POSIX_C_SOURCE defined: 200809L
_BSD_SOURCE defined
_SVID_SOURCE defined
_ATFILE_SOURCE defined
$ cc -D_XOPEN_SOURCE=500 ftm.c
$ ./a.out
_POSIX_SOURCE defined
_POSIX_C_SOURCE defined: 199506L
_XOPEN_SOURCE defined: 500
$ cc -D_GNU_SOURCE ftm.c
$ ./a.out
```

```
_POSIX_SOURCE defined
_POSIX_C_SOURCE defined: 200809L
_ISOC99_SOURCE defined
_XOPEN_SOURCE defined: 700
_XOPEN_SOURCE_EXTENDED defined
_LARGEFILE64_SOURCE defined
_BSD_SOURCE defined
_SVID_SOURCE defined
_ATFILE_SOURCE defined
_GNU_SOURCE defined
```

Program source

```
/* ftm.c */

#include <stdio.h>
#include <unistd.h>
#include <stdlib.h>

int
main(int argc, char *argv[])
{
#ifdef _POSIX_SOURCE
    printf("_POSIX_SOURCE defined\n");
#endif

#ifdef _POSIX_C_SOURCE
    printf("_POSIX_C_SOURCE defined: %ldL\n", (long) _POSIX_C_SOURCE);
#endif

#ifdef _ISOC99_SOURCE
    printf("_ISOC99_SOURCE defined\n");
#endif

#ifdef _XOPEN_SOURCE
    printf("_XOPEN_SOURCE defined: %d\n", _XOPEN_SOURCE);
#endif

#ifdef _XOPEN_SOURCE_EXTENDED
    printf("_XOPEN_SOURCE_EXTENDED defined\n");
#endif

#ifdef _LARGEFILE64_SOURCE
    printf("_LARGEFILE64_SOURCE defined\n");
#endif

#ifdef _FILE_OFFSET_BITS
    printf("_FILE_OFFSET_BITS defined: %d\n", _FILE_OFFSET_BITS);
#endif

#ifdef _BSD_SOURCE
    printf("_BSD_SOURCE defined\n");
#endif

#ifdef _SVID_SOURCE
```

```
    printf("_SVID_SOURCE defined\n");
#endif

#ifdef _ATFILE_SOURCE
    printf("_ATFILE_SOURCE defined\n");
#endif

#ifdef _GNU_SOURCE
    printf("_GNU_SOURCE defined\n");
#endif

#ifdef _REENTRANT
    printf("_REENTRANT defined\n");
#endif

#ifdef _THREAD_SAFE
    printf("_THREAD_SAFE defined\n");
#endif

#ifdef _FORTIFY_SOURCE
    printf("_FORTIFY_SOURCE defined\n");
#endif

    exit(EXIT_SUCCESS);
}
```

SEE ALSO

libc(7), **standards(7)**

The section "Feature Test Macros" under *info libc*.

/usr/include/features.h

COLOPHON

This page is part of release 3.22 of the Linux *man-pages* project. A description of the project, and information about reporting bugs, can be found at <http://www.kernel.org/doc/man-pages/>.