

NAME

`epoll_ctl` – control interface for an epoll descriptor

SYNOPSIS

```
#include <sys/epoll.h>
```

```
int epoll_ctl(int epfd, int op, int fd, struct epoll_event *event);
```

DESCRIPTION

This system call performs control operations on the epoll instance referred to by the file descriptor *epfd*. It requests that the operation *op* be performed for the target file descriptor, *fd*.

Valid values for the *op* argument are :

EPOLL_CTL_ADD

Register the target file descriptor *fd* on the **epoll** instance referred to by the file descriptor *epfd* and associate the event *event* with the internal file linked to *fd*.

EPOLL_CTL_MOD

Change the event *event* associated with the target file descriptor *fd*.

EPOLL_CTL_DEL

Remove (deregister) the target file descriptor *fd* from the **epoll** instance referred to by *epfd*. The *event* is ignored and can be NULL (but see BUGS below).

The *event* argument describes the object linked to the file descriptor *fd*. The *struct epoll_event* is defined as :

```
typedef union epoll_data {
    void    *ptr;
    int     fd;
    __uint32_t  u32;
    __uint64_t  u64;
} epoll_data_t;

struct epoll_event {
    __uint32_t  events;    /* Epoll events */
    epoll_data_t data;    /* User data variable */
};
```

The *events* member is a bit set composed using the following available event types:

EPOLLIN

The associated file is available for **read**(2) operations.

EPOLLOUT

The associated file is available for **write**(2) operations.

EPOLLRDHUP (since Linux 2.6.17)

Stream socket peer closed connection, or shut down writing half of connection. (This flag is especially useful for writing simple code to detect peer shutdown when using Edge Triggered monitoring.)

EPOLLPRI

There is urgent data available for **read**(2) operations.

EPOLLERR

Error condition happened on the associated file descriptor. **epoll_wait**(2) will always wait for this event; it is not necessary to set it in *events*.

EPOLLHUP

Hang up happened on the associated file descriptor. **epoll_wait(2)** will always wait for this event; it is not necessary to set it in *events*.

EPOLLET

Sets the Edge Triggered behavior for the associated file descriptor. The default behavior for **epoll** is Level Triggered. See **epoll(7)** for more detailed information about Edge and Level Triggered event distribution architectures.

EPOLLONESHOT (since Linux 2.6.2)

Sets the one-shot behavior for the associated file descriptor. This means that after an event is pulled out with **epoll_wait(2)** the associated file descriptor is internally disabled and no other events will be reported by the **epoll** interface. The user must call **epoll_ctl()** with **EPOLL_CTL_MOD** to re-arm the file descriptor with a new event mask.

RETURN VALUE

When successful, **epoll_ctl()** returns zero. When an error occurs, **epoll_ctl()** returns `-1` and *errno* is set appropriately.

ERRORS**EBADF**

epfd or *fd* is not a valid file descriptor.

EEXIST

op was **EPOLL_CTL_ADD**, and the supplied file descriptor *fd* is already registered with this *epoll* instance.

EINVAL

epfd is not an **epoll** file descriptor, or *fd* is the same as *epfd*, or the requested operation *op* is not supported by this interface.

ENOENT

op was **EPOLL_CTL_MOD** or **EPOLL_CTL_DEL**, and *fd* is not registered on with this *epoll* instance.

ENOMEM

There was insufficient memory to handle the requested *op* control operation.

The limit imposed by

`/proc/sys/fs/epoll/max_user_watches` was encountered while trying to register (**EPOLL_CTL_ADD**) a new file descriptor on an *epoll* instance. See **epoll(7)** for further details.

EPERM

The target file *fd* does not support **epoll**.

CONFORMING TO

epoll_ctl() is Linux-specific, and was introduced in kernel 2.5.44.

NOTES

The **epoll** interface supports all file descriptors that support **poll(2)**.

BUGS

In kernel versions before 2.6.9, the **EPOLL_CTL_DEL** operation required a non-NULL pointer in *event*, even though this argument is ignored. Since Linux 2.6.9, *event* can be specified as NULL when using **EPOLL_CTL_DEL**. Applications that need to be portable to kernels before 2.6.9 should specify a non-NULL pointer in *event*.

SEE ALSO

epoll_create(2), **epoll_wait(2)**, **poll(2)**, **epoll(7)**

COLOPHON

This page is part of release 3.22 of the Linux *man-pages* project. A description of the project, and information about reporting bugs, can be found at <http://www.kernel.org/doc/man-pages/>.