

**NAME**

`rhnpplugin.conf` – Configuration file for the **rhnpplugin(8)** **yum(8)** plugin.

**SYNOPSIS**

`/etc/yum/pluginconf.d/rhnpplugin.conf`

**DESCRIPTION**

**rhnpplugin.conf** contains configuration options which are specific to **rhnpplugin(8)**. The configuration file is located at `/etc/yum/pluginconf.d/rhnpplugin.conf`.

**[main] OPTIONS**

All options of **yum.conf(5)** are available. Most notable are:

**enabled**

Either '0' or '1'. Determines whether the plugin will be used by yum or not. Default value is '1'.

**gpgcheck**

Either '0' or '1'. Determines whether gpg signature checking will be performed on packages coming from Red Hat Network. Default value is '1'. If this option is not set, the value from **yum.conf(5)** will be used.

**timeout**

The amount of time (in seconds) that you want to wait for a response before timing out. If this option is not set, the value from **yum.conf(5)** will be used.

**[channel-label] OPTIONS**

Individual channels available to client can be configured (enabled/disabled, ...) in sections named by channel label.

**FILES**

`/etc/yum/pluginconf.d/rhnpplugin.conf`

The location of this configuration file.

**SEE ALSO**

**rhnpplugin(8)**, **yum(8)**, **up2date(5)**, **yum.conf(5)**.

**AUTHORS**

James Bowes <jbowes@redhat.com> and Peter Vetere <pvetere@redhat.com>.

**BUGS**

Report bugs to <<http://bugzilla.redhat.com>>.

**COPYRIGHT**

Copyright © 2006 Red Hat, Inc.

This is free software; see the source for copying conditions. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.