

NAME

`mq_send`, `mq_timedsend` – send a message to a message queue

SYNOPSIS

```
#include <mqueue.h>
```

```
mqd_t mq_send(mqd_t mqdes, const char *msg_ptr,
              size_t msg_len, unsigned msg_prio);
```

```
#define _XOPEN_SOURCE 600
```

```
#include <time.h>
```

```
#include <mqueue.h>
```

```
mqd_t mq_timedsend(mqd_t mqdes, const char *msg_ptr,
                  size_t msg_len, unsigned msg_prio,
                  const struct timespec *abs_timeout);
```

Link with `-lrt`.

DESCRIPTION

mq_send() adds the message pointed to by *msg_ptr* to the message queue referred to by the descriptor *mqdes*. The *msg_len* argument specifies the length of the message pointed to by *msg_ptr*; this length must be less than or equal to the queue's *mq_msgsize* attribute. Zero-length messages are allowed.

The *msg_prio* argument is a non-negative integer that specifies the priority of this message. Messages are placed on the queue in decreasing order of priority, with newer messages of the same priority being placed after older messages with the same priority.

If the message queue is already full (i.e., the number of messages on the queue equals the queue's *mq_maxmsg* attribute), then, by default, **mq_send()** blocks until sufficient space becomes available to allow the message to be queued, or until the call is interrupted by a signal handler. If the **O_NONBLOCK** flag is enabled for the message queue description, then the call instead fails immediately with the error **EAGAIN**.

mq_timedsend() behaves just like **mq_send()**, except that if the queue is full and the **O_NONBLOCK** flag is not enabled for the message queue description, then *abs_timeout* points to a structure which specifies a ceiling on the time for which the call will block. This ceiling is an absolute timeout in seconds and nanoseconds since the Epoch (midnight on the morning of 1 January 1970), specified in the following structure:

```
struct timespec {
    time_t tv_sec;      /* seconds */
    long   tv_nsec;     /* nanoseconds */
};
```

If the message queue is full, and the timeout has already expired by the time of the call, **mq_timedsend()** returns immediately.

RETURN VALUE

On success, **mq_send()** and **mq_timedsend()** return zero; on error, `-1` is returned, with *errno* set to indicate the error.

ERRORS**EAGAIN**

The queue was empty, and the **O_NONBLOCK** flag was set for the message queue description referred to by *mqdes*.

EBADF

The descriptor specified in *mqdes* was invalid.

EINTR

The call was interrupted by a signal handler; see **signal(7)**.

EINVAL

The call would have blocked, and *abs_timeout* was invalid, either because *tv_sec* was less than zero, or because *tv_nsec* was less than zero or greater than 1000 million.

EMSGSIZE

msg_len was greater than the *mq_msgsize* attribute of the message queue.

ETIMEDOUT

The call timed out before a message could be transferred.

CONFORMING TO

POSIX.1-2001.

NOTES

On Linux, **mq_timedsend()** is a system call, and **mq_send()** is a library function layered on top of that system call.

SEE ALSO

mq_close(3), **mq_getattr(3)**, **mq_notify(3)**, **mq_open(3)**, **mq_receive(3)**, **mq_unlink(3)**, **feature_test_macros(7)**, **mq_overview(7)**, **time(7)**

COLOPHON

This page is part of release 3.22 of the Linux *man-pages* project. A description of the project, and information about reporting bugs, can be found at <http://www.kernel.org/doc/man-pages/>.