

**NAME**

subscriptions.conf – subscriptions file for cups

**DESCRIPTION**

The *subscriptions.conf* file defines the local subscriptions that are active. It is normally located in the */etc/cups* directory and is generated automatically by the *cupsd(8)* program when subscriptions are created, renewed, or cancelled.

Each line in the file can be a configuration directive, a blank line, or a comment. Comment lines start with the # character.

**DIRECTIVES**

<Subscription NNN> ... </Subscription>

Defines a subscription.

Events name [ ... name ]

Specifies the events that are subscribed.

ExpirationTime unix-time

Specifies the expiration time of a subscription as a UNIX time value in seconds since January 1st, 1970.

Interval seconds

Specifies the preferred time interval for event notifications in seconds.

JobId job-id

Specifies the job ID associated with the subscription.

LeaseDuration seconds

Specifies the number of seconds that the subscription is valid for. If 0, the subscription does not expire.

NextEventId number

Specifies the next notify-sequence-number to use for the subscription.

NextSubscriptionId number

Specifies the next subscription-id to use.

Owner username

Specifies the user that owns the subscription.

PrinterName printername

Specifies the printer or class associated with the subscription.

Recipient uri

Specifies the notify-recipient-uri value for push-type notifications.

UserData hex-escaped-data

Specifies user data to be included in event notifications. This is typically the "from" address in mailto: notifications.

**SEE ALSO**

*classes.conf(5)*, *cupsd(8)*, *cupsd.conf(5)*, *mime.convs(5)*, *mime.types(5)*, *printers.conf(5)*  
<http://localhost:631/help>

**COPYRIGHT**

Copyright 2007-2009 by Apple Inc.