

**NAME**

rpc – rpc program number data base

**SYNOPSIS**

*/etc/rpc*

**DESCRIPTION**

The *rpc* file contains user readable names that can be used in place of RPC program numbers. Each line has the following information:

name of server for the RPC program  
 RPC program number  
 aliases

Items are separated by any number of blanks and/or tab characters. A '#' indicates the beginning of a comment; characters from the '#' to the end of the line are not interpreted by routines which search the file.

Here is an example of the */etc/rpc* file from the Sun RPC Source distribution.

```
#
# rpc 88/08/01 4.0 RPCSRC; from 1.12 88/02/07 SMI
#
portmapper          100000      portmap sunrpc
rstatd              100001      rstat rstat_svc rup perfmeter
rusersd             100002      rusers
nfs                  100003      nfsprog
ypserv               100004      ypprog
mountd              100005      mount showmount
ypbind              100007
walld                100008      rwall shutdown
yppasswd             100009      yppasswd
etherstat            100010      etherstat
rquotad             100011      rquotaprog quota rquota
sprayd               100012      spray
3270_mapper          100013
rje_mapper           100014
selection_svc        100015      selnsvc
database_svc         100016
rex                  100017      rex
alis                 100018
sched                100019
llockmgr             100020
nlockmgr             100021
x25.inr              100022
statmon              100023
status               100024
bootparam            100026
ypupdated            100028      ypupdate
keyserv              100029      keyserver
tfsd                 100037
nsed                 100038
nsemntd              100039
```

**FILES**

*/etc/rpc*

RPC program number data base

**SEE ALSO**

**getrpcent(3)**

**COLOPHON**

This page is part of release 3.22 of the Linux *man-pages* project. A description of the project, and information about reporting bugs, can be found at <http://www.kernel.org/doc/man-pages/>.