

NAME

nsswitch.conf – System Databases and Name Service Switch configuration file

DESCRIPTION

Various functions in the C Library need to be configured to work correctly in the local environment. Traditionally, this was done by using files (e.g., */etc/passwd*), but other nameservices (like the Network Information Service (NIS) and the Domain Name Service (DNS)) became popular, and were hacked into the C library, usually with a fixed search order.

The Linux libc5 with NYS support and the GNU C Library 2.x (libc.so.6) contain a cleaner solution of this problem. It is designed after a method used by Sun Microsystems in the C library of Solaris 2. We follow their name and call this scheme "Name Service Switch" (NSS). The sources for the "databases" and their lookup order are specified in the */etc/nsswitch.conf* file.

The following databases are available in the NSS:

aliases Mail aliases, provides a system-wide mechanism to redirect mail for local recipients. Used by mail transfer agents such as Postfix or **sendmail**(8). Note: On Linux, not like on other Unices, Sendmail uses its own aliases resolution system independent on *'/etc/nsswitch.conf'*.

ethers Ethernet numbers.

group Groups of users, used by **getgrent**(3) functions.

hosts Host names and numbers, used by **gethostbyname**(3) and similar functions.

netgroup

Network wide list of hosts and users, used for access rules. C libraries before glibc 2.1 only support netgroups over NIS.

networks

Network names and numbers, used by **getnetent**(3) functions.

passwd

User passwords, used by **getpwent**(3) functions.

protocols

Network protocols, used by **getprotoent**(3) functions.

publickey

Public and secret keys for Secure_RPC used by NFS and NIS+.

rpc Remote procedure call names and numbers, used by **getrpcbyname**(3) and similar functions.

services

Network services, used by **getservent**(3) functions.

shadow

Shadow user passwords, used by **getspnam**(3).

An example */etc/nsswitch.conf* (namely, the default used when */etc/nsswitch.conf* is missing):

```
passwd:      compat
group:       compat
shadow:      compat

hosts:       dns [!UNAVAIL=return] files
networks:    nis [NOTFOUND=return] files
ethers:      nis [NOTFOUND=return] files
protocols:   nis [NOTFOUND=return] files
rpc:         nis [NOTFOUND=return] files
services:    nis [NOTFOUND=return] files
```

The first column is the database. The rest of the line specifies how the lookup process works. You can specify the way it works for each database individually.

The configuration specification for each database can contain two different items:

- * The service specification like 'files', 'db', or 'nis'.
- * The reaction on lookup result like '[NOTFOUND=return]'.

For libc5 with NYS, the allowed service specifications are 'files', 'nis', and 'nisplus'. For hosts, you could specify 'dns' as extra service, for passwd and group 'compat', but not for shadow.

For glibc, you must have a file called `/lib/libnss_SERVICE.so.X` for every SERVICE you are using. On a standard installation, you could use 'files', 'db', 'nis', and 'nisplus'. For hosts, you could specify 'dns' as extra service, for passwd, group, and shadow 'compat'. These services will not be used by libc5 with NYS. The version number X is 1 for glibc 2.0 and 2 for glibc 2.1.

If System Security Services Daemon (SSSD) is installed on your system, you can use this service with the 'sss' keyword. SSSD supports the following databases: passwd, group, services and netgroup.

The second item in the specification gives the user much finer control on the lookup process. Action items are placed between two service names and are written within brackets. The general form is

```
'[ ( '!'? STATUS '=' ACTION )+ ]'
```

where

STATUS => success | notfound | unavail | tryagain

ACTION => return | continue

The case of the keywords is insignificant. The STATUS values are the results of a call to a lookup function of a specific service. They mean:

success No error occurred and the wanted entry is returned. The default action for this is 'return'.

notfound

The lookup process works ok but the needed value was not found. The default action is 'continue'. However, if the selected action for the 'group' database is 'return', the next lookup function is always called, without affecting the search result.

unavail

The service is permanently unavailable. This can either mean the needed file is not available, or, for DNS, the server is not available or does not allow queries. The default action is 'continue'.

tryagain

The service is temporarily unavailable. This could mean a file is locked or a server currently cannot accept more connections. The default action is 'continue'.

Interaction with +/- syntax (compat mode)

Linux libc5 without NYS does not have the name service switch but does allow the user some policy control. In `/etc/passwd` you could have entries of the form `+user` or `+%netgroup` (include the specified user from the NIS passwd map), `-user` or `-%netgroup` (exclude the specified user), and `+` (include every user, except the excluded ones, from the NIS passwd map). Since most people only put a `+` at the end of `/etc/passwd` to include everything from NIS, the switch provides a faster alternative for this case ('passwd: files nis') which doesn't require the single `+` entry in `/etc/passwd`, `/etc/group`, and `/etc/shadow`. If this is not sufficient, the NSS 'compat' service provides full +/- semantics. By default, the source is 'nis', but this may be overridden by specifying 'nisplus' as source for the pseudo-databases **passwd_compat**, **group_compat** and **shadow_compat**. These pseudo-databases are only available in GNU C Library.

FILES

A service named SERVICE is implemented by a shared object library named `libnss_SERVICE.so.X` that resides in `/lib`.

<code>/etc/nsswitch.conf</code>	configuration file
<code>/lib/libnss_compat.so.X</code>	implements 'compat' source for glibc2
<code>/lib/libnss_db.so.X</code>	implements 'db' source for glibc2
<code>/lib/libnss_dns.so.X</code>	implements 'dns' source for glibc2

<code>/lib/libnss_files.so.X</code>	implements 'files' source for glibc2
<code>/lib/libnss_hesiod.so.X</code>	implements 'hesiod' source for glibc2
<code>/lib/libnss_nis.so.X</code>	implements 'nis' source for glibc2
<code>/lib/libnss_nisplus.so.2</code>	implements 'nisplus' source for glibc 2.1

NOTES

Within each process that uses **nsswitch.conf**, the entire file is read only once; if the file is later changed, the process will continue using the old configuration.

With Solaris, it isn't possible to link programs using the NSS Service statically. With Linux, this is no problem.

COLOPHON

This page is part of release 3.22 of the Linux *man-pages* project. A description of the project, and information about reporting bugs, can be found at <http://www.kernel.org/doc/man-pages/>.