

Service Lifecycle Operations for Input

CYBOL Operation \ Channel	inline	file directory	serial port	terminal	socket	display
maintain/startup	-	-	+ (cybol, for client list)	+ (cybol, for client list)	+ (cybol)	+ (cybol)
activate/enable	-	-	-	-	+ (cybol with handler)	+ (cybol with handler)
dispatch/open	-	-	+ (cybol with handler)	+ (cybol with handler)	+ (called by enable)	+ (window id)
feel/sense	-	-	+ (called by open)	+ (called by open)	+ (called by enable)	- (global event loop)
feel/suspend	-	-	-	-	-	-
dispatch/close	-	-	-	-	+ (automatically)	+ (automatically)
activate/disable	-	-	-	-	+ (automatically)	+ (automatically)
maintain/shutdown	-	-	-	-	+ (automatically)	+ (automatically)
Display:						
open window manually so that its client entry contains a buffer						
catch events of ALL windows using global function of window system						
get id of window that the event stems from						
let event handler assign the event to the correct buffer of the corresponding client window id						
use irq pipe to inform main thread						
read sender (client window id) from irq pipe in order to assign correct handler						
use client window id in handler in order to use the correct buffer of the client entry						
Serial Port and Terminal:						
The actually have no service running in the background.						
However, maintain/startup has to be called anyway in order to allocate server resources which contain a client list that is needed to manage the terminals.						
The identification numbers of client terminals and gui windows should NOT be managed in the cybol application.						
Instead, they should be added to the cyboi-internal client list.						
When a gui event occurs, it contains the corresponding window id so that the cybol app may use it (assigned to a cybol property handed over before).						