

Service Lifecycle Operations for Input

CYBOL Operation \ Channel	inline	file directory	serial port	terminal	client socket	server socket	display
maintain/startup	-	-	+ (cybol, for client list)	+ (cybol, for client list)	-	+ (cybol)	+ (cybol)
activate/enable	-	-	-	-	-	+ (cybol with handler)	+ (cybol with handler)
dispatch/open	-	-	+ (cybol with handler)	+ (cybol with handler)	-	+ (called by enable)	+ (window id)
feel/sense	-	-	+ (called by open)	+ (called by open)	-	+ (called by enable)	- (global event loop)
communicate/receive	+	+	+	+	+	+	+
communicate/send	+	+	+	+	+	+	+
feel/suspend	-	-	-	-		-	-
dispatch/close	-	-	-	-		+ (automatically)	+ (automatically)
activate/disable	-	-	-	-		+ (automatically)	+ (automatically)
maintain/shutdown	-	-	-	-		+ (automatically)	+ (automatically)
Display:							
open window manually so that its client entry contains a buffer							
catch events of ALL windows using global function of window system							
get id of window that the event stems from							
let event handler assign the event to the correct buffer of the corresponding client window id							
use irq pipe to inform main thread							
read sender (client window id) from irq pipe in order to assign correct handler							
use client window id in handler in order to use the correct buffer of the client entry							
Serial Port and Terminal:							
The actually have no service running in the background.							
However, maintain/startup has to be called anyway in order to allocate server resources which contain a client list that is needed to manage the terminals.							
The identification numbers of client terminals and gui windows should NOT be managed in the cybol application.							
Instead, they should be added to the cybol-internal client list.							
When a gui event occurs, it contains the corresponding window id so that the cybol app may use it (assigned to a cybol property handed over before).							