

Service Lifecycle Operations for Input

CYBOL Operation \ Channel	inline	file	directory	serial port	terminal	socket	display
maintain/startup	-	-	-	+ (for client list)	+ (for client list)	+	+
activate/enable	-	-	-	-	-	+ (with handler)	+ (with handler)
dispatch/open	-	-	-	+	+	(called internally)	+ (window id)
sense/resume	-	-	-	+ (with handler)	+ (with handler)	(called internally)	-
sense/suspend	-	-	-	-	-	-	-
dispatch/close	-	-	-	-	-	+ (automatically)	+ (automatically)
activate/disable	-	-	-	-	-	+ (automatically)	+ (automatically)
maintain/shutdown	-	-	-	-	-	+ (automatically)	+ (automatically)
Display:							
open window manually so that its client entry contains a buffer							
catch events of ALL windows using global function of window system							
get id of window that the event stems from							
let event handler assign the event to the correct buffer of the corresponding client window id							
use irq pipe to inform main thread							
read sender (client window id) from irq pipe in order to assign correct handler							
use client window id in handler in order to use the correct buffer of the client entry							
Serial Port and Terminal:							
The actually have no service running in the background.							
However, maintain/startup has to be called anyway in order to allocate server resources which contain a client list that is needed to manage the terminals.							