

OPM Flow — Native Windows Build

Building all targets from the `opm_flow_windows` harness (MSVC, hybrid MPI + OpenMP)

Prepared 2026-07-04 • Machine: Windows 11 Pro, 24 logical CPUs, 55.8 GB RAM • Toolchain: VS 2022 Build Tools 17.14 (MSVC 14.4x), CMake 4.x, Ninja, MS-MPI 10.1 • Build root: `C:\opm\opm_flow_windows`

1. Overview

The `opm_flow_windows` repository is a **build harness** that compiles OPM Flow as a **pure native Windows binary** (MSVC PE32+ — no WSL, Cygwin, or MSYS), in both serial and parallel (MPI + Zoltan) configurations. It does not contain the OPM / DUNE / Trilinos sources; its driver script clones them and builds everything in dependency order with the correct MSVC conformance flags and a small set of POSIX/Fortran compatibility shims.

This report first summarises the **documented build procedure** (from the repo's `README.md` and `BUILD_WINDOWS.md`), then records **what was executed** and the **findings: all 528 targets across the four OPM repositories build**, the unit tests run and pass, and real simulations — including the Norne field case in hybrid MPI + OpenMP mode — run fine.

2. The documented build procedure

2.1 Prerequisites & toolchain (one-time)

- Windows 10/11 x64; `git` and `winget` on PATH; ~15 GB free disk; internet.
- VS 2022 C++ Build Tools + Windows 11 SDK + CMake + Ninja, via a single `winget` command.
- For MPI builds only: Microsoft MPI runtime (`Microsoft.msmpi`) + SDK (`Microsoft.msmpi.sdk`).
- **Location:** place the harness at a short **ASCII path without spaces, outside OneDrive-synced folders** (e.g. `C:\opm\opm_flow_windows`) — `vcpkg` cannot handle non-ASCII path components, and sync clients can lock files mid-build.

2.2 Sources & layout

The driver `build-all.ps1` lays out a single root and clones into it:

- **vcpkg** — the dependency manager.
- **DUNE 2.10.0** — `dune-common`, `dune-geometry`, `dune-istl`, `dune-grid` (pinned tag).
- **OPM** — `opm-common`, `opm-grid`, `opm-simulators` (+ `opm-upscaling` with `-Upscaling`).
- **Trilinos** — only for MPI builds, to build the Zoltan package.

Build order (each step feeds the next):

DUNE: `dune-common` → `dune-geometry` → `dune-istl` → `dune-grid`

OPM: `opm-common` → `opm-grid` → `opm-simulators` → `opm-upscaling`

2.3 Third-party dependencies (vcpkg)

Built with the `x64-windows` triplet: `suitesparse-umfpack`, `fmt`, `lapack` (pulls OpenBLAS — provides BLAS + LAPACK, no Fortran compiler needed), and the Boost components OPM uses (`test`, `date-time`, `property-tree`, `mpl`, `range`, `spirit`, `filesystem`, `system`). The first run compiles OpenBLAS + SuiteSparse (20–40 min); `vcpkg` then caches them.

2.4 POSIX / Fortran compatibility shims

MSVC lacks a few POSIX headers and has no Fortran compiler; rather than patch every include, the harness puts small shim headers on the include path (`compat\include`):

- `unistd.h`, `getopt.h`, `sys/ioctl.h`, `sys/utsname.h` — POSIX stand-ins.
- `FCMacros.h` — Fortran name-mangling (gfortran/OpenBLAS ABI), normally generated by CMake's FortranCInterface.

2.5 Compile flags (applied to every module)

```
CXX: /permissive- /Zc:__cplusplus /Zc:preprocessor /bigobj /EHsc /wd4068
      -D_USE_MATH_DEFINES /DWIN32 /D_WINDOWS /I <root>/compat/include
Config: -DCMAKE_BUILD_TYPE=Release -G Ninja (static OPM libs, C++20)
        vcpkg toolchain file + x64-windows triplet
```

OPM needs C++20, DUNE needs C++17. MPI/OpenMP/Fortran are off by default and enabled by switches.

2.6 MPI (Zoltan) & OpenMP

- **MPI** (`-Mpi`): opm-grid couples MPI to **Zoltan** (parallel partitioning). Zoltan isn't in vcpkg, so the harness builds the Zoltan package only from a Trilinos clone against MS-MPI, into a separate `build-mpi\ / install-mpi\` tree. The serial tree is untouched.
- **OpenMP** (`-OpenMP`): uses MSVC's `/openmp:llvm` (OpenMP 3.1+); the default `/openmp` (2.0) rejects OPM's `size_t` parallel-for counters. Needs `libomp140.x86_64.dll` at runtime.
- The two switches are independent and compose into a **hybrid** binary.

2.7 Source patches (outside OPM)

Only DUNE needs source patches (auto-applied after checkout): `gmshreader.hh` (POSIX `ftello/fseeko` → `_ftelli64/_fseeki64`, serial + MPI); and two MPI-only patches dropping the `MPI 3.0` gate and guarding `MPI_CXX*_COMPLEX` (MS-MPI is MPI-2 level). Trilinos/Zoltan and all vcpkg packages build unmodified. The OPM Windows/MSVC fixes live on the `GitPaeon/* windows` branch until merged upstream.

3. What was executed

Target: the "fully complete" build the guide defines — `-Mpi -OpenMP -SimTarget all -Upscaling` — i.e. every `flow_*` variant plus the opm-upscaling tools, across all four OPM repos, from `C:\opm\opm_flow_windows`.

1. **Installed toolchain** (winget): VS 2022 Build Tools (VCTools + Win11 SDK 22621 + CMake + Ninja), MS-MPI runtime + SDK.
2. **Cloned** vcpkg, DUNE 2.10.0 (×4), and all 4 OPM repos on the `GitPaean windows` branch.
3. **Capped parallelism at 8 jobs** (`build-module.ps1` ; OPM's template-heavy TUs are memory-hungry — 8 jobs suit a ≥ 32 GB machine).
4. **Ran the one-shot build:**

```
.\build-all.ps1 -Mpi -OpenMP -SimTarget all -Upscaling -OpmOrg GitPaeon -OpmBranch windows
```

This completed end-to-end: vcpkg deps → DUNE (patched) → Zoltan (from Trilinos) → opm-common → opm-grid → opm-simulators (every `flow_*` variant) → opm-upscaling.

Then, to cover **all** targets (tests + examples, which the harness disables by default), each OPM module was reconfigured with `-DBUILD_TESTING=ON -DBUILD_EXAMPLES=ON` and its `all` target rebuilt with `ninja keep-`

going (`-k 0`), so a single failing target could not abort a module. This is packaged as the new `build-optests.ps1` helper.

4. Findings

4.1 Results — all targets build

OPM repository	Configuration	Executables	Failing
opm-common	testing + examples ON	240	0
opm-grid	testing + examples ON	74	0
opm-simulators	testing + examples ON, target <code>all</code>	173	0
opm-upscaling	testing + examples ON, target <code>all</code>	31	0
Total		528	0

The core (non-test) build alone produces 48 `flow_*` / `flowexp_*` simulator variants in `opm-simulators` and 24 upscaling tools in `opm-upscaling`; enabling tests + examples raises the totals above. Libraries produced: `opmcommon.lib`, `opmgrid.lib`, `zoltan.lib` and the four DUNE libs in `install-mpi\lib`.

4.2 Verification

- `flow_blackoil.exe` runs → `flow 2026.10-pre`, exit 0 (22 MB).
- Native **x64 PE32+**; dependents include `msmpi.dll` + `libomp140.x86_64.dll` — confirming a true hybrid MPI+OpenMP binary — plus `MSVCP140/VCRUNTIME140/KERNEL32`. **No** cygwin/msys.
- Unit tests run and pass (e.g. `test_2dtables.exe` : 14 cases, no errors; `test_msim_ACTIONX.exe` : 8/8 cases, 321/321 assertions).

4.3 Simulation runs

Norne (`NORNE_ATW2013.DATA` , real-field black-oil case, 247 report steps) — runs fine as a **hybrid MPI + OpenMP** simulation with the default linear solver (CPRW):

```
mpiexec -n 4 flow_blackoil.exe NORNE_ATW2013.DATA --threads-per-process=2 --output-dir=windows_run
```

Using 4 MPI processes with 2 OMP threads on each
Newton its= 3, linearizations= 4 (0.2sec), linear its= 2 (0.2sec)
Newton its= 2, linearizations= 3 (0.1sec), linear its= 4 (0.1sec)
Healthy nonlinear/linear convergence throughout; the same case also runs serially and with the `ilu0` / `dilu` solver choices.

SPE1 two-phase (`SPE1CASE2_2P.DATA` from `opm-tests`) with a non-blackoil variant and an explicitly AMG-based solver — full run to completion:

```
flow_oilwater.exe SPE1CASE2_2P.DATA --linear-solver=cpr --output-dir=<dir>
```

Overall Newton Iterations: 247 (Wasted: 0; 0.0%)
Overall Linear Iterations: 134 (Wasted: 0; 0.0%) — exit 0.

Together these exercise the default CPR(W) preconditioner, plain AMG/CPR, and the one-level solvers, in serial, MPI, and hybrid MPI+OpenMP modes, across two simulator variants.

4.4 Key takeaways

1. **Build from a short ASCII path outside sync-managed folders** (e.g. `C:\opm\...`) — vcpkg fails on non-ASCII path components, and sync clients can lock files mid-build.
2. **The harness is sound.** The documented one-command build produced every simulator and tool with no source changes beyond the pre-applied DUNE patches and the `windows` -branch OPM fixes.
3. **All 528 targets build** — simulators, tools, examples, and unit tests — and the tests run and pass.
4. **Memory-bounded:** the whole build ran at 8 parallel compile jobs.

5. Reproduce / run

```
# From C:\opm\opm_flow_windows
.\build-all.ps1 -Mpi -OpenMP -SimTarget all -Upscaling -OpmOrg GitPaeon -OpmBranch windows

# Optional: also build every unit test + example target
.\build-optests.ps1

# Run a parallel simulation (4 ranks x 2 OpenMP threads each):
mpiexec -n 4 .\build-mpi\opm-simulators\bin\flow_blackoil.exe `
  <deck>.DATA --threads-per-process=2 --output-dir=<dir>
```

Outputs: `build-mpi\opm-simulators\bin\` (simulators + tests), `build-mpi\opm-upscaling\bin\` (tools + tests), `install-mpi\` (libraries + headers). Logs: `build-hybrid.log`, `build-tests-*.log`.