



**A**

## **Project Report on**

### **“VOICE CONTROLLED AI ROBOT (VOCIBOT)”**

*Submitted In partial fulfillment of requirement for the award of Degree in  
Bachelor of Technology in*

### **Electronics & Telecommunication Engineering**

**Submitted By**

- |                           |                           |
|---------------------------|---------------------------|
| <b>1) Reshma Satpute</b>  | <b>2) Raksha Sonewane</b> |
| <b>3) Vedant Pathrabe</b> | <b>4) Lavanya Gabhane</b> |
| <b>5) Mahek Gupta</b>     |                           |

**Under the guidance of**

**Dr. J. Y. Hande**

**Department of Electronics & Telecommunication Engineering**

**Priyadarshini Bhagwati College of Engineering, Nagpur**

**An Autonomous Instituted Affiliated to RTMNU, Nagpur**

**Accredited with grade ‘A’ by NAAC**

**Hapur Nagar, Umred Road, Nagpur – 440024**

**Session 2025-2026**

# **Priyadarshini Bhagwati Collage Of Engineering, Nagpur**

An Autonomous Instituted Affiliated to RTMNU, Nagpur

Accredited with grade 'A' by NAAC

Hapur Nagar, Umred Road, Nagpur – 440024



## **Department of Electronics & Telecommunication Engineering**

### **Certificate**

This is to certify that the

**“VOICE CONTROLLED AI ROBOT (VOCIBOT)”**

Has been successfully completed by

- |                    |                    |
|--------------------|--------------------|
| 1) Reshma Satpute  | 2) Vedant Pathrabe |
| 3) Raksha sonewane | 4) Lavanya Gabhane |
| 5) Mahek Gupta     |                    |

Under the guidance of Dr.J.Y.Hande in recognition to the partial fulfillment for award of degree of Bachelor of Technology in Electronics & Telecommunication Engineering , from Rashtrasant Tukadoji Maharaj Nagpur University, Nagpur for the session 2025-2026.

**Dr. J. Y. Hande**  
Asst. Professor (ETC)

**Dr.P.B.Pokle**  
H.O.D (ETC)

**Dr. A. M. Shende**  
Principal

## **DECLARATION**

We, Reshma Satpute, Vedant Pathrabe, Raksha Sonewane, Lavanya Gabhane, Mahek Gupta student of 8<sup>th</sup> semester, B-Tech, 2025-26, Electronics and Telecommunication Engineering hereby declare that all the statement made in this report are true, complete and correct to the best of my knowledge.

Reshma Satpute (ET806)

Vedant Pathrabe (ET827)

Raksha Sonewane (ET830)

Lavanya Gabhane (ET839)

Mahek Gupta (ET849)

**Date:**

**Place: PBCoE, Nagpur**

## **ACKNOWLEDGEMENT**

The success of any work depends on efforts of many individuals. We would like to take this opportunity to express our deep gratitude to those who extended their support and have guided us to complete this project work.

We wish to express our sincere and deepest gratitude to our guide **Dr. J.Y.Hande** for his invaluable and unique guidance. We would also like to thank him for the constant source of help, inspiration and encouragement in this successful completion of project. It has been our privilege and pleasure to work under his expert guidance.

We would like to thank **Dr. P. B. Pokle (H.O.D)** for providing us the necessary information. We would again like to thank **Dr. A. M. Shende**, principal of our college, for providing us the necessary help and facilities we required.

We express our sincere thanks to all the staff members of the Electronics and Telecommunication department who directly or indirectly have extended their kind cooperation in the completion of this Project Report.

We would like to thank our friends and colleagues for their co-operation and help towards the completion of this Project Report.

**Date:**

**Place:** Nagpur

**PROJECTEES**

Mahek Gupta

Vedant Pathrabe

Lavanya Gabhane

Raksha Sonewane

Reshma Satpute

## LIST OF FIGURES/ PHOTOS

| Figure No | Name                                                                    | Page No |
|-----------|-------------------------------------------------------------------------|---------|
| 4.1       | Arduino Uno Microcontroller                                             | 15      |
| 4.2       | L293D Motor Driver Module                                               | 16      |
| 4.3       | HC-05 Bluetooth Module                                                  | 17      |
| 4.4       | Speaker                                                                 | 17      |
| 4.5       | Mobile Voice Control Application                                        | 19      |
| 4.6       | Circuit diagram Of Arduino Uno with L293D Motor Driver and DC motor     | 20      |
| 4.7       | Circuit Diagram of Audio Playback Module with Speaker and Camera System | 20      |
| 4.8       | Block Diagram                                                           | 21      |
| 4.9       | Flowchart od Vocibot                                                    | 22      |
|           | Review Paper                                                            | 30-31   |
|           | Certificates Of Review Paper                                            | 32      |
|           | Research Paper Images                                                   | 33-35   |
|           | Certificates Of Research paper                                          | 36      |
|           | Project Poster                                                          | 37      |
|           | Project Images                                                          | 37      |

# INDEX

| TITLE                                       | ..... | PAGE NO |
|---------------------------------------------|-------|---------|
| CERTIFICATE                                 | ..... | 2       |
| DECLARATION                                 | ..... | 3       |
| ACKNOWLEDGEMENT                             | ..... | 4       |
| ABSTRACT                                    | ..... | 7       |
| 1) INTRODUCTION                             | ..... | 8-9     |
| 2) LITERATURE SURVEY                        | ..... | 10-12   |
| 3) PROBLEM DEFINITION, AIM AND OBJECTIVE    | ..... | 13-14   |
| 4) SYSTEM DESIGN                            | ..... | 15      |
| Arduino Uno Microcontroller                 | ..... | 16      |
| L293D Motor Driver                          | ..... | 17      |
| HC-05 Bluetooth Module                      | ..... | 17-18   |
| Audio Output System (speaker and Amplifier) | ..... | 18      |
| SOFTWARE                                    | ..... | 19-20   |
| Circuit Diagram                             | ..... | 21      |
| Block Diagram                               | ..... | 22      |
| Flowchart                                   | ..... | 23      |
| 5) METHODOLOGY                              | ..... | 24-25   |
| 6) RESULT AND DISCUSSION AND FUTURE SCOPE   | ..... | 26-27   |
| 7) CONCLUSION                               | ..... | 28-29   |
| 8) REFERENCE                                | ..... | 30-31   |
| 9) PROJECT PUBLICATION                      | ..... | 35      |
| REVIEW PAPER PUBLICATION                    | ..... | 35-36   |
| CERTIFICATION OF REVIEW PAPER               | ..... | 37      |
| RESEARCH PAPER                              | ..... | 38-40   |
| CERTIFICATE OF RESEARCH PAPER               | ..... | 41      |
| PROJECT POSTER                              | ..... | 42      |
| PROJECT IMAGE                               | ..... | 42      |

## **ABSTRACT**

Voice-controlled AI robots represent a transformative advancement in human-machine interaction, enabling intuitive, natural, and hands-free control of robotic systems. With rapid developments in artificial intelligence, embedded systems, and wireless communication technologies, voice-based robotic platforms have evolved from simple command-execution systems to increasingly intelligent and autonomous machines. This thesis presents a comprehensive review and analytical study of existing voice-controlled robotic architectures, examining both hardware and software perspectives.

The research explores core components of such systems, including speech recognition techniques (cloud-based and on-device processing), natural language processing mechanisms, embedded control platforms, wireless communication protocols, motor driver configurations, and multimedia feedback integration. Particular emphasis is placed on the comparative evaluation of Bluetooth- and Wi-Fi-based robotic systems implemented using Arduino and ESP32 microcontroller platforms. Their performance is analyzed in terms of latency, response accuracy, scalability, processing capability, power consumption, cost-effectiveness, and real-time operational efficiency.

Furthermore, the study investigates system design challenges such as noise sensitivity, connectivity reliability, limited onboard computational power, and energy constraints. Security concerns in wireless communication and IoT-enabled robotic environments are also addressed. Through experimental analysis and literature review, the thesis identifies key research gaps related to autonomy, robustness in dynamic environments, adaptive learning capabilities, and edge intelligence.

Finally, this work outlines future research directions aimed at enhancing real-time decision-making, integrating on-device artificial intelligence models, improving multimodal interaction, and enabling seamless IoT connectivity. The findings contribute to the development of more reliable, scalable, and intelligent voice-controlled robotic systems suitable for applications in smart homes, healthcare, industrial automation, assistive technologies, and service robotics.

# **CHAPTER 1**

## **INTRODUCTION**

## INTRODUCTION

Voice-controlled robotic systems have emerged as a significant area of research due to rapid advancements in automatic speech recognition (ASR), artificial intelligence (AI), embedded systems, and wireless communication technologies. The integration of these technologies has enabled the development of intuitive human–robot interaction (HRI) systems, where natural voice commands replace conventional manual interfaces such as joysticks, keypads, and remote controllers. This shift enhances accessibility, operational efficiency, and user convenience across a wide range of applications.

In recent years, intelligent robotic systems have gained widespread adoption in fields such as industrial automation, healthcare, surveillance, defense, and domestic environments. Traditional control methods, although effective, often limit seamless interaction between humans and machines. Voice recognition technology provides a more natural and efficient alternative by enabling hands-free control and real-time interaction, making it particularly useful in assistive and remote-control applications.

This project, titled VOCIBOT, focuses on the design and development of a voice-controlled AI robotic assistant integrated with wireless communication and real-time monitoring capabilities. The system is implemented using embedded platforms such as Arduino and ESP32, along with modules including Bluetooth, motor drivers, and camera systems. It combines AI-based voice command processing, robotic movement control, and live video streaming into a single intelligent platform.

The proposed system aims to enhance human–machine interaction by providing a cost-effective, scalable, and user-friendly robotic solution capable of operating in both manual and autonomous environments.

Furthermore, VOCIBOT integrates multiple functionalities beyond basic robotic movement, including voice-based control, wireless communication, and real-time video monitoring. The system enables seamless interaction between the user and the robot through mobile applications and Bluetooth/Wi-Fi connectivity, allowing efficient remote operation. The inclusion of a wireless camera module enhances the system by providing live visual feedback, improving usability in surveillance and monitoring applications. The modular design of the system allows future expansion, such as the integration of additional sensors, cloud connectivity, and advanced AI-based features, making VOCIBOT a scalable and adaptable robotic platform.

## **CHAPTER 2**

### **LITERATURE SURVEY**

## LITERATURE SURVEY

**1. Elmzaghi, M., Fahad, M., & Guo, Y. (2019). Implementing Robust Voice-Control for Human Robot Interaction for Autonomous Robot Guides. In 2019 IEEE MIT Undergraduate Research Technology Conference, URTC 2019 (2019 IEEE MIT Undergraduate Research Technology Conference, URTC 2019). <https://doi.org/10.1109/URTC49097.2019.9660499>**

This paper presents a robust voice-control system for autonomous robot guides operating in real-world environments. It focuses on improving speech recognition accuracy under noise and dynamic conditions. The system enhances human-robot interaction through reliable real-time command processing.

**2. R. K. Megalingam, R. S. Reddy, Y. Jahnavi and M. Motheram, "ROS Based Control of Robot Using Voice Recognition," 2019 Third International Conference on Inventive Systems and Control (ICISC), Coimbatore, India, 2019, pp. 501-507, doi: 10.1109/ICISC44355.2019.9036443.**

This study develops a voice-controlled mobile robot using ROS and PocketSphinx for speech recognition. It uses Hidden Markov Models to interpret voice commands and control robot movement. The system demonstrates effective real-time navigation through voice input.

**3. S. Poirier, F. Routhier and A. Campeau-Lecours, "Voice Control Interface Prototype for Assistive Robots for People Living with Upper Limb Disabilities," 2019 IEEE 16th International Conference on Rehabilitation Robotics (ICORR), Toronto, ON, Canada, 2019, pp. 46-52, doi: 10.1109/ICORR.2019.8779524.**

The paper introduces a voice control interface designed for assistive robots used by people with upper limb disabilities. It emphasizes usability, task efficiency, and accessibility. The system improves independence by enabling hands-free robot operation.

**4. Li, S.-A.; Liu, Y.-Y.; Chen, Y.-C.; Feng, H.-M.; Shen, P.-K.; Wu, Y.-C. Voice Interaction Recognition Design in Real-Life Scenario Mobile Robot Applications. Appl. Sci. 2023, 13, 3359, MDPI Journal. <https://doi.org/10.3390/app13053359>**

This research focuses on voice interaction in mobile robots using deep learning-based speech recognition. It integrates voice commands with real-time navigation systems like SLAM. The system performs effectively in real-life noisy environments.

**5. A. Chatterjee, K. Pulasinghe, K. Watanabe and K. Izumi, "A particle-swarm-optimized fuzzy-neural network for voice-controlled robot systems," in IEEE Transactions on Industrial Electronics, vol. 52, no. 6, pp. 1478-1489, Dec. 2005, doi: 10.1109/TIE.2005.858737.**

This paper proposes a hybrid AI model combining fuzzy logic, neural networks, and particle swarm optimization for voice-controlled robots. It improves accuracy and adaptability in interpreting voice commands. The approach enhances intelligent decision-making in robotic systems.

**6. Lu, Y., Li, L., Chen, S., & Qiang, H. (2010). Voice based control for humanoid teleoperation. In Proceedings - 2010 International Conference on Intelligent System Design and Engineering Application, ISDEA 2010 (pp. 814-818). Article 5743532 (Proceedings - 2010 International Conference on Intelligent System Design and Engineering Application, ISDEA 2010; Vol. 2). IEEE Computer Society. <https://doi.org/10.1109/ISDEA.2010.430>**

The study presents a voice-based control system for humanoid robot teleoperation. It allows users to control robot actions remotely using speech commands. The system provides a natural and intuitive human-machine interaction interface.

**7. C. Pornpanomchai and P. Sukklay, “Controlling a Robot Arm by Thai Voice Commands,” AMM, vol. 110–116, pp. 5189–5194, Oct. 2011, doi: 10.4028/www.scientific.net/amm.110-116.5189.**

This research demonstrates a robot arm controlled using voice commands in the Thai language. It evaluates system accuracy and performance in different environments. The results show high accuracy in controlled conditions.

**8. Parikka, O., & Pieters, R. (2025). LMPVC and Policy Bank: Adaptive voice control for industrial robots with code generating LLMs and reusable Pythonic policies. ArXiv. <https://arxiv.org/abs/2506.22028>**

This paper introduces an advanced voice control system using Large Language Models (LLMs) for industrial robots. It generates executable code from voice commands and uses reusable policy structures. The approach enables adaptive and intelligent robot behavior.

**9. Chang, P., Liu, S., McPherson, D. L., & Driggs-Campbell, K. (2021). Learning Visual-Audio Representations for Voice-Controlled Robots. ArXiv. <https://arxiv.org/abs/2109.02823>**

This study explores multimodal learning by combining audio and visual data for voice-controlled robots. It uses deep learning to improve command understanding and environmental awareness. The system enhances robot perception and interaction capabilities.

# **CHAPTER 3**

## **PROBLEM DEFINITION, AIM AND OBJECTIVE**

## **PROBLEM DEFINITION, AIM AND OBJECTIVE**

### **1. Problem Definition**

With the increasing adoption of automation and robotics across sectors such as healthcare, defense, surveillance, and domestic environments, there is a growing need for more intuitive and efficient human–robot interaction (HRI). Traditional robotic control systems rely heavily on manual interfaces like joysticks, switches, and mobile applications, which limit user convenience, accessibility, and real-time responsiveness.

These conventional control methods are not suitable for individuals with physical disabilities and can be inefficient in situations requiring hands-free or remote operation. Additionally, many existing robotic systems lack integrated real-time monitoring capabilities, such as live video and audio feedback, which are crucial for surveillance and security applications.

Although voice recognition technology has advanced significantly with the help of Artificial Intelligence (AI) and Automatic Speech Recognition (ASR), its integration into compact, low-cost robotic systems with wireless communication and real-time monitoring remains limited. Therefore, there is a need to develop a smart robotic system that combines voice-based control, wireless communication, and live audio-video streaming into a unified platform.

### **2. Aim**

The main aim of this project is to design and develop a Voice Controlled AI Robot with Wireless Camera and Audio System that enables intuitive human–robot interaction using voice commands, while providing real-time video and audio monitoring through wireless communication technologies.

### **3. Objectives**

- To design a voice-controlled robotic system  
Develop a robot that can interpret and execute user voice commands using AI-based speech recognition.
- To improve human–robot interaction (HRI)  
Replace traditional manual controls with natural voice-based interaction for better usability and accessibility.
- To enhance safety and remote operability  
Enable hands-free operation and real-time monitoring for use in hazardous or inaccessible environments.

## **CHAPTER 4**

### **SYSTEM DESIGN**

## SYSTEM DESIGN

### *Hardware Components*

The hardware architecture of the proposed VOCIBOT (Voice-Controlled Intelligent Bot) is designed to provide reliable performance, modular integration, and efficient power management. The system integrates multiple embedded components including a microcontroller, wireless communication modules, actuators, power management units, and audio-visual devices to enable intelligent robotic interaction.

### *Arduino Uno Microcontroller*

The Arduino Uno serves as the primary control unit of the robotic platform. It is based on the ATmega328P microcontroller and is responsible for processing incoming commands received through the Bluetooth communication interface. The controller interprets these commands and generates appropriate control signals to drive the motors through the motor driver module.



Fig. 4.1: Arduino Uno Microcontroller

Arduino-based controllers are widely used in robotic systems due to their ease of programming, low cost, and compatibility with various peripheral modules. The Arduino IDE allows rapid development and debugging of embedded firmware, making it suitable for academic and prototype-based robotic systems.

The microcontroller manages the following functions:

- Decoding wireless control commands
- Generating motor control signals
- Managing robot navigation logic
- Interfacing with motor driver circuits

## ***L293D Motor Driver***

The L293D Motor Driver IC is a dual H-bridge integrated circuit used to control the direction and speed of DC motors in embedded and robotic systems. It serves as an interface between low-power controls devices such as microcontrollers and high-power components like motors.

An H-bridge circuit allows a motor to rotate in both directions by reversing the polarity of the applied voltage. The L293D contains two internal H-bridge circuits, enabling independent control of two DC motors. This makes it suitable for applications requiring simultaneous control of multiple actuators.



Fig. 4.2: L293D Motor Driver Module

### ***Working Principle***

The motor driver receives digital input signals from a microcontroller and converts them into appropriate output signals to drive the motors. Each motor is controlled using:

- Two input pins (IN1, IN2 / IN3, IN4) for direction control
- One enable pin (EN1 / EN2) for enabling and speed control

The enable pins can be connected to PWM signals, allowing control over motor speed by adjusting the duty cycle.

The L293D supports:

- Bidirectional motor rotation
- Independent motor control
- Current amplification for DC motors

This configuration enables the robot to perform movements such as forward motion, backward motion, left turn, right turn, and stop operations.

## ***HC-05 Bluetooth Module***

Wireless communication between the robotic platform and the mobile application is established using the HC-05 Bluetooth module. The module operates using the Serial Communication Protocol (UART), allowing easy integration with the Arduino microcontroller.

The HC-05 module receives control commands generated by the mobile voice recognition application and transmits them to the Arduino controller.




Fig. 4.3: HC- 05 Bluetooth Module

Advantages of the HC-05 module include:

- Low power consumption
- Reliable short-range wireless communication
- Easy serial interface with microcontrollers.

#### ***Audio Output System (Speaker and Amplifier)***

To enable audio interaction, the system includes a speaker connected through a small audio amplifier module. The amplifier increases the output audio signal strength to produce clear voice responses generated by the AI system.

The speaker is used to play responses received from the AI based assistant (Gemini), allowing the robot to interact with users through voice output. This component enables the robot to function not only as a mobility platform but also as an interactive AI-based assistant



Fig. 4.4: Speaker 4 $\Omega$  / 8 $\Omega$

## **SOFTWARE**

### ***Software Implementation***

The software architecture of the VOCIBOT system consists of embedded firmware running on the microcontroller and external software applications responsible for voice processing and artificial intelligence integration.

#### ***Embedded Firmware (Arduino IDE)***

The embedded firmware is developed using the Arduino Integrated Development Environment (IDE) and programmed in Embedded C. The firmware controls the robot's movement by interpreting commands received through the Bluetooth communication module.

The firmware performs several tasks including:

- Serial communication with Bluetooth module
- Command decoding
- Motor driver control
- Movement execution

The robot follows a command-based navigation logic where each movement corresponds to a predefined instruction. Example control commands include:

- Forward movement
- Backward movement
- Left turn
- Right turn
- Stop

This simple yet effective command-based architecture ensures fast response and reliable control.

#### ***Mobile Voice Control Application***

A mobile voice control application is used to convert spoken commands into digital control instructions. The application utilizes the smartphone's built-in speech recognition capabilities to process user voice input.

Once the voice command is recognized, the application maps it to a predefined control signal and sends it to the robot through the Bluetooth module

The mobile application interface allows users to:

- Connect to the robot via Bluetooth
- Issue voice commands
- Control robot movement

- Adjust movement speed




Fig. 4.5: Mobile Voice Control Application

The user interface of the application is shown in the figure above, where directional controls and a microphone button enable voice-based navigation.

### AI Interaction using Gemini

For intelligent conversational interaction, the system integrates Google Gemini AI through an external device such as a smartphone or computer. Gemini processes user queries and generates appropriate responses using natural language processing. When the user asks a question, the mobile application sends the request to the Gemini AI system. The generated response is converted into speech and played through the Robot's speaker system. This integration enables the robot to function not only as a remotely controlled vehicle but also as an AI-powered interactive assistant capable of answering questions and providing information.

### Camera Streaming Interface

The ESP32-CAM module runs independent firmware responsible for Wi-Fi connection and live video streaming. Users can access the camera feed through a web interface or mobile application. The camera provides continuous visual feedback from the robot's environment, allowing remote monitoring and enhancing operational awareness during robot movement.

## CIRCUIT DIAGRAM




Fig. 4.6: Circuit Diagram of Arduino UNO with L293D Motor Driver and DC Motors




Fig. 4.7: Circuit Diagram of Audio Playback Module with Speaker and Camera System

## BLOCK DIAGRAM





Fig. 4.8: Block Diagram



**Fig. 4.9: Flowchart of Vocibot**

## **CHAPTER 5**

### **METHODOLOGY**

## **METHODOLOGY**

The methodology of VOCIBOT describes the systematic approach followed for the design and implementation of a voice-controlled robotic system. The system integrates voice recognition, wireless communication, embedded processing, and motor actuation to achieve efficient human–robot interaction.

The overall operation of the system is carried out in a sequence of stages, beginning from user input to the execution of actions by the robot.

### **1. Voice Input Acquisition**

The process begins with the user providing voice commands through a mobile application equipped with voice recognition capability. The spoken commands are captured using the smartphone microphone and converted into text or predefined command signals using built-in speech processing algorithms.

### **2. Command Processing and Transmission**

The converted command is transmitted wirelessly to the robotic system using the HC-05 Bluetooth module. The module communicates with the Arduino microcontroller through UART (Universal Asynchronous Receiver Transmitter) protocol, ensuring reliable serial data transmission.

### **3. Data Reception and Interpretation**

The Arduino microcontroller receives the transmitted command via serial communication and processes it by comparing the input with predefined command instructions programmed into the system. Based on the recognized command, the controller determines the appropriate action to be performed.

### **4. Motor Control and Robot Movement**

The processed command is converted into control signals that are sent to the motor driver (L293D). The motor driver acts as an interface between the Arduino and the DC motors, allowing control of motor direction and movement. Based on the command, the robot performs actions such as forward movement, backward movement, left turn, or right turn.

### **5. System Integration and Execution**

All system components, including the voice input interface, Bluetooth communication module, microcontroller, motor driver, and motors, are integrated to function as a unified system. The system operates in real-time, ensuring minimal delay between command input and robot response, resulting in smooth and efficient operation.

**CHAPTER 6**  
**RESULT, DISCUSSIONS AND**  
**FUTURE SCOPE**

## ***Result***

The VOCIBOT system was successfully designed, implemented, and tested. The robot demonstrated accurate response to voice commands received through the mobile application. It was able to perform directional movements such as forward, backward, left, and right with consistent and reliable control.

The use of the HC-05 Bluetooth module enabled stable wireless communication between the mobile device and the robotic system. The data transmission was smooth, and the system exhibited low response time, ensuring real-time interaction. During testing, the robot operated effectively within the specified communication range and maintained stable performance in indoor environments.

Overall, the system achieved its intended functionality of voice-controlled robotic operation with satisfactory accuracy and efficiency.

## ***Discussion***

The developed VOCIBOT system demonstrates a practical implementation of voice-controlled robotics, improving human–robot interaction by replacing traditional manual control methods with natural speech-based commands. This approach enhances user convenience and allows hands-free operation of the robotic system.

The system performance was found to be reliable, with quick response to commands and smooth motor operation. However, certain limitations were observed during testing. The accuracy of voice recognition is influenced by factors such as background noise, pronunciation differences, and speech clarity. Additionally, the Bluetooth communication module restricts the operational range of the robot, limiting its use to short-distance applications.

Despite these limitations, the system proves to be cost-effective, easy to implement, and suitable for basic automation and assistive applications. The modular design of the system allows further improvements and scalability for advanced use cases.

## ***Future Scope***

- Integration of WiFi or IoT-based communication to enable long-range and remote operation
- Enhancement of voice recognition accuracy using advanced speech processing techniques
- Implementation of noise reduction methods to improve performance in noisy environments
- Development of a dedicated mobile application with improved interface and additional control features
- Integration of sensor modules for autonomous functionality and intelligent decision-making
- Improvement in power management and battery efficiency for longer operational time

## **CHAPTER 7**

## **CONCLUSION**

## CONCLUSION

The project successfully demonstrates the design and development of a voice-controlled AI-based robotic system integrated with wireless video streaming and audio capabilities. The system effectively combines embedded hardware and intelligent software to enable seamless human–robot interaction through natural voice commands. By eliminating traditional manual control methods, the robot provides a more intuitive and user-friendly interface, enhancing accessibility and operational convenience.

The implementation of wireless communication using the HC-05 Bluetooth Module ensures reliable command transmission between the user and the robot, while the integration of the ESP32-CAM Module enables real-time video streaming for effective remote monitoring. Additionally, the motor control mechanism using the L293D Motor Driver IC allows precise and responsive movement based on user input.

The system demonstrates efficient coordination between different subsystems, including speech recognition, wireless communication, motor actuation, and visual feedback. This integration highlights the practical application of concepts from artificial intelligence, embedded systems, and IoT in developing modern robotic solutions. The robot is capable of performing fundamental navigation tasks such as forward, backward, left, and right movements with satisfactory response time and accuracy.

Furthermore, the project emphasizes cost-effectiveness by utilizing readily available components, making it suitable for scalable and educational applications. Its modular design allows future expansion, such as integration with cloud-based AI services, improved speech processing algorithms, and enhanced sensor-based automation.

Despite its successful implementation, certain limitations exist, such as sensitivity to background noise in voice recognition, limited communication range due to Bluetooth constraints, and dependency on stable network conditions for video streaming. However, these challenges can be addressed by incorporating advanced noise filtering techniques, long-range communication modules, and optimized streaming protocols.

In conclusion, the project validates the feasibility of developing an intelligent, interactive robotic system capable of real-time operation and remote monitoring. It serves as a strong foundation for future advancements in smart robotics, particularly in applications such as surveillance, assistive robotics, hazardous environment exploration, and automated control systems.

## REFERENCE

## REFERENCE:

- [1] K. Nakadai et al., “A Robust Speech Recognition System for Communication Robots in Noisy Environments,” *IEEE Trans. Robotics*, vol. 24, no. 3, pp. 759–763, 2008, doi: 10.1109/TRO.2008.919305.
- [2] X. Lv, M. Zhang, and H. Li, “Robot Control Based on Voice Command,” in *Proc. IEEE Int. Conf. on Automation and Logistics (ICAL)*, 2008, doi: 10.1109/ICAL.2008.4636587.
- [3] K. Megalingam, R. S. Reddy, Y. Jahnavi, and M. Motheram, “ROS Based Control of Robot Using Voice Recognition,” in *Proc. IEEE Int. Conf. on Inventive Systems and Control (ICISC)*, 2019, doi: 10.1109/ICISC44355.2019.9036443.
- [4] H.-D. Bui and N. Y. Chong, “Autonomous Speech Volume Control for Social Robots in a Noisy Environment Using Deep Reinforcement Learning,” in *Proc. IEEE Int. Conf. on Robotics and Biomimetics (ROBIO)*, 2019, doi: 10.1109/ROBIO49542.2019.8961810.
- [5] A. R. Fayjie, R. Amir, O. Doukhi, and D. Lee, “Voice Enabled Smart Drone Control,” in *Proc. IEEE Int. Conf. on Ubiquitous and Future Networks (ICUFN)*, 2017, doi: 10.1109/ICUFN.2017.7993759.
- [6] M. Price, J. Glass, and A. P. Chandrakasan, “A Scalable Speech Recognizer with Deep-Neural-Network Acoustic Models,” in *Proc. IEEE Int. Solid-State Circuits Conf. (ISSCC)*, 2017, doi: 10.1109/ISSCC.2017.7870352.
- [7] M. T. Wolf et al., “Gesture-Based Robot Control with Variable Autonomy from the JPL BioSleeve,” in *Proc. IEEE Int. Conf. on Robotics and Automation (ICRA)*, 2013, doi: 10.1109/ICRA.2013.6630718.
- [8] R. Kawade et al., “Sortify: An Autonomous Voice Controlled 6-DOF Robotic Arm for Object Detection and Sorting,” in *Proc. IEEE Int. Conf. on Intelligent Technologies (CONIT)*, 2025, doi: 10.1109/CONIT65521.2025.11167579.

## **APPENDIX**

## PROJECT CODE

```
#include "AF Motor.h"
Const int MOTOR_1 = 1;
const int MOTOR_2 = 2;
const int MOTOR_3 = 3;
const int MOTOR_4 = 4;

AF_DCMotor motor1(MOTOR_1, MOTOR12_64KHZ);
AF_DCMotor motor2(MOTOR_2, MOTOR12_64KHZ);
AF_DCMotor motor3(MOTOR_3, MOTOR12_64KHZ);
AF_DCMotor motor4(MOTOR_4, MOTOR12_64KHZ);
int state;
int Speed = 130;
void setup()
{
  motor1.setSpeed(Speed);
  motor2.setSpeed(Speed);
  motor3.setSpeed(Speed);
  motor4.setSpeed(Speed);
  Serial.begin(9600);
  delay(500);
}
void loop(){
  if(Serial.available() > 0){
    state = Serial.read();
    if(state > 10){Speed = state;}
  }
  motor1.setSpeed(Speed);
  motor2.setSpeed(Speed);
  motor3.setSpeed(Speed);
  motor4.setSpeed(Speed);

  if(state == 1){forward();}
  else if(state == 2){backward();}
  else if(state == 3){turn Left();}
  else if(state == 4){turn Right();}
  else if(state == 5){Stop();}
  else if(state == 6){turn Left(); delay(400); state = 5;}
  else if(state == 7){turn Right(); delay(400); state = 5;}
  delay(80);
}
void forward()
{
  motor1.run(FORWARD);
  motor2.run(FORWARD);
  motor3.run(FORWARD);
  motor4.run(FORWARD);
}
```

```
}  
void backward(){  
motor1.run(BACKWARD);  
motor2.run(BACKWARD);  
motor3.run(BACKWARD);  
motor4.run(BACKWARD);  
}  
void turn Right()  
{  
motor1.run(FORWARD);  
motor2.run(FORWARD);  
motor3.run(BACKWARD);  
motor4.run(BACKWARD);  
}  
void turnLeft()  
{  
motor1.run(BACKWARD);  
motor2.run(BACKWARD);  
motor3.run(FORWARD);  
motor4.run(FORWARD);  
}  
void Stop()  
{  
motor1.run(RELEASE);  
motor2.run(RELEASE);  
motor3.run(RELEASE);  
motor4.run(RELEASE);  
}
```

# PAPER PUBLICATION

International Journal of Engineering Research and Development  
e-ISSN: 2278-067X, p-ISSN: 2278-800X, www.ijerd.com  
Volume 22, Issue 2 (February 2026), PP 44-48

## A Review on Voice Controlled AI Robot (VOCIBOT)

Reshma Satpute<sup>1</sup>, Vedant Patrabhe<sup>2</sup>, Raksha Sonewane<sup>3</sup>, Lavanya Gabhane<sup>4</sup>,  
Mahak Gupta<sup>5</sup>

<sup>1,2,3,4,5</sup>UG Students, Department of E&TC, Priyadarshini Bhagwati Collage of Engineering,  
Nagpur Maharashtra, India

**Abstract**—Voice controlled AI robots represent an important advancement in human-machine interaction by enabling intuitive, hands-free control of robotic systems. This review presents an in-depth analysis of existing voice controlled robotic architectures, focusing on speech recognition techniques, embedded control platforms, wireless communication technologies, motor control strategies, and multimedia integration. The study evaluates Bluetooth- and Wi-Fi-based systems implemented using Arduino and ESP32 platforms, highlighting their performance, scalability, and limitations. Furthermore, the paper identifies key research gaps related to autonomy, robustness, and intelligence, and outlines future research directions aimed at improving real-time decision-making, on-device intelligence, and IoT integration.

**Keywords**—Voice Controlled Robot, Embedded Systems, Speech Recognition, Arduino Uno, ESP32, Bluetooth, Wi-Fi, Artificial Intelligence

Date of Submission: 24-01-2026

Date of acceptance: 06-02-2026

### I. INTRODUCTION

Voice-controlled robotic systems have emerged as a significant research area due to advancements in speech recognition, embedded systems, and wireless communication technologies. Early research focused on basic voice-controlled vehicles and robotic arms, demonstrating the feasibility of replacing traditional manual control mechanisms with speech-based interfaces [1], [2]. With the growth of low-cost microcontrollers such as Arduino and ESP32, researchers have developed more reliable and cost-effective voice-controlled robotic platforms for real-world applications [4], [6].

Recent studies emphasize the integration of mobile-based speech recognition and wireless communication to improve system accuracy and usability. Bluetooth-based systems are widely adopted for short-range control due to their simplicity and low latency [6], [7], while Wi-Fi-enabled platforms such as ESP32 support advanced features including IoT connectivity and real-time video streaming [9], [10]. These developments have expanded the application scope of voice-controlled robots to assistive technologies, smart homes, surveillance, and educational environments.

### II. LITERATURE REVIEW

Recent progress in embedded systems, artificial intelligence, and wireless communication has significantly contributed to the development of voice-controlled robotic systems. Researchers have explored various architectures to enable speech-based interaction with robots, aiming to improve usability, accessibility, and operational efficiency. Existing literature can be broadly categorized based on control methodology, speech processing techniques, communication technologies, and system enhancements.

#### A. Voice-Based Robotic Control Approaches


Early research on voice-controlled robots primarily focused on replacing conventional input devices such as switches and joysticks with basic speech commands. Initial systems relied on predefined voice patterns stored within microcontrollers, which resulted in limited vocabulary size and poor noise tolerance [4]. Despite these constraints, these studies demonstrated the feasibility of speech-driven robotic motion.

Subsequent work introduced smartphone-assisted voice control, where speech recognition was handled externally using mobile applications. Sarada et al. developed a Bluetooth-enabled robotic system controlled through an Android device, demonstrating reliable execution of basic navigation commands such as forward, backward, and turning motions [6]. This approach significantly improved recognition accuracy compared to onboard processing.

Mehlam Ali et al. further enhanced this architecture by integrating obstacle detection mechanisms with voice-controlled navigation. Their system showed improved safety during indoor operation and highlighted the

44

## A Review on Voice Controlled AI Robot (VOCIBOT)



### IV. WORKING OF SYSTEM

Voice-controlled robotic systems described in the literature generally follow a structured operational flow consisting of voice acquisition, speech recognition, wireless communication, embedded processing, and actuation. Although specific implementations vary, the core working principle remains consistent across most studies.

The working process begins with the acquisition of voice commands through a microphone, typically integrated into a smartphone or mobile device. Due to the limited computational resources of low-cost microcontrollers, speech recognition is commonly performed externally using mobile-based or cloud-supported speech-to-text algorithms [7], [8], [9]. This approach improves recognition accuracy and reduces the processing burden on the embedded controller.

After speech recognition, the converted text command is mapped to predefined control instructions and transmitted wirelessly to the robotic system. Several studies have demonstrated the effectiveness of Bluetooth-based communication, particularly using HC-05 modules, for short-range voice-controlled applications due to low latency and reliable data transmission [6], [7]. Bluetooth communication is widely preferred in indoor and educational robotic systems.

More recent research highlights the adoption of Wi-Fi-enabled microcontrollers such as ESP32, which support both Bluetooth and Wi-Fi communication and enable advanced features including IoT connectivity and remote access [9], [10]. These systems allow real-time command transmission and monitoring but may depend on network stability.

At the robotic end, the embedded controller, commonly Arduino Uno or ESP32, receives the transmitted command and performs command validation to ensure it matches predefined actions such as forward, backward, left, right, or stop [4], [7]. Invalid or unrecognized commands are discarded to prevent unintended motion.

Once validated, the controller generates control signals for the motor driver circuit, typically using ICs such as L293D or L298N. These motor drivers amplify low-power control signals and regulate the direction and speed of DC motors, enabling accurate robot movement as reported in multiple experimental studies [4], [6].

Several works further enhance system functionality by integrating monitoring and safety mechanisms, including ultrasonic sensors for obstacle detection and camera modules such as ESP32-CAM for visual feedback

46

## A Review on Voice Controlled AI Robot (VOCIBOT)

benefits of combining voice interfaces with sensor-based feedback [7]. Similar concepts were reported in URASET, emphasizing the simplicity and effectiveness of mobile-based speech control for robotic vehicles [8].

### B. Speech Recognition Techniques in Robotic Systems

Speech recognition plays a central role in voice-controlled robotic systems. Due to limited computational resources of low-cost microcontrollers, most implementations rely on external speech processing using smartphone APIs or cloud-based services [7], [8]. This approach allows the use of advanced AI-based speech recognition models while keeping the robotic hardware simple and cost-effective.

Studies published in MDPI journals indicate that distributing speech processing tasks between mobile devices and embedded controllers improves system responsiveness and reduces overall complexity [9]. However, this dependency introduces challenges related to internet connectivity, latency, and privacy.

### C. Wireless Communication Technologies

Wireless communication is essential for transmitting voice commands from the user to the robotic platform. Bluetooth technology, particularly HC-05 modules, is widely used due to its low power consumption, ease of interfacing, and sufficient data rates for command transmission [6], [7]. Bluetooth-based systems are especially suitable for short-range and indoor applications.

More recent research has focused on Wi-Fi-enabled robotic systems using microcontrollers such as ESP32. These systems support long-range communication, IoT integration, and real-time data streaming, expanding the application scope of voice-controlled robots [9], [10]. However, Wi-Fi-based architectures often face challenges related to network stability and security.

### D. Embedded Controllers and Actuation Mechanisms

Microcontrollers such as Arduino Uno and ESP32 are commonly employed in voice-controlled robotic systems due to their flexibility and strong developer support. Arduino Uno is frequently used in educational and prototype-level systems because of its simplicity and low cost [4], [6]. Motor driver ICs such as L293D are widely adopted to interface these controllers with DC motors, providing reliable motion control.

The ESP32 platform has gained attention in recent studies due to its higher processing capability and integrated wireless features. Literature reports indicate that ESP32-based systems are better suited for advanced applications involving multimedia processing and IoT connectivity [10].

### E. Vision and Safety Enhancements

To improve usability and operational safety, several researchers have incorporated vision-based monitoring and obstacle detection into voice-controlled robots. Camera modules such as ESP32-CAM enable real-time video streaming, which enhances situational awareness during remote operation [10]. Ultrasonic sensors are commonly used for obstacle detection, providing reliable distance measurements in indoor environments [7].

The integration of voice control with vision and safety modules represents a significant step toward more intelligent and reliable robotic systems.

### F. Summary of Literature and Identified Trends

The reviewed literature indicates that most voice-controlled robotic systems rely on external speech recognition, short-range wireless communication, and low-cost embedded platforms. While these systems demonstrate promising results in controlled environments, they remain limited in terms of autonomy, adaptability, and robustness. These observations underline the need for more integrated and intelligent architectures, motivating further research in this domain [6]–[10].

### III. Flowchart of the System Architecture

The system architecture of voice-controlled AI robotic systems reported in the literature is designed to enable effective coordination among voice command acquisition, wireless communication, embedded control, motor actuation, and real-time monitoring components. Most existing architectures follow a modular and layered approach to ensure reliable interaction between software-based speech processing and hardware-based robotic control.

In a typical architecture, voice commands are captured using an external device, such as a smartphone, where speech recognition and command interpretation are performed. The processed commands are then transmitted to the robotic platform through wireless communication technologies, commonly Bluetooth or Wi-Fi. Upon reception, the embedded controller validates the commands and translates them into appropriate control signals for motor driver circuits, which in turn regulate the movement of the robotic actuators.

45

## A Review on Voice Controlled AI Robot (VOCIBOT)

[7], [10]. These additions improve navigation safety and provide real-time situational awareness, especially in surveillance and inspection applications.

Overall, existing literature indicates that voice-controlled robotic systems operate using a distributed processing architecture, where speech recognition is handled externally while embedded controllers focus on real-time control and actuation. This architecture has proven effective for improving system responsiveness, scalability, and usability in practical applications [6]–[10].

### V. APPLICATIONS OF VOICE-CONTROLLED AI ROBOTIC SYSTEMS

Voice-controlled AI robotic systems have been widely explored in **assistive and healthcare applications**, where hands-free interaction is essential. Existing studies report that voice-based control enables individuals with physical disabilities and elderly users to operate robotic platforms without manual input, improving accessibility and independence in daily activities [4], [7]. Such systems reduce physical effort and enhance user comfort in controlled indoor environments.

In **home automation and smart environments**, voice-controlled robots are used to interact with smart appliances and IoT-based systems. Research shows that the integration of wireless communication technologies such as Bluetooth and Wi-Fi allows robots to execute user commands and interact with connected devices efficiently [9], [10]. These applications demonstrate improved convenience and adaptability within smart homes.

Several studies also highlight the use of voice-controlled robots in **surveillance and security applications**, particularly when combined with camera modules and wireless video transmission. Robots equipped with ESP32-CAM modules enable real-time visual monitoring and remote navigation in hazardous or inaccessible areas, making them suitable for inspection and security tasks [10].

In **educational and research settings**, voice-controlled robotic platforms serve as low-cost experimental tools for learning embedded systems, robotics, and artificial intelligence. Literature indicates that Arduino- and ESP32-based systems are frequently adopted in academic institutions due to their simplicity, open-source nature, and ease of integration with speech recognition applications [6], [8].

Industrial and service-oriented applications have also been reported, where voice-controlled robots assist in repetitive operations, inspection tasks, and human-robot interaction scenarios. These applications aim to reduce operator workload and enhance operational efficiency in constrained environments [5], [9].

### VI. CHALLENGES AND LIMITATIONS

Despite technological advancements, voice-controlled AI robotic systems face several unresolved challenges. One major limitation is **reduced speech recognition accuracy in noisy environments**, where background noise and speech variation significantly affect command interpretation [7], [8]. Another critical limitation is the **dependence on external devices and cloud-based services** for speech processing. Most systems rely on smartphones or internet connectivity, which limits autonomy and reliability in network-constrained environments [9].

Existing systems also suffer from **restricted natural language understanding**, as most implementations support only predefined command sets. This limitation reduces flexibility and prevents conversational interaction between humans and robots [6], [7].

Wireless communication introduces additional challenges. Bluetooth-based systems have limited operational range, while Wi-Fi-based systems are susceptible to latency, packet loss, and cybersecurity vulnerabilities [9], [10]. Furthermore, low-cost embedded platforms face **power and hardware constraints**, restricting the deployment of advanced AI algorithms on-board [4], [10].

### VII. RESEARCH GAPS

Analysis of the reviewed literature reveals multiple research gaps that require further investigation. Firstly, **on-device speech recognition and decision-making** remain underexplored, as most systems rely on external processing rather than embedded intelligence [9], [10].

Secondly, there is limited research on **robust, noise-resistant speech recognition models** suitable for real-world environments. Current approaches lack adaptability to varying acoustic conditions [7], [8].

Another gap lies in the **absence of context-aware and adaptive robotic behavior**. Existing systems do not dynamically adjust actions based on environmental feedback or user intent, limiting system intelligence [6], [9]. Security and privacy concerns are also insufficiently addressed in the literature. Wireless voice-controlled systems remain vulnerable to unauthorized access, and standardized security mechanisms are rarely implemented [10].

Finally, there is a lack of **standardized evaluation metrics** for comparing system performance across studies. Most papers use custom benchmarks, making objective comparison difficult [4]–[10].

47

### VIII. CONCLUSION

This review has presented a detailed analysis of voice-controlled AI robotic systems, emphasizing speech recognition methods, embedded control platforms, wireless communication technologies, and multimedia integration. While current systems demonstrate promising results in controlled environments, significant improvements are required to achieve full autonomy, robustness, and scalability. Addressing the identified research gaps will enable the development of next-generation intelligent robots capable of reliable operation in real-world scenarios.

### References

- [1]. International Conference on Advances Automotive Technologies 2016, Yildiz Technical University, Istanbul, Turkey, AAT2016.
- [2]. Lens, Thomas., Kunz, Jurgen, and Stryk, Oskar Von., Bio Rob- Arm: A Quickly Deployable and Intrinsically Safe, Light-Weight Robot Arm for Service Robotics Applications.
- [3]. A SMART VOICE CONTROLLED PICK AND PLACE ROBOT International Research Journal of Engineering and Technology (IRJET).
- [4]. Kannan, K. & Selvakumar, J. (2015). Arduino Based Voice Controlled Robot, International Research Journal of Engineering and Technology (IRJET).
- [5]. Muhammed, J. N., Neetha, J, Muhammed, F., Midhun, M., Mithun, S. & Safwan, C. N. (2015). Wireless Control Robotic Arm Using an Android Application, International Journal of Advanced Research in Electrical, Electronics and Instrumentation Engineering .
- [6]. B. Sarada et al., "Voice Controlled Robot using Bluetooth," IJERT.
- [7]. Melham Ali et al., "Arduino Based Bluetooth Voice Controlled Robot Car and Obstacle Detector," IJSRST.
- [8]. "Voice Controlled and Obstacles Detection Robotic Vehicle," IJRASET.
- [9]. "Speech Recognition Wireless Control System for Mobile Robotics," MDPI.
- [10]. "Voice Controlled Application using ESP32," Journal of Electrical Engineering and Automation.

# CERTIFICATES OF REVIEW PAPER

e-ISSN: 2278-067X p-ISSN: 2278-800X

**INTERNATIONAL JOURNAL OF ENGINEERING RESEARCH AND DEVELOPMENT**  
e-ISSN: 2278-067X p-ISSN: 2278-800X

**CERTIFICATE**

It is certified that the paper entitled by "A Review on Voice Controlled AI Robot (VOCBOT)" has been published in International Journal of Engineering Research and Development (IJERD).

**Your article has been published with following details:**

Author's Name: Mahak Gupta  
Journal Name: International Journal of Engineering Research and Development (IJERD)  
Journal URL: www.ijerd.com  
Journal Type: Online & Offline  
Publication Year: 2026  
Publication Month: February  
Vol No.: 22  
Issue No.: 02



Editor-In-Chief  
International Journal of Engineering Research and Development (IJERD)  
ISSN(Online) : 2278-067X, ISSN(Print) : 2278-800X  
E-mail ID: ijerd@editorials.com  
URL: www.ijerd.com

e-ISSN: 2278-067X p-ISSN: 2278-800X

**INTERNATIONAL JOURNAL OF ENGINEERING RESEARCH AND DEVELOPMENT**  
e-ISSN: 2278-067X p-ISSN: 2278-800X

**CERTIFICATE**

It is certified that the paper entitled by "A Review on Voice Controlled AI Robot (VOCBOT)" has been published in International Journal of Engineering Research and Development (IJERD).

**Your article has been published with following details:**

Author's Name: Vidant Pathrabe  
Journal Name: International Journal of Engineering Research and Development (IJERD)  
Journal URL: www.ijerd.com  
Journal Type: Online & Offline  
Publication Year: 2026  
Publication Month: February  
Vol No.: 22  
Issue No.: 02



Editor-In-Chief  
International Journal of Engineering Research and Development (IJERD)  
ISSN(Online) : 2278-067X, ISSN(Print) : 2278-800X  
E-mail ID: ijerd@editorials.com  
URL: www.ijerd.com

e-ISSN: 2278-067X p-ISSN: 2278-800X

**INTERNATIONAL JOURNAL OF ENGINEERING RESEARCH AND DEVELOPMENT**  
e-ISSN: 2278-067X p-ISSN: 2278-800X

**CERTIFICATE**

It is certified that the paper entitled by "A Review on Voice Controlled AI Robot (VOCBOT)" has been published in International Journal of Engineering Research and Development (IJERD).

**Your article has been published with following details:**

Author's Name: Lavanya Gabbane  
Journal Name: International Journal of Engineering Research and Development (IJERD)  
Journal URL: www.ijerd.com  
Journal Type: Online & Offline  
Publication Year: 2026  
Publication Month: February  
Vol No.: 22  
Issue No.: 02



Editor-In-Chief  
International Journal of Engineering Research and Development (IJERD)  
ISSN(Online) : 2278-067X, ISSN(Print) : 2278-800X  
E-mail ID: ijerd@editorials.com  
URL: www.ijerd.com

e-ISSN: 2278-067X p-ISSN: 2278-800X

**INTERNATIONAL JOURNAL OF ENGINEERING RESEARCH AND DEVELOPMENT**  
e-ISSN: 2278-067X p-ISSN: 2278-800X

**CERTIFICATE**

It is certified that the paper entitled by "A Review on Voice Controlled AI Robot (VOCBOT)" has been published in International Journal of Engineering Research and Development (IJERD).

**Your article has been published with following details:**

Author's Name: Raksha Sonewane  
Journal Name: International Journal of Engineering Research and Development (IJERD)  
Journal URL: www.ijerd.com  
Journal Type: Online & Offline  
Publication Year: 2026  
Publication Month: February  
Vol No.: 22  
Issue No.: 02



Editor-In-Chief  
International Journal of Engineering Research and Development (IJERD)  
ISSN(Online) : 2278-067X, ISSN(Print) : 2278-800X  
E-mail ID: ijerd@editorials.com  
URL: www.ijerd.com

e-ISSN: 2278-067X p-ISSN: 2278-800X

**INTERNATIONAL JOURNAL OF ENGINEERING RESEARCH AND DEVELOPMENT**  
e-ISSN: 2278-067X p-ISSN: 2278-800X

**CERTIFICATE**

It is certified that the paper entitled by "A Review on Voice Controlled AI Robot (VOCBOT)" has been published in International Journal of Engineering Research and Development (IJERD).

**Your article has been published with following details:**

Author's Name: Reshma Satpute  
Journal Name: International Journal of Engineering Research and Development (IJERD)  
Journal URL: www.ijerd.com  
Journal Type: Online & Offline  
Publication Year: 2026  
Publication Month: February  
Vol No.: 22  
Issue No.: 02



Editor-In-Chief  
International Journal of Engineering Research and Development (IJERD)  
ISSN(Online) : 2278-067X, ISSN(Print) : 2278-800X  
E-mail ID: ijerd@editorials.com  
URL: www.ijerd.com

# RESEARCH PAPER

HBRP  
PUBLICATION

Journal of Advancement in Communication System

e-ISSN: 3048-4758

Volume 09 Issue 02 May-Aug, 2026

\*Corresponding Author:  
Vedant Pathrahe,  
Student, Department of  
Electronics &  
Telecommunication  
Engineering, Priyadarshini  
Bhagwati College of  
Engineering, Nagpur,  
Maharashtra, India

Submission Date: Mar 24,  
2026  
Copyright Received Date:  
Mar 27, 2026  
Published Date: Apr 27,  
2026

Cite as:  
Reshma Satpute, Vedant  
Pathrahe, Raksha  
Sonewane, Lavanya  
Gabhane, Mahak Gupta, &  
Dr. J.Y. Hande. (2026).  
Design and Implementation of a  
Voice-Controlled AI Robot (VOCIBOT). Journal  
of Advancement in  
Communication System,  
9(2), 34-45.  
<https://doi.org/10.5281/zenodo.19817098>

## Design and Implementation of a Voice-Controlled AI Robot (VOCIBOT)

Reshma Satpute<sup>1</sup>, Vedant Pathrahe<sup>2\*</sup>, Raksha Sonewane<sup>3</sup>,  
Lavanya Gabhane<sup>4</sup>, Mahak Gupta<sup>5</sup>, Dr. J.Y. Hande<sup>6</sup>

<sup>1,5</sup>Student, Department of Electronics &  
Telecommunication Engineering, Priyadarshini Bhagwati  
College of Engineering, Nagpur, Maharashtra, India  
<sup>3</sup>Assistant Professor, Department of Electronics &  
Telecommunication Engineering, Priyadarshini Bhagwati  
College of Engineering, Nagpur, Maharashtra, India

### ABSTRACT

This paper presents the design, implementation, and experimental validation of a voice-controlled AI robotic system named VOCIBOT. The proposed system enables hands-free robotic navigation using AI-based speech recognition combined with embedded control and wireless communication. Voice commands are processed externally using a mobile application and transmitted to the robotic unit via Bluetooth. An Arduino-based controller executes validated commands to drive motors, while an ESP32-CAM module provides real-time visual feedback. Experimental results demonstrate low response latency, reliable command execution, and stable indoor performance. The proposed system offers a cost-effective and scalable solution for assistive, surveillance, and educational robotic applications.

**Keywords:-** Voice-Controlled Robot, VOCIBOT, Embedded Systems, Arduino Uno, ESP32-CAM, Bluetooth, Human Robot Interaction

Page No. 34 <http://www.hbrppublication.com>

2026: 9 (2), 34-45

HBRP  
PUBLICATION

Journal of Advancement in Communication System

### INTRODUCTION

Advancements in artificial intelligence and embedded electronics have significantly transformed the field of human-robot interaction. Prior research demonstrates that traditional robotic systems often depend on manual controllers, limiting accessibility and flexibility [1], [2]. Voice-based control has emerged as an intuitive alternative, enabling hands-free interaction and improved usability, particularly for assistive and service robotics applications [3], [4].

Several studies report that the integration of speech recognition with embedded controllers improves human-robot interaction by reducing user effort and response time [4], [6]. However, most existing implementations focus on either basic motion control or conceptual system design, with limited emphasis on real-time monitoring and safety mechanisms [7], [8].

Motivated by these limitations, this research focuses on the practical realization of a voice-controlled robotic system emphasizing real-time responsiveness, operational safety, and visual feedback. Unlike survey-based studies such as [6]-[10], this work concentrates on system design, hardware integration, control logic implementation, and experimental validation, using low-cost embedded components.

### SYSTEM OVERVIEW

The proposed VOCIBOT system is developed using a modular and layered architecture, which is widely adopted in embedded robotic systems to improve design flexibility, scalability, and ease of maintenance [4], [6]. By separating the system into independent functional modules, hardware and software upgrades can be implemented without affecting the overall system operation. This approach is particularly beneficial for prototyping and research-oriented robotic platforms.

A key design feature of the system is the use of external AI-based speech recognition instead of on-board voice processing. Speech recognition is performed on a mobile device using an AI-enabled application, and only the processed control commands are transmitted to the robotic unit.

This strategy significantly reduces the computational and memory load on the embedded controller, enabling faster response times and improved system stability when compared to fully on-device speech recognition systems [7], [9].

Wireless communication between the user interface and the robot is established using Bluetooth technology, which has been extensively used in indoor robotic control applications due to its low latency, low power consumption, and implementation simplicity [6], [7]. Bluetooth communication ensures reliable command transmission within a short range, making it suitable for indoor navigation and experimental environments where real-time interaction is essential.

To enhance operational reliability, the system integrates real-time visual monitoring and safety mechanisms. An ESP32-CAM module provides live video streaming, allowing users to remotely observe the robot's surroundings during operation.

This feature improves situational awareness and enables safer remote control, especially in environments with limited visibility [10]. Additionally, an ultrasonic sensor is employed for continuous obstacle detection. Distance measurements are analyzed before executing motion commands, preventing collisions and improving navigation safety, as recommended in prior robotic safety studies [8].

Page No. 35 <http://www.hbrppublication.com>

2026: 9 (2), 34-45


HBRP  
PUBLICATION

Journal of Advancement in Communication System

Overall, the VOCIBOT system extends beyond conventional voice-controlled robots by combining external intelligence, embedded control, wireless communication, visual feedback, and safety features into a unified platform.

This integrated architecture enhances usability, reliability, and real-time performance, making the system suitable for assistive, educational, and experimental robotic applications.

### BLOCK DIAGRAM DESCRIPTION



The block diagram of the proposed VOCIBOT system illustrates the functional interaction between hardware and software modules responsible for voice processing, communication, control, actuation, monitoring, and safety. Each module is designed to operate independently while maintaining synchronized coordination to achieve reliable voice-controlled robotic navigation.

**Voice Command Processing Unit**  
The voice command processing unit is responsible for acquiring and interpreting user voice input. In the proposed system, voice commands are captured using a smartphone equipped with an AI-based speech recognition application. The spoken commands are converted into text and subsequently mapped to predefined robotic control instructions such as forward, backward, left, right, and stop.

Page No. 36 <http://www.hbrppublication.com>

2026: 9 (2), 34-45

HBRP  
PUBLICATION

Journal of Advancement in Communication System

Offloading speech recognition to an external device significantly improves recognition accuracy and system responsiveness, as mobile platforms provide higher computational capability and advanced AI models compared to low-cost embedded controllers. This approach also eliminates the need for complex signal processing on the microcontroller, thereby reducing system complexity and power consumption. Similar external speech processing architectures have been successfully employed in voice-controlled robotic systems reported in previous studies [7], [9].

### Wireless Communication Unit

The wireless communication unit enables command transmission between the user interface and the robotic platform. In this system, an HC-05 Bluetooth module is used to establish a serial wireless communication link. Bluetooth technology is selected due to its low implementation cost, ease of configuration, and suitability for short-range indoor robotic applications.

Once the voice command is converted into a control instruction, it is transmitted via Bluetooth to the embedded controller. Bluetooth-based communication ensures minimal latency, enabling near real-time command execution. Prior research has demonstrated that Bluetooth modules provide stable and reliable connectivity for voice-controlled robotic systems operating in indoor environments [6], [7].

### Embedded Control Unit

The embedded control unit serves as the core processing module of the VOCIBOT system. An Arduino Uno microcontroller is employed to receive wireless commands, validate control instructions, and coordinate the operation of actuators and sensors. The microcontroller executes a predefined control algorithm that interprets incoming commands and generates appropriate output signals.

Arduino-based platforms are widely used in research and educational robotics due to their simplicity, affordability, and extensive software support. The use of Arduino enables rapid development and easy integration of multiple peripherals, making it suitable for experimental robotic prototypes. Similar embedded control strategies have been reported in voice-controlled and Bluetooth-operated robotic systems [4], [6].

### Motor Actuation Unit

The motor actuation unit converts control signals generated by the microcontroller into physical motion. The L293D motor driver IC is used as an interface between the Arduino and the DC motors. Since microcontroller output pins cannot directly drive motors due to current limitations, the motor driver amplifies the control signals and provides bidirectional motor control.

By selectively enabling driver inputs, the system achieves precise control over motor direction and speed, allowing smooth navigation of the robotic platform. The L293D motor driver is commonly used in low-power robotic systems and has been proven effective in similar robotic implementations [4], [6].

### Monitoring and Safety Unit

The monitoring and safety unit enhances operational awareness and prevents accidental collisions. An ESP32-CAM module is integrated into the system to provide real-time video streaming. Live video feedback allows the user to remotely monitor the robot's environment and make informed control decisions, particularly in areas with limited visibility or restricted access [10].

In addition to visual monitoring, an ultrasonic sensor is employed for obstacle detection. The sensor continuously measures the distance between the robot and nearby objects. When an obstacle is


Page No. 37 <http://www.hbrppublication.com>

2026: 9 (2), 34-45

detected within a predefined threshold distance, the control unit restricts or overrides motion commands to prevent collisions. Ultrasonic-based obstacle

detection has been widely recognized as a reliable and cost-effective safety mechanism for indoor robotic navigation [7], [8].

#### SYSTEM FLOW AND OPERATION



The operational workflow of the proposed VOCIBOT system is based on a distributed processing architecture, in which computationally intensive speech recognition tasks are executed externally, while the embedded controller is dedicated to real-time decision-making and actuation [7], [9]. This separation of processing

responsibilities improves system efficiency and ensures consistent real-time performance on resource-constrained embedded hardware.

The operation begins with system initialization, during which all hardware modules including the microcontroller,

Bluetooth interface, motor driver, ultrasonic sensor, and camera module are powered and configured. The Bluetooth module then enters a pairing mode and waits for successful connection with the user's mobile device. Once pairing is established, the system transitions into a command-listening or idle state, indicating readiness to receive voice-based instructions.

When a voice command is issued by the user, speech recognition is performed on the mobile device, and the corresponding control instruction is transmitted wirelessly to the robotic platform. Upon reception, the Arduino microcontroller performs command validation by checking the instruction against a predefined command set. This validation process prevents the execution of unintended or corrupted commands, an approach widely recommended in safety-aware embedded robotic systems [4], [7].

Before executing the received command, the controller simultaneously evaluates sensor inputs, particularly data from the ultrasonic sensor. If an obstacle is detected within a predefined safety threshold, the controller either modifies or blocks the execution of motion commands, thereby reducing the risk of collision. This conditional execution mechanism introduces a safety layer into the control flow, extending functionality beyond basic voice-controlled motion systems [8].

During motion execution, the motor driver actuates the Gear motors according to the validated control signals. At the same

time, the ESP32-CAM module continuously streams real-time video data, providing visual feedback to the user. This parallel operation of motion control and visual monitoring enables informed remote operation and improves situational awareness, particularly in indoor or confined environments [10].

After the completion of each command, the system returns to the command-listening state, allowing continuous and interactive operation. This cyclic operational flow ensures responsive human-robot interaction while maintaining safety and system stability.


The overall flow architecture is consistent with previously reported Bluetooth-based voice-controlled robotic systems [6]–[9] but extends them through the integration of real-time visual feedback and obstacle-based safety intervention, thereby enhancing reliability and practical usability.

#### HARDWARE AND SOFTWARE IMPLEMENTATION

##### Hardware Components

The hardware architecture of the proposed VOCIBOT (Voice-Controlled Intelligent Bot) is designed to provide reliable performance, modular integration, and efficient power management. The system integrates multiple embedded components including a microcontroller, wireless communication modules, actuators, power management units, and audio-visual devices to enable intelligent robotic interaction.

#### Hardware connection



#### Software Implementation

The software architecture of the VOCIBOT system consists of embedded firmware running on the microcontroller and external software applications responsible for voice processing and artificial intelligence integration.

##### Embedded Firmware (Arduino IDE)

The embedded firmware is developed using the Arduino Integrated Development Environment (IDE) and programmed in Embedded C. The firmware controls the robot's movement by interpreting commands received through the Bluetooth communication module.

The firmware performs several tasks including:

- Serial communication with Bluetooth module
- Command decoding
- Motor driver control
- Movement execution

The robot follows command-based navigation logic where each movement corresponds to a predefined instruction.

Example control commands include:

- Forward movement
- Backward movement

- Left turn
- Right turn
- Stop

This simple yet effective command-based architecture ensures fast response and reliable control.

#### Mobile Voice Control Application

A mobile voice control application is used to convert spoken commands into digital

control instructions. The application utilizes the smartphone's built-in speech recognition capabilities to process user voice input.

Once the voice command is recognized, the application maps it to a predefined control signal and sends it to the robot through the Bluetooth module.



The mobile application interface allows users to:

- Connect to the robot via Bluetooth
- Issue voice commands
- Control robot movement
- Adjust movement speed

The user interface of the application is shown in the figure above, where directional controls and a microphone button enable voice-based navigation.

#### AI Interaction using Gemini

For intelligent conversational interaction, the system integrates Google Gemini AI

through an external device such as smartphone or computer. Gemini processes user queries and generate appropriate responses using natural language processing.

When the user asks a question, the mobile application sends the request to the Gemini AI system. The generated response is converted into speech and played through the robot's speaker system.

This integration enables the robot to function not only as a remotely controlled vehicle but also as an AI-powered

interactive assistant capable of answering questions and providing information.

#### EXPERIMENTAL RESULTS AND PERFORMANCE ANALYSIS

The VOCIBOT system was experimentally evaluated for real-time

voice-controlled navigation and operational safety.

Key performance metrics include command response time, communication reliability, navigation accuracy, and obstacle detection.



**Command Response Time**  
Command response time refers to the delay between issuing a voice command and motor activation.

Experimental results show an average response time of < 500 ms, achieved through external speech processing and efficient embedded control.

#### Wireless Communication Reliability

The HC-05 Bluetooth module maintained stable communication within an indoor range of 8-10 meters, with negligible delay or packet loss, confirming its suitability for short-range applications.

#### Navigation


The system achieved an average navigation accuracy of ~95% in low-noise

environments. This performance is supported by reliable speech recognition and effective command execution.

#### Comparative Analysis

Compared to earlier systems, VOCIBOT demonstrates improved response time, higher accuracy, and enhanced safety due to integrated obstacle detection and real-time monitoring.

| Parameter            | Existing Systems [6], [7] | Proposed VOCIBOT |
|----------------------|---------------------------|------------------|
| Response Time        | 700-1200 ms               | < 500 ms         |
| Communication Range  | 5-8 m                     | 8-10 m           |
| Navigation Accuracy  | 85-90%                    | 95%              |
| Real-Time Monitoring | Not Available             | Available        |



#### APPLICATIONS

The proposed VOCIBOT system demonstrates versatility across multiple domains, enhanced by its real-time monitoring and safety features.

**Assistive Robotics:**  
VOCIBOT can support elderly and physically challenged individuals through intuitive voice-based control, reducing reliance on manual interfaces. The integration of obstacle detection further improves operational safety in indoor environments.

**Surveillance and Monitoring:**  
With the ESP32-CAM module, the system functions as a mobile surveillance platform capable of real-time video streaming. This enables remote monitoring of indoor spaces, making it suitable for home and office security applications.

**Educational and Laboratory Platforms:**  
The modular design and use of widely available components make VOCIBOT an effective tool for teaching embedded systems, robotics, and human-machine interaction. It facilitates hands-on learning in areas such as wireless communication, sensor integration, and real-time control.

#### Remote Inspection in Hazardous Environments:

VOCIBOT can be adapted for inspection in confined or unsafe environments. Voice control combined with live video feedback enables safe remote operation, reducing human exposure to risk.

#### FUTURE SCOPE

Although VOCIBOT demonstrates effective voice-controlled operation, several enhancements can improve its intelligence, autonomy, and efficiency.

**On-Device Speech Recognition:**  
Integrating onboard speech processing using advanced processors (e.g., ESP32-S3

or Raspberry Pi) would eliminate dependence on external devices and improve system autonomy.

**SLAM-Based Autonomous Navigation:**  
Incorporating SLAM algorithms with sensors such as LiDAR or depth cameras would enable autonomous navigation and environment mapping, extending usability in complex scenarios.

**Cloud-Based AI Integration:**  
Cloud connectivity can enable advanced functionalities such as natural language processing, image recognition, and intelligent decision-making, enhancing system capabilities without hardware upgrades.

**Extended Wireless Communication:**  
Replacing Bluetooth with Wi-Fi or LoRa would increase communication range, enabling remote operation over long distances and in large-scale environments.

#### Battery Management and Power Optimization:

Future improvements may include advanced battery monitoring, efficient power distribution, and low-power operation modes to enhance runtime and system reliability.

#### CONCLUSION

This paper presented the design and implementation of VOCIBOT, a voice-controlled robotic system with integrated vision and safety features. The system utilizes a distributed architecture, combining external speech processing with embedded real-time control.





Experimental results demonstrate fast response, reliable communication, and accurate navigation in indoor environments. The integration of ultrasonic obstacle detection significantly enhances safety compared to conventional systems.

Overall, VOCIBOT offers a cost-effective, modular, and efficient solution suitable for assistive, educational, and surveillance applications, contributing to the advancement of intuitive human-robot interaction systems.

#### REFERENCES

1. International Conference on Advances Automotive Technologies, 2016.
  2. T. Lens, J. Kunz, and O. von Stryk, "Bio Rob-Arm," International Symposium on Robotics, 2010.
  3. "A Smart Voice Controlled Pick and Place Robot," IRJET.
  4. "Voice Controlled Robot using Bluetooth," IJERT.
  5. "Speech Recognition Wireless Control System for Mobile Robotics," MDPI.
  6. "Voice Controlled Application using ESP32," Journal of Electrical Engineering and Automation.
  7. "Acoustic Robot Using Arduino," International Journal of Engineering Research & Technology (IJERT), 2017.
  8. "Arduino Based Voice Controlled Robot Vehicle," IOP Conference Series: Materials Science and Engineering.
  9. "Arduino Based Bluetooth Voice Controlled Robot Car and Obstacle Detector," International Journal of Scientific Research in Science, Engineering and Technology.
  10. "Voice Controlled Robot Using Bluetooth," International Journal of Engineering Research & Technology.
- "A Review on Voice Controlled AI Robot (VOCIBOT)" International Journal of Engineering Research and Development, Volume 22, Issue 2 (February 2026).

# CERTIFICATES OF RESEARCH PAPER



# PROJECT POSTER



## PROJECT POSTER




**PRIYADARSHINI BHAGWATI COLLEGE OF ENGINEERING, NAGPUR**  
An Autonomous Institution Affiliated to R.T.M. Nagpur University, Nagpur  
Accredited with Grade 'A' by NAAC



**VOCIBOT – Voice Controlled AI Robot**

|                                                                                                                                                                                                                                                              |                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>◆ <b>ABSTRACT :</b><br/>VOCIBOT is a voice-controlled robotic system that enables hands-free operation using AI-based speech recognition. It integrates Arduino, Bluetooth communication, and ESP32-CAM for real-time monitoring and safe navigation.</p> | <p>◆ <b>PROBLEM STATEMENT</b><br/>Traditional robotic systems rely on manual controllers, which limit natural human-machine interaction and accessibility. Additionally, many existing systems lack real-time monitoring and safety features, making them less suitable for assistive and surveillance applications.</p> | <br>                    |
| <p><b>BLOCK DIAGRAM – VOICE CONTROLLED AI ROBOT</b></p>                                                                                                                    | <p>◆ <b>OBJECTIVES</b></p> <ul style="list-style-type: none"> <li>Voice-based control</li> <li>Wireless communication</li> <li>Real-time monitoring</li> <li>Obstacle detection</li> </ul>                                                                                                                               |                                                                                                                                                                                               |
| <p>◆ <b>WORKING</b></p> <ul style="list-style-type: none"> <li>Voice input via mobile</li> <li>Converted to command</li> <li>Sent via Bluetooth</li> <li>Arduino processes</li> <li>Motors execute movement</li> </ul>                                       | <p>◆ <b>RESULT</b></p> <ul style="list-style-type: none"> <li>Response time: &lt;500ms</li> <li>Communication Range: 8-10m</li> <li>Accuracy: 95%</li> <li>Smooth and reliable Real-time operation</li> </ul>                                                                                                            | <p>◆ <b>APPLICATION</b></p> <ul style="list-style-type: none"> <li>Home assistant</li> <li>Education and Learning</li> <li>Office/ Reception Assistant</li> <li>Personal Assistant</li> </ul> |
| <p>◆ <b>FUTURE SCOPE</b></p> <ul style="list-style-type: none"> <li>Autonomous Navigation</li> <li>Face recognition</li> <li>Obstacle Detection</li> <li>Advanced AI Learning</li> </ul>                                                                     | <p>◆ <b>Session - 2025-26</b><br/> <b>Guided By:</b> <u>Dr. J. Y. Hande</u><br/> <b>Designed By:</b> Reshma Satpute<br/> Vedant Pathrabe<br/> Raksha Sonewane<br/> Lavanya Gabhane<br/> Mahek Gupta</p>                                                                                                                  |                                                                                                                                                                                               |

## PROJECT IMAGE



## PROFILE OF STUDENTS

|                                                                                     |                           |                                                                                      |
|-------------------------------------------------------------------------------------|---------------------------|--------------------------------------------------------------------------------------|
|    | <b>Name:</b>              | Reshma Namdeo Satpute                                                                |
|                                                                                     | <b>Mobile No.:</b>        | 72194 73814                                                                          |
|                                                                                     | <b>E-mail ID:</b>         | <a href="mailto:Reshmasatpute19@gmail.com">Reshmasatpute19@gmail.com</a>             |
|                                                                                     | <b>Permanent Address:</b> | At Post. Ganeshpur, Tah. Warud, Dist. Amravati                                       |
|                                                                                     | <b>Name:</b>              | Vedant R Pathrabe                                                                    |
|                                                                                     | <b>Mobile No.:</b>        | 8208295228                                                                           |
|                                                                                     | <b>E-mail ID:</b>         | <a href="mailto:vedantpathrabe31@gmail.com">vedantpathrabe31@gmail.com</a>           |
|                                                                                     | <b>Permanent Address:</b> | Jaghnath, Budhwari, Oppsite TB Hospital, karandhinkar line, Pathrabe mohalla, Nagpur |
|   | <b>Name:</b>              | Raksha Sonewane                                                                      |
|                                                                                     | <b>Mobile No.:</b>        | 8329368775                                                                           |
|                                                                                     | <b>E-mail ID:</b>         | <a href="mailto:rakshasonewane437@gmail.com">rakshasonewane437@gmail.com</a>         |
|                                                                                     | <b>Permanent Address:</b> | At Pst. Indora Khurd, Tah. Tirora, Dist. Gondia                                      |
|  | <b>Name:</b>              | Lavanya Bhaskar Gabhane                                                              |
|                                                                                     | <b>Mobile No.:</b>        | 8830958930                                                                           |
|                                                                                     | <b>E-mail ID:</b>         | <a href="mailto:gabhane.lavanya31@gmail.com">gabhane.lavanya31@gmail.com</a>         |
|                                                                                     | <b>Permanent Address:</b> | Katkamwar Layout, Swami vivekanand Ward, Bypass Road, Ramtek                         |
|  | <b>Name:</b>              | Mahek Gupta                                                                          |
|                                                                                     | <b>Mobile No.:</b>        | 8484079881                                                                           |
|                                                                                     | <b>E-mail ID:</b>         | <a href="mailto:guptamahek419@gmail.com">guptamahek419@gmail.com</a>                 |
|                                                                                     | <b>Permanent Address:</b> | Deshpande layout wardhman nagpur near water tank nagpur,444008                       |