

Lokmanya Tilak Jankalyan Shikshan Sanstha's



**PRIYADARSHINI BHAGWATI COLLEGE OF ENGINEERING,
NAGPUR**

Harpur Nagar, Umred Road, Nagpur- 440024

An Autonomous Institution Affiliated to R.T.M. Nagpur University, Nagpur

Accredited with Grade 'A' by NAAC



Synopsis Report

On

VOCIBOT – Voice Controlled AI Robot

Academic Session

2025-26

Submitted by:

Reshma Satpute (06)

Raksha Sonewane(30)

Vedant Pathrabe (27)

Lavanya Gabhane (39)

Mahek Gupta (50)

Branch & Semester:

ELECTRONICS AND TELECOMMUNICATION (4TH YEAR)

ABSTRACT:

The continuous growth of embedded systems, artificial intelligence, and wireless communication technologies has significantly influenced the development of intelligent robotic systems. Human-machine interaction has evolved from traditional manual controls to more natural and user-friendly interfaces such as voice-based control. The Voice Control AI Robot is an advanced robotic system designed to perform movements and actions based on spoken commands, providing an efficient and hands-free method of controlling robotic operations.

This project focuses on the design and development of a mobile robotic platform that integrates voice command processing, wireless communication, motor control, and real-time visual monitoring. The system is primarily controlled using an Arduino Uno Rev3, which acts as the central processing unit responsible for interpreting received commands and controlling the robot's movement. Voice commands are transmitted wirelessly using an HC-05 Bluetooth module, enabling seamless communication between the user and the robot through a smartphone or compatible voice interface.

The robot's motion is controlled using an L293D motor driver shield, which allows safe and reliable control of multiple DC motors. The robot is equipped with BO motors and N20 geared motors with wheels, ensuring smooth movement, sufficient torque, and stability on flat surfaces. A caster wheel is incorporated to maintain balance and enable easy directional changes. The mechanical structure of the robot is fabricated using a 5 mm sunboard sheet, making the system lightweight, durable, and suitable for educational and experimental use.

To enhance the intelligence and monitoring capability of the system, an ESP32-CAM module is integrated into the robot. This module enables live video streaming over Wi-Fi, allowing the user to visually monitor the robot's surroundings in real time. The inclusion of the camera module adds a surveillance and observation feature to the robot, making it useful for security monitoring, indoor inspection, and remote observation applications. The ESP32-CAM operates independently while coordinating with the Arduino-based control system.

An audio feedback mechanism is incorporated using a Bluetooth audio player and a 1.5-inch speaker, allowing the robot to produce voice prompts or sound indications based on user commands or system status. This feature improves user interaction and provides feedback regarding command execution. Power management is handled using 18650 lithium-ion batteries, along with appropriate battery holders, an ON/OFF switch, battery charger, and battery level indicator. These components ensure stable power supply, safe operation, and ease of maintenance.

The working principle of the system involves receiving voice commands from the user, transmitting them wirelessly to the robot, processing the commands through the microcontroller, and executing the corresponding motor actions. The robot responds in real time, enabling forward movement, backward movement, left and right turns, and stop operations. The integration of wireless communication, embedded control, and AI-based vision makes the robot highly flexible and adaptable to different operating conditions.

The Voice Control AI Robot demonstrates the effective integration of embedded systems, Bluetooth communication, motor control technology, and artificial intelligence-based vision. The system offers an intuitive control mechanism that reduces human effort and eliminates the need for traditional remote controllers or manual switches. It is particularly beneficial for applications requiring hands-free operation and ease of use.

Overall, this project serves as a practical implementation of modern robotics concepts and provides a strong foundation for future enhancements such as obstacle avoidance, machine learning-based decision making, gesture control, and full integration with smart home and IoT platforms. The developed system highlights the importance of voice-controlled intelligent robots in advancing automation and human-machine interaction.

LITERATURE SURVEY:

1. Voice-Controlled Robotic Systems

Voice-controlled robots aim to enhance human–machine interaction using spoken language as the main control interface. Earlier systems used preset voice patterns stored in microcontrollers, which required extensive training and were limited in vocabulary and accuracy. With advancements in speech recognition algorithms and smartphone integration, modern voice-controlled robots can interpret natural language commands more accurately and reliably.

A study by *B. Sarada et al.* demonstrates a Bluetooth-based voice-controlled robot that uses a mobile app to send voice commands to the robot via an HC-05 module. Commands such as forward, backward, left, and right are interpreted and executed by an onboard controller, proving effective control using simple hardware and software integration. [IJERT](#)

Similarly, *Mehlam Ali et al.* present an Arduino-based Bluetooth voice-controlled robot with integrated obstacle detection, illustrating real-time response to voice commands and safe navigation in indoor environments. [IJSRST](#)

Another work published in *IJRASSET* explores a robotic vehicle controlled by voice via Bluetooth and an Android app. The study highlights the importance of combining mobile speech interfaces with microcontroller-driven hardware for intuitive operation. [IJRASET](#)

2. Speech Recognition and Control Techniques

The use of wireless communication to transmit voice commands from mobile devices to robots is a major trend in recent research. Bluetooth modules like HC-05 are widely adopted due to their low power usage and ease of interfacing with microcontrollers such as Arduino Uno. Bluetooth provides a reliable short-range communication link suitable for indoor applications. [ijsart.com](#)

An advanced wireless control system described by *MDPI* uses an ESP32 microcontroller in combination with an Android application to perform speech recognition and command execution. This architecture distributes processing between the robot and the mobile device, resulting in reduced command latency and improved responsiveness during navigation tasks. [MDPI](#)

Research also shows that Wi-Fi-based voice systems can enable remote monitoring and cloud-assisted speech processing. However, these systems often depend on stable internet connectivity and may face network latency issues compared to Bluetooth-based solutions, which remain a preferred choice for local control. [irojournals.com](#)

3. Embedded Control Systems in Robotics

Microcontrollers such as Arduino Uno and ESP32 have become foundational in robotics due to their flexibility, community support, and ease of interfacing with sensors and actuators. The Arduino platform allows seamless integration with DC motors, motor drivers like L293D, and communication modules, making it ideal for prototype-level robotics projects. [jespublication.com](#)

The ESP32 microcontroller is gaining popularity due to its built-in Wi-Fi and Bluetooth capabilities, enabling more compact designs with fewer external modules. Research on voice controlled applications using ESP32 shows that it can host both communication and processing tasks efficiently, making it suitable for complex robotics applications where machine learning models or real-time analytics are needed. [irojournals.com](#)

Motor driver ICs such as L293D and L298N are commonly used to interface low-power control boards with high-current DC motors. These drivers act as safe intermediaries between the microcontroller and the motors, ensuring reliable motion control without damaging the control circuitry. Several studies confirm that these ICs are effective for indoor robotic platforms requiring precise directional control. [IJERT](#)

4. Wireless Communication Techniques

Wireless communication is indispensable in remote control robotics. *Bluetooth modules (HC-05)* are widely documented for their ease of use and wide adoption in mobile-to-robot transmission systems for voice commands. Projects documented in *IJSART* successfully used Bluetooth to transfer voice-derived signals from smartphones to microcontroller systems, demonstrating reliable voice command following motion actions. ijsart.com

Wi-Fi communication using modules like ESP32 also provides benefits such as remote video monitoring and cloud integration. However, the complexity in implementation and potential latency due to network fluctuation are highlighted as limitations compared to Bluetooth-based local control systems. [MDPI](http://mdpi.com)

5. Integration of Vision and Safety Systems

Recent works emphasize augmenting basic voice-controlled robots with vision and safety features. The inclusion of camera modules like ESP32-CAM allows real-time video streaming and basic computer vision tasks such as object detection and navigation assistance. Literature suggests that robots with visual sensing show higher adaptability and autonomous behavior than robots relying solely on voice commands and basic sensors. irojournals.com

Obstacle detection systems—commonly using ultrasonic sensors (e.g., HC-SR04)—are frequently integrated to prevent collisions and enhance safe navigation. Studies indicate that ultrasonic sensors provide reliable range measurements for indoor robotics, enabling the robot to make real-time decisions about movement and path correction. [IJERT](http://ijert.org)

6. Limitations in Existing Research

Despite significant progress, existing systems still face challenges such as:

- *Noise sensitivity:* Voice recognition performance degrades in high noise environments unless sophisticated filtering or offline models are used.
- *Dependency on mobile/cloud processing:* Many speech recognition implementations depend on smartphone processing or cloud services, which may introduce latency or connectivity dependencies.
- *Limited command sets:* Some systems only recognize a fixed set of predefined commands, reducing flexibility compared to natural language understanding.

These limitations have been noted across multiple studies and indicate areas for further improvement. [MDPI](http://mdpi.com)

7. Research Gap and Motivation

From the reviewed literature, it is clear that while several systems successfully combine voice recognition, wireless communication, and basic motion control, there is a gap in integrating all these with AI-powered vision and real-time processing in a compact, robust platform. Existing research often focuses on one or two subsystems at a time, but comprehensive systems that fuse voice control, vision, safety (obstacle avoidance), and efficient embedded control remain less explored.

The proposed Voice Control AI Robot aims to fill this gap by integrating:

- Arduino-based embedded control with Bluetooth voice commands,
- ESP32-CAM for real-time video monitoring,
- Safe motion control with ultrasonic obstacle detection,
- Modular design for enhanced scalability and future AI improvements.

This integrated approach enhances usability, adaptability, and practical deployment in indoor robotics applications.

Cited Sources

1. *Voice Controlled Robot using Bluetooth* — IJERT publication:
<https://www.ijert.org/voice-controlled-robot-using-bluetooth> IJERT
2. *Arduino Based Bluetooth Voice Controlled Robot Car and Obstacle Detector* — IJSRSET article:
<https://ijsrset.com/IJSRSET231097> IJSRST
3. *Voice Controlled and Obstacles Detection Robotic Vehicle* — IJRASET:
<https://www.ijraset.com/research-paper/voice-controlled-and-obstacles-detection-robotic-vehicle> IJRASET
4. *Speech Recognition Wireless Control System for Mobile Robotics* — MDPI:
<https://www.mdpi.com/2673-4052/6/3/25> MDPI
5. *Voice Controlled Application using ESP32* — Journal of Electrical Engineering and Automation:
<https://irojournals.com/iroeea/article/view/7/3/2> irojournals.com
6. *Voice Controlled Robot with Obstacle Detection* — IJSART:
<https://ijsart.com/public/storage/paper/pdf/IJSARTV7I648854.pdf> ijsart.com
7. *Voice Controlled Robot with HC-05 and ultrasonic sensors* — IJRASET:
<https://www.ijraset.com/research-paper/voice-controlled-robot> IJRASET

PROBLEM STATEMENT

In today's world, robotic systems are increasingly used in areas such as education, security, assistance, and smart automation. However, most low-cost robotic platforms still depend on manual control methods like switches, joysticks, or basic mobile apps, which limit ease of use and intelligence. These systems often lack natural interaction, real-time monitoring, and multimedia feedback.

There is a need for a cost-effective, intelligent mobile robot that can be controlled wirelessly, provide live visual monitoring, give audio feedback, and operate reliably on battery power. Such a system should be simple enough for students to build, yet advanced enough to demonstrate modern technologies like Bluetooth control, Wi-Fi camera streaming, motor automation, and embedded systems.

The challenge is to design and develop a multi-functional robotic vehicle using affordable components such as Arduino Uno, motor driver shields, Bluetooth modules, camera modules, and battery management systems, while ensuring smooth movement control, wireless communication, and efficient power usage.

AIM AND OBJECTIVES:

AIM:

The aim of this project is to design and develop a low-cost smart robotic vehicle that can be wirelessly controlled using Bluetooth, provide live video monitoring through a Wi-Fi camera, and operate efficiently using a rechargeable battery system, for educational, surveillance, and automation purposes.

OBJECTIVES:

The main objectives of the project are:

1. To design a mobile robotic system using Arduino Uno and DC motors for smooth and controlled movement.

2. To implement wireless control of the robot using a Bluetooth module (HC-05) for easy and flexible operation.
3. To integrate a Wi-Fi camera module (ESP32-CAM) for real-time video streaming and remote monitoring.
4. To control motor direction and speed using a motor driver shield (L293D).
5. To develop a battery-powered system using rechargeable lithium-ion batteries with battery level indication.
6. To provide audio output using a Bluetooth audio module and speaker for alerts or interaction.
7. To design a compact and stable robot chassis using sunboard and wheel assemblies.
8. To ensure reliable ON/OFF control and safe power management for continuous operation.
9. To create an educational prototype that helps students understand embedded systems, wireless communication, and robotics.
10. To build a scalable platform that can be enhanced in the future with sensors, AI, or autonomous features.

PROJECT INTRODUCTION:


With the advancement of Artificial Intelligence (AI) and wireless communication, voice-controlled robotic systems are becoming increasingly popular in automation, surveillance, and assistive technologies. Traditional robots usually depend on manual controls such as switches, remotes, or mobile buttons, which can be inconvenient and less interactive.

This project presents the design and development of a Voice Controlled AI Robot with Wireless Camera and Audio System using Arduino Uno, Bluetooth, and ESP32-CAM. The robot can be controlled using human voice commands, making interaction more natural and user-friendly. Voice commands such as *forward*, *backward*, *left*, *right*, and *stop* are given through a smartphone or voice-enabled application, where AI-based speech recognition converts spoken words into control signals.


The robot uses an HC-05 Bluetooth module to receive processed voice commands and an L293D motor driver shield to control DC motors. A Wi-Fi camera module (ESP32-CAM) provides real-time video streaming for remote monitoring. An audio module and speaker are included for sound alerts or feedback. The system is powered using rechargeable lithium-ion batteries with a battery level indicator for safe operation.

This project demonstrates the practical application of AI-based voice control, embedded systems, wireless communication, and robotics, making it ideal for educational, surveillance, and assistive applications.

BLOCK DIAGRAM:



FLOW CHART:



RESEARCH METHODOLOGY:

The research methodology describes the systematic approach followed to design, develop, and implement the Voice Controlled AI Robot. The methodology includes system analysis, hardware design, software development, integration, and testing.

1. System Analysis and Requirement Study

Initially, the project requirements were analysed to understand the need for a hands-free, voice-controlled robotic system with real-time monitoring and audio feedback. The system was required to:

- Accept voice commands
- Convert voice into text using AI
- Control robot movement wirelessly
- Provide live video streaming
- Operate using a battery-powered system

Based on these requirements, suitable hardware and software components were selected.

2. Hardware Methodology

The hardware design focuses on selecting and integrating electronic components to build the robotic system.

Hardware Components Used

- Arduino UNO – Main control unit
- HC-05 Bluetooth Module – Wireless communication
- L293D Motor Driver Shield – Motor control
- DC Motors with Wheels – Robot movement
- ESP32-CAM – Wi-Fi camera for live video streaming
- Bluetooth Audio Module & Speaker – Audio output
- Lithium-ion Batteries (18650) – Power supply
- Battery Level Indicator – Power monitoring
- ON/OFF Switch – Power control
- Robot Chassis (Sunboard) – Mechanical structure

Hardware Working Methodology

1. The battery pack supplies power to all modules.
2. The HC-05 Bluetooth module receives control signals from the smartphone.
3. The Arduino UNO processes the received commands.
4. The motor driver (L293D) amplifies Arduino signals to drive DC motors.
5. The ESP32-CAM streams live video over Wi-Fi independently.
6. The audio module and speaker generate sound output when required.
7. All components are mounted securely on the chassis.

3. Software Methodology

The software methodology defines how voice commands are processed and executed.

Software Tools Used

- Arduino IDE – Programming Arduino UNO
- ESP32-CAM Arduino Core – Camera programming
- Voice Recognition Mobile App / Google Assistant – Speech processing
- Bluetooth Controller Application – Command transmission
- Embedded C / Arduino Language – Control logic

Software Working Methodology

1. The user gives a voice command through a mobile AI application.
2. The AI application converts speech into text.
3. The text command is mapped to predefined control actions.
4. The command is sent to the robot via Bluetooth.
5. Arduino reads and validates the command.
6. Motor control logic is executed based on the command.
7. Camera streaming and audio output run simultaneously.
8. The system loops continuously for new commands.

4. Integration Methodology

After individual module testing, the hardware and software components were integrated step-by-step:

- Bluetooth communication tested first
- Motor control tested separately
- Camera streaming tested independently
- Audio module tested
- Final system integration and synchronization performed

5. Testing and Validation

The system was tested under different conditions:

- Voice command accuracy
- Bluetooth range and response time
- Motor movement correctness
- Video streaming stability
- Battery backup performance

The robot responded accurately to voice commands such as **forward, backward, left, right, and stop**.

6. Methodology Outcome

The adopted methodology successfully resulted in the development of a reliable, low-cost, and intelligent voice-controlled AI robot, demonstrating effective integration of hardware, software, and AI technologies.

PROPOSED PLAN OF WORK:

Months	Phase /Title	Activities to be Performed	Expected Outcome
Month 1	Problem Identification & Literature Survey	• Identify project problem and objective • Study existing voice-controlled robot systems • Review research papers and online resources • Finalize project scope	Clear problem definition and feasibility study
Month 2	System Design & Planning	• Design block diagram and flow chart • Select hardware components (Arduino, HC-05, ESP32-CAM, motors, battery) • Select software tools and platforms	Complete system design and finalized component list
Month 3	Hardware Implementation	• Fabricate robot chassis • Mount motors, wheels, battery pack • Interface Arduino with motor driver and Bluetooth module • Power supply connections	Fully assembled robotic hardware
Month 4	Software Development	• Write Arduino code for motor control • Configure Bluetooth communication • Program ESP32-CAM for video streaming • Configure voice control mobile application	Working software modules
Month 5	System Integration & Testing	• Integrate hardware and software • Test voice command execution • Test robot movement, camera, and audio • Debug and optimize system	Stable and tested prototype
Month 6	Evaluation & Documentation	• Evaluate system performance • Record results and observations • Prepare project report and presentation • Final review and submission	Completed project with documentation

APPLICATION AND ADVANTAGES:

Applications:

The Voice Controlled AI Robot can be used in various real-world applications where hands-free control, automation, and remote monitoring are required.

1. Home Automation
 - Used to control and monitor household activities using voice commands.
 - Helpful for elderly and physically challenged persons.
2. Surveillance and Security
 - Live video streaming using ESP32-CAM enables remote area monitoring.
 - Useful in restricted or unsafe environments.
3. Defence and Military Applications
 - Can be used for reconnaissance and surveillance in hazardous zones.
 - Reduces human risk during critical operations.
4. Industrial Automation
 - Voice-based control of mobile robots in industries.
 - Useful in warehouses and manufacturing units.
5. Educational Purpose
 - Helps students understand AI, robotics, embedded systems, and IoT concepts.
 - Suitable for academic projects and demonstrations.
6. Healthcare Assistance
 - Assists in patient monitoring and medicine delivery in hospitals.
 - Minimizes direct human contact.
7. Search and Rescue Operations
 - Useful in disaster-affected areas for locating victims using camera feedback.

Advantages:

1. Hands-Free Operation
 - Robot can be controlled completely using voice commands.
2. Low Cost and Affordable
 - Uses economical components like Arduino UNO and HC-05.
3. User-Friendly Interface
 - Voice control makes it easy for non-technical users.
4. Wireless Control
 - Bluetooth communication provides flexible and remote operation.
5. Real-Time Video Monitoring

- ESP32-CAM enables live video streaming.
- 6. Expandable System
 - Additional sensors (ultrasonic, gas, temperature) can be added easily.
- 7. Energy Efficient
 - Battery-powered system with level indicator ensures power monitoring.
- 8. Portable and Compact Design
 - Lightweight and easy to carry.

REFERENCES:

- Arduino Official Website – *Arduino UNO Technical Documentation*
<https://www.arduino.cc>
- Espressif Systems – *ESP32-CAM Technical Reference Manual*
<https://www.espressif.com>
- HC-05 Bluetooth Module Datasheet
<https://components101.com>
- L293D Motor Driver Datasheet – Texas Instruments
- Google Speech-to-Text API Documentation
<https://cloud.google.com/speech-to-text>
- M. Banzi, *Getting Started with Arduino*, O'Reilly Media
- IEEE Research Papers on Voice Controlled Robotics

Project Guide

Project Co-ordinator

HOD (ETC)

Dr. J. Y. Hande

Dr. J. Y. Hande

Prof. S. D. Kakde

Dr. P. B. Pokle