Early Fish Degradation Trigger Alert System

A White Paper

Author: Sowmya Maddala
Date: August 2025

Contents:

1. Executive Summary
2. Background & Motivation
3. Data & Assumptions
4. Methodology
    a. Data Acquisition
    b. Rolling Statistical Features
    c. Initial Change Point Detection
    d. Multi-Statistic Consensus Filtering (Per Sensor)
    e. Multi-Sensor Fusion
    f. Label Engineering
    g. Machine Learning Models
    h. Model Based Confirmation Layer
5. Micro Example (Intuition)
6. Visualization & Reporting
    a. Methodology Workflow
    b. ML models - Seer
    c. ML models - Tuna
7. Insights & Key Learnings
8. Results
9. Findings
10. Business & Real-World Impact
11. Limitations & Assumptions
12. Future Improvements
13. Conclusion
14. Appendix A: Glossary
15. Appendix B: Practical Settings

1) Executive Summary

Fish spoilage is a gradual yet critical process that significantly impacts food quality, safety, and economic value. Ensuring the freshness and quality of fish during storage and transportation is a critical challenge in the seafood industry. Traditional quality assessment methods rely on manual inspection or laboratory analysis, which are time-consuming, subjective, costly, and unsuitable for real-time monitoring.

This white paper presents the development of an **Early Fish Degradation Trigger Alert System** of **Seer** & **Tuna** fish species, which uses **multisensor time-series data** (e.g., hydrogen sulfide [H_2S], ammonia [NH_3], temperature, etc.), **rolling statistical features** and **machine learning models** to provide **early, reliable, and automated alerts** for fish degradation. The system is designed for **real-time monitoring**, enabling businesses across the seafood supply chain to make **proactive, data-driven decisions** that reduce spoilage, cost, and improve consumer safety.

---

2) Background & Motivation

- **Problem:** Fish is highly perishable, and spoilage can occur rapidly under improper storage. Even small delays in detection can lead to significant financial loss and consumer health risks. Early detection of spoilage indicators can help reduce waste, optimize storage conditions, and ensure food safety.

- **Traditional Limitations:** Manual inspections are inconsistent, subjective, and unable to capture early microscopic chemical/biological changes.

- **Goal:** Develop an **automated, sensor-driven system** that detects spoilage signals at their earliest onset by fusing multiple data streams into a single **early warning trigger alert** that is biologically meaningful, data-driven, and practical for operations.

---

3) Data & Assumptions

To ensure practical relevance, the dataset was collected under controlled conditions. Sensor readings were recorded continuously from the point when each fish sample was fresh until it was identified as spoilt. This provided a natural progression of freshness loss over time.

---

4) Methodology

4.1 Data Acquisition

- The dataset consists of two fish species: *Seer* (229 data points) and *Tuna* (195 data points). Data collection was carried out in September 2021. Each sample was monitored using gas sensors(eg., H_2S, NH_3, CO_2, O_2, VOC) and temperature sensors, with readings taken at regular intervals(e.g., every 5 minutes) until spoilage. This structure allowed us to capture the entire degradation process in a time-series manner, essential for developing early warning alerts.

- **Gaps** handled with a **specialized imputation algorithm** designed for online use (deduplicates timestamps, supports multiple interpolation methods, and—when enough history exists—can switch to dynamic LSTM; otherwise uses robust rolling IQR/median logic).

4.2 Rolling Statistical Features

For each sensor, compute with a **1-hour sliding window**:

- **Mean** and **Median** (central tendency)

- **Z-Score:** $z(t) = x(t) - \mu 1h(t)/\sigma 1h(t)$

- **Rate of Change (ROC):** $ROC(t) = x(t) - x(t - \Delta)$ (Δ chosen within the 1-hour window)

- **Relative ROC:** $rROC(t) = x(t) - x(t - \Delta)|x(t - \Delta)| + \epsilon$

- **Rolling quantiles:** Q1, Q2 (median), Q3, and IQR = Q3 − Q1 for **dynamic** thresholds.

  Intuition: Rolling statistics capture both gradual drift (median/mean) and sharp transitions (ROC/rROC/z-score) while adapting to local context.

4.3 Initial Change Point (CP) Detection

- **Rule:** Mark a **candidate CP** when a chosen rolling statistic (e.g., rolling mean, z-score, ROC, rROC) stays **above its own rolling median (Q2)** for **≥ 30 consecutive minutes**.

4.4 Multi-Statistic Consensus Filtering (Per-Sensor)

- Retain a candidate CP **only if at least 2 statistics** (e.g., ROC *and* rROC) agree for the same sensor.

- **Benefit:** Reduces noise-driven spikes and false positives.

4.5 Multi-Sensor Fusion

- Elevate a CP to a **final alert** only when **≥ 2 different sensors** detect a CP **at the same timestamp**.

- Apply a **1-hour minimum separation** between finalized CPs to avoid redundant detections. Apply the **1-hour separation only *after* a CP is finalized** (i.e., after multi-sensor agreement). This prevents suppressing valid detections that may occur shortly after a single-statistic, non-finalized candidate.

- **Empirical note: ROC** and **relative ROC** emerged as the most influential contributors to early CP detection.

4.6 Label Engineering

Because real spoilage labels were unavailable, we created **synthetic labels** that reflect expected biology and sensor behavior:

a) Spoilage Index (Regression; 0–1)

- **Linear** ramp via `np.linspace(0,1,N)`

- **Sigmoid** for slow-then-fast progression

- **Exponential** to mirror gases like **H_2S/NH_3** that accelerate as spoilage progresses

- **Purpose:** Train models to predict a continuous spoilage score from sensors at any time—independent of absolute elapsed time.

b) Spoilage Levels (Classification; {0=Fresh, 1=Medium, 2=Spoiled})

- Divide each experiment's timeline into **three equal segments** → synthetic stage labels.

- **Purpose:** Train models for a simple, operationally friendly freshness stage.

c) Time-to-Spoil (Regression)

- Label = `(end_time − current_time)` for each point.

- **Purpose:** Estimate remaining shelf life on the fly.

4.7 Machine Learning Models

a) Regression: Linear Regression, Random Forest, Gradient Boosting — trained to predict **spoilage index** and **time-to-spoil** from sensor inputs.

b) Classification: Logistic Regression, Random Forest, SVM — trained to predict **spoilage level (0/1/2)**.

4.8 Model-Based Confirmation Layer

After the multi-sensor CP is identified statistically (Steps 4.3–4.5), we apply **model-based gating** using predictions at the CP timestamp:

- **Linear spoilage index ≥ 0.3**
- **Sigmoid spoilage index ≥ 0.3**
- **Exponential spoilage index ≥ 0.1**
- **Predicted spoilage level ≥ 1** (on 0–2 scale)

Only CPs meeting **both** the statistical criteria **and** these model thresholds are retained as **critical alerts**. This removes “early but non-critical” fluctuations and focuses on meaningful events.

---

5) Micro-Example (Intuition)

- For **H_2S**, suppose the **rolling z-score** exceeds 1.0 at 10:00 and stays > 1.0 until 10:30.
- Simultaneously, **relative ROC** >> 5%(1-hour rolling median of rolling relative ROC) over next 30 minutes starting from 10:00 to 10:30.
- **Per-sensor consensus:** (z-score, rROC) → candidate CP at 10:00–10:30 window.
- **Multi-sensor fusion:** NH_3 shows the same pattern in that interval with (median, mean) from 10:00 to 10:30 → **final CP at 10:00, triggered at 10:30**.
- **Model layer:** Predicted exponential spoilage index = 0.42, sigmoid = 0.38, linear = 0.35; spoilage level = 1 → **alert retained**.

---

6) Visualization & Reporting

Methodology Workflow

1a) Temperature Initial Change Point Detection







1b) Hydrogen Sulfide Initial Change Point Detection







2a) Temperature Multi-Statistic Consensus Filtering



2b) Hydrogen Sulfide Multi-Statistic Consensus Filtering



3) Multi-Sensor Fusion - Final Change Points





4) Model Based Confirmation Layer - Critical Change Points

Seer





Tuna





ML Models - Seer

1a) Spoilage Index Labeling



1b) Spoilage Index Predictions



2) Spoilage Level Predictions



ML Models - Tuna

1a) Spoilage Index Labeling



1b) Spoilage Index Predictions



2) Spoilage Level Predictions



---

7) Insights & Key Learnings

1. **Consensus is king:** Requiring ≥2 statistics (per sensor) and ≥2 sensors (system-level) dramatically reduces false positives.

2. **Dynamic thresholds win:** Rolling medians and IQR of calculated statistics adapt to drift and seasonality better than static thresholds.

3. **Model gating matters:** Spoilage index/level predictions filter “early but likely benign” bumps, yielding actionable alerts.

4. **H_2S & NH_3 behave exponentially:** This validates the exponential label for regression and the emphasis on these sensors for CPs.

5. **Real-time nuance:** Only apply the 1-hour separation **after** finalization to avoid suppressing valid detections.

6. The system successfully balances **sensitivity (catching spoilage early)** and **specificity (avoiding false triggers)**.

---

8) Results

- **Before model gating:** Multiple early CPs (especially from ROC/rROC) → useful but noisy.
- **After model gating:** Early, low-impact CPs dropped; **fewer, more credible alerts** remained.
- **Alignment:** Final CPs on forecasted data matched or slightly preceded CPs on actuals—supporting **early warning** value.

---

9) Findings

- Early spoilage was detected **several hours before visible signs** in most test cases.
- The hybrid approach reduced **false positives by ~40%** compared to single-metric detection.
- Model integration further **improved confidence and interpretability** of alerts.
- The system reliably **triggered critical alerts 1–2 hours in advance**, allowing intervention time.
- Achieved reliable spoilage index predictions in the range **0–1** aligned with expected spoilage trends.
- Classification models correctly separated spoilage into 3 freshness levels with good accuracy (within the assumptions of synthetic labels).

---

10) Business & Real-World Impact

- **Waste Reduction:** Early detection allows removal of spoiled lots before contamination spreads.
- **Supply Chain Efficiency:** Enables rerouting or early sales decisions to minimize loss by dynamic shelf-life estimation.
- **Food Safety**: Prevents spoiled fish from reaching consumers.

- **Scalability:** Online-compatible, species-agnostic core; thresholds and models can be adapted per species or site.

- **Cost Savings**: Reduced losses and extended shelf life translate to significant financial benefits.

---

11) Limitations

- **Synthetic labels:** Until true spoilage ground truth is collected, regression/classification is anchored to biologically reasonable surrogates.

- **Site dependence:** Baselines may vary by storage, season, handling.

---

12) Future Improvements

1. **Forecasting Models** for sensor data to predict spoilage trends ahead of time.
2. **Integration with IoT systems** for fully automated real-time alerts.
3. **Online Real-Time Deployment** by extending a system for live sensor data streams.
4. **Larger dataset validation** with real-world spoilage ground truth.
5. **Adaptive thresholds** personalized for different fish types, storage conditions, and environments.

---

13) Conclusion

By combining **dynamic rolling statistics**, **multi-level consensus**, and a **model-based confirmation layer** trained on **synthetic yet biologically-informed labels**, this system provides **early, reliable, and interpretable** alerts for fish degradation of **Seer & Tuna**. It is robust to missing data, practical for real-time use, and designed for continuous improvement as richer labels become available. The framework is flexible, extendable, and capable of being deployed in **real-time supply chain monitoring systems**, offering both **scientific insights** and **tangible business impact**. The Early Fish Degradation Trigger Alert System represents a significant step toward **smarter cold-chain monitoring**, ensuring fresher products for consumers and reducing losses for businesses.

Appendix A: Glossary

- **Rolling mean/median:** Average/median computed over the last hour, shifting each minute.
- **Rolling Z-score:** How many standard deviations the current value is from its 1-hour average.
- **ROC (rate of change):** The step change vs. a previous point (e.g., 30 minutes ago).
- **Relative ROC:** ROC divided by the earlier value (i.e., percentage change).
- **IQR (interquartile range):** Spread between the 75th and 25th percentiles; robust to outliers.
- **CP (change point):** A time when the pattern meaningfully shifts.
- **Spoilage index (0–1):** A continuous score estimating where we are on the fresh→spoiled spectrum.
- **Spoilage level (0/1/2):** Fresh, Medium, Spoiled—simple operational categories.

Appendix B: Practical Settings (Defaults)

- Rolling window: **1 hour**
- Candidate CP rule: **> rolling median for ≥ 30 minutes**
- Per-sensor consensus: **≥ 2 statistics** (often **ROC & rROC**)
- Multi-sensor fusion: **≥ 2 sensors** simultaneously
- Real-time separation: **1 hour applied only after final CP**
- Model gating thresholds: **Linear ≥ 0.3**, **Sigmoid ≥ 0.3**, **Exponential ≥ 0.1**, **Level ≥ 1**