

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

```
mysql> CREATE DATABASE MONIKA_8018531
-> CREATE DATABASE MONIKA_8018531;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to
MySQL 8.0 for the right syntax to use near 'CREATE DATABASE MONIKA_8018531' at line 2
mysql> CREATE DATABASE MONIKA_8018531;
Query OK, 1 row affected (0.12 sec)

mysql> SHOW DATABASES;
+-----+
| Database |
+-----+
| information_schema |
| monika_8018531     |
| mysql              |
| performance_schema |
| sys                |
| world              |
+-----+
6 rows in set (0.06 sec)

mysql> USE MONIKA_8018531;
Database changed
mysql>
```

```
Query OK, 0 rows affected (0.26 sec)

mysql> CREATE TABLE flights(
-> id INT NOT NULL AUTO_INCREMENT,
-> origin VARCHAR(15) NOT NULL,
-> destination VARCHAR(15) NOT NULL,
-> duration INT NOT NULL,
-> PRIMARY KEY(id)
-> );
Query OK, 0 rows affected (0.46 sec)

mysql> CREATE TABLE flights_noIndex(
-> id INT NOT NULL,
-> origin TEXT NOT NULL,
-> destination TEXT NOT NULL,
-> duration INTEGER NOT NULL
-> );
Query OK, 0 rows affected (1.10 sec)

mysql> INSERT INTO flights
-> (origin,destination,duration)
-> VALUES ("New York","London",415);
Query OK, 1 row affected (0.13 sec)

mysql> INSERT INTO flights
-> (origin,destination,duration)
-> VALUES ("Shanghai","paris",760);
Query OK, 1 row affected (0.21 sec)

mysql> INSERT INTO flights
```

```
-> (origin,destination,duration)
-> VALUES ("Shanghai","Paris",760);
Query OK, 1 row affected (0.21 sec)

mysql> INSERT INTO flights
      -> (origin,destination,duration)
      -> VALUES ("Istanbul","Tokyo",700);
Query OK, 1 row affected (0.21 sec)

mysql> INSERT INTO flights
      -> (origin,destination,duration)
      -> VALUES ("Istanbul","Paris",435);
Query OK, 1 row affected (0.12 sec)

mysql> INSERT INTO flights
      -> (origin,destination,duration)
      -> VALUES ("New York","Paris",435);
Query OK, 1 row affected (0.10 sec)

mysql> INSERT INTO flights
      -> (origin,destination,duration)
      -> VALUES ("Moscow","Paris",245);
Query OK, 1 row affected (0.17 sec)

mysql> INSERT INTO flights
      -> (origin,destination,duration)
      -> VALUES ("Lima","New York",455);
Query OK, 1 row affected (0.10 sec)

mysql>
```

```
mysql> SELECT * FROM flights WHERE id=3;
+-----+-----+-----+-----+
| id | origin | destination | duration |
+-----+-----+-----+-----+
| 3 | Istanbul | Tokyo | 700 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> SELECT * FROM flights WHERE origin="New York";
+-----+-----+-----+-----+
| id | origin | destination | duration |
+-----+-----+-----+-----+
| 1 | New York | London | 415 |
| 5 | New York | Paris | 435 |
+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM flights WHERE duration>500;
+-----+-----+-----+-----+
| id | origin | destination | duration |
+-----+-----+-----+-----+
| 2 | Shanghai | paris | 760 |
| 3 | Istanbul | Tokyo | 700 |
+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM flights WHERE duration>500 AND destination="paris";
+-----+-----+-----+-----+
| id | origin | destination | duration |
+-----+-----+-----+-----+
| 2 | Shanghai | paris | 760 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> SELECT * FROM flights WHERE duration>500 OR destination="paris";
```

id	origin	destination	duration
2	Shanghai	paris	760
3	Istanbul	Tokyo	700
4	Istanbul	Paris	435
5	New York	Paris	435
6	Moscow	Paris	245

```
5 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM flights WHERE origin IN ("New York","Lima");
```

id	origin	destination	duration
1	New York	London	415
5	New York	Paris	435
7	Lima	New York	455

```
3 rows in set (0.05 sec)
```

```
mysql> SELECT * FROM flights WHERE origin like"%a%";
```

id	origin	destination	duration
2	Shanghai	paris	760
3	Istanbul	Tokyo	700
4	Istanbul	Paris	435
7	Lima	New York	455

```
4 rows in set (0.06 sec)
```

```
mysql>
```

MySQL 8.0 Command Line Client

4 rows in set (0.06 sec)

```
mysql> SELECT DISTINCT origin,destination FROM flights WHERE origin IN("New York", "Lima");
```

origin	destination
New York	London
New York	Paris
Lima	New York

3 rows in set (0.05 sec)

```
mysql> SELECT DISTINCT origin FROM flights WHERE origin IN("New York", "Lima");
```

origin
New York
Lima

2 rows in set (0.00 sec)

```
mysql> SELECT * FROM flights LIMIT 5;
```

id	origin	destination	duration
1	New York	London	415
2	Shanghai	paris	760
3	Istanbul	Tokyo	700
4	Istanbul	Paris	435
5	New York	Paris	435

5 rows in set (0.00 sec)

mysql>

MySQL 8.0 Command Line Client

```
mysql> SELECT * FROM flights order by duration;
```

id	origin	destination	duration
6	Moscow	Paris	245
1	New York	London	415
4	Istanbul	Paris	435
5	New York	Paris	435
7	Lima	New York	455
3	Istanbul	Tokyo	700
2	Shanghai	paris	760

7 rows in set (0.00 sec)

```
mysql> SELECT ORIGIN,COUNT(DURATION) FROM FLIGHTS GROUP BY ORIGIN;
```

ORIGIN	COUNT(DURATION)
New York	2
Shanghai	1
Istanbul	2
Moscow	1
Lima	1

5 rows in set (0.00 sec)

```
mysql> SELECT ORIGIN,COUNT(DURATION) FROM FLIGHTS GROUP BY ORIGIN having count(duration)>2;  
Empty set (0.28 sec)
```

```
mysql> SELECT ORIGIN,COUNT(DURATION) FROM FLIGHTS GROUP BY ORIGIN having count(duration)=2;
```

ORIGIN	COUNT(DURATION)
New York	2

MySQL 8.0 Command Line Client

New York	2
Shanghai	1
Istanbul	2
Moscow	1
Lima	1

5 rows in set (0.00 sec)

```
mysql> SELECT ORIGIN,COUNT(DURATION) FROM FLIGHTS GROUP BY ORIGIN having count(duration)>2;
Empty set (0.28 sec)
```

```
mysql> SELECT ORIGIN,COUNT(DURATION) FROM FLIGHTS GROUP BY ORIGIN having count(duration)=2;
```

ORIGIN	COUNT(DURATION)
New York	2
Istanbul	2

2 rows in set (0.00 sec)

```
mysql> SELECT ORIGIN,COUNT(DURATION) FROM FLIGHTS GROUP BY ORIGIN having count(duration)<2;
```

ORIGIN	COUNT(DURATION)
Shanghai	1
Moscow	1
Lima	1

3 rows in set (0.00 sec)

```
mysql>
mysql> UPDATE flights
  -> SET duration = 430
  -> WHERE origin="New York"
  -> AND destination="London";
Query OK, 1 row affected (0.10 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> select * from flights;
+----+-----+-----+-----+
| id | origin | destination | duration |
+----+-----+-----+-----+
| 1 | New York | London | 430 |
| 2 | Shanghai | paris | 760 |
| 3 | Istanbul | Tokyo | 700 |
| 4 | Istanbul | Paris | 435 |
| 5 | New York | Paris | 435 |
| 6 | Moscow | Paris | 245 |
| 7 | Lima | New York | 455 |
+----+-----+-----+-----+
7 rows in set (0.06 sec)

mysql> DELETE FROM flights WHERE destination="Tokyo";
Query OK, 1 row affected (0.13 sec)

mysql> select * from flights;
+----+-----+-----+-----+
| id | origin | destination | duration |
+----+-----+-----+-----+
| 1 | New York | London | 430 |
| 2 | Shanghai | paris | 760 |
| 4 | Istanbul | Paris | 435 |
| 5 | New York | Paris | 435 |
| 6 | Moscow | Paris | 245 |
| 7 | Lima | New York | 455 |
+----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql> select AVG(duration) from flights;
+-----+
| AVG(duration) |
+-----+
| 460.0000 |
+-----+
```

```
mysql> select COUNT(duration) from flights;
+-----+
| COUNT(duration) |
+-----+
|          6      |
+-----+
1 row in set (0.10 sec)

mysql> select COUNT(duration) from flights where orgin="New York";
ERROR 1054 (42S22): Unknown column 'orgin' in 'where clause'
mysql> select COUNT(duration) from flights where origin="New York";
+-----+
| COUNT(duration) |
+-----+
|          2      |
+-----+
1 row in set (0.00 sec)

mysql> select sum(duration) from flights;
+-----+
| sum(duration)   |
+-----+
|          2760   |
+-----+
1 row in set (0.00 sec)

mysql> select min(duration) from flights;
+-----+
| min(duration)   |
+-----+
|          245    |
+-----+
1 row in set (0.05 sec)

mysql> select max(duration) from flights;
+-----+
| max(duration)   |
+-----+
|          760    |
+-----+
1 row in set (0.00 sec)

mysql>
```



```
mysql> select max(duration) from flights;
```

```
+-----+  
| max(duration) |  
+-----+  
|           760 |  
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> START TRANSACTION;
```

```
Query OK, 0 rows affected (0.00 sec)
```

```
mysql> INSERT INTO flights
```

```
-> (origin,destination,duration)
```

```
-> VALUES ("Chennai","Bangalore",123);
```

```
ERROR 1146 (42S02): Table 'monika_8018531.flights' doesn't exist
```

```
mysql> INSERT INTO flights
```

```
-> (origin,destination,duration)
```

```
-> VALUES ("Chennai","Bangalore",123);
```

```
Query OK, 1 row affected (0.06 sec)
```

```
mysql> COMMIT;
```

```
Query OK, 0 rows affected (0.11 sec)
```

```
mysql> SET AUTOCOMMIT=0;
```

```
Query OK, 0 rows affected (0.00 sec)
```

```
mysql> select * from flights;
```

```
+-----+-----+-----+-----+  
| id | origin  | destination | duration |  
+-----+-----+-----+-----+  
| 1  | New York | London      | 430      |  
| 2  | Shanghai | paris       | 760      |  
| 4  | Istanbul | Paris       | 435      |  
| 5  | New York | Paris       | 435      |  
| 6  | Moscow   | Paris       | 245      |  
| 7  | Lima     | New York    | 455      |  
| 8  | Chennai  | Bangalore   | 123      |  
+-----+-----+-----+-----+
```

```
7 rows in set (0.06 sec)
```

```
mysql> INSERT INTO flights
```

```
-> (origin,destination,duration)
```

```
-> VALUES ("Chennai","Goa",533);
```

```
mysql> INSERT INTO flights
-> (origin,destination,duration)
-> VALUES ("Chennai","Goa",533);
Query OK, 1 row affected (0.05 sec)

mysql> INSERT INTO flights
-> (origin,destination,duration)
-> VALUES ("Madurai","Goa",933);
Query OK, 1 row affected (0.00 sec)

mysql> select * from flights
-> ;
+----+-----+-----+-----+
| id | origin  | destination | duration |
+----+-----+-----+-----+
| 1  | New York | London      | 430      |
| 2  | Shanghai | paris       | 760      |
| 4  | Istanbul | Paris       | 435      |
| 5  | New York | Paris       | 435      |
| 6  | Moscow   | Paris       | 245      |
| 7  | Lima     | New York    | 455      |
| 8  | Chennai  | Bangalore   | 123      |
| 9  | Chennai  | Goa         | 533      |
| 10 | Madurai  | Goa         | 933      |
+----+-----+-----+-----+
9 rows in set (0.00 sec)

mysql> Delete from flights WHERE origin="New York";
Query OK, 2 rows affected (0.06 sec)

mysql> select * from flights;
+----+-----+-----+-----+
| id | origin  | destination | duration |
+----+-----+-----+-----+
| 2  | Shanghai | paris       | 760      |
| 4  | Istanbul | Paris       | 435      |
| 6  | Moscow   | Paris       | 245      |
| 7  | Lima     | New York    | 455      |
| 8  | Chennai  | Bangalore   | 123      |
| 9  | Chennai  | Goa         | 533      |
| 10 | Madurai  | Goa         | 933      |
+----+-----+-----+-----+
7 rows in set (0.00 sec)
```

```
mysql> Rollback;  
Query OK, 0 rows affected (0.12 sec)
```

```
mysql> select * from flights;
```

id	origin	destination	duration
1	New York	London	430
2	Shanghai	paris	760
4	Istanbul	Paris	435
5	New York	Paris	435
6	Moscow	Paris	245
7	Lima	New York	455
8	Chennai	Bangalore	123

```
7 rows in set (0.06 sec)
```

```
mysql> CREATE TABLE airports(  
  -> id INT NOT NULL AUTO_INCREMENT,  
  -> code VARCHAR(3) NOT NULL,  
  -> city VARCHAR(15) NOT NULL,  
  -> PRIMARY KEY(id)  
  -> );
```

```
Query OK, 0 rows affected (1.41 sec)
```

```
mysql> INSERT INTO airports (code,city)VALUES("JFK","New York");  
Query OK, 1 row affected (0.09 sec)
```

```
mysql> INSERT INTO airports (code,city)VALUES("PVG","Shanghai");  
Query OK, 1 row affected (0.00 sec)
```

```
mysql> INSERT INTO airports (code,city)VALUES("IST","Istanbul");  
Query OK, 1 row affected (0.00 sec)
```

```
mysql> INSERT INTO airports (code,city)VALUES("LHR","London");  
Query OK, 1 row affected (0.00 sec)
```

```
mysql> INSERT INTO airports (code,city)VALUES("SVO","Moscow");  
Query OK, 1 row affected (0.07 sec)
```

```
mysql> INSERT INTO airports (code,city)VALUES("LIM","Lima");  
Query OK, 1 row affected (0.00 sec)
```

# MySQL 8.0 Command Line Client

Query OK, 1 row affected (0.00 sec)

```
mysql> INSERT INTO airports (code,city)VALUES("LHR","London");
```

Query OK, 1 row affected (0.00 sec)

```
mysql> INSERT INTO airports (code,city)VALUES("SVO","Moscow");
```

Query OK, 1 row affected (0.07 sec)

```
mysql> INSERT INTO airports (code,city)VALUES("LIM","Lima");
```

Query OK, 1 row affected (0.00 sec)

```
mysql> INSERT INTO airports (code,city)VALUES("CDG","Paris");
```

Query OK, 1 row affected (0.00 sec)

```
mysql> INSERT INTO airports (code,city)VALUES("NRT","Tokyo");
```

Query OK, 1 row affected (0.00 sec)

```
mysql> select * from airports;
```

+-----+-----+			
id   code   city			
+-----+-----+			
1	JFK	New York	
2	PVG	Shanghai	
3	IST	Istanbul	
4	LHR	London	
5	SVO	Moscow	
6	LIM	Lima	
7	CDG	Paris	
8	NRT	Tokyo	

8 rows in set (0.00 sec)

MySQL 8.0 Command Line Client

ERROR 1051 (42S02): Unknown table 'monika\_8018531.passenger'

```
mysql> CREATE TABLE passenger (  
-> id INT NOT NULL,  
-> fname VARCHAR(15) NOT NULL,  
-> lname VARCHAR(15) NOT NULL,  
-> flight_id INT,  
-> INDEX par_ind (flight_id),  
-> CONSTRAINT fk_flights FOREIGN KEY(flight_id)  
-> REFERENCES flights(id)  
-> ON DELETE SET NULL  
-> ON UPDATE SET NULL  
-> );
```

Query OK, 0 rows affected (1.84 sec)

```
mysql> INSERT INTO Passenger(id,fname,lname,flight_id) VALUES(1,"Harry","Potter",1);
```

Query OK, 1 row affected (0.07 sec)

```
mysql> INSERT INTO Passenger(id,fname,lname,flight_id) VALUES(2,"Ron","Weasley",1);
```

Query OK, 1 row affected (0.00 sec)

```
mysql> INSERT INTO Passenger(id,fname,lname,flight_id) VALUES(2,"Hermione","Granger",2);
```

Query OK, 1 row affected (0.00 sec)

```
mysql> INSERT INTO Passenger(id,fname,lname,flight_id) VALUES(2,"Draco","Malfoy",42);
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '1' at line 1

```
mysql> INSERT INTO Passenger(id,fname,lname,flight_id) VALUES(2,"Draco","Malfoy",42);
```

ERROR 1452 (23000): Cannot add or update a child row: a foreign key constraint fails (`monika\_8018531`.`passenger`, CONSTRAINT `fk\_flights` (`id`) ON DELETE SET NULL ON UPDATE SET NULL)

```
mysql> INSERT INTO Passenger(id,fname,lname,flight_id) VALUES(2,"Draco","Malfoy",4);
```

Query OK, 1 row affected (0.10 sec)

```
mysql> INSERT INTO Passenger(id,fname,lname,flight_id) VALUES(2,"Luna","Lovegood",6);
```

Query OK, 1 row affected (0.00 sec)

```
mysql> INSERT INTO Passenger(id,fname,lname,flight_id) VALUES(2,"Ginny","Weasley",6);
```

Query OK, 1 row affected (0.00 sec)

```
mysql> select * from passenger;
```

id	fname	lname	flight_id
1	Harry	Potter	1
2	Ron	Weasley	1

```
mysql> select * from passenger;
```

id	fname	lname	flight_id
1	Harry	Potter	1
2	Ron	Weasley	1
2	Hermione	Granger	2
2	Draco	Malfoy	4
2	Luna	Lovegood	6
2	Ginny	Weasley	6

```
6 rows in set (0.00 sec)
```

  

```
mysql> SELECT flight_id,fname,lname,origin,destination
-> From flights JOIN passenger
-> ON passenger.flight_id=flights.id;
```

flight_id	fname	lname	origin	destination
1	Harry	Potter	New York	London
1	Ron	Weasley	New York	London
2	Hermione	Granger	Shanghai	paris
4	Draco	Malfoy	Istanbul	Paris
6	Luna	Lovegood	Moscow	Paris
6	Ginny	Weasley	Moscow	Paris

```
6 rows in set (0.11 sec)
```

  

```
mysql> SELECT flight_id,fname,lname,origin,destination
-> From flights OUTER JOIN passenger
-> ON passenger.flight_id=flights.id;
```

```
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL version
ON passenger.flight_id=flights.id' at line 2
```

```
mysql> SELECT flight_id,fname,lname,origin,destination
-> From flights RIGHT OUTER JOIN passenger
-> ON passenger.flight_id=flights.id;
```

flight_id	fname	lname	origin	destination
1	Harry	Potter	New York	London
1	Ron	Weasley	New York	London
2	Hermione	Granger	Shanghai	paris

```
mysql> SELECT flight_id,fname,lname,origin,destination
-> From flights RIGHT OUTER JOIN passenger
-> ON passenger.flight_id=flights.id;
```

flight_id	fname	lname	origin	destination
1	Harry	Potter	New York	London
1	Ron	Weasley	New York	London
2	Hermione	Granger	Shanghai	paris
4	Draco	Malfoy	Istanbul	Paris
6	Luna	Lovegood	Moscow	Paris
6	Ginny	Weasley	Moscow	Paris

5 rows in set (0.08 sec)

```
mysql> SELECT flight_id,fname,lname,origin,destination
-> From flights LEFT OUTER JOIN passenger
-> ON passenger.flight_id=flights.id;
```

flight_id	fname	lname	origin	destination
1	Harry	Potter	New York	London
1	Ron	Weasley	New York	London
2	Hermione	Granger	Shanghai	paris
4	Draco	Malfoy	Istanbul	Paris
NULL	NULL	NULL	New York	Paris
6	Luna	Lovegood	Moscow	Paris
6	Ginny	Weasley	Moscow	Paris
NULL	NULL	NULL	Lima	New York
NULL	NULL	NULL	Chennai	Bangalore

9 rows in set (0.00 sec)

```
mysql>
```