

Theory of Computation, Fall 2021

Assignment 5 (Due November 12 Friday 9:35am)

- Q1. Let a, b, c be three distinct symbols. Use pumping theorem to show that $A = \{wcw : w \in \{a, b\}^*\}$ is not context-free.
- Q2. Let A be a context-free language. Let B be a regular language. Prove that $A \cap B$ is context-free. You may assume that A and B are defined over the same alphabet Σ . (Hint: let P_A be a PDA accepting A . Let M_B be an NFA accepting B . Construct a PDA P_\cap that conceptually runs P_A and M_B in parallel.)
- Q3. Let $A = \{w \in \{a, b, c\}^* : w \text{ has same number of } a\text{'s, } b\text{'s, and } c\text{'s}\}$.
- (a) Prove that A is not context-free. (Hint: It is not necessary to use pumping theorem. You may try the conclusion of Q2.)
 - (b) Show that \overline{A} is context-free. (Hint: it suffices to show that \overline{A} is a union of several context-free languages)
- Q4. Fix an alphabet Σ contains \triangleright and \sqcup . Given a precise definition for the head-moving machine M_\rightarrow , which, regardless of the symbol it reads, always moves its head to the right and then halt immediately.
- Q5. What happens if you run the machine L_\sqcup on the tape $\triangleright ba \sqcup$?
- Q6. Design a right-shifting machine S_\rightarrow that transforms $\triangleright \sqcup w \sqcup$ into $\triangleright \sqcup \sqcup w \sqcup$, where w is a string that contains no blank symbol. You may use the machines and the diagrams we presented in class.

References

- [1] Sipser M.. Introduction to the Theory of Computation. CENGAGE Learning (2013)
- [2] Lewis H., Papadimitriou C.. Elements of the Theory of Computation. Prentice-Hall (1998)