

# SPI, Intel 8080, and Motorola 6800 communication protocol between MCU and OLED driver.

## Application Note

AN007

### Introduction

This application note describes three different communication protocols between MCU and an OLED driver.

### SPI

SPI stands for Serial Peripheral Interface. It's a serial bus standard established by Motorola. Devices communicate using a master/slave relationship, in which the master initiates the data frame. SPI is a synchronous serial interface in which data in an 8-bit byte can be shifted one bit at a time (Refer to Figure 1).




Figure 1: Two SPI Modules Connected in a Master-Slave Configuration

In the master SPI, the bits are sent out of the SDIN pin. The CS# pin must be low to select a slave device. SDIN is shifted into an 8-bit shift register on every rising edge of SCLK in the order of D7, D6, ..., D0. D/C is sampled on every eight clock and the data byte in the shift register is written to the Display Data RAM or command register in the same clock (Refer to Figure 2).




Figure 2 – Display data write procedure in SPI mode

## 6800-series Parallel Interface

The parallel interface consists of 8 bi-directional data pins ( $D_7$ - $D_0$ ),  $WR\#$ ,  $RD\#$ , and  $CS\#$ . An input high on  $R/W\#$  ( $WR\#$ ) indicates a read operation from RAM or the status register.  $R/W\#$  ( $WR\#$ ) input low indicates a write operation to display data RAM or Internal Command Registers depending on the status of  $D/C\#$  input. The  $E$  ( $RD\#$ ) input serves as data latch signal (clock) when high provided that  $CS\#$  is low.




Figure 3: 6800-series MPU Timing Diagram

## 8080-series Parallel Interface

The parallel interface consists of 8 bi-directional data pins ( $D_7$ - $D_0$ ),  $E$  ( $RD\#$ ),  $R/W\#$  ( $WR\#$ ),  $D/C\#$ ,  $CS\#$ . The  $E$  ( $RD\#$ ) input serves as data read latch signal (clock) when it is low, and provided that  $CS\#$  is low. Data read latch signal is disabled when  $E$  ( $RD\#$ ) is high. Display data or status register read is controlled by  $D/C\#$ .  $R/W\#$  ( $WR\#$ ) input serves as data write latch signal (clock) when it is low and provided that  $CS\#$  is low. Display data or command register write is controlled by  $D/C\#$ .




Figure 4: 8080-series MPU Timing Diagram

**Author:** Sonny Remigio  
OLED Product Development  
San Jose, USA

May, 2005

**About Osram Opto Semiconductors**

Osram Opto Semiconductors GmbH, Regensburg, is a wholly owned subsidiary of Osram GmbH, one of the world's three largest lamp manufacturers, and offers its customers a range of solutions based on semiconductor technology for lighting, sensor and visualisation applications. The company operates facilities in Regensburg (Germany), San José (USA) and Penang (Malaysia). Further information is available at [www.osram-os.com](http://www.osram-os.com).

All information contained in this document has been checked with the greatest care. OSRAM Opto Semiconductors GmbH can however, not be made liable for any damage that occurs in connection with the use of these contents