Disentangling linguistic features effects in TMNRED EEG dataset: a mixed models re-analysis

Giulio Sesini

Department of Psychology, Milan-Bicocca University, Piazza dell'Ateneo Nuovo, Milan, 20126, Italy, .

Contributing authors: giulio.sesini@gmail.com;

Abstract

TMNRED is an open access EEG dataset recorded while chinese subjects read 400 chinese sentences (target and nontarget) divided in 8 blocks. In the current study EEG features were computed on MNE python, alongside linguistic features of such sentences computed through natural language processing and methodological features such as repetitions of the sentences across blocks and target-nontarget group division based on the original research design. A new approach based on Linear Mixed Modelling was used in order to test whether fixed effects would differ from the original study when taking into account repetitions, linguistic features, subject and sentence variability. RSA was used to test the relationship between representational dissimilarity matrices of neural responses to such sentences and a semantic representational similarity matrix between the same sentences. Results showed: smaller group effects and new significant linguistic features effects, with between-subject and trial-level variability dominating fixed effects; non significant RSA similarity between neural pattern and semantic similarity across sentences; classifiers accuracy in binary classification (target vs nontarget) mainly accounted for by linguistic features.

Keywords: neurolinguistics, EEG, NLP

1 Background

Language is one of the main advanced cognitive human functions. One of the core processes of language cognition is semantic semantic processing, which functions as

the foundation for human thought and behavior. Neuroimaging techniques allow for extraction and analysis of neural activities underlying semantic encoding [1].

Brain rhythms are surely one of the possible measures of brain activity used for this purpose. Regarding processing of sentences syntactic binding is possibly the main process underlying such function, that is the combination of words into larger structures. Brain rhythms seem to play a core role in syntactic binding, as older adults in older adults syntactic binding has been associated with increases in theta, alpha and beta power. In particular, modulations in the alpha and beta band are thought to underlie the actual binding taking place [2] . Specifically, semantic (retrieval) processes and any other highly cognitive loaded processes, such as syntactic dependencies processing, have been associated with modulation of alpha and beta power to support storage of information [2, 3].

The current study is based on an open access EEG dataset, namely "TMNRED", for semantic target identification in natural reading environments. The dataset was obtained from 30 participants who read 400 divided in 8 blocks, one for each of the 8 recording sessions. The sentences were derived from public internet and media sources, and divided into two groups: target semantic materials and non-target semantic materials, where target materials were of four types of semantics (i.e. names, means of transportation, animals, and fruits). The language used in such setting was Chinese, which, contrary to English, is a logographic language. Moreover, as an ideographic writing system, each character contains information on form, sound and semantics, with extensive presence of polysemous words and homophones [1]. Its word order rules and syntactic structures pose higher demands on the linguistic cognitive processes. The authors of such dataset originally tested for a group effect on EEG recording of channels of interest (Cz, C3, Pz, Oz) and of PSD features. The present study aims at testing these results on the relationship between EEG features and sentences semantic features, while taking into account variability within the experimental design, namely: sentence repetition across blocks, linguistic features of each sentence (i.e. word and character frequencies, number of strokes, surprisal, syntactic complexity), random subject and sentence variability. Moreover an ulterior objective was to carry out a Representational Similarity Analysis to further test whether the EEG responses to such sentences would be significantly related to their semantic similarities. Finally, classifiers would be used to assess the unique and combined contribution of nlp features and EEG features in distinguishing between target and nontarget sentences. The initial approach involved using across subject cross-validation only, but following LMM results, a pipeline for within subject cross validation was implemented as well with the intention of testing whether performances would differ when controlling for between subjects variability. Expected results included a weaker group effect when taking into account the above confounding variables and variability, and weak similarity from RSA, with weak performance of EEG based classifier and features not significantly improving the accuracy of EEG-nlp based classifiers compared to the nlp based classifier. As for the comparison between across-subjects and within subject models, better performances in within-subject midels were expected due to between-subject variability control.

2 Methods

An MNE python pipeline was used in order to carry out preprocessing of raw EEG data front he TMNRED dataset [1].The pipeline followed the steps carried out in the dataset paper and included: bad channel detection with channels with power spectra greater than twice the standard deviation of the mean power spectrum marked as bad; interpolation; re-referencing; 0.5-80Hz bandpass filter and 50Hz notch filter; downsampling to 200Hz; ICA; epoching based on the duration of each trial. Trials with median variance of each channel twice the standard deviation and median difference between each channel and its mean twice the standard deviation were dropped (4,5%).

An NLP pipeline was implemented in Python in order to extract linguistic and semantic features for each sentence. Syntactic complexity was computed as the maximum depth of the dependency tree derived from Stanza's dependency parse. Lexical surprisal was computed using the GPT-2 language model as the negative log-probability of each token given its preceding context, then sentence-level surprisal was computed as the average of word-level values [4, 5]. The number of strokes of each sentence was computed as the mean of the number of strokes of all Chinese characters of the sentence, which were obtained from a stroke-count dictionary derived from the Unihan database [6]. Lexical frequency of each sentence was estimated using SUBTLEX-CH norms, taking both the mean log character frequency and the mean log word frequency [6, 7]. In addition, sentence-level semantic representations were obtained using Sentence-BERT embeddings, and cosine similarity was computed for all possible pairs of the 400 sentences in order to generate a semantic representational similarity matrix [8].

The dataset derived from these pipelines included: subjects' ids; sessions' ids corresponding to the id of the block of sentences; group (i.e. target or nontarget sentence); unique labels of each sentences, that is when the sentence is repeated the label remains the same both times; labels indicating whether it is the first or second occurrence of the sentence; NLP features, namely syntactic complexity, surprisal, strokes, char_frequency, word_frequency; early (0-500ms) and late (¿500ms) EEG features, namely amplitude of channel of interest, amplitude of ROI (i.e. clusters of channels), theta-alpha-beta-gamma power in channel of interest, theta-alpha-beta-gamma power in ROI (e.g. left beta activation); Z_scores of the above features.

Considering the numerosity of the dataset (N=11455) and the nature of my research questions, z-scores were used to standardize the NLP variables and the EEG variables, in particular regarding the variables related to PSD features a natural logarithmic function was applied before the computation of their z-scores.

From literature [6] it emerged that linguistic features can sometimes show multicollinearity, therefore a correlation matrix was used to assess whether the NLP variables were highly correlated.

The original dataset splits 400 sentences in 8 blocks of 50 each, where some sentences repeat themselves across blocks. In order to assess the possible impact of such repetition on the statistical analysis a contingency table with χ^2 test was carried out.

An independent samples T-Test with all the nlp features as dependent variables, and the grouping variable "Group" (i.e. target-nontarget sentences) was used to test whether the means of the nlp features were different among groups (target-nontarget).

The dataset derived from the EEG preprocessing is characterized by dropped trials, therefore the dataset including all 400 sentences corrected by their repetition among blocks was modified by deleting the repeated sentences (from 400 sentences the dataset narrowed down to 276), before the t-test.

In order to replicate the group effect of the original TMNRED paper a paired t-test was carried out on a dataset where each line representing a subject was built, instead of representing one sentence. Using such dataset, where each line represents a single trial, Linear Mixed Models were carried out to test whether there was a Group effect on language processing-related EEG features as cited in the original paper [1], while controlling for both repetitions and nlp features.

Representational Dissimilarity Matrices (RDM) were computed for each subject, taking into consideration only the EEG features related to semantic processing in their late components (i.e. from 500 ms) [1], namely Cz, C3, Pz, alpha late global activation and beta late left activation (computed by averaging across F3, C3, P3 beta activation). For each subject, RDMs were computed using correlation distance (1 - Pearson correlation) only across unique trials, that is after deleting all repetitions of the same sentence and keeping only the first occurrence of it. This approach was chosen over averaging across repetitions after testing for spearman correlation between RDM based on the first occurrence only, and RDM based on the second occurrence only.

For each subject, Representational Similarity Analysis (RSA) was performed by correlating the upper triangle of the neural RDM with the corresponding semantic dissimilarity matrix using Spearman correlation. All subjects results were averaged together in order to obtain a group-level result.

A permutation-based sign-flipping test (10,000 permutations) was used to assess whether the group-level mean RSA differed significantly from zero.

Supervised binary classifiers, using Logistic regression, were used in order to assess whether the available EEG and nlp features contained sufficient information to reliably distinguish target from nontarget sentences. Models were either trained on nlp features only, EEG features only or a combination of both. All predictors were z-scored. An L2-logistic regression was chosen due to the small size of the feature spaces, and balanced accuracy was used to account for imbalance between target and nontarget trials.. The analysis included a comparison between performances of classifiers built on EEG features only, nlp features only and a combination of both. Within-subject cross-validation included 5-fold cross-validation for each subject separately, with classifiers trained on 4 and tested on 1. On the other hand, Across-subject cross-validation had the model trained on 29 subjects and tested on 1. In order to assess statistical significance a permutation test was performed, with 1000 permutations where labels were randomly shuffled. For each permutation the pipeline was repeated. The p-value was computed as the proportion of permuted mean accuracies exceeding the observed mean accuracy.

3 Results

As shown in Fig. 1 the NLP features correlation matrix showed that, except for surprisal-SyntacticComplexity and strokes-SyntacticComplexity pairs, the variables

reached a significance with p¡.001. Nevertheless, overall Pearson's r were all below 0.7.

Matrice di Correlazione

		Z_SyntacticComplexity	Z_Surprisal	Z_Strokes	Z_char_frequency	Z_word_frequency
Z_SyntacticComplexity	r di Pearson	—				
	gdl	—				
	valore p	—				
Z_Surprisal	r di Pearson	−0.033	—			
	gdl	11453	—			
	valore p	< .001	—			
Z_Strokes	r di Pearson	0.001	0.312	—		
	gdl	11453	11453	—		
	valore p	0.889	< .001	—		
Z_char_frequency	r di Pearson	−0.001	−0.297	−0.431	—	
	gdl	11453	11453	11453	—	
	valore p	0.933	< .001	< .001	—	
Z_word_frequency	r di Pearson	0.121	−0.277	−0.226	0.653	—
	gdl	11453	11453	11453	11453	—
	valore p	< .001	< .001	< .001	< .001	—

Fig. 1

In order to strengthen such findings a linear regression model was carried out, with a continuous variable as VD and all NLP variables as independent variables: as shown in Fig. 2 the VIF values were all below 3, therefore all NLP variables were kept in future analysis.

Statistiche di Collinearità

	VIF	Tolleranza
Z_SyntacticComplexity	1.03	0.974
Z_Surprisal	1.17	0.854
Z_Strokes	1.30	0.768
Z_char_frequency	2.08	0.482
Z_word_frequency	1.83	0.546

Fig. 2

The independent samples t-test, as showed in Fig. 3, reports that the only feature showing significantly different means between groups was Z_Word_Frequency, t(274)=4.307, p¡.001, d=0.5235.



Fig. 3

A χ^2 test resulted significant χ^2 (1)=72.9, p¡.001, that is the target and nontarget are not balanced in repeated sentences numbers, as shown in Fig. 4



Fig. 4

A paired t-test was carried out between the target and nontarget groups. The average amplitude in late Cz resulted as significantly higher in target than nontarget, t(29)=-3.8, p¡.001, d=-0.69. The average amplitude in late C3 resulted as significantly different between target-nontarget, t(29)=4.6, p¡.001, d=-0.85. The average alpha early global activation resulted as significantly different between target-nontarget, t(29)=-2.561, p=.016, d=-0.4. The average beta early left activation resulted as significantly different between target-nontarget, t(29)=-3.4, p=.002, d=-0.63.

A Linear Mixed Model was built with Z_Late_C3 as dependent variables and Group, repetition and NLP features as independent variables. The model reached significance, Conditional R^2 = 0.088, LRTX^2(20)=846.586, p¡.001, Marginal R^2 = 0.005, LRTX^2(13)=34.559, p¡.001. No effects reached significance.

$$LateC3 \sim 1 + Group + repetition + SyntacticComplexity + Surprisal + Strokes + characterfrequency + wordfrequency + Group : repetition + Group : SyntacticComplexity + Group : Surprisal + Group : Strokes + Group : characterfrequency + Group : wordfrequency + (1 + Group + repetition|subjects) + (1|sentences)$$

A Linear Mixed Model was built with Z_Late_Cz as a dependent variable and Group, repetition and NLP features as independent variables. The model reached significance, Conditional R^2 = 0.044, LRTX^2(20)=369.136, p¡.001, Marginal R^2 = 0.003, LRTX^2(13)=23.643, p=.035. No effects reached significance.

$$LateCz \sim 1 + Group + repetition + SyntacticComplexity + Surprisal + Strokes + characterfrequency + wordfrequency + Group : repetition + Group : SyntacticComplexity + Group : Surprisal + Group : Strokes + Group : characterfrequency + Group : wordfrequency + (1 + Group + repetition|subjects) + (1|sentences)$$

A Linear Mixed Model was built with Z_Alpha_Early_Global as a dependent variable and Group, repetition and NLP features as independent variables. The model reached significance, Conditional $R^2 = 0.629$, $LRTX^2(20)$=10796.971, p¡.001, Marginal $R^2 = 0.002$, $LRTX^2(13)$=32.938, p=.002.

$$AlphaEarlyGlobal \sim 1 + Group + repetition + SyntacticComplexity + Surprisal + Strokes + characterfrequency + wordfrequency + Group : repetition + Group : SyntacticComplexity + Group : Surprisal + Group : Strokes + Group : characterfrequency + Group : wordfrequency + (1 + Group + repetition|subjects) + (1|sentences)$$

The interaction effect Group*char_frequency reached significance controlling for the other independent variables, F(1,298)=5.8245, p=.016.

Simple effects showed that only when the mean frequency of the sentence, computed based on character frequencies, is 1 SD over the mean there is a trend towards group effect on the global alpha early activation, that is a trend towards a difference between target and nontarget. F(1,643)=3.446, p=.064. As shown in Fig.Fig. 5



Fig. 5

A Linear Mixed Model was built with Z_beta_early_left as a dependent variable and Group, repetition and NLP features as independent variables. The model reached significance, Conditional $R^2 = 0.687$, $LRTX^2(17)$=112724.414, p¡.001, Marginal $R^2 = 0.003$, $LRTX^2(13)$=34.696, p¡.001. The model originally had Group—Sub as a random slope, but it failed to converge, therefore it was excluded because of its small variance.

$$BetaEarlyLeft \sim 1 + Group + repetition + SyntacticComplexity + Surprisal + Strokes + characterfrequency + wordfrequency + Group : repetition + Group : SyntacticComplexity + Group : Surprisal + Group : Strokes + Group : characterfrequency + Group : wordfrequency + (1 + repetition|subjects) + (1|sentences)$$

Syntactic Complexity reached significance controlling for the other independent variables, that is it has a significant effect on beta early left activation, b=0.1626,

IC=0.00294-0.00296, t(353.8)=2.392, p=.017. When syntactic complexity increases by one unit, beta early left activation significantly increases by 0.1626.

Moreover char_frequency reached significance controlling for the other independent variables, that is it has a significant effect on beta early left activation, b=-0.01876, IC=0.03656–9.71e-4, t(295.8)=-2.067, p=.040. When sentence frequency based on character frequency increases by one unit, beta early left activation significantly decreases by 0.01876. Fig. 6



Fig. 6

A Linear Mixed Model was built with Z_Early_Oz as a dependent variable and Group, repetition and NLP features as independent variables. The model reached significance, Conditional R^2 = 0.041, LRTX^2(20)=315.246, p¡.001, Marginal R^2 = 0.001, LRTX^2(13)=6.383, p=.931. No effects reached significance.

$EarlyOz \sim 1 + Group + repetition + SyntacticComplexity + Surprisal + Strokes + characterfrequency + wordfrequency + Group : repetition + Group : SyntacticComplexity + Group : Surprisal + Group : Strokes + Group : characterfrequency + Group : wordfrequency + (1 + Group + repetition|subjects) + (1|sentences)$

A Linear Mixed Model was built with Z_Late_Pz as a dependent variable and Group, repetition and NLP features as independent variables. The model reached significance, Conditional R^2 = 0.033, LRTX^2(20)=264.131, p¡.001, Marginal R^2 = 0.003, LRTX^2(13)=29.297, p=.006.

$LatePz \sim 1 + Group + repetition + SyntacticComplexity + Surprisal + Strokes + characterfrequency + wordfrequency + Group : repetition + Group : SyntacticComplexity + Group : Surprisal + Group : Strokes + Group : characterfrequency + Group : wordfrequency + (1 + Group + repetition|subjects) + (1|sentences)$

Surprisal reached significance controlling for the other independent variables, that is it has a significant effect on beta early left activation, b=-0.04166, IC=-0.0638- -0.01950, t(393)=-3.6851, p=.017. When surprisal increases by one unit, Pz late amplitude significantly decreases by 0.04166.

Moreover char_frequency reached significance controlling for the other independent variables, that is it has a significant effect on beta early left activation, b=-0.03205, IC=-0.0601– -0.00398, t(342)=-2.2379, p=.026. When sentence frequency based on character frequency increases by one unit,Pz late amplitude significantly decreases by 0.03205.

The interaction effect Group*strokes reached significance controlling for the other independent variables, F(1,384)=8.38103, p=.004. Fig. 7



Fig. 7

Simple effects showed that only for the target group there is a strokes effect on the Pz late amplitude, b = -0.0446, IC=0.0187- -0.08128, t(615)=-2.38, p=.017, meaning that when strokes increases by 1 unit, Pz late amplitude decreases by 0.0446. As shown in Fig. 8.

A Linear Mixed Model was built with alpha late global as a dependent variable and Group, repetition and NLP features as independent variables. The model reached significance, Conditional R^2 = 0.564, LRTX^2(20)=88818.207, p¡.001, Marginal R^2 =



Fig. 8

0.003, LRTX^2(13)=21.454, p=.064.

$AlphaLateGlobal \sim 1 + Group + repetition + SyntacticComplexity + Surprisal + Strokes + characterfrequency + wordfrequency + Group : repetition + Group : SyntacticComplexity + Group : Surprisal + Group : Strokes + Group : characterfrequency + Group : wordfrequency + (1 + Group + repetition|subjects) + (1|sentences)$

Surprisal reached significance controlling for the other independent variables, that is it has a significant effect on beta early left activation, b=0.02712, IC=0.00763-0.0466, t(295)=2.7275, p=.007. When surprisal increases by one unit, alpha late global activation significantly increases by 0.02712.

A Linear Mixed Model was built with beta late left as a dependent variable and Group, repetition and NLP features as independent variables. The model reached significance, Conditional R^2 = 0.756, LRTX^2(20)=15401.312, p¡.001, Marginal R^2 = 0.001, LRTX^2(13)=10.396, p=.661.

$BetaLateLeft \sim 1 + Group + repetition + SyntacticComplexity + Surprisal + Strokes + characterfrequency + wordfrequency + Group : repetition + Group : SyntacticComplexity + Group : Surprisal + Group : Strokes + Group : characterfrequency + Group : wordfrequency + (1 + Group + repetition|subjects) + (1|sentences)$

Word_frequency reached significance controlling for the other independent variables, that is it has a significant effect on beta early left activation, b=0.02135, IC=0.00283-0.03986, t(342.6)=2.2602, p=.024. When word_frequency increases by one unit, beta late left activation significantly increases by 0.02135. As shown in Fig. 9.
Using the same EEG features, first the correlation between a RDM based only on first sentence occurrences and a RDM based only on second occurrences had an output of a mean rho across subjects of $\tilde{0}$.007. Therefore, using only first occurrences a RSA was carried out between the semantic RSM and EEG RSM (Fig. 10) across all subjects, but it did not reach significance following a permutation test, rho(mean)=0.007, p-value: 0.1055, d= 0.30.
Regarding within subject classification, permutation testing indicated that all models performed significantly (p¡.001), NLP-only model accuracy = 0.65, EEG-only model accuracy = 0.53, NLP+EEG model accuracy = 0.65. On the other hand, across subject classification models also all performed significantly (p¡.001), with NLP-only model



Fig. 9



Fig. 10

accuracy = 0.68, EEG-only model accuracy = 0.53, NLP+EEG model accuracy = 0.68.

4 Discussion

The paired t-test, carried out between the target and nontarget groups to replicate the original result, only showed some of the expected results, possibly due to methodological differences in preprocessing pipelines: only the amplitude in late Cz and late C3 resulted as significantly higher in target than nontarget; moreover only the alpha early global activation and the beta early left activation resulted as significantly different between target-nontarget.

The NLP features in the current study did not exhibit problematic collinearity as, although the variables reached significance in the correlation matrix, all Pearson's r were below 0.7 and VIF values were below 3. This indicates that each feature provides unique information, allowing the model to clearly isolate the individual effect of each.

The sentences used in TMNRED were originally balanced for length, strokes count and word frequency [1]. Nevertheless, word frequency, as computed in the current study, was significantly different between target and nontarget groups, while all other features showed no difference as expected.

Moreover, the amount of repeated sentences was significantly not balanced between target and nontarget sentences, adding validity and foundation to the mixed model approach used in the current study.

The Linear Mixed Model, accounting for repetitions, linguistic features, random subject and sentence variability, showed that, regarding channel components, early

Oz, late C3 and late Cz amplitudes had low explained variance by both fixed and random effects and fixed effects only, and no significant effects.

Regarding the RSA, the repetition of sentences posed a serious issue as RSA needed unique trials, therefore, in order to decide whether repetitions could be averaged, a correlation between the RDM based on the first occurrence of repeated sentences and RDM based on the second occurrence was carried out. The results suggested that second occurrences and first occurrences could not be interpreted as equivalent responses differentiated by just noise, therefore a deletion-based approach, that is leaving the second occurrence trials out of the RSA. The RSA results showed that the embedding-based semantic similarity was not aligned with the neural representational structure extracted from EEG features.

These results showed that group effects on EEG features are attenuated when controlling for repetitions, linguistic features, random subject and sentence variability. Moreover, the RSA result could further support semantic-related EEG features having weak direct relation with semantic aspects of the sentences.

In contrast, Late Pz also had low explained variance by both fixed and random effects and fixed effects only, but Surprisal had a significant effect, that is the more surprisal increased the more Pz late amplitude decreased; in addition, sentence frequency, derived from characters' frequencies, had also a significant effect, meaning that the more sentence frequency increased the more Pz late amplitude decreased. An interaction effect Group*strokes also reached significance, which could be interpreted as only for the target group there is a strokes effect on the PZ late amplitude, that is the higher average number of strokes is the more the late PZ amplitude decreases. While for high frequency sentences a decrease is expected, such evidence represents an unexpected result for surprising or high-strokes-number stimuli, which are typically associated with large amplitudes [9, 10]. In this sense, a possible insight could be derived from single stream models of N400 and P600 posterior neural responses. These models posit that N400 underlies lexical retrieval and P600 reflects the integration of retrieved word meaning, the former lingers until 600 ms while the latter emerges around 600 ms, meaning that within the 500 ms window used in the current study an overlap between the two components could elicit such result in posterior channels when exposed to surprising stimuli[9]. Moreover, beta early left activation had low explained variance by fixed effects only and high explained variance by both random and fixed effects, but syntactic complexity had a significant effect while controlling for other independent variables, that is the more syntactic complexity increased the more beta early left activation significantly increased, and moreover sentence frequency, derived from characters' frequencies, had also a significant effect, meaning that the more sentence frequency increased the more beta early left activation decreased. Alpha late global activation also showed low explained variance by fixed effects only and high explained variance by both random and fixed effects, with Surprisal having a significant effect while controlling for the other independent variables, that is the more surprisal increased the more alpha late global activation increased. Finally, beta late left activation, also showed low explained variance by fixed effects only and high explained variance by both random and fixed effects, with sentence frequency derived from words's frequencies having a significant effect, meaning that the more

sentence frequency increased the more beta late left activation increased. Overall, all mixed models with alpha and beta activity as dependent variables had marginal R^2 and substantially higher conditional R^2, meaning that a large proportion of variance is attributable to between-subject and between-trials variability. The fixed effects of nlp features on alpha and beta are consistent with the increased activation of these brain rhythms related to highly cognitive loaded processes, in particular semantic processes [3].

Target-nontarget classification was primarily driven by linguistic features, with balanced accuracy above chance, whereas EEG features alone only yielded marginally above-chance decoding accuracy in both cases. Combining EEG and linguistic features did not improve performance compared to linguistic features alone, in both within and across subject cases. These results suggest that the discriminative structure between target-nontarget is captured mainly by the linguistic properties of the stimuli, aligning with mixed models results where group effects were attenuated when controlling for linguistic predictors, and with RSA findings of weak alignment between neural and semantic representational spaces.

In conclusion, when controlling for repetitions, linguistic features and hierarchical variability, the experimental group effect on EEG features is attenuated. Moreover, EEG semantic-related features seem not to reflect semantic similarity between sentences and neither to be driving the classification into target or nontarget groups. Linguistic features and between-subject and between trial variability seem to explain more variance than grouping, suggesting that stimulus-level structure accounts for most of the differentiation between groups.

5 Limitations

Some of the theoretical interpretations draws on neurolinguistics studies on alphabetical languages such as Dutch and English. Epoching and time-window selection were constrained by the available event markers in the dataset, which only marked the start of the sentence. Finally, the relatively broad time windows may include possible overlaps of ERP components, as possibly suggested by the pattern observed for the late Pz.

References

[1] Bai, Y., Tang, Q., Zhao, R., Liu, H., Guo, M., Zhang, S., Guo, M., Wang, J., Wang, C., Xing, M., Ni, G., Ming, D.: TMNRED, a Chinese Language EEG Dataset for Fuzzy Semantic Target Identification in Natural Reading Environments. https://doi.org/10.18112/openneuro.ds005383.v1.0.0

[2] Poulisse, C., Wheeldon, L., Limachya, R., Mazaheri, A., Segaert, K.: The oscillatory mechanisms associated with syntactic binding in healthy ageing. Neuropsychologia **146**, 107523 (2020) https://doi.org/10.1016/j.neuropsychologia.2020.107523

[3] Zioga, I., Zhou, Y.J., Weissbart, H., Martin, A.E., Haegens, S.: Alpha and beta oscillations differentially support word production in a rule-switching task. eNeuro **11**(4), 0312–232024 (2024) https://doi.org/10.1523/eneuro.0312-23.2024

[4] Rezaii, N., Michaelov, J., Josephy-Hernandez, S., Ren, B., Hochberg, D., Quimby, M., Dickerson, B.C.: Measuring sentence information via surprisal: Theoretical and clinical implications in nonfluent aphasia. Annals of Neurology **94**(4), 647–657 (2023) https://doi.org/10.1002/ana.26744

[5] Jano, S., Cross, Z.R., Chatburn, A., Schlesewsky, M., Bornkessel-Schlesewsky, I.: Prior context and individual alpha frequency influence predictive processing during language comprehension. Journal of Cognitive Neuroscience **36**(9), 1898–1936 (2024) https://doi.org/10.1162/jocn_a_02196

[6] Sui, L., Woumans, E., Duyck, W., Boeve, S., Dirix, N.: The word and character frequency effect in chinese natural reading. Reading and Writing (2025) https://doi.org/10.1007/s11145-025-10681-5

[7] Cai, Q., Brysbaert, M.: Subtlex-ch: Chinese word and character frequencies based on film subtitles. PLoS ONE **5**(6), 10729 (2010) https://doi.org/10.1371/journal.pone.0010729

[8] Sun, K., Liu, H.: Attention-aware semantic relevance predicting chinese sentence reading. Cognition **255**, 105991 (2024) https://doi.org/10.1016/j.cognition.2024.105991

[9] Delogu, F., Aurnhammer, C., Brouwer, H., Crocker, M.W.: On the biphasic nature of the n400-p600 complex underlying language comprehension. Brain and Cognition **186**, 106293 (2025) https://doi.org/10.1016/j.bandc.2025.106293

[10] Yang, S., Zhang, S., Wang, Q.: P2 and behavioral effects of stroke count in chinese characters: Evidence for an analytic and attentional view. Neuroscience Letters **628**, 123–127 (2016) https://doi.org/10.1016/j.neulet.2016.06.006