Pentesting Reconnaissance Vulnerable

This test was conducted for academic and personal use. All exercises were performed in controlled environments using VMs, with an attacker machine like Kali Linux and a vulnerable machine like bWAPP (BeeBox). The following tools were used to scan for vulnerabilities:

- nslookup
- whois
- Sublist3r
- Nikto
- Gobuster
- Dirb

Phase 1:

In this phase, we conducted an IP scan using **Nmap**, which identified the IP address corresponding to our vulnerable bWAPP machine.

Phase 2:

Using Nmap, we identified the services running on the IP 192.168.56.106:

- FTP (Port 21): ProFTPD 1.3.1, a file transfer service.
- SSH (Port 22): OpenSSH 4.7p1, providing remote access to the machine.
- SMTP (Port 25): Postfix, an email service.
- HTTP (Port 80): Apache 2.2.8 web server with mod fastcgi and PHP.
- NetBIOS (Ports 139 and 445): Samba, used for file sharing in local networks.
- **Multiple HTTP services** on ports 8080, 8443, 9080, and 9443, running web servers like Nginx and Lighttpd.
- VNC (Port 5901): A remote desktop control protocol.
- MySQL (Port 3306): MySQL 5.0.96 database service.
- An unusual service was also detected on port 666.

```
Starting Namap 7.945M, https://mamp.org ) at 2024-10-12 00:29 EDT
Startis: 0:00:17 clapsed; 0 hosts completed (1 up), 1 undergoing SN Stealth Scan
SNN Steath Scan Timing: About 41.094 done; ETC: 00:30 (0:00:27 emaining)
Stats: 0:01:50 clapsed; 0 hosts completed (1 up), 1 undergoing Service Scan
Service scan Timing: About 41.094 done; ETC: 00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:31 (0:00:3
```

Phase 3:

We used the **nslookup** tool to determine the domain name associated with the IP address. In some cases, reverse lookup is performed. In this instance, no domain name was generated since the IP address used does not belong to a domain. Instead, it is publicly accessible and can be used by various devices such as phones, computers, etc.

Phase 4:

We used **WHOIS**, a protocol used to query databases for information on registered entities or assignees of an internet resource. The IP address belongs to the range 192.168.0.0 - 192.168.255.255, which is a block of addresses reserved for private networks (RFC 1918). It does not provide specific ownership information since this IP range is intended for use in local networks. These addresses are not routable over the public Internet.

```
Hethangs: 192.16.8.e. 192.168.e. 25.255

IDIN: 192.168.e. 192.168.
```

Phase 5:

We assessed vulnerabilities by scanning using **Nikto**. The scan was performed on the web server hosted at IP 192.168.56.106 on port 80.

- **Detected Server**: Apache/2.2.8 on an Ubuntu system, with PHP/5.2.4 and OpenSSL/0.9.8g.
- Vulnerabilities found:
 - **ETags**: The server may leak inodes through ETag headers, potentially allowing attacks like cache synchronization (CVE-2003-1418).
 - X-Frame-Options: The anti-clickjacking header is missing.
 - X-Content-Type-Options: This header is missing, which could allow browsers to interpret content in a different MIME type.
 - crossdomain.xml: This file allows any domain to make cross-site requests, posing a security risk.
 - mod_ssl, OpenSSL, PHP, Apache: These services are outdated, exposing the server to known vulnerabilities.
 - Allowed HTTP Methods: GET, HEAD, POST, OPTIONS, and TRACE, with TRACE being a risk for Cross-Site Tracing (XST).
 - phpMyAdmin: The MySQL database management tool is exposed without proper protection.
 - Directory Indexing: An index of files was found in /icons/, allowing access to view the contents of that folder.

```
L-$ nikto -h 192.168.56.186

- Nikto v2.5.0

+ Target IP: 192.168.56.186

+ Target Hostname: 192.168.56.186

+ Target Hostname: 192.168.56.186

+ Target Hostname: 192.168.56.186

+ Target Hostname: 192.168.56.186

+ Target Pot: 98

- Scarver: Apache/2.2.8 (Ubuntu) DAV/2 mod_fastcgi/2.4.6 PHP/5.2.4-2ubuntu5 with Suhosin-Patch mod_ssi/2.2.8 OpenSSL/0.9.8g

+ /: Server any Leak inoges via Elgas, header found with file /, inode: 838422, size: 588, mtime: Sun Nov 2 13:20:24 2014. See: http://cve.naire.org/cgi-bin/cvename.cgi/name=cVC-2083-1418

+ /: The arti-clickjacking X-Frame-options header is not present. See: https://developer.mozilla.org/en-U5/docs/Web/HTTP/Headers/X-Frame-Options

- Via Nut Symphosis Hostorians and Symphosis Hostorians and Symphosis Indicated Hostorians

- Via Nut Symphosis Hostorians and Symphosis Hostorians and Symphosis Indicated Hostorians

- Via Nut Symphosis Hostorians and Symphosis Hostorians and Symphosis Indicated Hostorians Indicated Hostorians and Symphosis Indicated Hostorians I
```

Phase 6:

We used **Gobuster** and **Dirb** to review vulnerable directories and assess which ones might be susceptible to brute-force attacks.

- **Gobuster**: The scan found several interesting paths on the server 192.168.56.106, including:
 - Sensitive files like .htaccess and .htpasswd, which are accessible but return HTTP code 403 (forbidden).
 - Directories of interest such as /drupal/, /evil/, /phpmyadmin/, /webdav/, and /server-status/.
 - Directories where file listing is enabled (such as /evil/ and /webdav/), potentially exposing sensitive information.
 - /phpmyadmin/ exposes the MySQL database management tool.

```
Gobuster v3.6
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)
[+] Url:
                              http://192.168.56.106
[+] Method:
                              GET
    Threads:
                              10
    Wordlist:
                              /usr/share/seclists/Discovery/Web-Content/common.txt
   Negative Status codes:
                              404
   User Agent:
                              gobuster/3.6
[+] Timeout:
                              10s
Starting gobuster in directory enumeration mode
/.htpasswd
/.hta
                       (Status: 403)
                                      [Size: 381]
                       (Status: 403)
                                      [Size: 376]
/.htaccess
                       (Status: 403)
                                      [Size: 381]
/README
                       (Status: 200)
                                      [Size: 2491]
/crossdomain
/crossdomain.xml
                       (Status: 200)
                                      [Size: 200]
                       (Status: 200)
                                      [Size: 200]
                       (Status: 301)
                                      [Size: 407]
                                                   [--> http://192.168.56.106/drupal/]
/drupal
/evil
                       (Status:
                                 301)
                                       [Size: 405]
                                                   [--> http://192.168.56.106/evil/]
/index.html
                       (Status: 200)
                                      [Size: 588]
/index
                       (Status: 200)
                                      [Size: 45]
/phpmyadmin
                       (Status: 301)
                                      [Size: 411] [--> http://192.168.56.106/phpmyadmin/]
                                      [Size: 8304]
                                200)
                       (Status:
/server-status
/webdav
                       (Status: 301)
                                      [Size: 407] [--> http://192.168.56.106/webdav/]
Progress: 4734 / 4735 (99.98%)
Finished
```

- **Dirb**: The results are similar to those found by **Gobuster**, highlighting paths such as:
 - /drupal/: A CMS (Content Management System) that could be an attack vector if not properly secured.
 - /phpmyadmin/: As with Gobuster, the MySQL management interface is exposed.
 - Several directories where file listing is enabled, meaning users can view the files they contain.

```
Entering directory: http://192.168.56.106/evil/
 (!) WARNING: Directory IS LISTABLE. No need to scan it.
      (Use mode '-w' if you want to scan it anyway)
      - Entering directory: http://192.168.56.106/phpmyadmin/ -
 + http://192.168.56.106/phpmyadmin/favicon.ico (CODE:200|SIZE:18902)
 + http://192.168.56.106/phpmyadmin/index.php (CODE:200|SIZE:8132)
 ==> DIRECTORY: http://192.168.56.106/phpmyadmin/js/
==> DIRECTORY: http://192.168.56.106/phpmyadmin/lang/
 ==> DIRECTORY: http://192.168.56.106/phpmyadmin/libraries/
 + http://192.168.56.106/phpmyadmin/phpinfo.php (CODE:200|SIZE:0)
 ==> DIRECTORY: http://192.168.56.106/phpmyadmin/scripts/
==> DIRECTORY: http://192.168.56.106/phpmyadmin/themes/
      - Entering directory: http://192.168.56.106/webdav/ -
 (!) WARNING: Directory IS LISTABLE. No need to scan it.
(Use mode '-w' if you want to scan it anyway)
 ---- Entering directory: http://192.168.56.106/drupal/includes/ --
(!) WARNING: Directory IS LISTABLE. No need to scan it.
(Use mode '-w' if you want to scan it anyway)
 ---- Entering directory: http://192.168.56.106/drupal/misc/ ----
(!) WARNING: Directory IS LISTABLE. No need to scan it.
(Use mode '-w' if you want to scan it anyway)
 ---- Entering directory: http://192.168.56.106/drupal/modules/ --
(!) WARNING: Directory IS LISTABLE. No need to scan it.
(Use mode '-w' if you want to scan it anyway)
 ---- Entering directory: http://192.168.56.106/drupal/profiles/ ----
(!) WARNING: Directory IS LISTABLE. No need to scan it.
(Use mode '-w' if you want to scan it anyway)
 ---- Entering directory: http://192.168.56.106/drupal/scripts/ --- (!) WARNING: Directory IS LISTABLE. No need to scan it.
      (Use mode '-w' if you want to scan it anyway)
 ---- Entering directory: http://192.168.56.106/drupal/sites/ ---- (!) WARNING: Directory IS LISTABLE. No need to scan it.
      (Use mode '-w' if you want to scan it anyway)
      - Entering directory: http://192.168.56.106/drupal/themes/ ---
 (!) WARNING: Directory IS LISTABLE. No need to scan it.
      (Use mode '-w' if you want to scan it anyway)

    Entering directory: http://192.168.56.106/phpmyadmin/js/ ----

 (!) WARNING: Directory IS LISTABLE. No need to scan it.
      (Use mode '-w' if you want to scan it anyway)
    - Entering directory: http://192.168.56.106/phpmyadmin/libraries/ ----
(!) WARNING: Directory IS LISTABLE. No need to scan it.
     (Use mode '-w' if you want to scan it anyway)
    Entering directory: http://192.168.56.106/phpmyadmin/scripts/ --
(!) WARNING: Directory IS LISTABLE. No need to scan it.
     (Use mode '-w' if you want to scan it anyway)
    - Entering directory: http://192.168.56.106/phpmyadmin/themes/ ----
(!) WARNING: Directory IS LISTABLE. No need to scan it.
     (Use mode '-w' if you want to scan it anyway)
```

END_TIME: Sat Oct 12 01:15:15 2024 DOWNLOADED: 14199 - FOUND: 21

Recommendations:

Update Services: It is recommended to update Apache, PHP, OpenSSL, Samba, and MySQL to their latest versions to mitigate known vulnerabilities.

Disable Directory Indexing: Disable directory listing on the /evil/ and /webdav/ directories to prevent exposure of sensitive files.

Secure phpMyAdmin: Restrict access to phpMyAdmin and sensitive files such as wp-config.php and others.

Implement Proper Access Control (Additional Suggestion): Limit access to essential services (such as SSH and FTP) by restricting access through firewalls or using IP whitelisting to reduce exposure to unauthorized users.