

8.1 Suppose that we decompose the schema  $R = (A, B, C, D, E)$  into

$$\begin{aligned} &(A, B, C) \\ &(A, D, E). \end{aligned}$$

Show that this decomposition is a lossless-join decomposition if the following set  $F$  of functional dependencies holds:

$$\begin{aligned} &A \rightarrow BC \\ &CD \rightarrow E \\ &B \rightarrow D \\ &E \rightarrow A \end{aligned}$$

**Answer:** A decomposition  $\{R_1, R_2\}$  is a lossless-join decomposition if  $R_1 \cap R_2 \rightarrow R_1$  or  $R_1 \cap R_2 \rightarrow R_2$ . Let  $R_1 = (A, B, C)$ ,  $R_2 = (A, D, E)$ , and  $R_1 \cap R_2 = A$ . Since  $A$  is a candidate key (see Practice Exercise 8.6), Therefore  $R_1 \cap R_2 \rightarrow R_1$ .

8.19 Give a lossless-join decomposition into BCNF of schema  $R$  of Exercise 8.1.

**Answer:** From Exercise 8.6, we know that  $B \rightarrow D$  is nontrivial and the left hand side is not a superkey. By the algorithm of Figure 8.11 we derive the relations  $\{(A, B, C, E), (B, D)\}$ . This is in BCNF.

8.20 Give a lossless-join, dependency-preserving decomposition into 3NF of schema  $R$  of Practice Exercise 8.1.

**Answer:** First we note that the dependencies given in Practice Exercise 8.1 form a canonical cover. Generating the schema from the algorithm of Figure 8.12 we get

$$R' = \{(A, B, C), (C, D, E), (B, D), (E, A)\}.$$

Schema  $(A, B, C)$  contains a candidate key. Therefore  $R'$  is a third normal form dependency-preserving lossless-join decomposition.

Note that the original schema  $R = (A, B, C, D, E)$  is already in 3NF. Thus, it was not necessary to apply the algorithm as we have done above. The single original schema is trivially a lossless join, dependency-preserving decomposition.