

[DL] A Survey of FPGA Based Neural Network Accelerator

KAIYUAN GUO, SHULIN ZENG, JINCHENG YU, YU WANG AND HUAZHONG YANG, Tsinghua University, China

Recent researches on neural network have shown great improvement in computer vision over traditional algorithms based on handcrafted features and models. Neural network is now greatly adopted in regions like image, speech and video recognition. But the great computation and storage complexity of neural network based algorithms poses great difficulty on its application. CPU platforms are hard to offer enough computation capacity. While GPU platforms are highly parallelized, the energy efficiency is low. The high energy cost of GPU causes problems for a wide application of neural network.

To address the above problems, various FPGA based hardware accelerators for neural networks have been proposed. Specialized hardware are designed to achieve high speed and low power neural network process. In this paper, we give an overview of previous work on neural network accelerators based on FPGA and summarize the main techniques used. Investigation from software to hardware, from circuit level to system level is carried out to complete analysis of FPGA based neural network accelerator design and serves as a guide to future work.

Additional Key Words and Phrases: FPGA, Neural Network

ACM Reference Format:

Kaiyuan Guo, Shulin Zeng, Jincheng Yu, Yu Wang AND Huazhong Yang. 2017. [DL] A Survey of FPGA Based Neural Network Accelerator. *ACM Trans. Reconfig. Technol. Syst.* 9, 4, Article 11 (December 2017), 2 pages. <https://doi.org/0000001.0000001>

1 INTRODUCTION

Recent research on Neural Network (NN) is showing great improvement over traditional algorithms in computer vision. Various network models, like convolutional neural network (CNN), recurrent neural network (RNN), have been proposed for image, video, and speech process. CNN [3] improves the top-5 image classification accuracy on ImageNet [4] dataset from 73.8% to 84.7% and further helps improve object detection [1] with its outstanding ability in feature extraction. RNN [2] achieves state-of-the-art word error rate on speech recognition. In general, NN features a high fitting ability to a wide range of pattern recognition problems. This makes NN a promising candidate to many artificial intelligence applications.

But the computation and storage complexity of NN models are high. The research on NN is also increasing the size of NN models. The largest neural network model for an 224×224 image classification requires upto 39 billion floating point operations (FLOP) and more than 500MB model parameters [5]. As the computation complexity is proportional to the input image size, processing images with higher resolutions may need more than 100 billion operations.

Thus traditional hardware platforms are not suitable for neural network process. A common CPU can perform 10-100G FLOP per second. which is too

Author's address: Kaiyuan Guo, Shulin Zeng, Jincheng Yu, Yu Wang AND Huazhong Yang, Tsinghua University, Tsinghua University, Beijing, Beijing, 100084, China, gky15@mails.tsinghua.edu.cn, yu-wang@mail.tsinghua.edu.cn.

ACM acknowledges that this contribution was authored or co-authored by an employee, contractor, or affiliate of the United States government. As such, the United States government retains a nonexclusive, royalty-free right to publish or reproduce this article, or to allow others to do so, for government purposes only.

© 2017 Association for Computing Machinery.

1936-7406/2017/12-ART11 \$15.00

<https://doi.org/0000001.0000001>

2. FPGA benefits from its great flexibility and is a good candidate. a wide range of FPGA servers have been

3. software design
4. hardware design
5. brief summary
6. paper organization

REFERENCES

- [1] Ross Girshick, Jeff Donahue, Trevor Darrell, and Jitendra Malik. 2014. Rich feature hierarchies for accurate object detection and semantic segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*. 580–587.
- [2] Awni Hannun, Carl Case, Jared Casper, Bryan Catanzaro, Greg Diamos, Erich Elsen, Ryan Prenger, Sanjeev Satheesh, Shubho Sengupta, Adam Coates, et al. 2014. Deep speech: Scaling up end-to-end speech recognition. *arXiv preprint arXiv:1412.5567* (2014).
- [3] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. 2012. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*. 1097–1105.
- [4] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. 2015. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)* 115, 3 (2015), 211–252. <https://doi.org/10.1007/s11263-015-0816-y>
- [5] Karen Simonyan and Andrew Zisserman. 2014. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556* (2014).