Model EDM-W and EDM-R

Wall and Rack Mounted Trace Moisture Analysers

The **Model EDM-W and EDM-R Trace Moisture Analysers** are the next generation of successful measuring instruments that work on a basis of P_2O_5 sensors and are used for the determination of moisture in most gases (excluding NH_3 ammonia) in the ppm range.

They consist of a separately installed measuring cell mainly of PVDF (for aggressive gases), that can be integrated in a Gas Handling System, and an electronic evaluation unit.



Wall Mounted

Rack Mounted





Colour Touch Screen - Rugged - Accurate - Easy Set Up - 1 to 4 Channels.

CE Measuring instrument conforms with EN 61326

FEATURES

- The EDM-W and EDM-R can process up to 4 independent channels simultaneously.
- Sharp resolution, full colour, touch screen and easy to use screen with built in keyboard feature.
- The display can be set in ppm(v) or ^{0}C dewpoint.
- 4 languages available - English, German, Russian and Chinese.
- Advanced menu navigation.
- Manufactured according to ISO 9000.
- ATEX certification can be arranged.
- Status signals for every channel are supplied as volt free relays for:
  - failure
  - function control
  - maintenance requirements
  - moisture alarm
- Self monitoring of instrument function.
- All changes and settings are saved on several levels (user and administrator) with password protection.
- The analogue output can be scaled freely.

APPLICATIONS

- Producers and users of technical and medical gases
- Microelectronics
- Chemical industries (especially for technologies with aggressive gases)
- Mechanical and apparatus engineering
- Heat treatment / hardening processes
- Research and laboratories

For more information on the Model EDM range Call +44 (0) 1274 733 100 or Email: info@amsystems.co.uk or see our website www.amsystems.co.uk

© Alpha Moisture Systems Ltd.

The Model EDM-W and EDM-R has been specifically designed for the use with aggressive gases, especially Chlorine and HCl-gas. Chemically resistant material (PTFE, PVDF) is used for all wetted parts.

TECHNICAL DATA FOR MODEL EDM

Each channel

- Lower detection limit	:	0.05 ppm(v)
- Measuring range	:	0 - 2000 ppm(v)
- Resolution	:	0.1 ppm(v)
- Auto sensor detection		
- Sensor check		
- Analogue output (free scalable)	:	4-20 mA
- Alarm output (NO/NC)	:	fully adjustable volt free change over relays
- 3 Status relays according to NAMUR	:	volt free change over relays.

Measuring cell

- Body material	:	PVDF or stainless steel
- Sensor	:	Noble Metal
- Measuring gas flow	:	20 Nl/h
- Measuring gas temperature	:	+5 - +65 °C
- Measuring gas pressure	:	max. 200 mbarg
- Accuracy	:	±5% of reading, not less than 0.4 ppm(v).
- Response time to a moisture event	:	Less 1 sec.
- Return time, T90	:	Less than 2 min.
- Reproducibility at 20 ppm(v)	:	+/- 2%.
- Gas connection (PVDF)	:	6mm dia. locking ring.
- Gas connection (Stainless Steel)	:	For 6mm, 1/8", 1/4"OD tube.
- Connection of measuring cell	:	5 pin Binder plug.
- Measuring cable	:	1.5m - 100m max.

Option:
Measuring cell mounted in an acrylic box with flow meter, 3 and 4 way valve for measuring and purging gases.

How to Order - Step 1 of 1

Select a Product below and number of sensors

Model EDM-W + [X]

Select number of Sensors/Channels: 1 or 2

Model EDM-R + [X]

Select number of Sensors/Channels: 1, 2, 3 or 4

Distributor Information

CERTIFICATE No. FM35600
BS EN ISO 9001:2008

Institute of Measurement and Control
Companion Company

Alpha Moisture Systems Limited. Registered Office: Alpha House, 96 City Road, Bradford, BD8 8ES
Registered in England and Wales No. 3902302 - VAT Registration No. GB 607 2075 63 - WEEE Producer Registration No. WEEE/EA0067TX

Tel +44 (0) 1274 733100
Fax +44 (0) 1274 733200
Email info@amsystems.co.uk
Website www.amsystems.co.uk

© Alpha Moisture Systems Ltd.