Model GCTU-PDT-PTY-SO2

4/1 SF6 Analyser - Gas Collection with Pump-Back

The **GCTU-PDT-PTY-SO2** is a 4 in 1 analyser designed to recycle and pump-back the entire SF_6 sample, giving a zero effect to the installation and protecting the environment by eliminating any discharge to atmosphere.

- **4-20mA transmitter (model PDT) with accuracy to ±2°C (3.6°F). Range -60°C to +20°C dewpoint. °F or ppmv.**
- **SF_6 Purity Analyser (%)**
- **SO_2 Analyser (ppmv)**
- **Transfer/Pump-Back Function**
- **Pre-factory set and fully calibrated**
- **Rugged transportation case**



Measuring instrument conforms to BS EN 61326-1

The **GCTU-PDT-PTY-SO2** has been specifically developed to sample and analyse dewpoint, SF_6 Purity (%) and SO_2 (ppmv). The unit collects the SF_6 sample from MV/HV Circuit Breakers, Switchgear and Transformers in the internal collection vessel of the instrument. After sampling and logging, the sample can simply be pumped back into the installation under test.

The user has only to connect, regulate flow, take sample, log, then pump back, typically in under 5 minutes (includes purging time).

FEATURES

- Full colour touch screen graphical display.
- Internal logging as standard with download function to PC via USB.
- Pre-set alarm points to IEC 60480:2004 for dew-point, % and ppmv for both MV and HV installations.
- Integrated Dewpoint Transmitter/ Hygrometer, SF_6 purity and SO_2 analyser.
- Unlimited Fill/Discharge Cycles.
- Integrated vaccuum assisted sample purge.
- Dual voltage 240v or 110 option available.
- 12 bar (175 PSIG) maximum back fill pressure.
- User friendly operation with built-in fail safe features.
- Supplied ready for use with a high quality 2 meter PTFE lined stainless steel braided sample hose.
- Extra strong IP66 (NEMA 4) rugged transportation case with retractable handle and tough in-line wheels.

Innovation • Precision • Quality • Performance

© Alpha Moisture Systems Ltd.

SPECIFICATIONS

SAMPLING SYSTEM:
Process pressure indicator.
Sample flow indicator.
Large internal collection vessel up to 15 litres.
Automatic shut down when collection vessel is full.
TRANSFER SYSTEM (Pump-Back):
Simple operation without disconnecting sample line.
High integrity discharge pump with output capability up to 12 barg (175PSI).
Automatic shut down when collection vessel evacuated.
4 in 1 INSTRUMENT:-
DEWPOINT
Sensor Type: 4-20mA Dewpoint Transmitter.
Measuring Range: -60°C to +20°CTd (-76°F to +68°FTd) or 5.3 to 23,000 ppm(V).
Accuracy to: ± 2°C (3.6°F).
Display: Full colour touch screen LCD.
Power Supply: Mains (AC) 240V or 110v 50/60Hz
SF6 PURITY (%)
Sensor Type: Katharometer
Range: 0 - 100%
Accuracy: ± 0.5%
Display: Full colour touch screen LCD.

SO2 (ppmv)
Sensor Type: Electrochemical Gas Sensor 4-20mA
Range: 0-100 ppmv (other ranges available)
INTEGRAL PUMP
Oil-less operation
No oil residue emissions
Complies within tolerances set out in the IEC 60480 Standard.
DATA LOGGING:
Built-in logging as standard. Comes with PC logging software and USB connecting cable.
TRANSPORTATION CASE:
Waterproof IP66 (NEMA4) rating.
Hard wearing, non-slip grip carrying handles.
Retractable pull along handle.
Pressure vents for air transportation.
DIMENSIONS:
24.6” x 19.7” x 11.6” (625 x 500 x 297mm).
WEIGHT:
49.5lb (22.5kg).



How to Order

Model GCTU-PDT-PTY-SO2 - [x]

Voltage
1 = 110v
2 = 240v

ORDER EXAMPLE:
To order this instrument for 240v applications in the EU:
The Part Number will look like this: **GCTU-PDT-PTY-SO2-2**

Authorised Distributor Information

Notes

Product specification may be subject to change, without prior notice, as part of our ongoing product development programme.

2385 Model GCTUPDTPTYSO2 pdfeb17-Iss1-T

CERTIFICATE No. FM35600
BS EN ISO 9001:2008

Institute of Measurement and Control
Companion Company

Alpha Moisture Systems Ltd. Registered Office: Alpha House, 96 City Road, Bradford, BD8 8ES
Registered in England and Wales No. 3902302 VAT Registration No. GB 607 2075 63 WEEE Producer Registration No. WEEE/EA0067TX

Tel +44 (0) 1274 733100
Fax +44 (0) 1274 733200
Email info@amsystems.co.uk
Website www.amsystems.co.uk

© Alpha Moisture Systems Ltd.