

---

# Removing Noise from Speech with Deep Learning

---

**Glávits Balázs**

Department of Measurement and Information Systems  
Budapest University of Technology and Economics  
email@email.email

**Kiss Andor**

Department of Automation and Applied Informatics  
Budapest University of Technology and Economics  
email@email.email

**Konrád Márk**

Department of Telecommunications and Media Informatics  
Budapest University of Technology and Economics  
konrad0816@gmail.com

## Abstract

TODO

## 1 Data acquisition and exploration

For our training and testing data, we used a dataset called "Noisy speech database for training speech enhancement algorithms and TTS models" by the University of Edinburgh. It consists of  $\sim 23000$  clean-noisy pairs from 56 different speakers. The samples are stored in separate .wav files of varying length.




Figure 1: Duration distribution histogram of a subset of speeches

## 2 Data preprocessing

### 2.1 Data selection by duration

We intend to zero pad the data in order to make the samples the same length. To reduce the number of zeroes we only use the  $n$  samples that are closest to each other in duration. This way we reduce the number of training samples, but hopefully, the efficiency of our network will be much better.

### 2.2 Zero padding

Our network architecture only supports samples of the same length. To fulfill this constraint, we add zeroes for the end of each recording. The number of zeroes was calculated from the difference between the longest and the current sample.




Figure 2: An example clean-noisy pair

Figure 3: An example clean-noisy pair after zero padding

### 2.3 $\mu$ -law transformation

To make future computations faster we, reduce the samples to 8 bit with  $\mu$ -law transformation.




Figure 4: An example clean-noisy pair after padding and  $\mu$ -law transformation