# 1 Issue 1 ([ADD-/REMOVE-]PACKAGE-LOCAL-NICKNAME return values)

# 1.1 Description

Return values of add-package-local-nickname and remove-package-local-nickname are inconsistent. The first one always returns *designated package*, while the second one returns *true* (generalized boolean) if a nickname was removed.

Moreover, there is no consensus among current implementations as to what the second function (remove-package-local-nickname) should return.

### 1.2 Examples

```
(defpackage #:foo (:use))
(defpackage #:bar (:use))

(add-package-local-nickname '#:nick '#:bar '#:foo)
; => #<PACKAGE "FOO"> (sbcl, ccl, ecl, acl, abcl, clasp, lispworks)
(add-package-local-nickname '#:nick '#:bar '#:foo)
; => #<PACKAGE "FOO"> (sbcl, ccl, ecl, acl, abcl, clasp, lispworks)
(remove-package-local-nickname '#:nick '#:foo)
; => T (sbcl, ccl, ecl, acl, clasp)
; => #<PACKAGE "BAR"> (abcl)
; => NIL (lispworks)
(remove-package-local-nickname '#:nick '#:foo)
; => NIL (sbcl, ccl, ecl, acl, abcl, clasp, lispworks)
```

# 1.3 Current behavior

sbcl, ccl, ecl, acl, abcl, clasp, lispworks: add-package-local-nickname always returns designated package.

sbcl, ccl, ecl, acl, clasp: remove-package-local-nickname returns T if a nickname was removed, and NIL otherwise.

abcl: remove-package-local-nickname if a nickname was removed, returns *true* (more specifically - the package that was nicknamed by that nickname), and NIL otherwise.

lispworks: remove-package-local-nickname always returns NIL.

#### 1.4 Proposal DESIGNATED-PACKAGE-IF-SUCCESSFUL

- add-package-local-nickname should return *designated package* if a new nickname was added and NIL otherwise, if the nickname already existed.
- remove-package-local-nickname should return designated package if a nickname was removed and NIL otherwise.

#### 1.5 Proposal ALWAYS-T

Similar to use-package and unuse-package:

• add-package-local-nickname should always return T.

 $\bullet$  remove-package-local-nickname should always return T.

# $1.6 \quad Proposal \; ELIMINATE\text{-}GENERALIZED_{BOOLEAN}$

- ullet add-package-local-nickname should alwyss return  $designated\ package.$
- ullet remove-package-local-nickname should return T if a nickname was removed and NIL otherwise.