

```
1 program bisection_method
2   implicit none
3   real :: a, b, c, f, tol, f_a, f_b, f_c
4   integer :: getNIt, i, n
5   logical :: verifyInterval, isValidInterval
6
7   print *, "Type a precision"
8   read (*,*) tol
9   if ( tol<=0 ) then
10    print *, "You should provide a positive tolerance value"
11    stop
12  end if
13
14  call getInterval(a, b)
15  isValidInterval = verifyInterval(f(a), f(b))
16  do while(.not.isValidInterval)
17    print *, "You should provide an interval where both f(a) and f(b) have
different sign"
18    call getInterval(a,b)
19    isValidInterval = verifyInterval(f(a), f(b))
20  end do
21
22  n = getNIt()
23  do i = 1, n
24    c = (a+b)/2
25    f_c = f(c)
26    print *, "c: ", c
27    print *, "f(c) = ", f_c
28    print *, "Interaction: ", i
29    if ( (abs(f_c).eq.0).or.(abs(f_c)<=tol) ) then
30      print *, "-----\\-----"
31      print *, "The found root is ", c
32      print *, "f(x = root) = ", f_c
33      print *, "Number of interaction used:", i
34      stop
35    end if
36    f_a = f(a)
37    f_b = f(b)
38    if ( ((f_a>0).and.(f_c>0)).or.((f_a<0).and.(f_c<0)) ) then
39      a = c
40    else
41      b = c
42    end if
43  end do
44
45  if ( f_c>tol ) then
46    print *, "The simulation require more number of interactions."
47    print *, " Please, restart the program and type a greater number of
interactions"
48  end if
49
50 end program bisection_method
51
52 subroutine getInterval(a, b)
53 implicit none
54 real :: a, b
55 print *, "Type a value for 'a'"
56 read (*,*) a
57
58 print *, "type a value for 'b'"
```

```
59 read (*,*) b
60
61 end subroutine getInterval
62
63 function getNIIt() result(n)
64   implicit none
65   integer :: n
66   print *, "Type a number of interactions"
67   read (*,*) n
68   if ( n ≤ 0 ) then
69     print *, "You should provide a number of interaction more than zero"
70     stop
71   end if
72 end function getNIIt
73
74 function f(x) result(y)
75   implicit none
76   real, intent(in) :: x
77   real :: y
78   y = sin(x*cos(x)-sin(x))
79 end function f
80
81 function verifyInterval(f_a, f_b) result(isValid)
82   implicit none
83   real, intent(in) :: f_a, f_b
84   logical :: isValid
85   isValid = .true.
86   print *, f_a, f_b
87   if ( f_a.eq.0 ) then
88     print *, "The interval 'a' is a root of the equation"
89     stop
90   end if
91   if ( f_b.eq.0 ) then
92     print *, "The interval 'b' is a root of the equation"
93     stop
94   end if
95   if(((f_a>0).and.(f_b>0)).or.((f_a<0).and.(f_b<0))) then
96     isValid = .false.
97   end if
98 end function verifyInterval
```