

2019

# Theory of Computation

**Kun-Ta Chuang**

**Department of Computer Science and Information Engineering  
National Cheng Kung University**



# Outline



Deterministic Finite Accepters (DFA)

---



Nondeterministic Finite Accepters (NFA)

---



Equivalence of DFA and NFA

---




Reduction of the Number of States in FA\*

---

# Automata

**Automaton:** 模擬一台電腦的特定行為的model為automata

An abstract model of a digital computer




- Deterministic V.S. Nondeterministic
- An automaton whose output is YES or NO  
Accepter
- An automaton whose output are strings of symbols  
Transducer



# Transition Graph

## Finite Acceptor


具有有限的狀態數( $q_0, q_1, q_2, q_3, \dots$ )







# Initial Configuration





# Reading the Input
















Input finished







Output: "accept"

# Rejection












Input finished





# Another Rejection



看到lambda不屬於a,b所以看到它不用動作，停在q0就沒了，所以結果為reject














Output:  
"reject"

# Another Example














Input finished







# Rejection













Input finished



Output: "reject"

Trap state

# Definition 2.1

Deterministic Finite Acceptor (DFA) is define by the 5-tuple

$$M = (Q, \Sigma, \delta, q_0, F)$$

$Q$  : a finite set of **internal states**

$\Sigma$  : a finite set of symbols called **input alphabet**


$\delta$  :  $Q \times \Sigma \rightarrow Q$  called **transition function** (Total function)

$q_0$  :  $q_0 \in Q$  is the **initial state**

$F$  :  $F \subseteq Q$  is a set of **final states**


# Input Alphabet $\Sigma$

$$\Sigma = \{a, b\}$$




# Set of States $Q$

$$Q = \{q_0, q_1, q_2, q_3, q_4, q_5\}$$




# Initial State $q_0$



# Set of Final States $F$


$$F = \{q_4\}$$






# Transition Function $\delta$


$$\delta : Q \times \Sigma \rightarrow Q$$




$$\delta(q_0, a) = q_1$$



$$\delta(q_0, b) = q_5$$




$$\delta(q_2, b) = q_3$$



# Transition Function $\delta$


$\delta$	$a$	$b$
$q_0$	$q_1$	$q_5$
$q_1$	$q_5$	$q_2$
$q_2$	$q_5$	$q_3$
$q_3$	$q_4$	$q_5$
$q_4$	$q_5$	$q_5$
$q_5$	$q_5$	$q_5$

在transition table, transition function中每一個格子都必須有state  
不能空著或是有2個state以上




# Extended Transition Function $\delta^*$


$$\delta^*: Q \times \Sigma^* \rightarrow Q$$



$$\delta^*(q_0, ab) = q_2$$




$$\delta^*(q_0, abba) = q_4$$





$$\delta^*(q_0, abbbaa) = q_5$$




**Observation:** If there is a walk from  $q$  to  $q'$  with label  $w$

■ Theorem 2.1

$$\text{iff } \delta^*(q, w) = q'$$




$$w = \sigma_1 \sigma_2 \cdots \sigma_k$$



**Example:** There is a walk from  $q_0$  to  $q_5$   
with label  $abbbaa$


$$\delta^*(q_0, abbbaa) = q_5$$



# Recursive Definition

$$\delta^*(q, \lambda) = q$$

$$\delta^*(q, w\sigma) = \delta(\delta^*(q, w), \sigma)$$



$$\begin{array}{l}
 \left. \begin{array}{l} \delta^*(q, w\sigma) = q' \\ \delta(q_1, \sigma) = q' \end{array} \right\} \Rightarrow \left. \begin{array}{l} \delta^*(q, w\sigma) = \delta(q_1, \sigma) \\ \delta^*(q, w) = q_1 \end{array} \right\} \Rightarrow \delta^*(q, w\sigma) = \delta(\delta^*(q, w), \sigma)
 \end{array}$$

$$\delta^*(q_0, ab) =$$


$$\delta(\delta^*(q_0, a), b) =$$

$$\delta(\delta(\delta^*(q_0, \lambda), a), b) =$$

$$\delta(\delta(q_0, a), b) =$$

$$\delta(q_1, b) =$$

$$q_2$$



# Languages Accepted by DFAs

Take DFA  $M$

**Definition:** 一個DFA都會對應到一個Language


– The language  $L(M)$  contains  
all input strings accepted by  $M$

–  $L(M) = \{ \text{strings that drive } M \text{ to a final state} \}$

# Example

$$L(M) = \{abba\}$$


$M$



# Another Example

$$L(M) = \{\lambda, ab, abba\}$$

$M$






# Formally

For a DFA  $M = (Q, \Sigma, \delta, q_0, F)$

Language accepted by  $M$  :


$$L(M) = \{w \in \Sigma^* : \delta^*(q_0, w) \in F\}$$



# Observation


- Language rejected by  $M$  :

$$\overline{L(M)} = \{w \in \Sigma^* : \delta^*(q_0, w) \notin F\}$$




# Example 2.2 $M = (Q, \Sigma, \delta, q_0, F)$

$$L(M) = \{a^n b : n \geq 0\}$$




# Example 2.3

$L(M) = \{ \text{all strings with prefix } ab \}$



# Example 2.4

$L(M) = \{ \text{all strings without substring } 001 \}$



可以先把最基本的一條會出現001的路徑畫出來

# Regular Languages

A language  $L$  is **regular** iff there exists some DFA  $M$  such that  $L = L(M)$

All regular languages form a language family

## Examples of regular languages:

$$\{abba\} \quad \{\lambda, ab, abba\} \quad \{a^n b : n \geq 0\}$$

{ all strings with prefix *ab* }


{ all strings without substring **001** }

There exists DFA that accept these Languages

# Example 2.5

The language  $L = \{awa : w \in \{a,b\}^*\}$  is regular:


$$L = L(M)$$






# Example 2.6

The language  $L = \{awa : w \in \{a,b\}^*\}$  is regular, how about  $L^2$ ?



$$L^2 = \{aw_1aaw_2a : w_1, w_2 \in \{a,b\}^*\}$$

$$L(M) = \{a^n b : n \geq 0\}$$




$$L = \{a^n b^n : n \geq 0\} ?$$

無法將此Language畫出DFA，因為dfa沒有記憶性


There exist languages which are not Regular:  
 There is no DFA that accepts such a language  
 (we will prove this later in the class)

# DFA Recap



- A machine with finite number of **states**, some states are **accepting** states, others are **rejecting** states
- At any time, it is in one of the states
- It reads an input string, one character at a time

# DFA Recap



- After reading each character, it moves to another state depending on what is read and what is the current state
- If reading all characters, the DFA is in an accepting state, the input string is accepted.
- Otherwise, the input string is rejected.

# Definition 2.1

Deterministic Finite Acceptor (DFA) is define by the 5-tuple

$$M = (Q, \Sigma, \delta, q_0, F)$$

$Q$  : a finite set of **internal states**

$\Sigma$  : a finite set of symbols called **input alphabet**

$\delta$  :  $Q \times \Sigma \rightarrow Q$  called **transition function**

$q_0$  :  $q_0 \in Q$  is the **initial state**

$F$  :  $F \subseteq Q$  is a set of **final states**

# Regular Languages

A language  $L$  is **regular** iff there exists some DFA  $M$  such that  $L = L(M)$

## Definition:


- The language  $L(M)$  contains all input strings accepted by a DFA  $M$
- $L(M) = \{ \text{strings that drive } M \text{ to a final state} \}$

p.63~68注意, 一定會考

# More Examples


- All strings that contain exactly 4 "0"s.
- All strings containing exactly 4 "0" s and at least 2 "1" s.
- All strings of length at most five.
- All strings ending in "1101".
- All strings whose binary interpretation is divisible by 5.
- All strings that contain the substring 0101.
- All strings that don't contain the substring 110.

一開始在畫DFA時都先將對的路徑畫出來



# More Examples


- All strings that contain exactly 4 "0"s.
- All strings containing exactly 4 "0" s and at least 2 "1" s.
- All strings of length at most five.
- All strings ending in "1101".
- All strings whose binary interpretation is divisible by 5.
- All strings that contain the substring 0101.
- All strings that don't contain the substring 110.





# More Examples


- All strings that contain exactly 4 "0"s.
- All strings containing exactly 4 "0" s and at least 2 "1" s.
- All strings of length at most five.
- All strings ending in "1101".
- All strings whose binary interpretation is divisible by 5.
- All strings that contain the substring 0101.
- All strings that don't contain the substring 110.



# More Examples

- All strings that contain exactly 4 "0"s.
- All strings containing exactly 4 "0" s and at least 2 "1" s.
- All strings of length at most five.
- All strings ending in "1101". 必考
- All strings whose binary interpretation is divisible by 5.
- All strings that contain the substring 0101.
- All strings that don't contain the substring 110.

連續2個1以上一樣等同於看到2個1的狀態




# More Examples

- All strings that contain exactly 4 "0"s.
- All strings containing exactly 4 "0" s and at least 2 "1" s.
- All strings of length at most five.
- All strings ending in "1101".


可能會考 – All strings whose binary interpretation is divisible by 5.

- All strings that contain the substring 0101.
- All strings that don't contain the substring 110.



# More Examples


- All strings that contain exactly 4 "0"s.
- All strings containing exactly 4 "0" s and at least 2 "1" s.
- All strings of length at most five.
- All strings ending in "1101".
- All strings whose binary interpretation is divisible by 5.
- All strings that contain the substring 0101.
- All strings that don't contain the substring 110.



Hint: 直接在狀態上面標記已經可以看到的pattern, 可以幫助把圖畫出來

# More Examples

- All strings that contain exactly 4 "0"s.
- All strings containing exactly 4 "0" s and at least 2 "1" s.
- All strings of length at most five.
- All strings ending in "1101".
- All strings whose binary interpretation is divisible by 5.
- All strings that contain the substring 0101.
- All strings that don't contain the substring 110.




# Exercise 2.1.7

Find DFAs for the following languages on  $\Sigma=\{a,b\}$

(a)  $L = \{w: |w| \bmod 3 = 0\}$

(b)  $L = \{w: n_a(w) \bmod 3 > n_b(w) \bmod 3\}$




# Exercise 2.1.7

Find DFAs for the following languages on  $\Sigma=\{a,b\}$

(a)  $L = \{w: |w| \bmod 3 = 0\}$

(b)  $L = \{w: n_a(w) \bmod 3 > n_b(w) \bmod 3\}$




# Exercise 2.1.9

(a) Every 00 is followed immediately by a 1.

Ex: 101, 0010, 0010011001  $\in L$

0001 and 00100  $\notin L$

$\Sigma = \{0,1\}$






Questions?

# Short Quiz

- All strings that start with 0 and have odd length or start with 1 and have even length.
- All strings where every odd position is a 1.

# Short Quiz

- All strings that start with 0 and have odd length or start with 1 and have even length.



- All strings where every odd position is a 1.

