



TOURNIQUET
Non-Printed Material Specs

Sewing Material	Specs
3/4" nylon webbing https://jtsoutdoorfabrics.com/black_nylon_webbing	Break Strength is estimated at: 3/4" - 745 lbs 100% Nylon Fibers, 840 Denier. Standard Heat and UV Radiation stabilized. Catch cord applied. Yarn Count: Warp: 840 D Weft: 210 D Passes Motor Vehicle Safety Standard 302 Fire Code Thickness: 1.1 mm
1.5" nylon hook and loop tape https://jtsoutdoorfabrics.com/Economical-Nylon-Loop-Tape--Black--82-Roll_p_17017.html	Content: 100% Nylon Peel Cleavage: 2.5 N/cm Shear: 10 N/sq cm Shrinkage: Less than 2% Strength: Above 250 N/cm Temperature: Melting temperature: Above 200 degrees Celsius Thickness: 2mm
1.5" grosgrain ribbon https://ribbonfactory.com/store/display_item/646.html	Fiber: 100% Polyester (PET) • Properties: Synthetic fiber provides high dimensional stability, excellent resistance to shrinking/stretching, and good elasticity recovery. It is naturally resistant to mildew, moths, and most household chemicals. Weave Type: Grosgrain (a heavy-weft variation of the plain/standard weave) • Construction: Achieved by alternating a thick, dominant weft (crosswise) yarn with finer warp (lengthwise) yarns. This creates the characteristic transverse ribs running perpendicular to the ribbon's length. • Density: Tightly woven with a high thread count, resulting in a dense, opaque structure with a stiff, crisp hand. Tensile Strength: Medium-to-high for a decorative ribbon. The polyester fibers and tight ribbed weave provide good load distribution, though exact break strength varies by width (typically estimated at 15–40 lbs of force for a 1½" width depending on yarn denier). • Elongation at Break: Low (~3–5%). The minimal stretch ensures the ribbon holds its shape under tension but does not absorb shock

	like elastic or nylon webbing. • Friction & Hardware Grip: The ribbed surface offers moderate friction, but it is not engineered to grip buckles or friction-fit hardware under high tension. Unlike industrial webbing, the flat plain-weave structure cannot lock onto fasteners. • Fray Resistance: High. The heavy weft ribs and synthetic fiber prevent edges from unraveling, even when cut without heat sealing.
9.5mm jean ring rivets (brass) https://www.micronamerica.com/product/9-5mm-ring-rivets-100-sets/	 T = 9.5 mm H = 2.7 mm S = 4.6 mm  T = 9.5 mm H = 8.3 mm S = 2.5 mm