

|  |         |                               |          |                    |
|--|---------|-------------------------------|----------|--------------------|
| Prepared (also subject responsible if other)<br>ETH/XZX Endre Kulcsár +36 1 437 7469 |         | No.<br>155 17-CNL 113 588 Uen |          |                    |
| Approved<br>ETH/XZXC (Tibor Csöndes)   | Checked | Date<br>2012-06-14            | Rev<br>A | Reference<br>GASK2 |

## The Real Time Streaming Protocol (RTSP) Protocol Modules for TTCN-3 Toolset with TITAN, Function Specification

### Contents

|       |   |   |
|-------|---|---|
| 1     | Introduction .....                                  | 2 |
| 1.1   | Revision history .....                              | 2 |
| 1.2   | How to Read this Document .....                     | 2 |
| 1.3   | Scope.....  | 2 |
| 1.4   | References .....                                    | 2 |
| 1.5   | Abbreviations .....                                 | 2 |
| 1.6   | Terminology .....                                   | 3 |
| 2     | General .....                                       | 3 |
| 3     | Functional Specification .....                      | 3 |
| 3.1   | Protocol Version Implemented .....                  | 3 |
| 3.1.1 | Implemented Messages .....                          | 3 |
| 3.1.2 | Implemented Methods .....                           | 3 |
| 3.1.3 | Supported Header Fields .....                       | 4 |
| 3.1.4 | Implemented But Not Specified Header Fields .....   | 5 |
| 3.1.5 | Header Field Extensibility.....                     | 7 |
| 3.1.6 | Header Implementation .....                         | 7 |
| 3.2   | Protocol Modifications/Deviations .....             | 8 |
| 3.2.1 | Relaxed Conditions .....                            | 8 |
| 3.2.2 | Restrictions.....                                   | 9 |
| 3.3   | Encoding/Decoding and Other Related Functions ..... | 9 |
| 3.4   | Encoding/Decoding Logic.....                        | 9 |

|  |         |                               |          |                    |
|--|---------|-------------------------------|----------|--------------------|
| Prepared (also subject responsible if other)<br>ETH/XZX Endre Kulcsár +36 1 437 7469 |         | No.<br>155 17-CNL 113 588 Uen |          |                    |
| Approved<br>ETH/XZXC (Tibor Csöndes)   | Checked | Date<br>2012-06-14            | Rev<br>A | Reference<br>GASK2 |

# 1 Introduction

## 1.1 Revision history

| Date       | Rev | Characteristics           | Prepared |
|------------|-----|---------------------------|----------|
| 2008-04-28 | PA1 | First draft version       | ETHBAAT  |
| 2010-03-19 | PA2 | Updated for TITAN R8B     | ETMEMOD  |
| 2010-03-25 | PA3 | Corrected after review    | ETMEMOD  |
| 2012-05-07 | PA4 | Implemented CR_TR00019322 | ETHEKR   |

## 1.2 How to Read this Document

This is the Function Specification for the Real Time Streaming Protocol (RTSP) protocol modules. RTSP protocol modules are developed for the TTCN-3 Toolset with TITAN. This document should be read together with Product Revision Information [4].

## 1.3 Scope

The purpose of this document is to specify the content of the Real Time Streaming Protocol (RTSP) protocol modules [1] and [4]. Basic knowledge of TTCN-3 [2] and TITAN TTCN-3 Test Executor [3] is valuable when reading this document.

## 1.4 References

- [1] IETF RFC 2326  
Real Time Streaming Protocol (RTSP)
- [2] ETSI ES 201 873-1 v.3.2.1 (02/2007)  
The Testing and Test Control Notation version 3. Part 1: Core Language
- [3] 2/198 17-CRL 113 200 Uen  
Programmer's Technical Reference for the TITAN TTCN-3 Test Executor
- [4] 109 21-CNL 113 588-1  
The Real Time Streaming Protocol (RTSP) Protocol Modules for TTCN-3 Toolset with TITAN, Product Revision Information
- [5] CBC/XL-12:0167 Uen  
Interface Description, RTSPx

## 1.5 Abbreviations

|      |   |
|------|---|
| ETSI | European Telecommunications Standards Institute |
| IETF | Internet Engineering Task Force                 |
| RFC  | Request for Comments                            |

|  |         |                               |          |                    |
|--|---------|-------------------------------|----------|--------------------|
| Prepared (also subject responsible if other)<br>ETH/XZX Endre Kulcsár +36 1 437 7469 |         | No.<br>155 17-CNL 113 588 Uen |          |                    |
| Approved<br>ETH/XZXC (Tibor Csöndes)   | Checked | Date<br>2012-06-14            | Rev<br>A | Reference<br>GASK2 |

RTSP      Real Time Streaming Protocol

TTCN-3      Testing and Test Control Notation version 3

## 1.6 Terminology

TITAN TTCN-3 Test Executor (see [3]).

## 2 General

Protocol modules implement the message structures of the related protocol in a formalized way, using the standard specification language TTCN-3. This allows defining of test data (templates) in the TTCN-3 language [2] and correctly encoding/decoding messages when executing test suites using the TITAN TTCN-3 test environment [3].

Please note: This version of the protocol module is not compatible with TITAN releases earlier than R8B.

## 3 Functional Specification

### 3.1 Protocol Version Implemented

This set of protocol modules implements protocol messages and constants of The Real Time Streaming Protocol (RTSP). The modules are based on RFC 2326 (see [1]) and Interface Description [5].

#### 3.1.1 Implemented Messages

According to [1] both RTSP message types “request” and “response” are implemented. Additionally the message type “erroneous message” is introduced for not decodable messages.

#### 3.1.2 Implemented Methods

All methods specified in Chapter 6.1 of [1] are implemented as follows:

"DESCRIBE"

"ANNOUNCE"

"GET\_PARAMETER"

"OPTIONS"

"PAUSE"

"PLAY"

"RECORD"

"REDIRECT"

|  |         |                               |          |                    |
|--|---------|-------------------------------|----------|--------------------|
| Prepared (also subject responsible if other)<br>ETH/XZX Endre Kulcsár +36 1 437 7469 |         | No.<br>155 17-CNL 113 588 Uen |          |                    |
| Approved<br>ETH/XZXC (Tibor Csöndes)   | Checked | Date<br>2012-06-14            | Rev<br>A | Reference<br>GASK2 |

"SETUP"

"SET\_PARAMETER"

"TEARDOWN"

### 3.1.3 Supported Header Fields

All header field specified in Chapter 12 of [1] is supported as listed below. The fields in parentheses are not listed in Chapter 12 of [1] but listed in subchapters of chapter 12 of [1].

Accept

Accept-Encoding

Accept-Language

Allow

Authorization

Bandwidth

Blocksize

Cache-Control

Conference

Connection

Content-Base

Content-Encoding

Content-Language

Content-Length

Content-Location

Content-Type

Content-Type

CSeq

Date

Expires

From

|  |         |                               |          |                    |
|--|---------|-------------------------------|----------|--------------------|
| Prepared (also subject responsible if other)<br>ETH/XZX Endre Kulcsár +36 1 437 7469 |         | No.<br>155 17-CNL 113 588 Uen |          |                    |
| Approved<br>ETH/XZXC (Tibor Csöndes)   | Checked | Date<br>2012-06-14            | Rev<br>A | Reference<br>GASK2 |

(Host)

(If-Match)

If-Modified-Since

Last-Modified

Proxy-Authenticate

Proxy-Require

Public

Range

Referer

Require

Retry-After

RTP-Info

Scale

Session

Server

Speed

(Time-Stamp)

Transport

Unsupported

User-Agent

(Vary)

Via

WWW-Authenticate

### 3.1.4 Implemented But Not Specified Header Fields

The list of implemented header fields which are not specified in [1] is as follows. They are used in Ericsson proprietary solutions.

RDTFeatureLevel

|  |         |                               |          |                    |
|--|---------|-------------------------------|----------|--------------------|
| Prepared (also subject responsible if other)<br>ETH/XZX Endre Kulcsár +36 1 437 7469 |         | No.<br>155 17-CNL 113 588 Uen |          |                    |
| Approved<br>ETH/XZXC (Tibor Csöndes)   | Checked | Date<br>2012-06-14            | Rev<br>A | Reference<br>GASK2 |

RealChallenge1

Reconnect

Rtcp-Interval

StatsMask

Vsrc

x-Real-usestrackid

x-Vig-Bno

x-Vig-MSISDN

x-retransmit

x-dynamic-rate

x-transport-options

x-prebuffer

In addition the following headers specified in [5] are also implemented:

X-Action

X-EncodingFiles

X-UdpPipe

X-MbmsSync

X-Bandwidth

X-Content

X-Fec

X-UserPlaneDest

X-FluteBitrate

X-Tsi

X-ContentFdtSendInterval

X-Reporting

|  |         |                                |          |                    |
|--|---------|--------------------------------|----------|--------------------|
| Prepared (also subject responsible if other)<br>ETH/XZX Endre Kulcsár +36 1 437 7469 |         | No.<br>155 17-CNLC 113 588 Uen |          |                    |
| Approved<br>ETH/XZXC (Tibor Csöndes)   | Checked | Date<br>2012-06-14             | Rev<br>A | Reference<br>GASK2 |

### 3.1.5 Header Field Extensibility

Each header field listed in 3.1.3 and in 3.1.4 are available as optional fields having value of characterstring. To provide the extensibility for future development, extension header list is implemented. It is a list of name-value pairs where both names and values are arbitrary charstrings (see 3.1.6).

### 3.1.6 Header Implementation

According to 3.1.3, 3.1.4 and 3.1.5 common header implemented for RTSP request and response to support positive and negative test as follows:

```
type set HeaderStruct {
    charstring    accept          optional, //12.1
    charstring    acceptEncoding  optional, //12.2
    charstring    acceptLanguage  optional, //12.3
    charstring    allow           optional, //12.4
    charstring    authorization    optional, //12.5
    charstring    bandwidth        optional, //12.6
    charstring    blocksize        optional, //12.7
    charstring    cacheControl     optional, //12.8
    charstring    conference       optional, //12.9
    charstring    connection       optional, //12.10
    charstring    contentBase      optional, //12.11
    charstring    contentEncoding  optional, //12.12
    charstring    contentLanguage  optional, //12.13
    charstring    contentLength    optional, //12.14
    charstring    contentLocation  optional, //12.15
    charstring    contentType     optional, //12.16
    charstring    cSeq             optional, //12.17
    charstring    date             optional, //12.18
    charstring    expires          optional, //12.19
    charstring    fromField        optional, //12.20
    charstring    host             optional, //12.21
    charstring    ifMatch          optional, //12.22
    charstring    ifModifiedSince  optional, //12.23
    charstring    lastModified     optional, //12.24
    charstring    location         optional, //12.25
    charstring    proxyAuth        optional, //12.26
    charstring    proxyRequire     optional, //12.27
    charstring    publicField      optional, //12.28
    charstring    range            optional, //12.29
    charstring    rdtFeatureLevel  optional, //additional
    charstring    realChallenge1   optional, //additional
    charstring    reconnect        optional, //additional
    charstring    referer          optional, //12.30
    charstring    retryAfter       optional, //12.31
    charstring    require          optional, //12.32
    charstring    rtcpInterval     optional, //additional
    charstring    rtpInfo          optional, //12.33
    charstring    scale            optional, //12.34
```

|  |         |                                |          |                    |
|--|---------|--------------------------------|----------|--------------------|
| Prepared (also subject responsible if other)<br>ETH/XZX Endre Kulcsár +36 1 437 7469 |         | No.<br>155 17-CNLC 113 588 Uen |          |                    |
| Approved<br>ETH/XZXC (Tibor Csöndes)   | Checked | Date<br>2012-06-14             | Rev<br>A | Reference<br>GASK2 |

|            |                         |                        |
|------------|-------------------------|------------------------|
| charstring | speed                   | optional, //12.35      |
| charstring | server                  | optional, //12.36      |
| charstring | session                 | optional, //12.37      |
| charstring | statsMask               | optional, //additional |
| charstring | timeStamp               | optional, //12.38      |
| charstring | transport               | optional, //12.39      |
| charstring | unsupported             | optional, //12.40      |
| charstring | userAgent               | optional, //12.41      |
| charstring | vary                    | optional, //12.42      |
| charstring | via                     | optional, //12.43      |
| charstring | vsrsc                   | optional, //additional |
| charstring | wwwAuth                 | optional, //12.44      |
| charstring | xRealUsestrackid        | optional, //additional |
| charstring | xVigBno                 | optional, //additional |
| charstring | xVigMsisdn              | optional, //additional |
| charstring | xRetransmit             | optional, //additional |
| charstring | xDynamicRate            | optional, //additional |
| charstring | xTransportOptions       | optional, //additional |
| charstring | xPrebuffer              | optional, //additional |
| charstring | xAction                 | optional, // RTSPx     |
| charstring | xEncodingFiles          | optional, // RTSPx     |
| charstring | xUdpPipe                | optional, // RTSPx     |
| charstring | xMbmsSync               | optional, // RTSPx     |
| charstring | xBandwidth              | optional, // RTSPx     |
| charstring | xContent                | optional, // RTSPx     |
| charstring | xFec                    | optional, // RTSPx     |
| charstring | xUserPlaneDest          | optional, // RTSPx     |
| charstring | xFluteBitrate           | optional, // RTSPx     |
| charstring | xTsi                    | optional, // RTSPx     |
| charstring | xContentFdtSendInterval | optional, //RTSPx      |
| charstring | xReporting              | optional, // RTSPx     |

```
//extensionHeaders:  
    HeaderLines extensionHeaders optional  
}  
Where
```

```
type record HeaderLine {  
    charstring header_name,  
    charstring header_value  
};
```

## 3.2 Protocol Modifications/Deviations

### 3.2.1 Relaxed Conditions

- 1 There is no constraint between received and sent messages. The constraints should be implemented in the user's test program.
- 2 URI in the request line is a simple charstring. Its correctness is not checked.
- 3 Reason Code can be any integer in the Status Line



|  |         |                                |          |                    |
|--|---------|--------------------------------|----------|--------------------|
| Prepared (also subject responsible if other)<br>ETH/XZX Endre Kulcsár +36 1 437 7469 |         | No.<br>155 17-CNLC 113 588 Uen |          |                    |
| Approved<br>ETH/XZXC (Tibor Csöndes)   | Checked | Date<br>2012-06-14             | Rev<br>A | Reference<br>GASK2 |

- 4 Reason Phrase can be any charstring. There is no constraint between them for test purposes.

### 3.2.2 Restrictions

Octetestrings supported only.

Utf8text not supported.

The encoded message is octetstring. Within it the request line, the status line and the header shall be convertible for charstring, the body can be any octetstring.

## 3.3 Encoding/Decoding and Other Related Functions

This product also contains encoding/decoding functions that assure correct encoding of messages when sent from TITAN and correct decoding of messages when received by TITAN. Implemented encoding/decoding functions and the extra length calculator function are:

| Name                    | Type of formal parameters  | Type of return value | Description  |
|-------------------------|--|----------------------|--|
| <b>enc_PDU_RTSP</b>     | <b>in PDU_RTSP msg,</b><br><b>in Boolean automaticContentLengthCalc :=true</b>                                   | <b>Octetstring</b>   | <b>Encodes the RTSP PDU into octetstring</b>   |
| <b>dec_PDU_RTSP</b>     | <b>in octetstring stream,</b><br><b>inout PDU_RTSP msg,</b><br><b>in boolean debugging := tsp_RTSP_debugging</b> | <b>integer</b>       | <b>Decodes the message in octetstring into PDU_RTSP</b>  |
| <b>f_RTSP_getMsgLen</b> | <b>In octetstring stream</b>   | <b>integer</b>       | <b>Calculates the length of the message "stream" from the beginning of the message (especially from the field Content-Length).</b> |

## 3.4 Encoding/Decoding Logic

According to RFC2326 [1], the following rules are followed in the decoding and encoding processes:

|  |         |                               |          |                    |
|--|---------|-------------------------------|----------|--------------------|
| Prepared (also subject responsible if other)<br>ETH/XZX Endre Kulcsár +36 1 437 7469 |         | No.<br>155 17-CNL 113 588 Uen |          |                    |
| Approved<br>ETH/XZXC (Tibor Csöndes)   | Checked | Date<br>2012-06-14            | Rev<br>A | Reference<br>GASK2 |

- 1 The RTSP message consists of three parts.
- 2 The lines are finished by “\r\n”. Message lines finished only by “\n” can be tolerated. The degree of tolerance is ERROR, WARNING, WARNING\_ONCE or ACCEPT.
- 3 If the message begins with “RTSP/” it is an RTSP response, otherwise it is an RTSP request.
- 4 The first line of the message is the first part of the message. It is the Status Line for message type of request otherwise the first line is the Request Line. They are split up according to RFC 2326 [1].
- 5 The second part of the message is the header. It consists of header fields. Details can be found in §.1.3 - §.1.6.
- 6 The header finished by an additional “\r\n” (i.e a sequence “\r\n\r\n” is the end of the header).
- 7 The third field of the message is the body. It can be any octetstring.
- 8 The header field “Content-Length” is present (with correct value) in the encoded message if and only if the body length is greater than zero and the automaticContentLengthCalc parameter of the encoding function is true.  
If this parameter is set false then the “Content-Length” header field is encoded as it is in the “HeaderStruct” and its value doesn’t depend on the length of the body so it’s suitable for making negative tests.