Okuma America Corporation

THINC-API Release Notes for Lathe

Document No.: S5015-008-21

| THINC-API | Version: | S5015-008-21 |
|-------------------------|---------------------------------|--------------|
| Release Notes For Lathe | otes For Lathe Date: 09/25/2013 | |

Revision History

| | | INCVISION MISCO | <u> </u> |
|------------|--------------|--|----------|
| Date | Version | Description | Author |
| 5/21/2007 | S5015-008-00 | Public release for Lathe THINC-API version 1.0.0.0 | LHuynh |
| 6/04/2007 | S5015-008-01 | Public release for Lathe THINC-API version 1.1.0.0 | Lhuynh |
| 08/15/2007 | S5015-008-02 | Public release for Lathe THINC-API version 1.2.0.0 | Lhuynh |
| 2/22/2008 | S5015-008-03 | Public Release 1.6.0.0 for Lathe THINC-API | Lhuynh |
| 4/11/2008 | S5015-008-04 | Public Release 1.6.0.0 for Lathe THINC-API | Lhuynh |
| 06/27/2008 | S5015-008-05 | Public Release 1.6.3.0 for Lathe THINC-API | Lhuynh |
| 07/25/2008 | S5015-008-06 | Public Release 1.6.4.0 for Lathe THINC-API | Lhuynh |
| 10/27/2008 | S5015-008-07 | Public Release 1.7.0.0 for Lathe THINC-API | Lhuynh |
| 12/18/2008 | S5015-008-08 | Public Release 1.8.0.0 for Lathe THINC-API | Lhuynh |
| 04/30/2009 | S5015-008-09 | Public Release 1.9.1.0 for Lathe THINC-API | Lhuynh |
| 10/12/2009 | S5015-008-10 | Public Release 1.10.0.0 for Lathe THINC-API | Lhuynh |
| 04/28/2010 | S5015-008-11 | Public Release 1.11.0.0 for Lathe THINC-API | Lhuynh |
| 09/14/2010 | S5015-008-12 | Public Release 1.11.1.0 for Lathe THINC-API | Lhuynh |
| 01/04/2011 | S5015-008-13 | Public Release 1.12.0.0 for Lathe THINC-API | Lhuynh |
| 02/02/2011 | S5015-008-14 | Public Release 1.12.1.0 for Lathe THINC-API | Lhuynh |
| 11/14/2011 | S5015-008-15 | Beta Release 1.14.0.0 for Lathe THINC-API | Lhuynh |
| 01/15/2012 | S5015-008-16 | Beta Release 1.14.1.0 for Lathe THINC-API | Lhuynh |
| 09/21/2012 | S5015-008-17 | Beta Release 1.14.2.0 for Lathe THINC-API | Lhuynh |
| 12/04/2012 | S5015-008-18 | Public Release 1.15.0.0 for Lathe THINC-API | Lhuynh |
| | | THINC-API | |

| THINC-API Release notes | ©Okuma America Corporation, | Page 2 of 8 |
|-------------------------|-----------------------------|-------------|
| | 2013 | |

| THINC-API | Version: | S5015-008-21 |
|-------------------------|------------------|--------------|
| Release Notes For Lathe | Date: 09/25/2013 | |

| 03/06/2013 | S5015-008-19 | Beta Release 1.15.1.0 for Lathe THINC-API | Lhuynh |
|------------|--------------|---|--------|
| 03/18/2013 | S5015-008-20 | Beta Release 1.15.2.0 for Lathe THINC-API | Lhuynh |
| 09/25/2013 | S5015-008-21 | Public Release 1.16.0.0 for Lathe THINC-API | Lhuynh |

| THINC-API | Version: | S5015-008-21 |
|-------------------------|------------------|--------------|
| Release Notes For Lathe | Date: 09/25/2013 | |

Table of Contents

| 1. | Introd | duction | 5 |
|----|--------|--|---|
| | 1.1 | Disclaimer of Warranty | 5 |
| | 1.2 | Purpose | 5 |
| | 1.3 | Scope | 5 |
| | 1.4 | Definitions, Acronyms, and Abbreviations | 5 |
| | 1.5 | References | 5 |
| 2. | Abou | at This Release | 5 |
| 3. | New | Features | 7 |
| 4. | Know | vn Bugs and Limitations | 7 |
| | 4.1 | Defect | 7 |
| | 4.2 | General Defect | 7 |
| | | 4.2.1 Data-API | 7 |
| | 4.3 | Defects Fixed in this Release | 8 |

| THINC-API | Version: | S5015-008-21 |
|-------------------------|------------------|--------------|
| Release Notes For Lathe | Date: 09/25/2013 | |

Release Notes for Lathe

1. Introduction

1.1 Disclaimer of Warranty

Okuma America Corporation makes no representations or warranties, either expressed or implied, by or with respect to anything in this document, and shall not be liable for any implied warranties of merchantability or fitness for a particular purpose or for any indirect, special or consequential damages.

Copyright © 2013, Okuma America Corporation. All rights reserved.

GOVERNMENT RIGHTS LEGEND: Use, duplication or disclosure by the U.S. Government is subject to restrictions set forth in the applicable Okuma America Corporation license agreement and as provided in DFARS 227.7202-1(a) and 227.7202-3(a) (1995), DFARS 252.227-7013(c)(1)(ii) (Oct 1988), FAR 12.212(a) (1995), FAR 52.227-19, or FAR 52.227-14, as applicable.

"Okuma America Corporation" and Okuma America Corporation's products are trademarks of Okuma America Corporation. References to other companies and their products use trademarks owned by the respective companies and are for reference purpose only.

1.2 Purpose

The purpose of the *Release Notes* document is to communicate major new features and changes in this release of the THINC-API for Lathe libraries. It also documents known problems and workarounds.

1.3 Scope

This document describes Public Release 1.16.0.0 of THINC-API for Lathe.

1.4 Definitions, Acronyms, and Abbreviations

GAC - Global Assembly Cache Windows folder located in 'C:\WINDOWS\assembly'

1.5 References

None.

About This Release

Public Release 1.16.0.0 of the THINC-API library for Lathe supports the following:

From this release, THINC API libraries will check dependency libraries during installation and at run-time. THINC API will fail to install or load if version of dependency libraries cannot support current version of THINC API.

In current release, some of the existing functions related to ATC, Tool, TailStock, and Chuck Data from DATA-API or Command API might not function correctly on OSP-P300S (LP) and OSP-P300L control unless they have been revised as listed in the Change section.

Version of Okuma.CLDATAPI.dll in Public Release 1.16.0.0 is 2.5.0.0

Version of Okuma.CLCMDAPI.dll in Public Release 1.16.0.0 is 1.9.0.0

Version of APINotifierService.exe in Public Release 1.16.0.0 is 1.16.0.0

Version of APINotifierStatus.exe in Public Release 1.16.0.0 is 1.0.0.0

Version of Okuma.Flexnet.dll in Public Release 1.16.0.0 is 1.3.0.0

| THINC-API Release notes | ©Okuma America Corporation, | Page 5 of 8 |
|-------------------------|-----------------------------|-------------|
| | 2013 | |

| THINC-API | Version: | S5015-008-21 |
|-------------------------|------------------|--------------|
| Release Notes For Lathe | Date: 09/25/2013 | |

Version of Okuma. Apilog.dll in Public Release 1.16.0.0 is 1.4.0.0

The following functions of Okuma.CLDATAPI.dll library will be only available in OSP-P200 control machines:

| Classes | Interfaces |
|----------|--|
| CMachine | OnOffStateEnum GetNCStatus(NCStatusEnum enNCStatus) |
| CMachine | CCurrentAlarm* GetCurrentAlarm() |
| CIO | OnOffStateEnum GetUserTasklOVariable(IOTypeEnum enIO, Int32 intIndex); |
| CIO | void SetUserTaskOutputVariable(Int32 intIndex, OnOffStateEnum enValue); |
| CIO | OnOffStateEnum GetProtectedUserTaskOutputVariable(Int32 intIndex); |
| CIO | void SetProtectedUserTaskOutputVariable(Int32 intIndex, OnOffStateEnum enValue); |

The following functions of Okuma.CLCMDAPI.dll library will be only available in OSP-P200 control machines:

| Classes | Interfaces |
|----------|--|
| CATC | Sub RegisterToolPot(ByVal intPotNo As Integer, ByVal intToolNo As Integer, ByVal enSettingToolKind As SettingToolKindEnum, ByVal enSettingToolSize As SettingToolSizeEnum, ByVal enReturnMagazine As ReturnMagazineEnum) |
| CATC | Sub SetNextTool(ByVal intToolNo As Integer, ByVal enSettingToolKind As SettingToolKindEnum, ByVal enSettingToolSize As SettingToolSizeEnum, ByVal enReturnMagazine As ReturnMagazineEnum) |
| CATC | Sub SetToolInStation(ByVal intToolNo As Integer, ByVal enSettingToolKind As SettingToolKindEnum, ByVal enSettingToolSize As SettingToolSizeEnum, ByVal enReturnMagazine As ReturnMagazineEnum, ByVal enTurretStation As TurretStationEnum) |
| CATC | Sub UnRegisterToolPot(ByVal intPotNo As Integer) |
| CProgram | CancelMainProgram() |
| CProgram | SelectMainProgramRSide(ByVal strMainProgramFileName As String, Optional ByVal strSubProgramFileName As String = "", Optional ByVal strSystemSubtituteProgramFileName As String = "", Optional ByVal strProgramName As String = "") |
| CProgram | SelectMainProgramLSide(ByVal strMainProgramFileName As String, Optional ByVal strSubProgramFileName As String = "", Optional ByVal strSystemSubtituteProgramFileName As String = "", Optional ByVal strProgramName As String = "") |
| CTools | CalcualteToolOffset(ByVal intToolNo As Integer, ByVal enAxisIndex As OffsetAxisIndexEnum, ByVal enSubSystem As SubSystemEnum, ByVal dblValue As Double) |
| CTools | AddConstantToolOffset(ByVal intOffsetNo As Integer, ByVal enAxisIndex As OffsetAxisIndexEnum, ByVal enSubSystem As SubSystemEnum, ByVal enCuttingPosition As CuttingPositionEnum) |
| CTools | AddConstantNoseRadiusCompensation(ByVal intOffsetNo As Integer, ByVal enAxisIndex As OffsetAxisIndex2Enum, ByVal enSubSystem As SubSystemEnum, ByVal enCuttingPosition As CuttingPositionEnum) |
| CTools | AddConstantToolWear(ByVal intOffsetNo As Integer, ByVal enAxisIndex As OffsetAxisIndex2Enum, ByVal enSubSystem As SubSystemEnum, ByVal enCuttingPosition As CuttingPositionEnum) |
| CTools | SubtractConstantToolOffset(ByVal intOffsetNo As Integer, ByVal enAxisIndex As OffsetAxisIndexEnum, ByVal enSubSystem As SubSystemEnum, ByVal enCuttingPosition As CuttingPositionEnum) |

| THINC-API Release notes | ©Okuma America Corporation, | Page 6 of 8 |
|-------------------------|-----------------------------|-------------|
| | 2013 | |

| THINC-API | Version: S5015-008-21 |
|-------------------------|-----------------------|
| Release Notes For Lathe | Date: 09/25/2013 |

| CTools | SubtractConstantNoseRadiusCompensation(ByVal intOffsetNo As Integer, ByVal enAxisIndex As OffsetAxisIndex2Enum, ByVal enSubSystem As SubSystemEnum, ByVal enCuttingPosition As CuttingPositionEnum) |
|----------|---|
| CTools | SubtractConstantToolWear(ByVal intOffsetNo As Integer, ByVal enAxisIndex As OffsetAxisIndex2Enum, ByVal enSubSystem As SubSystemEnum, ByVal enCuttingPosition As CuttingPositionEnum) |
| CProgram | SelectScheduleProgramLSide(ByVal strScheduleProgramFileName As String) |
| CProgram | SelectScheduleProgramRSide(ByVal strScheduleProgramFileName As String) |
| CMachine | Public Sub SetUserAlarm(ByVal enAlarm As UserAlarmEnum, Optional ByVal strAlarmMessage As String = "", Optional ByVal enUserAlarmSubSystem As UserAlarmSubSystemEnum = 0) |
| CMachine | Public Sub ClearUserAlarmD(ByVal enUserAlarmSubSystem As UserAlarmSubSystemEnum) |

Note: User Alarm will require OKUMA.Lathe.UserAlarm license feature in order to function on OSP-P200 machine if machine can support.

3. New Features

None

4. Known Bugs and Limitations

This section identifies known problems with Public Release 1.16.0.0 and describes any work-arounds.

4.1 Defect

4.2 General Defect

DATA-API library, Okuma.CLDATAPI.dll, cannot create directly under ASP.NET web application.

Solution/Work-arounds: Create and initialize DATA-API in a separate thread. All function calls must be called from objects created inside separated thread mentioned above.

DATA-API library can only support applications designed with single-threaded apartment of COM threading model. The underlying library, LDATAPI.dll, cannot be loaded during call to CMachine::Init function when an MTAThread attribute is applied to the application.

Solution/Work-arounds: None

4.2.1 Data-API

4.2.1.1 MacMan.COperationHistory class

Function:

Int32 COperation* GetOperationHistory(Int32 intIndex);
ArrayList* GetOperationHistory(Int32 intFromIndex, Int32 intToIndex);
Int32 GetMaxCount();
Int32 GetCount();

Symptom: Failed to get correct data for Subsystem L and R side if MacMan screen is different than current setting of subsystem. It always gets the data from current MacMan screen.

| THINC-API Release notes | ©Okuma America Corporation, | Page 7 of 8 |
|-------------------------|-----------------------------|-------------|
| | 2013 | |

| THINC-API | Version: | S5015-008-21 |
|-------------------------|--------------|--------------|
| Release Notes For Lathe | Date: 09/25/ | /2013 |

Solution/Work around: None

4.2.1.2 CAxis class

Function:

 $Double\ GetActual Position Program Coord(\ AxisIndex 1 Enum\ en AxisIndex);$

Double GetTargetPosition (AxisIndex1Enum enAxisIndex);

Symptom: The Z-axis position for sub system NC-AL and NC-AR does not return data correctly. It is based on the current selection of spindle in NC panel or command program G140/G141.

Solution/Work around: None

4.3 Defects Fixed in this Release

None

| THINC-API Release notes | ©Okuma America Corporation, | Page 8 of 8 |
|-------------------------|-----------------------------|-------------|
| | 2013 | |