
Okuma America Corporation

THINC-API Release Notes for Lathe

Document No.: S5015-008-10

| | |
|-------------------------|-----------------------|
| THINC-API | Version: S5015-008-10 |
| Release Notes For Lathe | Date: 10/12/2009 |

Revision History

| Date | Version | Description | Author |
|------------|--------------|--|--------|
| 5/21/2007 | S5015-008-00 | Public release for Lathe THINC-API version 1.0.0.0 | LHuynh |
| 6/04/2007 | S5015-008-01 | Public release for Lathe THINC-API version 1.1.0.0 | Lhuynh |
| 08/15/2007 | S5015-008-02 | Public release for Lathe THINC-API version 1.2.0.0 | Lhuynh |
| 2/22/2008 | S5015-008-03 | Public Release 1.6.0.0 for Lathe THINC-API | Lhuynh |
| 4/11/2008 | S5015-008-04 | Public Release 1.6.0.0 for Lathe THINC-API | Lhuynh |
| 06/27/2008 | S5015-008-05 | Public Release 1.6.3.0 for Lathe THINC-API | Lhuynh |
| 07/25/2008 | S5015-008-06 | Public Release 1.6.4.0 for Lathe THINC-API | Lhuynh |
| 10/27/2008 | S5015-008-07 | Public Release 1.7.0.0 for Lathe THINC-API | Lhuynh |
| 12/18/2008 | S5015-008-08 | Public Release 1.8.0.0 for Lathe THINC-API | Lhuynh |
| 04/30/2009 | S5015-008-09 | Public Release 1.9.1.0 for Lathe THINC-API | Lhuynh |
| 10/12/2009 | S5015-008-10 | Public Release 1.10.0.0 for Lathe THINC-API | Lhuynh |

| | |
|-------------------------|-----------------------|
| THINC-API | Version: S5015-008-10 |
| Release Notes For Lathe | Date: 10/12/2009 |

Table of Contents

| | | |
|-------|--|---|
| 1. | Introduction | 4 |
| 1.1 | Disclaimer of Warranty | 4 |
| 1.2 | Purpose | 4 |
| 1.3 | Scope | 4 |
| 1.4 | Definitions, Acronyms, and Abbreviations | 4 |
| 1.5 | References | 4 |
| 2. | About This Release | 4 |
| 3. | New Features | 6 |
| 3.1 | Data API | 6 |
| 3.2 | Change | 6 |
| 3.2.1 | Data API | 6 |
| 4. | Known Bugs and Limitations | 6 |
| 4.1 | Defect | 7 |
| 4.2 | General Defect | 7 |
| 4.2.1 | Data-API | 7 |
| 4.3 | Defects Fixed in this Release | 8 |
| 4.3.1 | Data API | 8 |

| | |
|-------------------------|-----------------------|
| THINC-API | Version: S5015-008-10 |
| Release Notes For Lathe | Date: 10/12/2009 |

Release Notes for Lathe

1. Introduction

1.1 Disclaimer of Warranty

Okuma America Corporation makes no representations or warranties, either expressed or implied, by or with respect to anything in this document, and shall not be liable for any implied warranties of merchantability or fitness for a particular purpose or for any indirect, special or consequential damages.

Copyright © 2009, Okuma America Corporation.
All rights reserved.

GOVERNMENT RIGHTS LEGEND: Use, duplication or disclosure by the U.S. Government is subject to restrictions set forth in the applicable Okuma America Corporation license agreement and as provided in DFARS 227.7202-1(a) and 227.7202-3(a) (1995), DFARS 252.227-7013(c)(1)(ii) (Oct 1988), FAR 12.212(a) (1995), FAR 52.227-19, or FAR 52.227-14, as applicable.

"Okuma America Corporation" and Okuma America Corporation's products are trademarks of Okuma America Corporation. References to other companies and their products use trademarks owned by the respective companies and are for reference purpose only.

1.2 Purpose

The purpose of the *Release Notes* document is to communicate major new features and changes in this release of the THINC-API for Lathe libraries. It also documents known problems and workarounds.

1.3 Scope

This document describes Public Release 1.10.0.0 of THINC-API for Lathe.

1.4 Definitions, Acronyms, and Abbreviations

GAC – Global Assembly Cache Windows folder located in 'C:\WINDOWS\assembly'

1.5 References

None.

2. About This Release

Public Release 1.10.0.0 of the THINC-API library for Lathe supports the following:

From this release, THINC API libraries will check dependency libraries during installation and at run-time. THINC API will fail to install or load if version of dependency libraries cannot support current version of THINC API.

Version of Okuma.CLDATAPI.dll in Public Release 1.10.0.0 is 1.10.0.0

Version of Okuma.CLCMDAPI.dll in Public Release 1.10.0.0 is 1.6.0.0

Version of APINotifierService.exe in Public Release 1.10.0.0 is 1.10.0.0

Version of Okuma.Flexnet.dll in Public Release 1.10.0.0 is 1.2.0.0

Version of Okuma.Apilog.dll in Public Release 1.10.0.0 is 1.1.0.0

| | |
|-------------------------|-----------------------|
| THINC-API | Version: S5015-008-10 |
| Release Notes For Lathe | Date: 10/12/2009 |

The following functions of Okuma.CLDATAPI.dll library will be only available in OSP-P200 control machines:

| Classes | Interfaces |
|----------|---|
| CMachine | OnOffStateEnum GetNCStatus(NCStatusEnum enNCStatus) |
| CMachine | CCurrentAlarm* GetCurrentAlarm() |

The following functions of Okuma.CLCMDAPI.dll library will be only available in OSP-P200 control machines:

| Classes | Interfaces |
|----------|--|
| CATC | Sub RegisterToolPot(ByVal intPotNo As Integer, ByVal intToolNo As Integer, ByVal enSettingToolKind As SettingToolKindEnum, ByVal enSettingToolSize As SettingToolSizeEnum, ByVal enReturnMagazine As ReturnMagazineEnum) |
| CATC | Sub SetNextTool(ByVal intToolNo As Integer, ByVal enSettingToolKind As SettingToolKindEnum, ByVal enSettingToolSize As SettingToolSizeEnum, ByVal enReturnMagazine As ReturnMagazineEnum) |
| CATC | Sub SetToolInStation(ByVal intToolNo As Integer, ByVal enSettingToolKind As SettingToolKindEnum, ByVal enSettingToolSize As SettingToolSizeEnum, ByVal enReturnMagazine As ReturnMagazineEnum, ByVal enTurretStation As TurretStationEnum) |
| CATC | Sub UnRegisterToolPot(ByVal intPotNo As Integer) |
| CProgram | CancelMainProgram() |
| CProgram | SelectMainProgramRSide(ByVal strMainProgramFileName As String, Optional ByVal strSubProgramFileName As String = "", Optional ByVal strSystemSubstituteProgramFileName As String = "", Optional ByVal strProgramName As String = "") |
| CProgram | SelectMainProgramLSide(ByVal strMainProgramFileName As String, Optional ByVal strSubProgramFileName As String = "", Optional ByVal strSystemSubstituteProgramFileName As String = "", Optional ByVal strProgramName As String = "") |
| CTools | CalcualteToolOffset(ByVal intToolNo As Integer, ByVal enAxisIndex As OffsetAxisIndexEnum, ByVal enSubSystem As SubSystemEnum, ByVal dblValue As Double) |
| CTools | AddConstantToolOffset(ByVal intOffsetNo As Integer, ByVal enAxisIndex As OffsetAxisIndexEnum, ByVal enSubSystem As SubSystemEnum, ByVal enCuttingPosition As CuttingPositionEnum) |
| CTools | AddConstantNoseRadiusCompensation(ByVal intOffsetNo As Integer, ByVal enAxisIndex As OffsetAxisIndex2Enum, ByVal enSubSystem As SubSystemEnum, ByVal enCuttingPosition As CuttingPositionEnum) |
| CTools | AddConstantToolWear(ByVal intOffsetNo As Integer, ByVal enAxisIndex As OffsetAxisIndex2Enum, ByVal enSubSystem As SubSystemEnum, ByVal enCuttingPosition As CuttingPositionEnum) |
| CTools | SubtractConstantToolOffset(ByVal intOffsetNo As Integer, ByVal enAxisIndex As OffsetAxisIndexEnum, ByVal enSubSystem As SubSystemEnum, ByVal enCuttingPosition As CuttingPositionEnum) |
| CTools | SubtractConstantNoseRadiusCompensation(ByVal intOffsetNo As Integer, ByVal enAxisIndex As OffsetAxisIndex2Enum, ByVal enSubSystem As SubSystemEnum, ByVal enCuttingPosition As CuttingPositionEnum) |
| CTools | SubtractConstantToolWear(ByVal intOffsetNo As Integer, ByVal enAxisIndex As OffsetAxisIndex2Enum, ByVal enSubSystem As SubSystemEnum, ByVal enCuttingPosition As CuttingPositionEnum) |
| CProgram | SelectScheduleProgramLSide(ByVal strScheduleProgramFileName As String) |
| CProgram | SelectScheduleProgramRSide(ByVal strScheduleProgramFileName As String) |

| | |
|-------------------------|-----------------------|
| THINC-API | Version: S5015-008-10 |
| Release Notes For Lathe | Date: 10/12/2009 |

3. New Features

The new classes/functions available in Public Release 1.10.0.0 are:

3.1 Data API

| Classes | Interfaces |
|---------|--|
| Cspec | Boolean IsValidSystem(ByVal enSubSystem As SubSystemEnum) |
| Cspec | Boolean GetPLCSpecCode(Int32 intPLCSpecCodeIndex, Int32 intBit) |
| Cspec | Boolean GetPLCSpecCode2(Int32 intPLCSpecCodeIndex, Int32 intBit) |

3.2 Change

3.2.1 Data API

By default, all objects will be created and initialized with sub system NC-AL if applicable. For MacMan classes, all objects will be created and initialized with SubSystem_1 if applicable.

3.2.1.1 CAxis class

Enumerations:

The following members are removed from the enumeration of AllAxisIndexEnum.

| Member Name | Description |
|-----------------------|----------------|
| SPECIAL_Axis_2 | Special Axis 2 |
| SPECIAL_Axis_1 | Special Axis 1 |

Functions:

AxisTypeEnum CAxis::GetAxisType (AllAxisIndexEnum enAxisIndex)

The ApplicationException is removed from function error handling.

GetActualPositionMachineCoord (AxisIndex6Enum enAxisIndex)

Axis parameter uses AxisIndex6Enum instead of AxisIndex1Enum due to some members of AxisIndex1Enum cannot be supported in this function.

3.2.1.2 CSpec class

Function:

String* CSpec::GetMachineSerialNumber()

This function is available on P100II and OSP-200 controls.

4. Known Bugs and Limitations

This section identifies known problems with Public Release 1.10.0.0 and describes any work-arounds.

| | |
|-------------------------|-----------------------|
| THINC-API | Version: S5015-008-10 |
| Release Notes For Lathe | Date: 10/12/2009 |

4.1 Defect

4.2 General Defect

DATA-API library, Okuma.CLDATAPI.dll, cannot create directly under ASP.NET web application.

Solution/Work-arounds: Create and initialize DATA-API in a separate thread. All function calls must be called from objects created inside separated thread mentioned above.

DATA-API library can only support applications designed with single-threaded apartment of COM threading model. The underlying library, LDATAPI.dll, cannot be loaded during call to CMachine::Init function when an MTAThread attribute is applied to the application.

Solution/Work-arounds: None

4.2.1 Data-API

4.2.1.1 MacMan.COperationHistory class

Function:

```
Int32 COperation* GetOperationHistory(Int32 intIndex) ;
ArrayList* GetOperationHistory(Int32 intFromIndex, Int32 intToIndex);
Int32 GetMaxCount() ;
Int32 GetCount() ;
```

Symptom: Failed to get correct data for Subsystem L and R side if MacMan screen is different than current setting of subsystem. It always gets the data from current MacMan screen.

Solution/Work around: None

4.2.1.2 CAxis class

Function:

```
Double GetActualPositionProgramCoord( AxisIndex1Enum enAxisIndex);
Double GetActualPositionMachineCoord( AxisIndex1Enum enAxisIndex);
Double GetDistanceToTargetPosition( AxisIndex1Enum enAxisIndex);
Double GetTargetPosition( AxisIndex1Enum enAxisIndex);
```

Symptom: Axis data for XI, ZI return -1 meanwhile NC displays *.*.*

Solution/Work around: None

Function:

```
Double GetActualPositionProgramCoord( AxisIndex1Enum enAxisIndex);
Double GetTargetPosition (AxisIndex1Enum enAxisIndex);
```

Symptom: The Z-axis position for sub system NC-AL and NC-AR does not return data correctly. It is based on the current selection of spindle in NC panel or command program G140/G141.

Solution/Work around: None

| | |
|-------------------------|-----------------------|
| THINC-API | Version: S5015-008-10 |
| Release Notes For Lathe | Date: 10/12/2009 |

4.3 Defects Fixed in this Release

4.3.1 Data API

4.3.1.1 CAxis Class

Function:

```
enum AxisTypeEnum GetAxisType(enum AxisIndexEnum enValue)
```

Symptom: Failed to return axis type for C Axis when machine is in B turret mode.

4.3.1.2 CBallScrew class

Function:

```
Public Function GetInterval(ByVal enAxisIndex As AxisIndex3Enum) As Double
```

Symptom: The function return data in metric unit even it has been set Inch unit.

4.3.1.3 CChuck class

Function:

```
Public Sub CalGrippingFaceToProgramZeroDistance(ByVal enValue As ChuckIndexEnum, ByVal dblValue As Double)
```

Symptom: The function allows performing a calculation over max setting limit.

Valid setting range is -393.70078 to +393.70078 for inch unit.

4.3.1.4 COptionalParameter class

```
Public Sub SetNCOptionalParameterLongWord(ByVal intLongWordIndex As Integer, ByVal intValue As Integer)
```

Symptom: This function fails to set value that is greater than 32767.

```
Public Sub AddNCOptionalParameterLongWord(ByVal intLongWordIndex As Integer, ByVal intValue As Integer)
```

Symptom: This function fails to set value that is greater than 32767.

4.3.1.5 CProgram class

Function:

```
Boolean CProgram::CycleComplete(MachineSideEnum enMachineSide)
```

Symptom: This function fails get the status correctly based on machine side.

For single side machine, left side is the valid side instead of right side.

```
Boolean CProgram::ScheduleProgramCycleComplete (MachineSideEnum enMachineSide)
```

Symptom: This function fails get the status correctly based on machine side.

For single side machine, left side is the valid side instead of right side.

4.3.1.6 CWorkpiece class

```
Public Sub CalZeroOffset(ByVal enAxisIndex As AxisIndex4Enum, ByVal dblValue As Double)
```

Symptom: This function allows performing over the max setting limit. The allowable setting limit is:

| | | |
|-------------------------|-------------------------------------|-------------|
| THINC-API Release notes | ©Okuma America Corporation, 2009 | Page 8 of 9 |
|-------------------------|-------------------------------------|-------------|

| | |
|-------------------------|-----------------------|
| THINC-API | Version: S5015-008-10 |
| Release Notes For Lathe | Date: 10/12/2009 |

| | Metric | Inch |
|---------------------------|-------------------------|-------------------------|
| 0.1 micron option | -9999.9999 To 9999.9999 | -393.70078 To 393.70078 |
| Without 0.1 micron option | -99999.999 To 99999.999 | -3937.0078 To 3937.0078 |

Public Sub CalZeroShift (ByVal *enAxisIndex* As AxisIndex4Enum, ByVal *dblValue* As Double)

Symptom: This function allows performing over the max setting limit. The allowable setting limit is:

| | Metric | Inch |
|---------------------------|-------------------------|-------------------------|
| 0.1 micron option | -9999.9999 To 9999.9999 | -393.70078 To 393.70078 |
| Without 0.1 micron option | -99999.999 To 99999.999 | -3937.0078 To 3937.0078 |