

## Finite Automata=Models for small memory

### Door controller

- front pad (DOOR) rear pad
  - door swings open to the rear
- Door is CLOSED or OPEN
- Four signals: FRONT, REAR, BOTH, NEITHER
- When CLOSED: NEITHER or BOTH  $\rightarrow$  CLOSED, FRONT  $\rightarrow$  OPEN; REAR  $\rightarrow$  CLOSED  
When OPEN: NEITHER  $\rightarrow$  CLOSED; FRONT or REAR  $\rightarrow$  OPEN; BOTH  $\rightarrow$  OPEN

## Finite Automata

- Door controller can be represented by a *state diagram*: Two states: closed, open

### Other Examples

- *Lexical analyzer* of a compiler for detecting identifiers, keywords, and punctuation
- *Model checking techniques* for verifying finite state systems (e.g., communication protocols, hardware systems)
- In the probabilistic setting, Markov chains (e.g. for PageRank)

## Example of Finite Automata

	0	1
$q_1$	$q_1$	$q_2$
$q_2$	$q_3$	$q_2$
$q_3$	$q_2$	$q_2$

*Start state* is  $q_1$ . *Accept state* is  $q_2$ .

Other examples:

- counting mod  $n$
- $M = \{w \mid \text{ends with a } 1\}$ .
- complement

## A formal definition of a Finite Automaton

A *finite automaton (FA)* is a structure  $M = (Q, \Sigma, \delta, q_0, F)$ , where

- $Q$  is a finite set of *states*,
- $\Sigma$  is the input symbols or alphabet,
- $\delta$ , the *transition function*, e.g.,  $\delta(q, a) = q'$  where  $q, q' \in Q$  and  $a \in \Sigma$
- $q_0 \in Q$  is the *start state*,
- $F$  is a subset of  $Q$ ; elements of  $F$  are called *accept states* or *final states*.
- The *language of* the machine  $M$  is the set  $A$  of all strings that  $M$  accepts. We write  $L(M) = A$  and say  $M$  *accepts (or recognizes)*  $A$ . If the machine  $M$  accepts no strings then  $L(M) = \emptyset$ .

## Formal definition of computation

Let  $M = (Q, \Sigma, \delta, q_0, F)$  be a finite automaton, and let  $w = w_1w_2...w_n$  be a string over  $\Sigma$ .

Then  $M$  *accepts*  $w$  if there is a sequence of states  $r_0, \dots, r_n$  in  $Q$  s.t.

1.  $r_0 = q_0$
2.  $\delta(r_i, w_{i+1}) = r_{i+1}$
3.  $r_n \in F$

$M$  *recognizes*  $A$  if  $A = \{w \mid M \text{ accepts } w\}$ . A language is called a *regular language* if some finite automaton recognizes it.

## More examples

Construct a finite automaton accepting the following language:

$$\{x \in \{a, b\}^* \mid x \text{ contains a substring of 3 consecutive } a\text{'s}\}$$

## Another example

Construct a finite automaton accepting the following language:

$$\{x \in \{a, b\}^* \mid x \text{ does not contain a substring of 3 consecutive } a\text{'s}\}$$

## Operations on Languages

Recall:

- A *language* is set of strings over an alphabet.
- We may apply set operations like union, intersection, and set difference to languages.
- The *union* of  $L$  and  $M$  is denoted  $L \cup M$ , and is the set of strings that are in either  $L$  or  $M$ .
- The complement of a language  $A$  is  $\Sigma^* - A$  or is denoted  $\bar{A}$  if  $\Sigma$  is understood.



## Operations on Languages (cont'd)

- If  $L_1$  and  $L_2$  are languages over  $\Sigma$  their concatenation is

$$L_1 L_2 = L_1 \cdot L_2 = \{w \in \Sigma^* \mid w = xy \text{ for some } x \in L_1 \text{ and } y \in L_2\}.$$

- The *star* of a language  $L$  is the set of all strings obtained by concatenating zero or more strings from  $L$ . Thus,

$$L^* = \{w \in \Sigma^* \mid w = w_1 \dots w_k \text{ for some } k \geq 0 \text{ and } w_1, \dots, w_k \in L\}.$$

## Closure of regular languages

A set is *closed* under some operation if applying that operation to elements of the set returns in another element of the set.

**Theorem:** If  $A_1$  and  $A_2$  are regular languages then so is  $A_1 \cup A_2$ .

**Proof Idea:** Let  $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$  and  $M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$  be the automaton that recognize  $A_1$  and  $A_2$  resp. We construct  $M = (Q, \Sigma, \delta, q_0, F)$  which recognizes  $A_1 \cup A_2$  by *simulating* both of these machines *concurrently*, and accepting if one of them accepts.

## Union Construction

1.  $Q = \{(r_1, r_2) \mid r_1 \in Q_1, r_2 \in Q_2\}$
2. For each  $(r_1, r_2) \in Q$  and each  $a \in \Sigma$ ,  $\delta(r_1, r_2), a) = (\delta_1(r_1, a), \delta_2(r_2, a))$ .
3.  $q_0 = (q_1, q_2)$
4.  $F = \{(r_1, r_2) \mid r_1 \in F_1 \text{ or } r_2 \in F_2\}$ .

Why this construction works: remembers the pairs of states the machine is in. Similarly, closed under intersection.

## Closed under concatenation

**Theorem:** If  $A_1$  and  $A_2$  are regular languages, then so is  $A_1 \cdot A_2$ .

Product construction doesn't help here... need to do two strings consecutively, not concurrently.