

1 **HaptiFab: A Wearable Toolkit Supports the Integration of Haptic Actuator and**
2 **Fabric for Interdisciplinary Design**

3
4 ANONYMOUS AUTHOR(S)



23 Fig. 1. HaptiFab's application in interdisciplinary design: a) an overview of the HaptiFab toolkit, b) participants using the kit to create,
24 c) the integration of the haptic actuator with the fabric, d) the final presentation of the wearable prototype.

25 Integrating different haptic sensations into wearable technology poses complex challenges due to the variety of options and the
26 interdisciplinary expertise required. A key limitation is the absence of effective tools to assist designers and engineers create prototypes.
27 In this paper, we first conducted a formative study and identified our design goals. We then proposed HaptiFab, a wearable toolkit that
28 integrates a haptic actuator with fabric, enabling interdisciplinary groups to create wearable prototypes effectively. Through a five-day
29 workshop with 30 participants from interdisciplinary backgrounds, we conducted a mixed-method analysis, demonstrating HaptiFab's
30 ability to support varied design goals with low learning barriers and high design efficiency for interdisciplinary groups. We provide a
31 detailed report on participants' goals, interactions, considerations, and potential design spaces enabled by HaptiFab. Drawing on these
32 findings, we discuss the advantages of combining haptic actuators to make different sensations with fabric, which could empower
33 interdisciplinary groups to create innovative, practical, and emotionally resonant wearable technologies for diverse user scenarios.
34
35

36 CCS Concepts: ^ Human-centered computing ! Systems and tools for interaction design .
37

38 Additional Key Words and Phrases: Haptic Actuator, Wearable Technology, Fabric, Haptic Sensation, Interdisciplinary Design
39

40 ACM Reference Format:

41 Anonymous Author(s). 2018. HaptiFab: A Wearable Toolkit Supports the Integration of Haptic Actuator and Fabric for Interdisciplinary
42 Design. In Proceedings of Make sure to enter the correct conference title from your rights con rmation email (Conference acronym 'XX').
43 ACM, New York, NY, USA, 33 pages. <https://doi.org/XXXXXX.XXXXXXX>

44
45 Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not
46 made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components
47 of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on
48 servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

49 © 2018 Copyright held by the owner/author(s). Publication rights licensed to ACM.

50 Manuscript submitted to ACM

51
52 Manuscript submitted to ACM

53 1 INTRODUCTION

54
55 Haptics is an important form of sensation that assists wearable technologies in realizing specific functions, conveying
56 affective information, and improving psychological experiences due to its wide distribution across the surface of human
57 skin [1, 2]. Recent research has transferred physically-grounded haptic interfaces [3] to haptic actuators [4], which
58 allows users to utilize the wearable technology at more precise stimulus actuation on the body [5], improving sensation
59 variety, and portability [6]. Fabric, as another essential material that provides unique haptic sensations, plays a vital
60 role in wearable technologies for energy harvesting, attitude sensing, and comfort evaluation [6–9]. Leveraging fabric’s
61 wearability and combining it with haptic actuators, various haptics advantages can be realized in different scenarios,
62 such as enhancing intimacy perception [10], synchronizing senses to reflect emotions [11].

63
64 However, when designing haptic sensation in wearable technology, designers and engineers often face a common yet
65 complex question: "I know haptics are amazing components, but which haptic sensation should I choose, and which haptic
66 actuator or fabric should I use to achieve my goal?" challenge arises primarily due to the wide range of options
67 available for selecting appropriate actuators and fabrics, in the design of haptic sensations for wearable technologies.
68 Each type of actuator (e.g., pneumatic silicone [12], vibration motor [13], and shape memory alloy (SMA) [14–16]) and
69 fabric (e.g., Soft-Harsh [17, 18] or Smooth-Rough [17, 18]) generates distinct types of haptic sensations. Furthermore,
70 each sensation type (e.g., compression [19], friction [20], stretch [21], and vibration [22, 23]) provides a unique sensory
71 experience.

72
73 In addition, designing wearable technology often requires interdisciplinary expertise, including interaction design
74 [24], fashion design [25], and programming [26]. This inherently complex process integrates research through design
75 (RtD) [27] with technical implementation, often requiring collaboration between specialists from diverse fields. A key
76 challenge lies in aligning these disciplines, such as blending haptic sensations with fabric design and engineering
77 [10], requiring both an understanding of user sensory experiences and the ability to bridge gaps between creative
78 design and technical feasibility [28]. Given these difficulties, previous researchers usually developed wearable toolkits
79 to facilitate this complex design process due to the advantages of simplifying prototyping [29, 30] and demystifying
80 abstract hardware and software concepts [31]. However, there are some existing issues: limited customization options
81 [32], the complexity of integration [33], and poor material compatibility [25]. To address these challenges, we propose
82 integrating haptic actuators and fabrics with different sensations into accessible toolkits, empowering interdisciplinary
83 groups to develop innovative and practical wearable technologies for diverse user scenarios. Therefore, this paper aims
84 to address the following questions.

- 85
86 • RQ1: How to design a wearable toolkit that effectively integrates different haptic sensations with fabric?
87
88 • RQ2: What are the considerations, challenges, and design space of interdisciplinary groups when prototyping a
89 wearable toolkit that integrates haptic actuators and fabric?

90
91 We first conducted a formative study with 16 participants to discover their general collaboration challenges and
92 expectations of wearable toolkits as our design goals. Based on that, we designed HaptiFab, a toolkit with haptic actuators
93 and fabric integration for interdisciplinary groups to design wearable technology. HaptiFab consists of three main
94 components: a) Haptic Generation Kit, b) Fabric Kit, and c) Design Manual to allow users to do DIY design prototypes
95 without fully understanding the background of professional wearable technology. We conducted a five-day workshop
96 with 30 participants to form seven interdisciplinary groups to use HaptiFab for wearable design. We used the mixed
97 research method, including interviews, observations, and questionnaires to evaluate HaptiFab by collecting participants’
98 experiences and perspectives on its usage. Our findings indicated that Haptifab could support varied designs, resulting
99
100
101
102
103
104

in prototypes spanning functional, emotional, and educational use cases. Our findings also revealed that HaptiFab can create practical and emotionally resonant solutions while fostering collaboration by lowering technical barriers and enhancing adaptability, supporting diverse user goals. We report participants' design considerations during usage, with more design space for HaptiFab's potential. This study demonstrates the potential of haptic and fabric integration to empower designers and engineers, expanding the possibilities for wearable technology in various user scenarios. We also discuss the advantages of haptic and fabric integration in wearable technology design and provide design suggestions for future toolkits.

2 RELATED WORKS

2.1 Haptic Actuator Sensations

In the field of wearable technology, haptic sensations triggered by external stimuli include vibration [13, 22, 34, 35], compression [17, 32, 36, 37], stretch [16, 21, 35, 38–42], contractile [43], bending [44], expanding [45], and pinching [45]. Among these, three key actuation methods—compression, stretch, and vibration—are particularly significant. The proper use of haptic actuators can provide suitable sensations to meet functional needs in various scenarios, such as social interaction [46], emotional communication [47], and entertainment games [33].

Compression. The sensations of compression are commonly achieved through pneumatic actuators [12, 17, 32, 36]. Pneumatic compression can produce a range of haptic effects, from subtle to intense and intimate sensations [48]. Compared to hydraulic systems, which may pose risks of liquid leakage and equipment damage, pneumatic silicone has demonstrated its suitability for wearable applications in several studies [17, 49]. Additionally, pneumatic silicone is easy to customize [49–51]. For example, He et al. [36] use custom-molded pneumatic silicone to provide a range of haptic cues on the arm. Customizable pneumatic silicone is highly effective as a compression device, offering both safety and comfort when applied to the body [36, 48].

Stretch. In wearable technology, stretch actuators attached to the body often generate skin-stretch sensations like dragging, pinching, or twisting [10]. Shape Memory Alloy (SMA) is ideal for producing such haptic sensations by applying shear forces to stimulate the skin's deformation detection [52]. SMA is lightweight and compact, allowing for seamless integration without altering the overall shape, such as in haptic pin arrays [40, 53, 54] and fingertip-mounted skin stretch devices [21]. Additionally, their silent and flexible activation makes them widely used in inconspicuous wearable technologies, such as in medical wearable exoskeletons [44, 55] and smart fabrics that support astronauts' cardiovascular systems [56, 57].

Vibration. Vibration actuators provide immediate yet sustained haptic feedback [28, 48]. They can offer specific or symbolic sensations, making them ideal for use in wearable devices, such as emotion-based social media applications [22, 23, 46], rehabilitation monitoring garments [58], and VR-enhancing devices [59]. Hollow cup motors [60] and linear motors [61] deliver high-frequency, precise, and low-power operation. In contrast, piezoelectric motors [62] have a smaller working range, and DC motors [63, 64] often require additional mechanical transmission systems, making them less suitable for applications requiring stronger feedback. These benefits make hollow cups and linear motors particularly well-suited for wearable device designs.

2.2 Fabric Sensations and Applications

Fabrics have been extensively applied in various domains, serving as both functional and sensory components in technology and design. Prior research highlights their versatility, including artistic expression [65, 66], assistive

157 devices [67, 68], electronic clothing [69–73], and interactive products [74]. In particular, the tactile properties of fabrics
158 significantly influence user sensations. Jiao et al. evaluated various fabrics (e.g., cotton, nylon, and polyester blends)
159 [75] and identified different sensations such as smooth-rough, soft-harsh, and hairy-stiff [76, 77]. Similarly, Bhömer
160 et al. explored anisotropic fabric structures through prototyping, demonstrating their potential to enhance the skin-
161 friendliness and comfort of wearable devices [25]. These studies illustrate the importance of fabric selection in designing
162 wearable systems that prioritize user comfort and experience.
163

164 Beyond material properties, research has explored different fabric construction techniques for wearable design.
165 For instance, organza fabric with a plain surface has been used to develop functional and aesthetic components in
166 interactive wearables [78]. Origami structures have enabled dynamic adaptability in wearable systems [79], while lace
167 constructions have been utilized for creating decorative skin inter, showcasing versatility in diverse design scenarios
168 [80]. These studies emphasize how fabric construction techniques are important in wearable design, offering both
169 functional and decorative potential.
170

171 In the domain of haptics, fabrics serve as passive responsive substrates [81], interacting with haptic actuators to act as
172 "carriers" within wearable devices. These fabrics enable the delivery of haptic sensations to users while simultaneously
173 enhancing experiences. For example, integrating haptic actuators into fabrics allows wearables to provide feedback
174 such as contraction [82] and compression deformation [83], enriching the interaction experience. However, integrating
175 these functionalities into adaptable wearable systems remains a complex challenge, requiring further exploration of
176 fabric properties, haptic feedback, and user experience to fully unlock the potential of fabrics in wearable technology.
177

178 Thus, advancing wearable technology requires the effective integration of haptic sensations from both fabrics and
179 actuators to meet diverse user needs. Our work addresses this challenge by integrating multiple fabric techniques in
180 our toolkit to enable versatile applications across different scenarios.
181

182 2.3 Adapting Haptic Toolkits and Theoretical Design Method for Wearable Technology

183 In the Human-Computer Interaction (HCI) community, the development of DIY prototyping toolkits for novel wearable
184 technology has aimed to provide low-cost, open-hardware solutions for wearable haptic interfaces [5, 30, 49, 84]. These
185 toolkits address challenges in design, fabrication, sensing, and actuation by introducing innovative materials and
186 workflow design [85], creating functional physical widgets and control components [86], or developing integrated
187 hardware and firmware environments [84], thereby lowering the barrier to entry and supporting the design of different
188 haptic sensations for various body parts [30]. For instance, Compressables-based haptic interactions on various body
189 parts support open-ended design [31]. Beyond specific use cases, toolkits of Soma design enhance body awareness, foster
190 aesthetic appreciation, and broaden the design space for intimate wearable technologies [87]. However, current wearable
191 toolkits have yet to adapt to the diverse needs, as most are typically designed for specific or limited contexts. This
192 limitation becomes more pronounced in interdisciplinary collaboration, where designers and engineers frequently face
193 obstacles. To address these interdisciplinary challenges, theoretical design methods provide a structured foundation for
194 guiding design processes, facilitating shared goals, and fostering a unified knowledge system [88]. Various theoretical
195 design methods [89, 90, 90, 91] have inspired our research. The Function-Behavior-Structure (FBS) model simplifies
196 design by breaking it into function, behavior, and structure, guiding designers and engineers in defining a system's
197 purpose and actions. Similarly, Hasso Plattner's five design thinking stages—empathizing, defining, ideating, prototyping,
198 and testing—provide a structured framework for problem-solving [91]. However, bridging design thinking and technical
199 principles in an interdisciplinary context remains challenging [92]. Zimmerman et al.'s framework of three types of
200 knowledge—how, true, and real [27]—provides a foundation for selecting appropriate haptic actuators [30] and fabrics
201
202 Manuscript submitted to ACM

[76], ensuring functionality and meaningful haptic experiences in wearable design. These integrated approaches help designers and engineers balance creativity with technical rigor [49], leading to innovative and practical wearable solutions.

Drawing on insights from these theoretical methods and existing literature, our goal is to develop a wearable toolkit that integrates different haptic actuators and fabrics. By leveraging these methods, the toolkit aims to help designers and engineers overcome interdisciplinary challenges and create rapid prototypes that adapt to various everyday scenarios, without requiring expertise in multiple disciplines.

3 Formative Study and Design Goals

To further explore the challenges in interdisciplinary design, we conducted a focus group with designers and engineers. Based on these findings, we identified our design goals, which played a crucial role in guiding the development of our design manual and the selection of prototypes.

3.1 Formative Study

3.1.1 Participant and Procedure We invited 16 participants with interdisciplinary expertise in design and engineering, as well as experience in prototype development and cross-disciplinary projects. Their diverse backgrounds enabled them to offer valuable insights and feedback. To explore the challenges of interdisciplinary design, particularly in integrating haptic actuators with fabric, we organized a two-hour focus group discussion. The session included an introduction to existing HCI research on haptic sensations and tactile prototypes using fabrics in wearable technology. During the discussion, we focused on the following two key topics: the challenges designers and engineers face when collaborating on interdisciplinary design, and advice for toolkit design to support the integration of haptic actuators and fabric. Based on the discussion, we identified key challenges and proposed potential improvements to guide the development of a framework that better supports interdisciplinary design processes.

3.1.2 Findings While participants acknowledged the importance of interdisciplinary collaboration for integrating haptic actuators and fabric, they also highlighted several challenges associated with this process. Based on their feedback, we identified the following key findings:

Communication Challenges Across Disciplines One of the major issues is the communication barrier between designers and engineers. Designers tend to focus on user experience and aesthetics, while engineers concentrate on hardware implementation and functionality. As one Fashion Designer reflected, due to differences in professional languages and working styles, communication efficiency and accuracy are often affected. To overcome this issue, some participants suggested adopting more structured communication processes, such as design manuals and visual tools, to align interdisciplinary design requirements.

Toolkit for Integrating Different Haptic Sensations Designers have emphasized that, in addition to ease of use, tools should support the simulation of diverse haptic sensations. Given the variety of sensations in modern products and research, it can be challenging to match specific actuators to their corresponding sensations. Effective tools would not only clarify these relationships but also enable designers to tailor haptic experiences to specific use cases and user groups. Engineers also face challenges, particularly in integrating haptic actuators into the fabric while ensuring comfort, and effectiveness, without compromising the fabric's flexibility and wearability. A well-structured toolkit

261 categorizing various fabric types and their compatibility with haptic actuators could support engineers in making
 262 informed design decisions aligned with material properties and user needs.
 263

264 Accessible and Cost-effective DIY Prototyping
 265 Translating abstract ideas into tangible prototypes is a shared challenge
 266 for both designers and engineers, particularly when it comes to sensory feedback or physical interactions. Designers
 267 often rely on intuitive exploration and iterative adjustments, which underscores the need for simple, user-friendly
 268 prototyping tools. However, existing tools, such as haptic actuators like motors, are often difficult to integrate and have
 269 a certain level of complexity. Engineers also mentioned that they face similar difficulties in communicating complex
 270 technical solutions, highlighting the need for accessible prototyping methods that promote collaboration and innovation
 271 across disciplines. In this context, DIY-friendly, easily accessible, and cost-effective kits have proven especially valuable
 272 for fostering creativity and conducting multiple iterations of experiments.
 273

275 3.2 Design Goals

276 Based on our literature review and formative study, we summarized a series of limitations of current wearable toolkits
 277 and the challenges of integrating haptic actuators and fabrics, including 1) Limited Customization Options, such as
 278 [32], 2) Complexity of Integration [33], 3) Poor Material Compatibility [25]. These disadvantages provide us with more
 279 insights into three design goals.
 280

- 281 • **Wearability:** Since different body parts have varying sensitivity thresholds, the haptic sensations experienced
 282 can differ across regions. As a wearable device, our toolkit should support designs for all body parts, as mentioned
 283 in existing studies [49]. It should incorporate haptic materials that easily adapt to the shape and size of the
 284 user's body, enhancing both comfort and flexibility.
- 285 • **Adaptability:** To ensure our toolkit can meet the needs of different scenarios and accommodate specific
 286 user expectations, we proposed offering various haptic modules in different sizes and configurations. These
 287 combinations allow for diverse sensory experiences, meeting individual customization preferences.
- 288 • **Accessibility:** To make the toolkit easier for interdisciplinary groups, we aim to explore ways to reduce technical
 289 barriers for non-programmers by designing a haptic generation kit adaptable to different programming skill
 290 levels. We recommend providing diverse sensory actuators, driver modules, and clear usage guidance to enhance
 291 accessibility and meet the practical needs of designers and engineers.

296 4 HAPTIFAB TOOLKIT

297 To answer our RQs, in this paper, we developed a wearable toolkit, HaptiFab, that enables the integration of haptic
 298 actuators and fabrics, allowing designers with a single background to engage in an interdisciplinary design process.
 299 HaptiFab consists of three parts: Haptic Generation Kits (Figure.2 a), Fabric Kits (Figure.2 b), and a Design Manual
 300 (Figure.2 c). This toolkit mainly draws on insights from the haptic toolkit [31, 84] and design-centered approaches [30].
 301 Based on our literature review, we critically reflected on the technical barriers in haptic design and the specialized
 302 knowledge required in fashion design to identify potential challenges users may encounter. Based on these reflections,
 303 we propose the following features for HaptiFab.
 304

305 4.1 Toolkits Features and Components

306 4.1.1 Haptic Generation Kit
 307 The Haptic Actuator Kit consists of three components: Electronic Modules, Haptic Output
 308 Actuators, and Driver and Adhesion Modules, as shown in Fig.2 a.
 309

310 Manuscript submitted to ACM
 311
 312




Fig. 2. HaptiFab overview. a) Haptic Generation Kit, a-1: electronic modules, a-2: output actuators, a-3: driver and adhesion modules, b) Fabric kit, b-1: Flat Surface, b-2: Structural Fabric/Surface , b-3: Decoration Surface , c) Design Manual.

Electronic Modules. The Electronic Modules are the core components for integrating wearable technology with various sensors and actuators. Users can design haptic feedback using these modules, which support both simple setups and advanced programmatic control. This design ensures accessibility for individuals of all skill levels, from beginners

365 to those experienced with platforms like Arduino. The modules have the same control ports as standard Arduino
 366 modules, including digital I/O, VCC, and GND ports. Our toolkit provides users with both manual and programmatic
 367 control components. For users without programming experience, we recommend using button and knob modules such
 368 as the Push Button Switch. For those familiar with open-source electronic prototyping platforms like Arduino, we
 369 provide programming examples for more advanced control. Additionally, we offer a basic Arduino-compatible kit with
 370 56 modules, covering nine sensors and various output modules, such as LEDs, microphones, relays, and PWM control
 371 modules.
 372

373 **Haptic Output Actuator** Based on literature review, we identified three commonly experienced haptic sensations:
 374 Compression [17, 32, 36, 48], Vibration [22, 23, 34, 46], and Stretching [35, 39, 41, 52, 93]. As illustrated in Fig.3, these
 375 sensations are commonly associated with specific haptic actuators. Based on insights from our formative study and
 376 design goals, we selected three haptic actuators for our system: Pneumatic Silicone, Vibration Motor, and Shape Memory
 377 Alloy (SMA) based on their ability to produce these desired sensations effectively. Detailed parameters are provided
 378 in Appendix A.2. These actuators were selected for their ability to offer diverse haptic feedback, adaptability across
 379 various wearable contexts, low cost, and DIY-friendly implementation for interdisciplinary groups, making them ideal
 380 for our study.
 381

385 Research	386 Haptic Actuator	387 Haptic Sensation					388 Wearing Position	389 Fields of Application
		390 Stretch	391 Compress	392 Vibration	393 Friction	394 Num		
Squeezeback [17]	Pneumatic Silicon		●			1	Full body	Gaming, Education, Food Testing
PneuHaptic [32]	Pneumatic Silicon		●			1	Arm	Remote Communication
PneuSleeve [36]	Pneumatic Silicon		●			1	Wrist, Arm	Gaming, Remote Communication
HYFAR [37]	Pneumatic Latex		●			1	Chest, Arms	VR/AR
TaSST [28]	Vibration Motor			●		1	Arm	Emotions Expressions
MouseClicker [34]	Vibration Motor			●		1	Hand	Medical Care
Rice Haptic Rocker [13]	Vibration Motor	●				1	Arm	Navigation
SqueezeBands [21]	SMA	●				1	Hand	Remote Communication
Sprout I/O [35]	SMA				●	1	Full body	Wearable
Sobee-SMA [40]	SMA	●				2	Arm	Medical Care
Soft Haptic Glove [41]	SMA	●				1	Hand	VR
ANISMA [42]	SMA	●				1	Full body	Coding

402 Fig. 3. Physical Sensation Corresponding to Different Haptic Actuators
 403
 404

405 Pneumatic silicone materials include both liquid silicone and sheet silicone, offering various parameters for selection
 406 by designers and engineers. Our study used liquid silicone (Shenzhen Guoyuan Technology Co., Ltd.), with hardness
 407 grades T00 and T05. Silicone sheets are relatively stiffer and less elastic than liquid silicone, the thickness of the silicone
 408 sheets ranges from 0.3 mm to 1.0 mm (Shenzhen Xinyin Environmental Rubber Product Co., Ltd.). As the hardness or
 409 thickness increases, a greater volume of air is required to deform the silicone. Users can create a variety of compound
 410 shapes through techniques, such as surface curving and texture changes [36, 50, 51], as illustrated in Fig.4. Liquid
 411 silicone is very soft and highly flexible, but it requires fixed molds for production to form a unified structure.
 412

413 Vibration motors include an X-axis Linear Motor (1016 motor, ACC®), which can be adjusted for frequency, amplitude,
 414 and duration. For the convenience of more designers who aren't familiar with the motor's parameters, we selected a
 415 Manuscript submitted to ACM

417 different rotor motor structure(0408T, Shenzhen Kuanyang Intelligent Technology Co., Ltd.) and Hollow Cup Motor
 418 (0412, Sanyo Japan massage motor; 0612 and 1234, Shenzhen Kuanyang Intelligent Technology Co., Ltd.) that allows for
 419 speed adjustment, as illustrated in Fig. 4. The Hollow Cup Motor adjusts speed and torque by controlling the current
 420 and the stator's magnetic field. The Rotor Motor generates rotation by interacting with the current and the rotor's
 421 magnetic field. The X-axis Linear Motor drives linear motion directly via electromagnetic force. These motors typically
 422 require Pulse Width Modulation (PWM), a frequency converter, or a speed controller for effective operation. To assist
 423 designers who may not be familiar with motor parameters, we provide arbitrary waveform generators for flexibility
 424 and accessibility.

425 Shape Memory Alloy (SMA010, Lanzhou Seemine Keli Advanced Material Co., Ltd) is commonly utilized in two
 426 driving methods widely adopted today: electrical deformation and heating deformation. We selected a two-way shape
 427 memory alloy without pre-formed shapes, as illustrated in Fig. 4, allowing flexible and customizable applications.
 428 Mechanical testing indicates a 4.5% length shrinkage after energization. Considering the heat generated by the SMA,
 429 we have equipped it with a soft silicon tube of appropriate size for the SMA [10] to provide insulation.
 430

Actuator		Deformation Library						Prototype
SMA	Memory Alloy		Parent Phase	Martensite	Parent Phase	Multiple SMA	Martensite	Parent Phase
Motor	X-axis Linear Motor	20Hz		50Hz		100Hz		
	Hollow Cup Motor Rotor Motor	0.03mm		0.05mm		0.8mm		Different Frequency Different Amplitude
Pneumatic Silicone	Liquid Silicone	0.6mm/s		2.5mm/s		8mm/s		Different Speed
	Sheet Silicone	Wavy		Line		Diagonal		Annular

462 Fig. 4. Actuator library showcasing SMA, Motor, and Pneumatic Silicone
 463

464 *Driver and Adhesion Modules.* Our toolkit also provides Driver and Adhesion Modules, which assist designers and
 465 engineers in bonding and driving haptic actuators. All output actuators are designed to be compatible with Arduino,
 466

allowing for seamless integration and control. The vibration motor's data can be modulated using a PWM (Pulse Width Modulation) signal. Utilizing arbitrary waveform generators (UTG4162A Waveform Generator, UNI-T®) enables designers to adjust frequency, amplitude, and duration without requiring programming skills. In addition, the SMA can be stretched using an electric adapter, making it user-friendly for non-technical users. The pneumatic silicone can be inflated with an air pump, available in 12V, 24V, and 36V options. Each pump is equipped with solenoid valves and an air pressure sensor. For liquid silicone, the actuator typically needs to be set for about 45 minutes, while sheet silicone requires bonding with a specialized silicone adhesive (Sil-Poxy, Smooth-On®). Detailed parameters are provided in Appendix A.2.

4.1.2 Fabric Kit In the context of wearable technology, fabrics that come into direct contact with the skin. The haptic properties of the fabric are important for clothing comfort [77] parameters such as pressure and friction forces are important for sensory stimuli and haptic feel [94]. Recognizing the importance of these factors, we offer 48 different fabrics, including polyester, wool, and cotton, to meet a wide range of usage scenarios [11], ensuring comprehensive evaluation and enhanced comfort in wearable applications, as illustrated in Fig.2 b, and the detailed components as shown in Appendix B.1 B.2. Most of these materials are produced through woven and knitted processes, with some undergoing special post-processing techniques such as skeletonization, pleating, and embroidery. Woven fabrics offer high stability and are less prone to deformation, while knitted fabrics provide good elasticity and can be easily shaped [95]. We also provide fabric samples of varying lengths and sizes, encouraging customization using knitting machines and looms to support designs tailored for different body parts, to improve wearability and adaptability. The selection of fabrics considers the diverse haptic sensations associated with different construction methods and materials, such as the roughness of irregular textures or the prickly feel of fine pinpoints [77]. These variations aid users in better categorization and differentiation. We classify Fabric Construction Techniques into three categories based on their characteristics and structural properties:

- Flat Surface Techniques: Focused on smooth and minimally processed fabrics, such as Plain Surfaces (No.1-10) and Smooth Surfaces (No.11-12).
- Structural Fabric Techniques: Enhancing physical structure and functionality, including Ripple Structures (No.13-NO.14), Origami (No.15-16), Elastic Structures (No.17-19), Smocking (No.20-22), Pleating (No.23-28), Mesh (No.29-32), and Cutwork (No.33-40).
- Surface Decoration Techniques: Adding visual and tactile embellishments, such as Embroidery (No.41-42), Pile (No.43-44), and 3D Surface Embellishments (No.45-48).

4.1.3 Design Manual We also provide a design manual to guide users through the prototyping process from a design discipline perspective, drawing on the 5 Phases of Design Thinking [96], the FBS Model [90], and RtD [27], as illustrated in Fig.2 c. This manual aids designers and engineers in constructing the 3 phases: User Goals, User Interaction, and Technical Functionality (material-structure-function). By following the step-by-step guide, we help designers and engineers incorporate unfamiliar materials and address challenges such as inconsistent foundations, terminology variations, and methodological differences [97].

User Goals (User-Scenario-Expectations) The first phase emphasizes understanding the target user groups, observing their needs, and analyzing relevant usage scenarios. This phase focuses on understanding the users' pain points and translating them into clear user goals. The design manual assists in visualizing user journeys and scenarios

[28, 39, 98], gathered from interviews and field observations. This structured approach ensures that the design process remains user-centered from the very beginning.

User Interaction (Input-Process-Output). User interaction refers to how users engage with the toolkit, encompassing their inputs, the processes triggered, and the resulting outputs or feedback. Designers can map how the toolkit dynamically responds to various inputs, such as physiological data [5], behavioral patterns [48], or manual commands [74], ensuring an intuitive and adaptive interaction process [33]. This approach aligns the output with user needs, fostering a seamless and engaging experience.

Technical Functionality (Material-Structure-Function). Defining technical functionality requires integrating haptic actuators with fabric to achieve the desired outcomes. This involves evaluating material interactions and properties (e.g., flexibility, durability) that impact the design. The structure must support the intended function, ensuring haptic actuators deliver precise and meaningful feedback. Adjusting material parameters to meet various haptic feedback requirements is important for a cohesive and satisfying user experience. This phase ties the entire design together by ensuring that the physical and technical aspects [76] align with user expectations and interaction goals.

5 WORKSHOP

To evaluate how participants interact with HaptiFab, we conducted a workshop study with 30 participants in seven interdisciplinary groups. We utilized mixed research methods to answer our research questions by 1) observing the prototype design process by each group, 2) gathering perceptions through focus group interviews, and 3) analyzing user questionnaires.

5.1 Participants and Procedure

We posted our recruitment on social platforms for ten days, receiving 182 applications. Participants were selected based on: (1) availability to attend the entire onsite workshop, (2) a portfolio demonstrating basic knowledge of haptics or fabrics, and (3) research focus on a relevant field (e.g., fashion design, interaction design, or engineering) without dual expertise in design and engineering, but with proven ability to produce comprehensive interaction design work.

We recruited 30 participants (7 males, 23 females), aged 19 to 37 ($M = 24.07$, $SD = 3.87$), as shown in Table 1. Most were undergraduate and graduate students in China, with some international students. All participants volunteered their time and received certificates after the final presentation. During the 5-day workshop, participants formed interdisciplinary groups to use HaptiFab for designing and developing interactive prototypes incorporating haptic fabrics. We selected 11 workshop assistants from our lab, all with relevant research experience, and provided technical support. We also provided pre-training to ensure workshop assistants were familiar with HaptiFab's techniques and research objectives before the workshop. During the workshop, these assistants joined various groups to offer technical support.

5.1.1 Opening Ceremony. The lab director introduced the lab's research on wearable technology to welcome participants. The workshop organizer (first author) then detailed this workshop's specific goals and research content, providing examples of possible usage scenarios to guide participants' thinking. We also held ice-breaking activities to facilitate group formation, resulting in seven groups of 4-5 people, each supported by 1-2 moderators. The organizer then introduced the workshop technologies, including pneumatic silicone prototyping, vibration motors, and SMA applications.

Table 1. Participants' Demographic information

Group	Participants	Gender	Age	Education	Field of Study
G1	P1	F	26	Postgraduate	Human Factors Engineering
	P2	F	21	Undergraduate	Engineering Design
	P3	F	20	Undergraduate	Landscape Architecture
	P4	F	24	Postgraduate	Industrial Engineering
G2	P5	F	22	Undergraduate	Entertainment Technology
	P6	F	26	Postgraduate	AI Analysis of Electrocardiograms
	P7	M	21	Undergraduate	Systems Engineering
	P8	F	21	Undergraduate	Product Design
G3	P9	F	25	Postgraduate	Interaction Design
	P10	M	23	Postgraduate	Industrial Engineering
	P11	F	22	Undergraduate	Fashion Accessories Design
	P12	F	37	Postgraduate	Communications Design
G4	P13	M	26	Postgraduate	Intelligent Manufacturing
	P14	M	24	Postgraduate	Textile Technology
	P15	F	29	Postgraduate	Fashion Design
	P16	F	22	Undergraduate	Interaction Design
G5	P17	F	22	Postgraduate	Industrial Design
	P18	M	24	Postgraduate	Electronic Information
	P19	F	29	Postgraduate	Digital Intelligence and Fashion
	P20	F	31	Postgraduate	Fashion Design
G6	P21	M	23	Postgraduate	Industrial Design
	P22	F	25	Postgraduate	Industrial Design
	P23	F	20	Undergraduate	Fashion Design and Engineering
	P24	F	20	Undergraduate	Interaction Design
	P25	F	22	Undergraduate	Interaction Design
G7	P26	M	23	Postgraduate	Art and Technology
	P27	F	28	Postgraduate	Design and Technology
	P28	F	21	Undergraduate	Apparel Engineering
	P29	F	26	Postgraduate	Textile Design
	P30	F	19	Undergraduate	Digital Media Arts

5.1.2 *Prototype Making*: After the opening ceremony, each group began their five-day design work, with workshop assistants regularly checking progress and providing technical guidance. On the third day, we held an offline mid-term exchange meeting where each group presented their design prototypes, focusing on application scenarios and technologies used. The lab director and research team conducted question-answer sessions with each group. In the following three days, groups refined their designs based on feedback, conducted tests, and optimized prototype performance. During the workshop process, we also observed participants' behavior, which focused mainly on the initial practical strategies of the participants, the mistakes they made, and the solutions they used during interactions with Haptifab. Two researchers took photos/screenshots, and wrote field notes, the entire course process for subsequent analysis.

Table 2. Prototypes Description

		Group Thematic	Haptic Actuator	Description
625 626 627 628 629 630 631 632	Functional Wearables	G1 HarmonicWeave (Fig.5 a)	Sheet and Liquid Silicone, X-axis Linear Motor, SMA	The device uses pneumatic silicone and vibrating motors to adjust vocal behavior. It incorporates a memory alloy to affect the opening and closing of the chest flower to assist in vocalization.
		G5 Smart Navigation Wristband (Fig.5 e)	Sheet Silicone	The pneumatic silicone smart wristband provides haptic navigation for both general users and those with sensory impairments.
633 634 635 636 637 638 639	Self-healing Wearables	G2 ViBreathe (Fig.5 b)	Vibration Motors	This design uses rhythmic haptic vibrations on the arms to guide users through synchronized breathing, enhancing meditation and relaxation.
		G4 HUG BANK – Portable Hug (Fig.5 d)	Sheet Silicone	This project turns clothing into an interactive medium, simulating hugs with an internal air pump system embedded in the fabric. Sensors trigger and regulate hug intensity in real time, offering therapeutic comfort.
640 641 642 643		G6 Marine Haptic Intelligent System (Fig.5 f)	Vibration motors, Sheet and Liquid Silicone	The design simulates the feeling of waves and sand through a combination of modular fabrics and pneumatic silicone, allowing city dwellers to feel the joy of a beach vacation even in their busy lives.
		G7 ZenTouch (Fig.5 g)	Vibration motors	The design uses vibrating motors to provide a gentle haptic sensation to provide emotional and physical interaction as well as spiritual solace for a new generation of religious believers.
644 645 646 647 648 649 650 651 652	Educational Wearables	G3 Mare Tactus (Fig.5 c)	Sheet Silicone	The design combines Sheet Silicone and fabric with multi-dimensional spatial interactions to create haptic resonance with both the positive and negative aspects of the ocean, fostering a deeper connection with the marine environment in public exhibitions.

653
654
655
656
657
658
659
660
661
662 5.1.3 *Final Presentation and Interviews.* On the fifth day of the workshop, we held a three-hour closing ceremony to facilitate mutual learning among participants. As shown in Table 2, each group presented their projects, detailing design rationale, technical specifics, and usage methodologies. We finally asked each participant to fill out the User Experience Questionnaire (UEQ) [99] utilizing a 7-point Likert scale and conduct focus group interviews with each group. Each focus group interview in Chinese lasted about 60 minutes and was audio-recorded with participants' content (See Appendix D.1).

663 5.2 Data Collection and Data Analysis

664 We utilized mixed research methods to analyze data within this study. We first conducted a quantitative analysis
665 of the UEQ results to assess participants' actual usability experiences of HaptiFab, focusing on its pragmatic and
666 hedonic qualities of haptic technologies and fabric materials. We then use the qualitative method for focus group
667

interviews and field notes through thematic analysis [100]. Two researchers initially reviewed the field data (prototypes, images, and presentation slides) and interview transcriptions for accuracy. After data cleaning, two researchers started independently coding and developed an initial set of codes to analyze the data. For the field notes analysis, we focused on practice-based behaviors and used words or phrases to describe them as code. This process involved several rounds of discussion to reach agreements and grouped similar codes into clusters. They then identified emerging common themes with internal connections and finally generated themes related to toolkit experiences using a collaborative affinity mapping approach [101]. Any disagreements during coding were resolved through joint discussions and consultation with an expert (the third author) until a consensus was reached.

6 FINDINGS

Our findings highlight that HaptiFab (1) supports a variety of design purposes effectively, (2) is both efficient and easy to use, and (3) is flexible enough to accommodate different design spaces. We also provide detailed insights into participants' perceptions of usage, material preferences, and interaction modalities when using HaptiFab.

6.1 Varied Purposes of Participants' Prototypes with HaptiFab

We generally found seven interdisciplinary groups used HaptiFab to create diverse and multifunctional wearable designs, each with unique themes. Based on the scenarios they designed, we categorized their prototypes into three distinct groups (see Table 2): Functional Wearables (G1, G5), Self-Healing Applications (G2, G4, G6, G7), and Educational Exhibits (G3).



Fig. 5. The prototypes made in the workshop. a) Harmonic Weave, b) ViBreathe, c) Mare Tactus, d) HUG BANK-Portable Hug, e) Smart Navigation Wristband, f) Marine Haptic Intelligent System, g) ZenTouch.

Two groups (G1 and G5) developed their prototypes with a function-oriented approach to improve the user experience by providing specific features. For example, G1 developed HarmonicWeave (Fig. 5a), a tool to monitor breathing during

Manuscript submitted to ACM

singing to enhance the user's vocal performance. They integrated knitted fabric with a sheet and liquid silicone deformation, enabling precise control over the chest and diaphragm. Additionally, they attached an X-axis linear motor with the larynx and dynamically bloomed floral pattern style SMAs, with fabric wrapped, to provide real-time vibrations corresponding to vocal frequencies. Another group, G5, created a Smart Navigation Wristband designed for individuals with sensory limitations, utilizing compressed feedback for the navigation process (Fig. 5 e). Their wristband indicates left or right turns through inflation and deflation of sheet silicone on the corresponding side, with the frequency increasing as the turn approaches to enhance the alert effect. They then customized a knitted wristband using a deformation-capable knitting machine to accommodate and integrate the pneumatic seamlessly within both silicone designs.

We were surprised to find that more than half of the groups focused on users' emotional status. They use Haptifab to design self-healing applications (G2, G4, G6, G7). For instance, G2 features a sleeve designed to assist users in synchronized breathing training (Fig. 5 b). Their design utilizes five 0408T rotor motors and stretchable and translucent wave yarn to create a coordinated vibration ensemble, stitched onto a stable ice sleeve for enhanced comfort and durability. G4 made the HUG BANK, a portable device simulating hug interactions to comfort users facing loneliness and anxiety (Fig. 5 d). This design also features a skin-friendly cotton inner layer for comfort and a rigid textured woven outer layer for style and controlled deformation. There is a sheet of silicone (0.5mm outer, 0.3mm inner) that uses COMSOL simulations to map pressure to air pump inputs, creating a realistic hugging experience. G6 also focuses on enhancing user experiences. They developed the Marine Haptic Neckband to provide urban dwellers with brief escapes from busy lives by simulating the sensations of waves and sand, evoking a fragmented vacation experience (Fig. 5 f). They used circular pneumatic silicone to simulate the rippling motion of waves, with four modular fabric components to simulate the tactile sensations of sand, home, and other textures. G7's design is more special. Their Zen Touch project aims to create a haptic metaphysical feedback system for Chinese Gen-Z inspired by traditional religious customs (Fig. 5 g). Their system integrates spiritual and calming practices from Chinese culture, particularly the Buddhist and Taoist beiyun (a decorative element of prayer beads symbolizing respect when draped on the back). Users can initiate blessings with hands clasped in prayer, or the system's heart rate sensor triggers a vibration on the back during moments of anxiety. The design features No.43 3D surface embellishments for a modern touch, while No.15, No.26, and No.29 create a rough, rustic feel symbolizing the strength of calloused hands. No.36's regular mesh reflects traditional bracelet elements, and smooth No.2 and No.7 materials are used on the back for comfort. These fabrics are sewn together to represent the five symbolic motifs of Fu, Lu, Shou, Xi, and Cai ¹.

Moreover, we also found that Haptifab supports users in designing wearables for educational exhibits. G3 developed a neck-worn device inspired by an aquarium experience (Fig. 5 c). They aim to address the limited interactivity in traditional aquarium exhibits, they utilized cutwork (mesh) fabric with a rough haptic sensation, combined with airbags featuring circular, linear air channels (0.5mm outer, 0.3mm inner) to create a sense of pressure. This design evokes negative haptic experiences, metaphorically representing the environmental stress and 'suffocation' caused by marine pollution, to heighten awareness of the ocean pollution crisis.

¹ In Chinese traditional culture, Fu (福) represents blessings and good fortune, Lu (禄) symbolizes power and success, Shou (寿) signifies longevity and health, Xi (禧) means joy and happiness, and Cai (财) has the connotation of wealth and fortune[102]. Together, these concepts reflect traditional values of a prosperous and fulfilling life in Chinese tradition.

781 6.2 Examining Participants' Exploration of HaptiFab

782 We observed that participants made diverse, practical decisions when using HaptiFab and selecting various components.
 783 In this section, we will discuss how users perceive these sensations and adapt to different usage contexts with three
 784 main considerations.
 785

786 6.2.1 Goals Consideration
 787 Guided by the design manual, participants usually first identified their goals, including
 788 target user and usage scenario. They then conducted detailed research on the expectations of these groups before
 789 integrating the haptic actuators and fabrics. For example, P1 mentioned, "...For some beginners or people with limited
 790 knowledge of vocal techniques, it is difficult to control... the vibration of the larynx and the breathing of the diaphragm.
 791 Overall...we selected the main parts of the human body that are most likely to affect singing..."
 792

793 After defining their user and scenario in the **user goals**, based on the design manual, participants developed specific
 794 expectations for their prototype, including both functional and experiential sensation aspects. For instance, G1 outlined
 795 functional expectations, with P4 noting: "...Therefore, we expect to...create haptic synchronized with the song, allowing
 796 users to feel the vibrations in their larynx to determine whether it matches the haptic component. If they do not match,
 797 it is obvious that the user's vocalization is incorrect." The participants also emphasized expectations of experiential
 798 sensation for their prototypes. For example, G7 aimed to create a sense of comfort or reassurance. For example, P26
 799 stated: "...In traditional blessings, the gods may not respond to you, but this smart product can give you a response..."
 800 such as G4, envisioned the prototype offering a more expansive feedback experience. P15, one of the group members
 801 mentioned that: "...When we think of a hug, we tend to think of the strength of the hug... or a feeling of being wrapped
 802 up, which is more expansive, and it can provide a strong sense of feedback." Participants identified target user groups
 803 and usage scenarios to conduct preliminary design research, aligning their designs with both functional needs and
 804 experiential sensations, which facilitated the creation of effective prototypes later in the process.
 805
 806

807 6.2.2 Interaction Consideration
 808 Participants in the focus group considered several aspects of user interaction consider-
 809 ations with wearable prototypes, including technical integration, body adaptability, sensory feedback, and cultural
 810 factors.
 811

812 Integration Techniques and Process
 813 When designing interactive prototypes, participants often incorporated electronic
 814 modules to trigger haptic interactions. The Arduino kits provided by HaptiFab played a crucial role in this process, and
 815 combined with the design manual, they helped the interdisciplinary groups refine their prototypes while exploring
 816 additional possibilities. For example, G1 used real-time IMU monitoring on the chest area to control the SMA within
 817 petal-like structures (Fig. 6 a). G7 employed a heart rate sensor to trigger vibration motors for soothing effects. In G4's
 818 design, the aim was to replicate the sensation of a hug. Therefore, P14 gathered user input on palm pressure and used
 819 finite element analysis to extract the pressure distribution of a real hug, which was then applied to their prototype for
 820 greater haptic realism (Fig. 6 d).
 821

822 Wearability and Adaptability in Different Body Parts
 823 As a full-body wearable toolkit, HaptiFab demonstrated significant wearability and adaptability across various body parts. Participants considered factors like user interaction needs,
 824 sensitivity thresholds, and body posture when selecting locations for haptic sensations (P9, P18, P22). For instance,
 825 G6's prototype focused on the sensation of submersion in seawater. P22 explained that the neck's high sensitivity was
 826 critical to their design. Precise pneumatic sensations and fabric textures mimicked seawater moving against the neck,
 827 enhancing immersion. G5's design also took sensitivity thresholds into account, focusing on the wrist, which has a
 828
 829

lower threshold and is more responsive to directional cues. P17 mentioned, "...The sensitivity of the wrist is not that high... our prototype initially featured a single ring-shaped airbag that would indicate directionality from left to right, but we found that the wrist's sensitivity wasn't clear enough¹¹." P17 also noted that factors such as age and gender needed to be considered in the design process. In addition, the design incorporates inspiration from cultural contexts. For example, G3's design, inspired by traditional Chinese medicine, aimed to evoke feelings of suffocation and entrapment, with a particular focus on the neck due to its sensitivity and symbolic association with breath control. Pneumatic silicone and fabric were used to simulate the sensation of being trapped in a fishing net, with the 'Fengchi'¹² acupoint was precisely stimulated. By inflating the silicone material around the 'Fengchi', G3's design created a tight feeling, intensifying the discomfort (P10).

Material Sensory Characteristics Participants expressed high satisfaction with the sensory diversity offered by both the haptic and fabric components of HaptiFab (P7, P9, P28, P30). They noted that the prototypes met their initial expectations for sensory feedback (P7, P28). For instance, P17 described the design of a navigation wristband for cyclists: "...The airbag provides a gentler reminder, while vibration might be more direct...Our prototype...is not designed for emergency alerts, but rather for guiding navigation, such as a 100-meter advance notice before [Figure].. This feedback highlighted the effectiveness of using different materials and haptic technologies to cater to the specific needs of users and interaction contexts. In conclusion, we found that integrating techniques into the design process shaped the prototype's outcome, meeting diverse user needs with immersive haptic feedback.


6.2.3 Technical Functionality Consideration Participants emphasized the importance of integrating haptic actuators and fabric to ensure the structure supports the intended function and provides accurate feedback.

Haptic Actuator Selection When using HaptiFab to create wearable prototypes, our participants carefully selected haptic actuators based on several key factors. Pneumatic silicone was the most frequently used material, valued for its large-area force sensations (P15) and soft (P2), skin-adhering surface (P17, P18). P2 highlighted its suitability for close body contact, with its adaptable volume and shape-enhancing design flexibility and applications [51]. However, factors such as air pathway design, pressure application, and material thickness affect performance (P4, P17). For instance, P3 observed that a 0.3 mm sheet of silicone was prone to bursting, while P4 recommended liquid silicone glue for stronger bonding. These challenges require iterative prototyping to optimize designs. Shape Memory Alloy (SMA) was praised by participants for its stretchable properties and ability to achieve multi-angle deformation (P2). While its range of deformation changes is less pronounced than that of other devices. P3 noted SMA's strong embedding properties, which allow it to be fully wrapped, making it ideal for wearable devices in space-limited designs [10]. Participants praised the vibration motors for their precision and timely sensation, providing direct haptic sensations (P26). Their small size and strong vibrations make them ideal for wearable designs requiring discretion and responsiveness. However, as P17 observed "...The small size of motors requires proximity to the skin for effective sensation, limiting their use in designs with larger direct contact surfaces." To address this limitation, the impact of the motor can be enhanced through vibration synthesis. Several motors can be combined to synthesize a haptic sensation (P18). This was demonstrated in G2's design, where an array of motors expanded the range of skin deformation, as shown in Fig. 6 b.

Aesthetics and Integration with Structure Participants integrated aesthetics and symbolic meanings to align with User Goals. Some symbolic meanings come from fabric, G3 used mesh fabrics and airbags to symbolize ocean pollution,

¹¹FengChi (风池) refers to an acupoint located in the hollow at the base of the skull just below the hairline, is significant in Chinese medicine culture. Stimulating it can relieve headaches and relax neck muscles, often accompanied by a sensation of soreness or mild pain.

885 creating a rough, trapped sensation around the neck (Fig. 5 c). Similarly, G7 used goldfish-shaped fabric with symbolic
 886 colors representing fortune and longevity, combining cultural metaphors with visual appeal. Some of the symbolic
 887 meanings come from haptic actuators, G1 used SMA and mesh to create a flower shape, symbolizing chest cavity
 888 movement during breathing and enriching the sensory experience. G4 uses pneumatic silicone shaped embracing hands
 889 to symbolize a hug. Another key aesthetic consideration was integrating haptic actuators seamlessly within the fabric.
 890 Most participants preferred the actuators to be fully wrapped (G1, G2, G4, G5, G7), and G1 concealed the SMA within
 891 petal-like structures that blossomed dynamically. Some preferred partial wrapping (G3, G6). G6 used modular designs
 892 with partial wrapping, allowing users to swap and customize haptic sensations, such as flocked fabric evoking a rough
 893 beach texture or looped velour providing a plush feel (P23).
 894



919 Fig. 6. These group figures provide a detailed explanation of the selection of materials, haptic actuators, and haptic sensations from
 920 each group's prototype. From a) to g), each single figure corresponds to Group 1 to Group 7, offering a visualized explanation.
 921

924 6.3 Effective Wearable Design Process Powered by HaptiFab

925 HaptiFab is adaptable, accessible, and user-friendly for interdisciplinary groups, as demonstrated through a mixed-
 926 method analysis.

927 6.3.1 The UEQ Result of HaptiFab At this stage, the UEQ evaluates the user experience of HaptiFab. We used the official
 928 UEQ Data Analysis Tool Version 12 [103] to convert the 1-7 scale values to a range of -3 to +3, where +3 indicates the
 929 most positive and -3 the most negative value. We assessed the reliability of the data collected from the 26 items in UEQ,
 930 obtaining a Cronbach's α of 0.949, which indicates high internal consistency. We also compared the UEQ results of
 931 HaptiFab with benchmark data from 468 studies concerning different products, and the findings are presented in the
 932 bar chart shown in Fig. 7.

933 Manuscript submitted to ACM

For the six dimensions, the questionnaire in HaptiFab scored highly in ‘Attractiveness’ ($M = 1.872$, $SD = 0.824$) and ‘Stimulation’ ($M = 1.792$, $SD = 0.974$) achieving an Excellent comparison to the benchmark and significantly supporting prototype creation. Meanwhile, ‘Perspicuity’ ($M = 1.367$, $SD = 1.096$), ‘Efficiency’ ($M = 1.45$, $SD = 0.95$), and ‘Dependability’ ($M = 1.433$, $SD = 0.858$) performed Above Average comparisons to the benchmark, helping interdisciplinary groups lower learning barriers and prototype efficiently. Since HaptiFab builds on recognized haptic sensations, the results for Novelty ($M = 1.475$, $SD = 1.075$) demonstrated a Good performance compared to the benchmark. These findings are consistent with interview results, discussed later.




Fig. 7. Comparison of HaptiFab Results with Benchmark Data of UEQ

6.3.2 Lowering Barriers in Interdisciplinary Context. During our focus group interview, participants praised HaptiFab for empowering them to create innovative HCI prototypes (P18) and facilitating collaboration in interdisciplinary contexts (P1, P15). For example, P27 praised the prototypes provided, stating: "...It is easy to use Arduino to adjust the rotor motor's accuracy and comfort and P18 mentioned that during the developing process, "...I think it's okay, it's just that the ones (HaptiFab) that are prepared are also quite easy to learn, it's just that they're not very complicated either..."

Also, our participants noted that the design manual was highlighted as a valuable resource to overcome difficulties, which helped them refine design ideas and select suitable haptic actuators and fabrics (P15, P17, P23). The UEQ result also proves ‘not understandable/understandable’ ($M = 1.733$, $SD = 1.258$), ‘difficult to learn/easy to learn’ ($M = 1.9$, $SD = 1.185$), ‘unfriendly/friendly’ ($M = 2.067$, $SD = 0.98$). These results highlight the manual’s role in aligning group members’ perspectives, fostering a shared vision between designers and engineers, and enhancing usability and collaboration. However, some participants indeed shared their vision for better HaptiFab’s iteration, such as providing more detailed explanations about fabrics and separating programming and non-programming tools into two distinct sets (P4). For instance, P9 stated that: "...I hope to see more technical information about fabric in the design manual...For example, can I weave different fabrics together to create a new form?" These insights offer actionable directions as future work to further enhance HaptiFab’s adaptability and accessibility.

989 6.4 Potential Design Spaces and Future Directions with HaptiFab

990 During the workshop, participants brainstormed various meaningful ideas, we summarized insights to identify three
 991 key design areas for HaptiFab: Emotional Expression Design, Augmented Design, and Therapeutic and Assistive Design.
 992

993 **994 6.4.1 Emotional Expression Design** Participants highlighted the potential for combining haptic actuators with fabric to
 995 create more emotionally resonant experiences (P11, P13, P16). P13 observed: "...*Clothing is like a second skin for humans,*
 996 *and the future trend of clothing will undoubtedly be greater intelligence. If people can interact with their second skin daily,*
 997 *it would indeed be a significant step toward the next stage of smart innovation...*" This aligns with the findings of Kim et
 998 al. [10], and G4 further noted that pneumatic silicone could effectively convey the intimacy of a remote hug, offering
 999 a more tactile, emotional connection. P16 also remarked: "...*I think this kind of haptic interaction can establish a good*
 1000 *connection with emotional expression, which should also inspire many explorations in emotional design...*" Building on this,
 1001 P6, integrating her professional background, proposed using haptic technology to simulate the heartbeat of deceased
 1002 loved ones or pets, addressing the limitations of current electrocardiograms (ECGs), which only provide visual feedback.
 1003 P14 underscored this potential by noting: "*Static clothing conveys little to no information, but with certain technologies,*
 1004 *such as vibrations, it can transmit some amount of information...or sensations.*" P19 also pointed out the power of haptic
 1005 adding on Static textile materials such as clothing to give the user a sense of security against the body, "...*So I think that*
 1006 *fabric materials themselves have certain advantages, but the problem is that because they are static, they stay there quietly,*
 1007 *and then when they have a more active brake. The braking mechanism may make it more vital, and it will be like many*
 1008 *things breathing...*" These insights highlight haptic technology's potential in advancing emotional expression design.
 1009

1010 **1011 6.4.2 Augmented Design** We also found that Haptics, as an actuator, can be well integrated with fabrics to enable
 1012 augmented design. P15 mentioned that: " *Generally, fabrics are static and do not make you feel any interaction or actively*
 1013 *provide force. However, with haptics...you can perceive it as if it were a living entity...giving you feedback that feels as though*
 1014 *it has emotions or a sense of life.*" Additionally, users have envisioned various applications of HaptiFab for augmented
 1015 design. P18 and P23 believe that wearable devices based on VR games can augment human sensations and enhance
 1016 immersion. In the future, wearable devices could render haptic data to synchronize with game experiences, as noted by
 1017 Han et al. (2023) [104]. Beyond gaming, P9 suggests that combining haptic technology with fabric is well-suited for
 1018 inclusive design to augment human ability:
 1019

1020 *1021 "...We want to create this museum because many current museum displays, like touchscreens, are flat and*
 1022 *1023 difficult for visually impaired visitors to understand... We hope the design can be more inclusive...can help*
 1024 *them interact with the surroundings in museums, galleries, cinemas, and other public spaces, making these*
 1025 *environments more accessible..."*

1026 Similarly, P12 proposed using pneumatic silicone in clothing to develop safety-focused augmented designs, such as
 1027 fall-prevention solutions for the elderly [105] or protective gear for skiers during training. These examples demonstrate
 1028 how integrating haptic technology with fabric can augment practical solutions and benefit society.
 1029

1030 **1031 6.4.3 Therapeutic and Assistive Design** Beyond wearables, participants envisioned using these HaptiFabs in therapeutic
 1032 and assistive contexts. For example, P14 discussed using SMA in medical devices like guidewires and stents. Additionally,
 1033 pneumatic silicone could be applied in corrective seating materials, while vibration motors could aid in posture correction
 1034 (P25) or guide breathing exercises (P7). By combining pneumatic silicone with rigid materials, P14 proposed haptic
 1035

1041 robots for precise grip force measurement and weight-bearing. P17 further suggested that SMA could serve as actuators
 1042 for soft robotics, expanding their functionality in both medical and industrial applications.
 1043

1044 7 DISCUSSION

1045 7.1 Enhancing Adaptability and Creative Comparing with Other Toolkits

1048 In this study, we presented HaptiFab, a toolkit integrating haptic actuators and fabric, to explore how these two valuable
 1049 components could benefit interdisciplinary group design wearable technology. Workshop insights show that HaptiFab
 1050 stands out from previous wearable tech toolkits because of its integrated haptic actuators and driven methods that
 1051 have been widely discussed in recent years within the field of HCI research [10, 49, 51]. HaptiFab provides considerable
 1052 adaptability, enabling designers and engineers to tailor prototypes to diverse scenarios, user expectations, and data
 1053 inputs. Compared to the fixed hardware modules of TactorBots [106], HaptiFab supports a broader range of wearable
 1054 forms and areas, offering diverse haptic metaphors and expectations. It also provides more actuator options than
 1055 compressables [49], with a DIY-friendly design enabling iterative customization of haptic outputs, sensory feedback,
 1056 and user experiences. Unlike SleevIO [107], where fabric serves only as a ‘substrate’, the function of fabric in our
 1057 toolkit is not only to provide a soft and comfortable wearable cover layer but also to enable users to adapt to diverse
 1058 scenarios and explore broader design possibilities. To support interdisciplinary design, our manual enhances the O&O
 1059 framework (Empathize-Define-Ideate-Prototype-Test) with intuitive, detailed solutions to methodological differences
 1060 [97], helping groups align their vision during prototype development. We provide clear guidance for merging technical
 1061 and design perspectives through a design manual combining design thinking and HCI principles [27]. This approach
 1062 enables participants to use HaptiFab for hands-on DIY creation, applying the RtD method to uncover new insights into
 1063 integrating haptic actuators and fabrics, contributing to advancements in wearable technology.
 1064

1065 7.2 Haptic Actuators and Fabric Integration in Wearable Toolkits

1066 Our workshop findings showed that HaptiFab expanded the designer’s diverse design space by integrating varied and
 1067 functional haptic devices into fabric-based wearable designs. Participants noted that inherently static fabrics could
 1068 provide richer emotional experiences when combined with haptic sensations, enhancing immersion. This underscores
 1069 that haptic sensations and fabric integration play a significant role because haptic sensations could leverage the fabric’s
 1070 core advantages, such as flexibility and tactile comfort, to new levels in wearable design.

1071 To implement this, the interaction and sensation capabilities of haptic actuators during prototyping could be prioritized,
 1072 with fabric serving as a carrier to ensure wearability. During hands-on experiences with HaptiFab, participants
 1073 found that HaptiFab reduced the technical and design complexities of integrating haptic actuators with fabric, which in
 1074 turn helped participants explore and expand their design space more effectively. For example, fashion designers without
 1075 engineering backgrounds were able to create desired interactive experiences across disciplines easily. We believed this
 1076 integration amplified designers’ creativity, enabling new design possibilities by blending rapid learning with existing
 1077 skill sets. These findings highlight HaptiFab’s potential to foster innovative designs while supporting a more inclusive
 1078 interdisciplinary design process.

1079 7.3 Limitations and Future Design Opportunities

1080 **Haptic Sensation Integration for Wearable Design.** Through the successful completion of prototypes by all seven
 1081 interdisciplinary groups, this workshop demonstrated the effectiveness of collaborative efforts in accelerating processes

1093 and addressing design complexity [88]. By exploring participants' considerations, challenges, and design spaces in
1094 integrating different haptic sensations and fabrics for wearable design, this work highlights the critical role of aligning
1095 haptic sensation choices with specific user goals. The findings reveal that different user needs—ranging from comfort
1096 and functionality to emotional engagement—demand tailored haptic solutions, making the exploration of goal-driven
1097 haptic integration a key avenue for future research. These insights offer valuable guidance for HCI researchers and
1098 designers in the fields of wearable technology to address diverse and evolving user goals.
1099

1100 **Software Simulation Design Tool for Enhancing Interdisciplinary Design.** Our findings show that all seven
1101 groups encountered minimal barriers when selecting fabrics, likely due to their familiarity with daily use. However,
1102 designers selecting haptic actuators faced challenges, requiring multiple iterations to identify suitable options. The
1103 inherent physical properties of certain actuators (P3, P4), such as the heat generation of SMA, are influenced by
1104 participants' preferences. Moreover, due to the 5-day workshop's time constraints and cognitive load, there were
1105 limitations in fully exploring the haptic sensations and fabric properties [108]. To address these challenges, developing
1106 a software design tool, to support interdisciplinary collaboration would be beneficial [10]. Such a tool could digitize the
1107 design manual, simulating the integration of haptic actuator parameters with fabric deformation and enhancing the
1108 design process. It also can integrate research on haptic effects and user perception, such as mapping user expectations
1109 to haptic parameters [109] and generating customized layouts [110], with software that recommends haptic parameters
1110 based on design scenarios.
1111

1112 **More Portability and Adaptability Future.** Additionally, while each group successfully achieved its desired
1113 outcomes and functionalities, we observed that some prototypes, such as those from Group G2, were larger than
1114 expected. P7 mentioned that this limitation was due to the insufficient PWM output channels of HaptiFab's electronic
1115 modules needed to drive the vibration motor matrix. To address these kinds of issues, future work should focus on
1116 customizing driver modules that improve the portability and offer greater adaptability of HaptiFab to accommodate
1117 complex vibration control requirements [22, 46]. Furthermore, as a wearable device, it is crucial to consider the
1118 modularity and detachability of haptic actuators, as well as durability, dirt resistance, and washability (P18). These
1119 improvements will help future toolkits meet the practical demands of long-term and versatile applications.
1120

1121 **Expanding Beyond Wearable.** Furthermore, our participants also envisioned broader applications beyond wearables,
1122 such as tangible toys (P6), therapeutic devices (P14, P25, P7), and sleep aids (P8). Our preliminary findings suggest
1123 that integrating haptic actuators and fabric within a single toolkit can significantly benefit wearable technology
1124 design. However, a gap remains in systematically understanding how specific haptic sensations contribute to the design
1125 workflow. Future toolkits should incorporate multi-sensory features to help users effectively visualize haptic simulations,
1126 as suggested in previous studies [30, 110].
1127

1128 8 CONCLUSION

1129 In this paper, we present HaptiFab, a wearable toolkit designed to support the integration of haptic actuators with fabric,
1130 assisting designers and engineers in balancing technical and design aspects during prototype creation. Through a five-day
1131 workshop study, our toolkit demonstrated its adaptability in supporting diverse design purposes, ranging from functional
1132 wearables to emotional and educational applications. We reported participants' perceptions and considerations regarding
1133 using HaptiFab for wearable technology in detail and outlined directions for future design space. Our findings also
1134 indicated that HaptiFab lowers barriers to entry for designers and engineers, fostering collaboration for Interdisciplinary
1135 Design. We finally discussed the advantages of fabric and haptic integration to empower interdisciplinary groups to
1136 create innovative wearable solutions. In conclusion, we explored the potential of integrating different sensations with
1137 Manuscript submitted to ACM
1138

fabric in wearable toolkits, enabling the creation of practical, inclusive, and emotionally resonant designs tailored to varied user scenarios.

References

- [1] Mohamad A Eid and Hussein Al Osman. Affective haptics: Current research and future directions. *IEEE Access* 26–40, 2015.
- [2] Shantonu Biswas and Yon Visell. Haptic perception, mechanics, and material technologies for virtual reality. *Advanced Functional Materials* 31(39):2008186, 2021.
- [3] Matteo Bianchi. A fabric-based approach for wearable haptics. *Electronics* 5(3):44, 2016.
- [4] Andrew A Stanley and Katherine J Kuchenbecker. Design of body-grounded tactile actuators for playback of human physical contact. In *2011 IEEE World Haptics Conference*, pages 563–568. IEEE, 2011.
- [5] Max Pfeiffer, Tim Duente, and Michael Rohs. Let your body move: a prototyping toolkit for wearable force feedback with electrical muscle stimulation. In *Proceedings of the 18th International Conference on Human-Computer Interaction with Mobile Devices and Services*, page 418–427, New York, NY, USA, 2016. Association for Computing Machinery.
- [6] Qian Qiu, Miaomiao Zhu, Zhaoling Li, Kaili Qiu, Xiaoyan Liu, Jianyong Yu, and Bin Ding. Highly flexible, breathable, tailorable and washable power generation fabrics for wearable electronics. *Nano Energy* 68:750–758, 2019.
- [7] Jianfeng Wen, Bingang Xu, Yuanyuan Gao, Meiqi Li, and Hong Fu. Wearable technologies enable high-performance textile supercapacitors with flexible, breathable and wearable characteristics for future energy storage. *Energy Storage Materials* 9:94–122, 2021.
- [8] Melkie Getnet Tadesse, Carmen Loghin, Ionuț Dulgheriu, and Emil Loghin. Comfort evaluation of wearable functional textiles. *Materials* 14(21):6466, 2021.
- [9] Ruiqing Li, Yeyang Wang, Yujie Chen, Jiaxuan Zhao, Yawei Wang, J. An, Yanan Lu, Yuehua Chen, Wenyong Lai, Xinwen Zhang, and Wei Huang. Efficient flexible fabric-based top-emitting polymer light-emitting devices for wearable electronics. *Small* pages e2305327–e2305327, 2023.
- [10] Jin Hee (Heather) Kim, Kumpeng Huang, Simone White, Melissa Comroy, and Cindy Hsin-Liu Kao. Knitdermis: Fabricating tactile on-body interfaces through machine knitting. In *Proceedings of the 2021 ACM Designing Interactive Systems Conference*, page 1183–1200, New York, NY, USA, 2021. Association for Computing Machinery.
- [11] Jing Xue, Bruna Beatriz Petreca, Christopher Dawes, and Marianna Obrist. Fabtouch: A tool to enable communication and design of tactile and affective fabric experiences. In *Proceedings of the 2023 CHI Conference on Human Factors in Computing Systems*, 2023.
- [12] Kyle T. Yoshida, Cara M. Nunez, Sophia R. Williams, Allison M. Okamura, and Ming Luo. 3-dof wearable, pneumatic haptic device to deliver normal, shear, vibration, and torsion feedback. In *2019 IEEE World Haptics Conference (WHDs)*, 97–102, 2019.
- [13] Janelle P Clark, Sung Y Kim, and Marcia K O’Malley. The rice haptic rocker: Comparing longitudinal and lateral upper-limb skin stretch perception. In *Haptics: Science, Technology, and Applications: 11th International Conference, EuroHaptics 2018, Pisa, Italy, June 13–16, 2018, Proceedings, Part II* 11 pages 125–134. Springer, 2018.
- [14] Nur Al-huda Hamdan, Adrian Wagner, Simon Voelker, Jürgen Steinle, and Jan Borchers. Springlets: Expressive, flexible and silent on-skin tactile interfaces. In *Proceedings of the 2019 CHI Conference on Human Factors in Computing Systems*, page 1–14, New York, NY, USA, 2019. Association for Computing Machinery.
- [15] B Holschuh and D Newman. Two-spring model for active compression textiles with integrated niti coil actuators. *Smart Materials and Structures* 24(3):035011, 2015.
- [16] Svetlana Yarosh, Kenya Mejia, Baris Unver, Xizi Wang, Yuan Yao, Akin Campbell, and Brad Holschuh. Squeezebands: Mediated social touch using shape memory alloy actuation. *Proc. ACM Hum.-Comput. Interact(CSCW)*, dec 2017.
- [17] Mengjia Zhu, Amirhossein H. Memar, Aakar Gupta, Majed Samad, Priyanshu Agarwal, Yon Visell, Sean J. Keller, and Nicholas Colonnese. Pneusleeve: In-fabric multimodal actuation and sensing in a soft, compact, and expressive haptic sleeve. In *Proceedings of the 2020 CHI Conference on Human Factors in Computing Systems ’20*, page 1–12, New York, NY, USA, 2020. Association for Computing Machinery.
- [18] Trevor L. Buckner, R. Adam Bilodeau, Sang Yup Kim, and Rebecca Kramer-Bottiglio. Roboticizing fabric by integrating functional fibers. *Proceedings of the National Academy of Sciences* 117(41):25360–25369, 2020.
- [19] Aakar Gupta, Antony Albert Raj Irudayraj, and Ravin Balakrishnan. Hapticclench: Investigating squeeze sensations using memory alloys. In *Proceedings of the 30th Annual ACM Symposium on User Interface Software and Technology*, page 109–117, New York, NY, USA, 2017. Association for Computing Machinery.
- [20] Marcelo Coelho and Pattie Maes. Sprout i/o: a texturally rich interface. In *Proceedings of the 2nd international conference on Tangible and embedded interaction*, pages 221–222, 2008.
- [21] Massimiliano Solazzi, William R Provancher, Antonio Frisoli, and Massimo Bergamasco. Design of a sma actuated 2-dof tactile device for displaying tangential skin displacement. In *2011 IEEE World Haptics Conference*, pages 31–36. IEEE, 2011.
- [22] Gijs Huisman and Aduén Darriba Frederiks. Towards tactile expressions of emotion through mediated touch. In *CHI ’13 Extended Abstracts on Human Factors in Computing Systems EA ’13*, page 1575–1580, New York, NY, USA, 2013. Association for Computing Machinery.
- [23] Leonardo Bonanni, Cati Vaucelle, Jeff Lieberman, and Orit Zuckerman. Taptap: a haptic wearable for asynchronous distributed touch therapy. In *CHI’06 extended abstracts on Human factors in computing systems*, pages 580–585, 2006.

- [1197] Kristina Hook. Designing with the body: Somaesthetic interaction design. Press, 2018.
- [1198] Martijn ten Bhömer, Ruggero Canova, and Eva de Laat. Body inspired design for knitted body-protection wearables. In Proceedings of the 2018 ACM Conference Companion Publication on Designing Interactive Systems Companion, pages 135–139, New York, NY, USA, 2018. Association for Computing Machinery.
- [1199] Hayes Solos Raffle, Amanda J. Parkes, and Hiroshi Ishii. Topobo: a constructive assembly system with kinetic memory. In Proceedings of the SIGCHI Conference on Human Factors in Computing Systems '04, page 647–654, New York, NY, USA, 2004. Association for Computing Machinery.
- [1200] John Zimmerman, Jodi Forlizzi, and Shelley Evenson. Research through design as a method for interaction design research in hci. In Proceedings of the SIGCHI conference on Human factors in computing systems '07, pages 493–502, 2007.
- [1201] Evan Pezent, Marcia K. O’Malley, Ali Israr, Majed Samad, Shea Robinson, Priyanshu Agarwal, Hrvoje Benko, and Nicholas Colonnese. Explorations of wrist haptic feedback for ar/vr interactions with tabs. In Extended Abstracts of the 2020 CHI Conference on Human Factors in Computing Systems CHI EA ’20, page 1–4, New York, NY, USA, 2020. Association for Computing Machinery.
- [1202] Qi Wang, Yuan Zeng, Runhua Zhang, Nianding Ye, Linghao Zhu, Xiaohua Sun, and Teng Han. Emtex: Prototyping textile-based interfaces through an embroidered construction kit. In Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology '23, page 1–11, 2023.
- [1203] Yuxuan Lei, Qi Lu, and Yingqing Xu. O&O: A diy toolkit for designing and rapid prototyping olfactory interfaces. In Proceedings of the 2022 CHI Conference on Human Factors in Computing Systems '22, page 1–21, 2022.
- [1204] Shreyosi Endow, Hedieh Moradi, Anvay Srivastava, Esau G Noya, and Cesar Torres. Compressables: A haptic prototyping toolkit for wearable compression-based interfaces. In Proceedings of the 2021 ACM Designing Interactive Systems Conference, page 1101–1114, New York, NY, USA, 2021. Association for Computing Machinery.
- [1205] Henning Pohl, Peter Brandes, Hung Ngo Quang, and Michael Rohs. Squeezeback: Pneumatic compression for notifications. In Proceedings of the 2017 CHI Conference on Human Factors in Computing Systems '17, pages 5318–5330, 2017.
- [1206] Sida Dai, Brygg Ullmer, and Winifred Elyssic Newman. Morphmatrix: A toolkit facilitating shape-changing interface design. In Proceedings of the Eighteenth International Conference on Tangible, Embedded, and Embodied Interaction '18, New York, NY, USA, 2014. Association for Computing Machinery.
- [1207] Atieh Taheri, Carlos Gilberto Gomez-Monroy, Vicente Borja, and Misha Sra. Mouseclicker: Exploring tactile feedback and physical agency for people with hand motor impairments. *ACM Transactions on Accessible Computing*(9):1–31, 2024.
- [1208] Soo-Min Lee and Juyeon Park. A soft wearable exoglove for rehabilitation assistance: a novel application of knitted shape-memory alloy as a flexible actuator. *Fashion and Textiles*(1):14, 2024.
- [1209] Liang He, Cheng Xu, Ding Xu, and Ryan Brill. Pneuhaptic: delivering haptic cues with a pneumatic armband. In Proceedings of the 2015 ACM International Symposium on Wearable Computer '15, page 47–48, New York, NY, USA, 2015. Association for Computing Machinery.
- [1210] Jose Barreiros, Tianshu Liu, Maurizio Chiaramonte, Kristy Jost, Yigit Menguc, Nicholas Colonnese, and Priyanshu Agarwal. Hyfar: A textile soft actuator for haptic clothing interfaces. In ACM SIGGRAPH 2022 Posters, pages 1–2, 2022.
- [1211] Aakar Gupta, Antony Albert Raj Irudayaraj, and Ravin Balakrishnan. Hapticclench: Investigating squeeze sensations using memory alloys. In Proceedings of the 30th Annual ACM Symposium on User Interface Software and Technology '17, New York, NY, USA, 2017. Association for Computing Machinery.
- [1212] Marcelo Coelho and Pattie Maes. Sprout i/o: a texturally rich interface. In Proceedings of the 2nd International Conference on Tangible and Embedded Interaction TEI '08, page 221–222, New York, NY, USA, 2008. Association for Computing Machinery.
- [1213] Yosuke Mizukami and Hideyuki Sawada. Tactile information transmission by apparent movement phenomenon using shape-memory alloy device. *International Journal on Disability and Human Development*(1):277–284, 2006.
- [1214] Qiaolian Xie, Qiaoling Meng, Wenwei Yu, Rongna Xu, Zhiyu Wu, Xiaoming Wang, and Hongliu Yu. Design of a soft bionic elbow exoskeleton based on shape memory alloy spring actuators. *Mechanical Sciences*(1):159–170, 2023.
- [1215] Moritz Alexander Messerschmidt, Sachith Muthukumarana, Nur Al-Huda Hamdan, Adrian Wagner, Haimo Zhang, Jan Borchers, and Suranga Chandima Nanayakkara. Anisma: A prototyping toolkit to explore haptic skin deformation applications using shape-memory alloys. *ACM Transactions on Computer-Human Interaction*(3):1–34, 2022.
- [1216] Rachael Granberry, Kevin Eschen, Brad Holschuh, and Julianne Abel. Functionally graded knitted actuators with niti-based shape memory alloys for topographically self-fitting wearables. *Advanced materials technologies*(1):1900548, 2019.
- [1217] Hussein FM Ali and Youngshik Kim. Design procedure and control of a small-scale knee exoskeleton using shape memory alloy springs. *Microsystem Technologies*(89(8)):1225–1234, 2023.
- [1218] Budiman Salam and Rachel Lee Siew Tan. Stretchability of electronic components assembled on fabric for wearable electronics applications, 2023.
- [1219] Kelly Dobson, Danah Boyd, Wendy Ju, Judith Donath, and Hiroshi Ishii. Creating visceral personal and social interactions in mediated spaces. In CHI'01 Extended Abstracts on Human Factors in Computing Systems '01, pages 151–152, 2001.
- [1220] Alice Haynes, Melanie F. Simons, Tim Helps, Yuichi Nakamura, and Jonathan Rossiter. A wearable skin-stretching tactile interface for human–robot and human–human communication. *IEEE Robotics and Automation Letters*(2):1641–1646, 2019.
- [1221] Henning Pohl, Dennis Becke, Eugen Wagner, Maximilian Schrapel, and Michael Rohs. Wrist compression feedback by pneumatic actuation. In Proceedings of the 33rd Annual ACM Conference Extended Abstracts on Human Factors in Computing Systems '15, New York, NY, USA, 2015. Association for Computing Machinery.
- [1222] Manuscript submitted to ACM

- [49] Shreyosi Endow, Hedieh Moradi, Anvay Srivastava, Esau G Noya, and Cesar Torres. Compressables: A haptic prototyping toolkit for wearable compression-based interfaces. In *Proceedings of the 2021 ACM Designing Interactive Systems Conference*, page 1101–1114, New York, NY, USA, 2021. Association for Computing Machinery.
- [50] Yue Yang, Lei Ren, Chuang Chen, Bin Hu, Zhuoyi Zhang, Xinyan Li, Yanchen Shen, Kuangqi Zhu, Junzhe Ji, Yuyang Zhang, Yongbo Ni, Jiayi Wu, Qi Wang, Jiang Wu, Lingyun Sun, Ye Tao, and Guanyun Wang. Snapinflatables: Designing inflatables with snap-through instability for responsive interaction. In *Proceedings of the 2024 CHI Conference on Human Factors in Computing Systems*, New York, NY, USA, 2024. Association for Computing Machinery.
- [51] Jifei Ou, Mélina Skouras, Nikolaos Vlavianos, Felix Heibeck, Chin-Yi Cheng, Jannik Peters, and Hiroshi Ishii. aeromorph-heat-sealing inflatable shape-change materials for interaction design. In *Proceedings of the 29th Annual Symposium on User Interface Software and Technology*, 121–132, 2016.
- [52] Susan J Lederman and Roberta L Klatzky. Haptic perception: A tutorial. *Attention, Perception, & Psychophysics* 72(6):1439–1459, 2009.
- [53] Ramiro Velazquez, Edwige E Pissaloux, Moustapha Hafez, and Jérôme Szewczyk. Tactile rendering with shape-memory-alloy pin-matrix. *IEEE Transactions on Instrumentation and Measurement* 57(5):1051–1057, 2008.
- [54] Parris S Wellman, William J Peine, Gregg Favalaro, and Robert D Howe. Mechanical design and control of a high-bandwidth shape memory alloy tactile display. In *Experimental Robotics V: The Fifth International Symposium Barcelona, Catalonia, June 15–16, 1997*, pages 1–6. Springer, 1998.
- [55] Qiaolian Xie, Qiaoling Meng, Wenwei Yu, Rongna Xu, Zhiyu Wu, Xiaoming Wang, and Hongliu Yu. Design of a soft bionic elbow exoskeleton based on shape memory alloy spring actuators. *Mechanical Sciences* 13(1):159–170, 2023.
- [56] Kevin Eschen, Rachael Granberry, Bradley Holschuh, and Julianna Abel. Amplifying and leveraging generated force upon heating and cooling in sma knitted actuators. *ACS Applied Materials & Interfaces* 12(48):54155–54167, 2020.
- [57] Bradley T Holschuh and Dava J Newman. Morphing compression garments for space medicine and extravehicular activity using active materials. *Aerospace medicine and human performance* 87(1):84–92, 2016.
- [58] Qi Wang, Marina Toeters, Wei Chen, Annick Timmermans, and Panos Markopoulos. Zishi: A smart garment for posture monitoring. In *Proceedings of the 2016 CHI Conference Extended Abstracts on Human Factors in Computing Systems*, page 3792–3795, New York, NY, USA, 2016. Association for Computing Machinery.
- [59] Masahiro Miyakami, Karen. A. Murata, and Hiroyuki Kajimoto. Hapballoon: Wearable Haptic Balloon-Based Feedback Device. 2018. Association for Computing Machinery, New York, NY, USA, 2019.
- [60] Shaoxiong Guo, Yan Yang, and Chao Zhai. A fiber positioner robotic arm with sensor based on 4mm motor. In *Advances in Optical and Mechanical Technologies for Telescopes and Instrumentation*, volume 13100, pages 730–738. SPIE, 2024.
- [61] Tobias Hemsel, Maik Mracek, Jens Twiefel, and Piotr Vasiljev. Piezoelectric linear motor concepts based on coupling of longitudinal vibrations. *Ultrasonics* 44:e591–e596, 2006.
- [62] Karlin Bark, Jason Wheeler, Gayle Lee, Joan Savall, and Mark Cutkosky. A wearable skin stretch device for haptic feedback. In *World Haptics 2009 - Third Joint EuroHaptics conference and Symposium on Haptic Interfaces for Virtual Environment and Teleoperator Systems*, pages 1–6, 2009.
- [63] Evan Pezent, Ali Isra, Majed Samad, Shea Robinson, Priyanshu Agarwal, Hrvoje Benko, and Nick Colomnese. Tasbi: Multisensory squeeze and vibrotactile wrist haptics for augmented and virtual reality. In *2019 IEEE World Haptics Conference (WHC)*, pages 1–6, 2019.
- [64] Samuel B. Schorr and Allison M. Okamura. Fingertip tactile devices for virtual object manipulation and exploration. In *Proceedings of the 2017 CHI Conference on Human Factors in Computing Systems*, page 3115–3119, New York, NY, USA, 2017. Association for Computing Machinery.
- [65] J. Berzowska and M. Coelho. Kukkia and vilkas: kinetic electronic garments. In *Ninth IEEE International Symposium on Wearable Computers (ISWC'05)*, pages 82–85, 2005.
- [66] Min-Woo Han and Sung-Hoon Ahn. Blooming knit flowers: Loop-linked soft morphing structures for soft robotics. *Advanced Materials (Deerfield Beach, Fla.)* 29(13), 2017.
- [67] Anne Roudaut, Abhijit Karnik, Markus Löchtefeld, and Sriram Subramanian. Morphées: toward high "shape resolution" in self-actuated flexible mobile devices. In *Proceedings of the SIGCHI conference on human factors in computing systems*, pages 593–602, 2013.
- [68] Joohee Park, Young-Woo Park, and Tek-Jin Nam. Wriggle: shape-changing peripheral for interpersonal mobile communication. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, page 3973–3976, New York, NY, USA, 2014. Association for Computing Machinery.
- [69] Li Liu, Ruomei Wang, Zhuo Su, Xiaonan Luo, and Chengying Gao. Mesh-based anisotropic cloth deformation for virtual fitting. *Multimedia Tools and Applications* 71(2):411–433, 2014.
- [70] Luisa von Radziewsky, Antonio Krüger, and Markus Löchtefeld. Scarfy: Augmenting human fashion behaviour with self-actuated clothes. In *Proceedings of the Ninth International Conference on Tangible, Embedded, and Embodied Interaction*, page 313–316, New York, NY, USA, 2015. Association for Computing Machinery.
- [71] Soo-Min Lee, Gyomyung Shin, Hyucksoon Im, Midum Oh, Sofia Castro Avalos, Mi-Jeong Yoon, Joon-Sung Kim, Juyeon Park, and Sung-Hoon Ahn. Feasibility of a warp-knitted shape memory alloy rehabilitation glove. *Journal of Industrial Textiles* 44:15280837241238446, 2024.
- [72] Joanna Berzowska and Di Mainstone. Skorpions: kinetic electronic garments. In *ACM SIGGRAPH 2008 talks*, pages 1–1, 2008.
- [73] Laura Perovich, Philippa Mothersill, and Jennifer Broutin Farah. Awakened apparel: embedded soft actuators for expressive fashion and functional garments. In *Proceedings of the 8th International Conference on Tangible, Embedded and Embodied Interaction*, 2014.

- [74] Simon Olberding, Sergio Soto Ortega, Klaus Hildebrandt, and Jürgen Steimle. Foldio: Digital fabrication of interactive and shape-changing objects with foldable printed electronics. In *Proceedings of the 28th Annual ACM Symposium on User Interface Software & Technology*, page 223–232, New York, NY, USA, 2015. Association for Computing Machinery.
- [75] First Authors Last and First Another. Neuro-perceptive discrimination on fabric tactile stimulation by electroencephalographic (eeg) spectra. *PLOS ONE* Volume(Issue):Page Range, Year.
- [76] Lei Chen, Zhijun Zhang, and Jian Fan. Investigation on tactile properties of fabrics based on physical and surface properties. *The Journal of the Textile Institute* 104(8):808–815, 2013.
- [77] Emilie Bertaux, Maryline Lewandowski, and Siegfried Derler. Relationship between friction and tactile properties for woven and knitted fabrics. *Textile Research Journal* 21(6):387–396, 2007.
- [78] Yuanhao Zhu, Annice Lee, Ziyue Hu, and Hsin-Liu (Cindy) Kao. Dynamicskin: Bio-inspired scaled sleeve for body temperature regulation and dynamic self-expression. In *Proceedings of the Augmented Humans International Conference 2022*, page 284–286, New York, NY, USA, 2022. Association for Computing Machinery.
- [79] Alice C Haynes and Jürgen Steimle. Flextiles: Designing customisable shape-change in textiles with sma-actuated smocking patterns. In *Proceedings of the 2024 CHI Conference on Human Factors in Computing Systems*, New York, NY, USA, 2024. Association for Computing Machinery.
- [80] Jeyeon Jo and Cindy Hsin-Liu Kao. Skinlace: Freestanding lace by machine embroidery for on-skin interface. In *Extended Abstracts of the 2021 CHI Conference on Human Factors in Computing Systems* 1–6, 2021.
- [81] Jinlian Hu, Mohammad Irfan Iqbal, and Fengxin Sun. Wool can be cool: water-actuating woolen knitwear for both hot and cold. *Advanced Functional Materials* 30(51):2005033, 2020.
- [82] Rachael Granberry, Kevin Eschen, Brad Holschuh, and Julianna Abel. Functionally graded knitted actuators with niti-based shape memory alloys for topographically self-fitting wearables. *Advanced materials technologies* 1(1):1900548, 2019.
- [83] Beyza Bozali, Sepideh Ghodrat, Linda Plaude, Joris JF van Dam, and Kaspar MB Jansen. Development of low hysteresis, linear weft-knitted strain sensors for smart textile applications. *Sensors* 22(19):7688, 2022.
- [84] Stefanie Schaack, George Chernyshov, Kirill Ragozin, Benjamin Tag, Roshan Peiris, and Kai Kunze. Haptic collar: Vibrotactile feedback around the neck for guidance applications. In *Proceedings of the 10th Augmented Human International Conference 2019*, New York, NY, USA, 2019. Association for Computing Machinery.
- [85] Harshika Jain, Kexin Lu, and Lining Yao. Hydrogel-based diy underwater morphing artifacts: A morphing and fabrication technique to democratize the creation of controllable morphing 3d underwater structures with low-cost, easily available hydrogel beads adhered to a substrate. In *Proceedings of the 2021 ACM Designing Interactive Systems Conference* 1242–1252, 2021.
- [86] Hyunyoung Kim, Aluna Everitt, Carlos Tejada, Mengyu Zhong, and Daniel Ashbrook. Morpheesplug: A toolkit for prototyping shape-changing interfaces. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems*, 2021.
- [87] Christoffer Eriksson. Supporting Caring Touch: A toolkit for sensitizing soma designers through subtle dispositions, KTH Royal Institute of Technology, 2023.
- [88] Peter Wehrspann and Lois Frankel. Interdisciplinary design: The need for collaboration to foster technological innovation to create competitive and sustainable products. 2010.
- [89] Alan M Rugman and Joseph R D'cruz. The " double diamond" model of international competitiveness: The canadian experience. *MIR: Management International Review* pages 17–39, 1993.
- [90] John S Gero. Design prototypes: a knowledge representation schema for design. *AI magazine* 11(4):26–26, 1990.
- [91] Hasso Plattner, Christoph Meinel, and Larry Leifer. *Design Thinking Research: Making Design Thinking Foundational*. Understanding Innovation. Springer, 2016.
- [92] John Zimmerman and Jodi Forlizzi. Research through design in hci. In *Ways of Knowing in HC* pages 167–189. Springer, 2014.
- [93] Qiang Liu, Sepideh Ghodrat, Gijs Huisman, and Kaspar M.B. Jansen. Shape memory alloy actuators for haptic wearables: A review. *Materials Design* 233:112264, 2023.
- [94] MG Gee, P Tomlins, A Calver, RH Darling, and M Rides. A new friction measurement system for the frictional component of touch. *Wear* 259(7-12):1437–1442, 2005.
- [95] Bart Gommers, Ignace Verpoest, and Paul Van Houtte. Modelling the elastic properties of knitted-fabric-reinforced composites. *Composites science and technology* 66(6):685–694, 1996.
- [96] Interaction Design Foundation, Rikke Friis Dam, and Teo Yu Siang. What is design thinking and why is it so popular?, 2021.
- [97] Fiona Maciver, Julian Malins, Julia Kantorovich, and Aggelos Liapis. United we stand: A critique of the design thinking approach in interdisciplinary innovation. 2016.
- [98] James J Gibson. *The ecological approach to visual perception: classic essays*. Psychology press, 2014.
- [99] Martin Schrepp, Jörg Thomaschewski, and Andreas Hinderks. Construction of a benchmark for the user experience questionnaire (ueq). 2017.
- [100] Virginia Braun and Victoria Clarke. *Thematic analysis*. American Psychological Association, 2012.
- [101] Michael Muller. Curiosity, Creativity, and Surprise as Analytic Tools: Grounded Theory Method. In Judith S. Olson and Wendy A. Kellogg, editors, *Ways of Knowing in HC* pages 25–48. Springer New York, New York, NY, 2014.
- [102] WANG Xuxiao. Lucky motifs in chinese folk art: Interpreting paper-cut from chinese shaanxi. *Asian Studies* 1(2):125–143, 2013.

- 1353 [103] Martin Schrepp, Andreas Hinderks, and Jörg Thomaschewski. Design and evaluation of a short version of the user experience questionnaire
 1354 (ueq-s). *International Journal of Interactive Multimedia and Artificial Intelligence*, 4 (6), 103–108.
- 1355 [104] Violet Yinuo Han, Abena Boadi-Agyemang, Yuyu Lin, David Lindlbauer, and Alexandra Ion. Parametric haptics: Versatile geometry-based tactile
 1356 feedback devices. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology*, 2023.
- 1357 [105] Han Chen, Shuqun Wang, Wanrou Tan, and Jie Luo. Stm32-based anti-fall smart vest system for the elderly. In *2022 IEEE 6th Information Technology
 1358 and Mechatronics Engineering Conference (ITME)*, 6, pages 516–520. IEEE, 2022.
- 1359 [106] Ran Zhou, Zachary Schwemler, Akshay Baweja, Harpreet Sareen, Casey Lee Hunt, and Daniel Leithinger. Tactorbots: a haptic design toolkit for
 1360 out-of-lab exploration of emotional robotic touch. In *Proceedings of the 2023 CHI Conference on Human Factors in Computing Systems*,
 1361 2023.
- 1362 [107] Ali Shtarbanov, Mengjia Zhu, Nicholas Colonnese, and Amirhossein Hajiagha Memar. Sleeveio: modular and reconfigurable platform for multimodal
 1363 wearable haptic feedback interactions. In *Proceedings of the 36th annual ACM symposium on user interface software and technology*, 2023.
- 1364 [108] John Sweller. Cognitive load during problem solving: Effects on learning. *Cognitive science* 2(2):257–285, 1988.
- 1365 [109] Rui Zhang, Yixuan Li, Zihuang Wu, Yong Zhang, Jie Zhao, and Yang Jiao. Semantictap: A haptic toolkit for vibration semantic design of smartphone.
 1366 In *Proceedings of the 26th International Conference on Multimodal Interaction*, 24, page 264–273, New York, NY, USA, 2024. Association for
 1367 Computing Machinery.
- 1368 [110] Yueyao Zhang, Nianchong Qu, Runhua Zhang, Ye Tao, Guanyun Wang, and Qi Wang. Laytex: A design tool for generating customized textile
 1369 sensor layouts in wearable computing. In *Adjunct Proceedings of the 2023 ACM International Joint Conference on Pervasive and Ubiquitous Computing
 1370 & the 2023 ACM International Symposium on Wearable Computing*, 63–67, 2023.
- 1371 =
- 1372
- 1373
- 1374
- 1375
- 1376
- 1377
- 1378
- 1379
- 1380
- 1381
- 1382
- 1383
- 1384
- 1385
- 1386
- 1387
- 1388
- 1389
- 1390
- 1391
- 1392
- 1393
- 1394
- 1395
- 1396
- 1397
- 1398
- 1399
- 1400
- 1401
- 1402
- 1403
- 1404

A Appendix A: Design Manual

This section provides an overview of the Design Manual, which guides users in integrating haptic actuators and fabrics. The manual outlines key steps and design considerations for the effective use of HaptiFab.




Fig. A.1. Design Manual Overview. p1) Workshop Arrangement, p2-p4) Design Guide.

1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478

HaptiFab

Toolkit Display - Actuators

In the final stage, we need to focus on selecting the appropriate integration of haptic actuators and fabric to achieve the desired outcomes and ensure that the st

Stretch

Ni-Ti memory alloy

Shrink by 4.5%
Model SMA010
Diameter [mm] 0.100
Resistance [Ω(m)] 126

Recommended load [N] ±1.3
Recommended drive current [A] 0.35
Recommended power-on duration [s] ≤0.4
Recommended strain [%] ±3.5

Compress

Liquid Silicone

Manufacturing process:
3D printing mold → Assembly mold → Silicone injection → Venting → Demould → Air inflation → quadrate → annular

Glue A + glue B 1:1
The curing time is about 2h
High temperature resistance ~250 degrees
Low temperature resistance ~50 degrees
Color: Translucent
Operation time 20-30min/25 degrees, Curing time 2-3h25 degrees
TOD: Shore hardness 0050, tensile strength 315psi, elongation 980%
TOS: Shore hardness 0020, tensile strength 180psi, elongation 845%

5

6

1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500

HaptiFab

Toolkit Display - Fabrics

In the final stage, we need to focus on selecting the appropriate integration of haptic actuators and fabric to achieve the desired outcomes and ensure

Flat Surface

Plain Surface (NO.1-NO.10)

NO.1 NO.2 NO.3 NO.4 NO.5 NO.6

Smooth Surface (NO.11-NO.12)

NO.7 NO.8 NO.9 NO.10 NO.11 NO.12

Cutwork (NO.25-32)

NO.25 NO.26 NO.27 NO.28 NO.29 NO.30

Mesh (NO.33-36)

NO.31 NO.32 NO.33 NO.34 NO.35 NO.36

Ripple Structures (NO.37-38) Origami Structures (NO.39-40)

NO.37 NO.38 NO.39 NO.40

7

8

Manuscript submitted to ACM

B Appendix B: Fabric Classification

This section categorizes fabrics based on their properties and construction techniques, while also explaining the materials used in different fabrics.


	Categories	Number	Fabric	Material		Categories	Number	Fabric	Material
1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560	Plain Surface Flat Surface Smooth Surface	1		100% Polyurethane	Elastic Structures Smocking Structural Fabric/Surface Pleating	13		100% Cotton	
		2		60% Polypropylene + 40% Polyurethane		14		100% Cotton	
		3		100% DuPont paper		15		100% Polypropylene	
		4		100% Terylene		16		100% Cotton	
		5		100% Nylon		17		100% Terylene	
		6		100% Nylon		18		100% Terylene	
		7		100% Polyester fiber		19		100% Polyester fiber	
		8		100% Polyethylene		20		100% Terylene	
		9		100% Cotton		21		100% Terylene	
		10		100% Cotton		22		100% Nylon	
		11		100% Terylene		23		100% Terylene	
		12		100% Terylene		24		60% Nylon + 40% Terylene	

Fig. B.1. Fabric Categories and Materials Explanation - 1

Categories		Number	Fabric	Material	Categories		Number	Fabric	Material
Structural Fabric/ Surface	Cutwork	25		100% Terylene	Structural Fabric/ Surface	Ripple Structures	37		100% Terylene
		26		100% Cotton			38		100% Terylene
		27		50% Wool + 50% Terylene		Origami Structures	39		100% Terylene
		28		57% Rayo + 43% Terylene			40		100% Polyurethane
		29		100% Cotton	Decoration Surface	Embroidery	41		100% Terylene
		30		65% Acrylic + 35% Terylene			42		100% Terylene
		31		100% Terylene		3D Surface Embellish -ments	43		100% Terylene (excluding embellishment)
		32		100% Cotton			44		100% Terylene (excluding embellishment)
Mesh	Mesh	33		100% Terylene	Decoration Surface	Pile	45		100% Terylene
		34		100% Terylene			46		100% Terylene
		35		100% Terylene			47		100% Terylene
		36		100% Terylene			48		100% Terylene

Fig. B.2. Fabric Categories and Materials Explanation - 2

Manuscript submitted to ACM

C Appendix C: Practical Applications

This section highlights practical applications developed by our seven interdisciplinary groups during workshop prototyping, following the design manual process, and utilizing HaptiFab.

Group	User Goals	User Interaction			Technical Functionality		
		Input	Process	Output	Material	Structure	Function
01	A person practicing singing alone at home with help	<ul style="list-style-type: none"> Singing Training Vocalization Dependent 	<p>Physiological data</p>	<p>Larynx Chest Diaphragm</p> <p>Vibration, Stretch, Compress Flower shape</p>		<p>Fully wrapped</p>	<p>Guiding</p>
02	A person is relaxed by rhythmically guided breathing	<ul style="list-style-type: none"> Life Work Breathing Anxious 	<p>STAT ANXIETY</p> <p>Singlechip & Physiological data</p>	<p>Arm</p> <p>Vibration Color and Light change</p>		<p>Partially wrapped</p>	<p>Relaxing</p> <p>The motors are arranged in an array around the arm</p>
03	Feel the protection of the environment while visiting the museum	<ul style="list-style-type: none"> Museum Education Visiting Atmosphere 	<p>Physiological & Environmental data</p>	<p>Neck and Right shoulder</p> <p>Compress Fishing net shape</p>		<p>Partially wrapped</p>	<p>Oppressive</p> <p>The air gives a squeezing sensation to the neck</p>
04	The sad are comforted by being hugged	<ul style="list-style-type: none"> Life Work Self-embrace Be comforted 	<p>Physiological data</p>	<p>Chest and back</p> <p>Compress Body Shape Natural</p>		<p>Fully wrapped</p>	<p>Consoled</p> <p>The human-shaped airway gives the feeling of being hugged</p>
05	People on the road can get timely safety warnings	<ul style="list-style-type: none"> Cycling Driving Ride or Drive Insecure 	<p>Singlechip & Manual command</p>	<p>Wrist</p> <p>Compress Fashion, For daily travel</p>		<p>Fully wrapped</p>	<p>Safety</p> <p>Design the airway to provide gentle and timely reminders</p>
06	People can also relax when they are working	<ul style="list-style-type: none"> Life Work Sedentaries Exhaustion 	<p>Behavioral patterns</p>	<p>Neck</p> <p>Compress Modulation Assembled</p>		<p>Fully wrapped</p>	<p>Mystical</p> <p>Pneumatic actuation is used as a carrier to combine haptic sensations</p>
07	Enhance the experience of meditation or yoga	<ul style="list-style-type: none"> Life Work Yoga Chinese culture 	<p>Singlechip</p>	<p>One shoulder and Back</p> <p>Vibration Traditional culture</p>		<p>Fully wrapped</p>	<p>Clam</p> <p>The motors interact with each other to achieve scene linkage</p>

Fig. C.1. Mapping with Workshop Case to Evaluating Workflow

D Appendix D: Question List

This section summarizes the semi-structured interviews conducted to evaluate HaptiFab. The interviews cover topics such as interdisciplinary design, haptic integration, and user experience.

Table D.1. Interview Topics and Sample Questions

Interview Topics	Interview Guide
Demographic	<ol style="list-style-type: none"> 1. How old are you? Studying or working? What's the grade? What is your major background or research direction? 2. Do you have any previous work or program experience?
Toolkit Usage and Effectiveness	<ol style="list-style-type: none"> 1. How did you utilize the HaptiFab in your program? What role did it play in the interdisciplinary design process? 2. In your view, how effective was the HaptiFab in lowering the barriers to prototyping? Did it open up new design spaces? 3. What could be improved in the HaptiFab to better support users?
Integration of Haptic Actuator and Fabric	<ol style="list-style-type: none"> 1. Why did you choose the specific fabric used to enclose the haptic Actuator? What were its advantages in terms of supporting your design goals? 2. What motivated the choice of specific haptic mechanisms (Stretch-SMA, Compress-pneumatic actuation, Vibration-motors)? How did they align with your design objectives? 3. How do you assess the performance of these integrations of haptic actuator and fabric across different contexts? Were there any noticeable deviations or preferences based on user scenarios?

Received 20 February 2007; revised 12 March 2009; accepted 5 June 2009