



Glory Rail
www.gloryrail.com

Glory Diamond Industry Co.,Ltd

International Building, No. 127 Zidong Road,
Guancheng District, Zhengzhou City,
Henan Province, China

Email: info@glorysteelwork.com
https://www.gloryrail.com

Edition


Rev.B

Date

2019/10/20

Scale

1:1.25 @A4



DRAWING NOTICE:

THIS CAD DRAWING, PROPRIETARY TO GLORY RAIL, IS PREPARED IN ACCORDANCE WITH APPLICABLE RAIL STANDARDS AND PROVIDED FOR ILLUSTRATION ONLY. FOR DETAILED DIMENSIONS OR TECHNICAL SOURCE FILES TO SUPPORT YOUR DESIGN, PLEASE CONTACT GLORY RAIL.

Materials: R260

Chemical composition(%)

C:0.60-0.80

Si:0.13-0.60

Mn:0.65-1.25

S:≤0.030

P:≤0.030

Mechanical property

Tensile strength: ≥880 MPa

Elongation: ≥10%

Hardness HB: 260-300

Rail Designation

54E1 (UIC54)

Rail Origin

CHINA

Standard

EN13674-1

Area of section

2337.9 mm²

Calculated Mass

54.77kg/m

Neutral Axis to base

75.13 mm