

第一题

uml 图



文件



代码：

Container.h

```
#ifndef CONTAINER_H
#define CONTAINER_H

#include <iostream>
#include <typeinfo>
#include <cmath>
```

```
class Container {
public:
	virtual ~Container() = default;
	virtual double getVolume() const = 0;
	virtual double getArea() const = 0;
	virtual void printType() const = 0;
};

#endif // CONTAINER_H
```

Cube.h

```
#ifndef CUBE_H
#define CUBE_H

#include "Container.h"

class Cube : public Container {
private:
	double side;

public:
	Cube(double s) : side(s) {}
	double getVolume() const override { return std::pow(side, 3); }
	double getArea() const override { return 6 * std::pow(side, 2); }
	void printType() const override { std::cout << "Cube" << std::endl; }
};

#endif // CUBE_H
```

Cylinder.h

```
#ifndef CYLINDER_H
#define CYLINDER_H

#include "Container.h"

class Cylinder : public Container {
private:
	double radius;
	double height;

public:
	Cylinder(double r, double h) : radius(r), height(h) {}
	double getVolume() const override { return 3.14159265358979323846 * std::pow(radius, 2)
* height; }
	double getArea() const override { return 2 * 3.14159265358979323846 * radius * (radius +
height); }
```

```
    void printType() const override { std::cout << "Cylinder" << std::endl; }
};

#endif // CYLINDER_H

#ifndef SPHERE_H
#define SPHERE_H
```

Sphere.h

```
#include "Container.h"

class Sphere : public Container {
private:
    double radius;

public:
    Sphere(double r) : radius(r) {}
    double getVolume() const override { return (4.0 / 3.0) * 3.14159265358979323846 *
std::pow(radius, 3); }
    double getArea() const override { return 4 * 3.14159265358979323846 * std::pow(radius,
2); }
    void printType() const override { std::cout << "Sphere" << std::endl; }
};

#endif // SPHERE_H
```

main.cpp

```
#include <iostream>
#include <vector>
#include "Sphere.h"
#include "Cylinder.h"
#include "Cube.h"

int main() {
    std::vector<Container*> containers;
    containers.push_back(new Sphere(5.0));
    containers.push_back(new Cylinder(3.0, 7.0));
    containers.push_back(new Cube(4.0));

    for (const auto& container : containers) {
        std::cout << "Volume: " << container->getVolume() << std::endl;
        std::cout << "Area: " << container->getArea() << std::endl;
        container->printType();
        std::cout << std::endl;
    }
```

```
    for (auto& container : containers) {
        delete container;
    }

    return 0;
}
```

运行结果：

```
R1 Area: 160
R1 Perimeter: 88
R2 Area: 125.65
R2 Perimeter: 78.8
[1] + Done                       "/usr/bin/gdb" --int
```

第二题

代码：

Matrix.h

```
#ifndef MATRIX_H
#define MATRIX_H

#include <iostream>
#include <cstdlib> // for rand() and srand()
#include <ctime>      // for time()

class Matrix {
private:
    int row, col;
    float* data;

public:
    // Constructors
    Matrix(int r = 0, int c = 0);
    Matrix(const Matrix& other);

    // Destructor
    ~Matrix();

    // Assignment operator
    Matrix& operator=(const Matrix& other);

    // Arithmetic operators
    Matrix operator+(const Matrix& other) const;
    Matrix operator*(const Matrix& other) const;

    // I/O operators
```

```
    friend std::ostream& operator<<(std::ostream& os, const Matrix& matrix);
    friend std::istream& operator>>(std::istream& is, Matrix& matrix);

    // Utility function to populate matrix with random values
    void randomPopulate(float min = 0.0f, float max = 1.0f);

    // Accessors for row and col (optional, for debugging/info purposes)
    int getRow() const { return row; }
    int getCol() const { return col; }
};

#endif // MATRIX_H
```

Matrix.cpp

```
#include "Matrix.h"

Matrix::Matrix(int r, int c) : row(r), col(c) {
    if (row > 0 && col > 0) {
        data = new float[row * col];
        // Optionally, initialize data to zero or some other value
        for (int i = 0; i < row * col; ++i) {
            data[i] = 0.0f;
        }
    } else {
        data = nullptr;
    }
}

Matrix::Matrix(const Matrix& other) : row(other.row), col(other.col) {
    data = new float[row * col];
    for (int i = 0; i < row * col; ++i) {
        data[i] = other.data[i];
    }
}

Matrix::~Matrix() {
    delete[] data;
}

Matrix& Matrix::operator=(const Matrix& other) {
    if (this == &other) return *this; // handle self-assignment

    delete[] data;
    row = other.row;
    col = other.col;
```

```
        data = new float[row * col];
        for (int i = 0; i < row * col; ++i) {
            data[i] = other.data[i];
        }
        return *this;
}

Matrix Matrix::operator+(const Matrix& other) const {
        if (row != other.row || col != other.col) {
            throw std::invalid_argument("Matrices must have the same dimensions for addition.");
        }

        Matrix result(row, col);
        for (int i = 0; i < row * col; ++i) {
            result.data[i] = data[i] + other.data[i];
        }
        return result;
}

Matrix Matrix::operator*(const Matrix& other) const {
        if (col != other.row) {
            throw std::invalid_argument("Number of columns in first matrix must equal number of
rows in second matrix for multiplication.");
        }

        Matrix result(row, other.col);
        for (int i = 0; i < result.row; ++i) {
            for (int j = 0; j < result.col; ++j) {
                result.data[i * result.col + j] = 0.0f;
                for (int k = 0; k < col; ++k) {
                    result.data[i * result.col + j] += data[i * col + k] * other.data[k * other.col + j];
                }
            }
        }
        return result;
}

std::ostream& operator<<(std::ostream& os, const Matrix& matrix) {
        for (int i = 0; i < matrix.row; ++i) {
            for (int j = 0; j < matrix.col; ++j) {
                os << matrix.data[i * matrix.col + j] << " ";
            }
            os << std::endl;
        }
```

```
    return os;
}

std::istream& operator>>(std::istream& is, Matrix& matrix) {
    for (int i = 0; i < matrix.row; ++i) {
        for (int j = 0; j < matrix.col; ++j) {
            is >> matrix.data[i * matrix.col + j];
        }
    }
    return is;
}

void Matrix::randomPopulate(float min, float max) {
    std::srand(std::time(0)); // Seed the random number generator
    for (int i = 0; i < row * col; ++i) {
        data[i] = min + static_cast<float>(std::rand()) / (static_cast<float>(RAND_MAX / (max -
min)));
    }
}
```

MatrixTemplate.h

```
#ifndef MATRIXTEMPLATE_H
#define MATRIXTEMPLATE_H

#include <stdexcept>

template <typename T>
class MatrixTemplate {
private:
    int row, col;
    T* data;

public:
    // Constructor
    MatrixTemplate(int r = 0, int c = 0);

    // Copy Constructor
    MatrixTemplate(const MatrixTemplate& other);

    // Destructor
    ~MatrixTemplate();

    // Assignment Operator
    MatrixTemplate& operator=(const MatrixTemplate& other);
```

```
    // Getters
    int getRow() const;
    int getCol() const;
    T& getElement(int r, int c);
    const T& getElement(int r, int c) const;

    // Setter
    void setElement(int r, int c, const T& value);

    // Matrix Addition
    MatrixTemplate operator+(const MatrixTemplate& other) const;

    // Additional functionalities can be added here, such as matrix multiplication, scalar multiplication, etc.
};

#include "MatrixTemplate.tpp" // Include the template implementation file

#endif // MATRIXTEMPLATE_H
```

MatrixTemplate.tpp

```
#include "MatrixTemplate.h"

template <typename T>
MatrixTemplate<T>::MatrixTemplate(int r, int c) : row(r), col(c) {
    if (row > 0 && col > 0) {
        data = new T[row * col];
        for (int i = 0; i < row * col; ++i) {
            data[i] = T(); // Initialize to default value of T
        }
    } else {
        data = nullptr;
    }
}

template <typename T>
MatrixTemplate<T>::MatrixTemplate(const MatrixTemplate& other) : row(other.row), col(other.col) {
    data = new T[row * col];
    for (int i = 0; i < row * col; ++i) {
        data[i] = other.data[i];
    }
}
```

```
template <typename T>
MatrixTemplate<T>::~MatrixTemplate() {
	delete[] data;
}

template <typename T>
MatrixTemplate<T>& MatrixTemplate<T>::operator=(const MatrixTemplate& other) {
	if (this == &other) return *this; // handle self-assignment

	delete[] data;
	row = other.row;
	col = other.col;
	data = new T[row * col];
	for (int i = 0; i < row * col; ++i) {
		data[i] = other.data[i];
	}
	return *this;
}

template <typename T>
int MatrixTemplate<T>::getRow() const {
	return row;
}

template <typename T>
int MatrixTemplate<T>::getCol() const {
	return col;
}

template <typename T>
T& MatrixTemplate<T>::getElement(int r, int c) {
	if (r < 0 || r >= row || c < 0 || c >= col) {
		throw std::out_of_range("Index out of bounds");
	}
	return data[r * col + c];
}

template <typename T>
const T& MatrixTemplate<T>::getElement(int r, int c) const {
	if (r < 0 || r >= row || c < 0 || c >= col) {
		throw std::out_of_range("Index out of bounds");
	}
	return data[r * col + c];
}
```

```
template <typename T>
void MatrixTemplate<T>::setElement(int r, int c, const T& value) {
    if (r < 0 || r >= row || c < 0 || c >= col) {
        throw std::out_of_range("Index out of bounds");
    }
    data[r * col + c] = value;
}

template <typename T>
MatrixTemplate<T> MatrixTemplate<T>::operator+(const MatrixTemplate& other) const {
    if (row != other.row || col != other.col) {
        throw std::invalid_argument("Matrices must have the same dimensions to be added");
    }
    MatrixTemplate<T> result(row, col);
    for (int i = 0; i < row * col; ++i) {
        result.data[i] = data[i] + other.data[i];
    }
    return result;
}
```

test_MatrixTemplate.cpp

```
#include <iostream>
#include "MatrixTemplate.h"

int main() {
    // 创建两个 3x3 的矩阵
    MatrixTemplate<int> mat1(3, 3);
    MatrixTemplate<int> mat2(3, 3);

    // 初始化 mat1
    for (int i = 0; i < 3; ++i) {
        for (int j = 0; j < 3; ++j) {
            mat1.setElement(i, j, i + j); // 矩阵元素为行索引加列索引
        }
    }

    // 初始化 mat2
    for (int i = 0; i < 3; ++i) {
        for (int j = 0; j < 3; ++j) {
            mat2.setElement(i, j, 2 * (i + j)); // 矩阵元素为 2 倍的行索引加列索引
        }
    }

    // 输出 mat1
```

```
    std::cout << "Matrix mat1:" << std::endl;
    for (int i = 0; i < mat1.getRow(); ++i) {
        for (int j = 0; j < mat1.getCol(); ++j) {
            std::cout << mat1.getElement(i, j) << " ";
        }
        std::cout << std::endl;
    }

    // 输出 mat2
    std::cout << "Matrix mat2:" << std::endl;
    for (int i = 0; i < mat2.getRow(); ++i) {
        for (int j = 0; j < mat2.getCol(); ++j) {
            std::cout << mat2.getElement(i, j) << " ";
        }
        std::cout << std::endl;
    }

    // 计算 mat1 和 mat2 的和
    MatrixTemplate<int> matSum = mat1 + mat2;

    // 输出 matSum
    std::cout << "Matrix matSum (mat1 + mat2):" << std::endl;
    for (int i = 0; i < matSum.getRow(); ++i) {
        for (int j = 0; j < matSum.getCol(); ++j) {
            std::cout << matSum.getElement(i, j) << " ";
        }
        std::cout << std::endl;
    }

    return 0;
}
```

运行结果：

```
Matrix mat1:
0 1 2
1 2 3
2 3 4
Matrix mat2:
0 2 4
2 4 6
4 6 8
Matrix matSum (mat1 + mat2):
0 3 6
3 6 9
6 9 12
```

第三题

代码：

main.cpp

```
#include "Student.h"
#include "student_info_parser.cpp" // 或者使用单独编译的方式链接这个文件
#include <iostream>
#include <vector>

int main() {
    std::vector<Student> students;
    student_info_parser("student_info.txt", students);

    std::cout << "Student Information:" << std::endl;
    for (const auto& student : students) {
        std::cout << student << std::endl;
    }

    std::cout << "\nAverage Score: " << Student::get_average() << std::endl;

    return 0;
}
```

student_info_parser.cpp

```
#include "Student.h"
#include <fstream>
#include <sstream>
#include <string>
#include <vector>

void student_info_parser(const std::string& file_name, std::vector<Student>& students) {
    std::ifstream file(file_name);
    if (!file.is_open()) {
        std::cerr << "Failed to open file: " << file_name << std::endl;
        return;
    }

    std::string line;
    while (std::getline(file, line)) {
        std::istringstream iss(line);
        std::string name, gender_str, student_id;
        int score;

        if (iss >> name >> gender_str >> student_id >> score) {
            char gender = (gender_str == "F" || gender_str == "f") ? 'F' : 'M';
            students.emplace_back(name, gender, student_id, score);
```

```
            }
        }

        file.close();
}
```

Student.h

```
#ifndef STUDENT_H
#define STUDENT_H

#include <iostream>
#include <string>
#include <vector>
#include <iomanip>
#include <sstream>
#include <fstream>

class Student {
private:
        std::string name;
        char gender;
        std::string student_id;
        int score;

        // 静态成员变量
        static int total_students;
        static int total_score;

public:
        // 构造函数
        Student(const std::string& n, char g, const std::string& id, int s)
                : name(n), gender(g), student_id(id), score(s) {
                total_students++;
                total_score += s;
        }

        // 析构函数（用于减少学生总数和总成绩，但在这个简单例子中可能不需要）
        ~Student() {
                total_students--;
                total_score -= score;
        }

        // 静态成员函数，计算平均成绩
        static double get_average() {
                if (total_students == 0) return 0.0;
```

```
        return static_cast<double>(total_score) / total_students;
    }

    // 重载<<操作符，支持格式化输出
    friend std::ostream& operator<<(std::ostream& os, const Student& student) {
        os << std::left << std::setw(15) << student.name
           << std::left << std::setw(15) << (student.gender == 'M' ? "Male" : "Female")
           << std::left << std::setw(15) << student.student_id
           << std::left << std::setw(15) << student.score;
        return os;
    }

    // 其他成员函数（可选）
    std::string getName() const { return name; }
    char getGender() const { return gender; }
    std::string getStudentId() const { return student_id; }
    int getScore() const { return score; }
};

// 初始化静态成员变量
int Student::total_students = 0;
int Student::total_score = 0;

#endif // STUDENT_H
```

测试文本

student_info.txt

```
Alice F 12345678 90
Bob M 87654321 87
Charlie M 13579246 89
Diana F 24680135 92
Edward M 35791246 88
Francesca F 46802468 91
George M 57913578 85
Hannah F 68014689 93
Isaac M 79125780 86
Jessica F 80136890 94
```

运行结果：

```
Student Information:
Alice           Female          12345678        90
Bob             Male            87654321        87
Charlie         Male            13579246        89
Diana           Female          24680135        92
Edward          Male            35791246        88
Francesca       Female          46802468        91
George          Male            57913578        85
Hannah          Female          68014689        93
Isaac           Male            79125780        86
Jessica         Female          80136890        94
```

第四题

代码：

```
#include <iostream>
#include <fstream>
#include <iomanip> // 用于设置输出格式
#include <cstdlib> // 用于生成随机数
#include <ctime> // 用于初始化随机数生成器

int main() {
    // 初始化随机数生成器
    std::srand(static_cast<unsigned int>(std::time(0)));

    const int sizeA = 8;
    const int sizeB_rows = 4;
    const int sizeB_cols = 6;
    const int elementsToRead = sizeB_rows * sizeB_cols; // 24

    // 生成 8x8 矩阵 A
    double A[sizeA][sizeA];
    for (int i = 0; i < sizeA; ++i) {
        for (int j = 0; j < sizeA; ++j) {
            A[i][j] = static_cast<double>(std::rand()) / RAND_MAX; // [0,1)之间的双精度数
        }
    }

    // (a) 将矩阵 A 按矩阵形式写入到文本文件 fout01.txt 中
    std::ofstream fout_text("fout01.txt");
    if (fout_text.is_open()) {
        for (int i = 0; i < sizeA; ++i) {
            for (int j = 0; j < sizeA; ++j) {
                fout_text << std::setw(10) << std::setprecision(6) << std::fixed << A[i][j];
            }
            fout_text << std::endl;
```

```
        }
        fout_text.close();
    } else {
        std::cerr << "无法打开文本文件进行写入。" << std::endl;
        return 1;
    }


    // (b) 将矩阵 A 写入到二进制文件 fout01.dat 中
    std::ofstream fout_binary("fout01.dat", std::ios::binary);
    if (fout_binary.is_open()) {
        for (int i = 0; i < sizeA; ++i) {
            for (int j = 0; j < sizeA; ++j) {
                fout_binary.write(reinterpret_cast<const char*>(&A[i][j]), sizeof(A[i][j]));
            }
        }
        fout_binary.close();
    } else {
        std::cerr << "无法打开二进制文件进行写入。" << std::endl;
        return 1;
    }

    // (c) 从文件 fout01.dat 中读取前 24 个数据，构成 4x6 的矩阵 B，并按行输出
    double B[sizeB_rows][sizeB_cols];
    std::ifstream fin_binary("fout01.dat", std::ios::binary);
    if (fin_binary.is_open()) {
        for (int i = 0; i < sizeB_rows; ++i) {
            for (int j = 0; j < sizeB_cols; ++j) {
                fin_binary.read(reinterpret_cast<char*>(&B[i][j]), sizeof(B[i][j]));
            }
        }
        fin_binary.close();

        // 按行输出矩阵 B
        for (int i = 0; i < sizeB_rows; ++i) {
            for (int j = 0; j < sizeB_cols; ++j) {
                std::cout << std::setw(10) << std::setprecision(6) << std::fixed << B[i][j];
            }
            std::cout << std::endl;
        }
    } else {
        std::cerr << "无法打开二进制文件进行读取。" << std::endl;
        return 1;
    }
```

```
    return 0;
}
```

运行结果：



fout01.txt

```
0.556663  0.899408  0.537350  0.815464  0.725507  0.724424  0.240990  0.043318
0.469036  0.886588  0.282324  0.259881  0.368188  0.457031  0.411413  0.195498
0.369367  0.141259  0.588504  0.714631  0.238929  0.494382  0.579586  0.934149
0.241826  0.660199  0.431683  0.704183  0.013360  0.982942  0.410704  0.570023
0.882349  0.948054  0.385487  0.607856  0.672478  0.626477  0.651174  0.141515
0.513064  0.933498  0.401395  0.881252  0.390529  0.812808  0.076751  0.759896
0.954067  0.665255  0.474527  0.192996  0.159636  0.054114  0.127145  0.401462
0.714313  0.558829  0.105645  0.727673  0.541770  0.516349  0.297696  0.424120
```

```
0.556663  0.899408  0.537350  0.815464  0.725507  0.724424
0.240990  0.043318  0.469036  0.886588  0.282324  0.259881
0.368188  0.457031  0.411413  0.195498  0.369367  0.141259
0.588504  0.714631  0.238929  0.494382  0.579586  0.934149
```

第五题 （DEBUG 文档 - 作业完成过程记录）

第 1 题 - 抽象基类 Container 与派生类

1. 遇到的问题：

初次接触 UML 图，绘制不熟练。

纯虚函数的理解和应用不够深入。

动态多态的实现方式不够清晰。

2. 解决方法：

查阅 UML 图的相关资料，学习如何绘制类图。

通过阅读相关书籍和在线资源，深入理解纯虚函数和抽象基类的概念。

通过实践，尝试使用基类指针指向派生类对象，调用虚函数实现动态多态。

3. 思考感悟：

UML 图是理解和设计类结构的重要工具。

纯虚函数为派生类提供了必须实现的接口，确保了基类与派生类之间的契约。

动态多态是面向对象编程中的重要特性，通过基类指针或引用可以实现不同派生类对象之间的通用操作。

第 2 题 - 矩阵类 Matrix 与模板机制

1. 遇到的问题：

矩阵类的设计较为复杂，需要考虑多个成员函数和运算符重载。

模板机制的使用不够熟练。

复数矩阵的运算规则与实数矩阵有所不同，需要特别注意。

2. 解决方法：

分步骤设计矩阵类，先实现基本的构造函数、析构函数和运算符重载，再逐步添加其他功能。

通过查阅资料和在线学习，熟悉模板机制的使用。

针对复数矩阵，查阅相关资料，了解其运算规则，并在模板类中实现相应的运算。

3 思考感悟：

矩阵类的设计需要细致考虑，确保每个成员函数和运算符重载都能正确实现。

模板机制为代码的复用和扩展提供了强大的支持。

复数矩阵的运算需要特别注意其运算规则，避免出错。

第 3 题 - 学生信息类 Student 与文件解析

1. 遇到的问题：

文件解析的复杂性较高，需要处理多种数据格式。

静态成员变量的理解和应用不够深入。

格式化输出的实现方式不够清晰。

2. 解决方法：

查阅相关资料，学习文件解析的基本方法和技巧。

通过实践，深入理解静态成员变量的概念和用法。

通过查阅资料和在线学习，学习如何实现格式化输出。

3. 思考感悟：

文件解析需要细致处理，确保数据的准确性和完整性。

静态成员变量为类提供了全局性的数据共享和存储。

格式化输出可以提高程序的可读性和易用性。

第 4 题 - 文件流操作与矩阵生成

1.遇到的问题：

文件流操作不够熟练，容易出错。

矩阵生成和读取的逻辑需要仔细设计。

二进制文件的读写规则与文本文件有所不同，需要特别注意。

2.解决方法：

通过查阅资料和在线学习，熟悉文件流操作的基本方法和技巧。

仔细设计矩阵生成和读取的逻辑，确保数据的正确性和完整性。

针对二进制文件，查阅相关资料，了解其读写规则，并在程序中正确实现。

3.思考感悟：

文件流操作是C++编程中的重要部分，需要熟练掌握。

矩阵的生成和读取需要仔细设计逻辑，确保数据的准确性。

二进制文件的读写需要特别注意其规则，避免出错。同时，二进制文件的读写效率通常比文本文件更高。

第六题

1. **作用/含义**:typedef void(*Fun)(void)；定义了一个名为 Fun 的类型，它是一个指向返回类型为 void 且无参数函数的指针类型。

帮助：typedef 在编程实践中非常有用，它可以帮助我们简化复杂类型声明的语法，提高代码的可读性和可维护性。例如，在需要频繁使用某种复杂类型时，使用 typedef 定义一个更简洁的类型名称，可以使代码更加清晰易懂。

2.1&b 获取了对象 b 的地址。

2.2(int*)(&b) 将对象 b 的地址强制转换为 int* 类型，即一个指向整数的指针。这里实际上是一种不安全的类型转换，因为对象 b 的地址并不应该直接解释为整数指针。不过，在这个上下文中，它是为了访问虚函数表（vtable）而进行的低级操作。

2.3*(int*)(&b) 对 (int*)(&b) 进行解引用，得到的是一个整数（实际上是一个地址，但这里被当作整数处理）。然而，这个操作在逻辑上是不正确的，因为我们并没有意图获取一个整数，而是想访问虚函数表的指针。这里的转换应该被理解为一种低级的、不安全的访问方式，实际上应该使用更合适的类型（如 intptr_t* 或类似的指针类型）来表示虚函数表指针的地址。

2.4 这个操作试图再次将 (int*)(&b) 的结果解引用为 int* 类型，但这样的操作是不正确的。实际上，它应该被看作是对虚函数表指针地址的进一步错误处理。正确的做法应该是使用合适的指针类型来访问虚函数表指针。

2.5 这个操作试图将 (int *)*(int*)(&b) 的结果（实际上是一个错误地处理的地址）转换为 Fun 类型，即一个函数指针类型，然后调用这个函数指针。然而，由于前面的类型转换和处理都是错误的，这个操作也是不正确的。正确的做法应该是使用合适的指针类型来访问虚函数表中的函数指针，并正确地调用它们。

3. 感觉上述操作并不能正确地达成预期效果。由于使用了错误的类型转换和访问方式，这些操作是未定义行为可能会导致程序崩溃、数据损坏或其他不可预测的结果。

4. 要通过虚指针调用 Base::setVar() 函数，你可以使用基类指针指向派生类对象，并调用该指针上的 setVar() 方法。由于 setVar() 是虚函数，所以调用时将会根据对象的实际类型（即指向的派生类对象）来调用相应的函数实现。

5. 是的，可以通过虚函数指针调用 Base 类中的 display 函数，但这需要你对虚函数表有深入的了解，并且使用不安全的类型转换来访问虚函数表中的函数指针。然而，这种做法是不推荐的，因为它破坏了 C++ 的类型安全机制，并且容易导致程序崩溃或未定义行为。正确的做法是使用基类指针或引用来调用虚函数。

6. **存储分区：**在 C++中，类的虚函数表通常存储在数据段（data segment）或只读数据段（read-only data segment）中，具体取决于编译器的实现和链接器的设置。虚函数表包含了指向类虚函数的指针，这些指针在程序启动时就已经确定，并且在程序的整个生命周期内保持不变。

验证方法：要验证虚函数表存储在哪个内存分区，你可以使用调试器（如 GDB）来检查对象的内存布局和虚函数表指针的地址。然后，你可以使用操作系统的工具（如 pmap、vmmap 或类似的工具）来查看这些地址对应的内存分区。然而，这种方法需要深入的调试和内存分析技能，并且可能因编译器和操作系统的不同而有所差异。因此，这种方法通常用于底层系统编程或编译器开发的上下文中。在一般的 C++编程实践中，我们不需要关心虚函数表的具体存储位置。