
Algorithm 2 User questions generation.**Input:** seed S , conversation plan p , number of questions per iteration I , generator G **Output:** Question set Q

```
1:  $p \leftarrow \{p_1, \dots, p_N\}$  ▷ Conversation plan with  $N$  sub-plans
2:  $Q \leftarrow \{\}$  ▷ Initialize empty question set
3: for each  $p_i \in P$  do
4:    $p_i = \{p_{i1}, \dots, p_{iK}\}$ 
5:   for each  $p_{ij} \in p_i$  do
6:      $Q_{ij} \leftarrow G(S, p_{ij}, \{p_{i1}, \dots, p_{i(j-1)}\}, \{p_1, \dots, p_{i-1}\}, I)$  ▷ Generate  $I$  questions using Listing 32
7:      $Q \leftarrow Q \cup \{Q_{ij}\}$  ▷ Append generated questions to the question set
8:   end for
9: end for
10: return  $Q$ 
```

Algorithm 3 Answer generation.**Input:** question set $Q = \{Q_1, \dots, Q_N\}$, seed S , conversation plan set P , thresholds δ_1, δ_2 , assistant-question detector ϕ , follow-up detector ψ , generator G **Output:** conversation list T

```
1:  $\mathcal{T} \leftarrow \{\}$  ▷ Initialize empty conversation list
2: for each  $Q_i \in Q$  do
3:    $Q_i = \{q_1, \dots, q_J\}$  ▷ Questions in sub-plan  $i$ 
4:   for each  $q_j \in Q_i$  do
5:      $t \leftarrow \{\}$  ▷ Initialize turn sequence
6:      $H_t^{(M)} \leftarrow$  recent- $M$  turn window at turn  $t$ 
7:      $\overline{H}_t \leftarrow$  summary of turns prior to  $H_t^{(M)}$ 
8:      $\overline{P}^{(<p)} \leftarrow$  summaries of conversation plans preceding  $p$ 
9:      $a_{ij} \leftarrow G_{\text{assistant}}(S, p_{1:(i-1)}, H_t^{(M)}, \overline{H}_t, \overline{P}^{(<p)})$  ▷ Generate assistant response with Listing 37
10:     $t \leftarrow t \cup \{a_{ij}\}$  ▷ Add assistant's response to current dialogues turn
11:     $isQ \leftarrow \phi(a_{ij}, H_t^{(M)}, \overline{H}_t)$  ▷ Checks if assistant response contains question from user with Listing 35
12:     $count \leftarrow 0$ 
13:    while  $isQ$  and  $count < \delta_1$  do
14:       $u_{ij} \leftarrow G_{\text{user}}(S, p_i, p_{1:(i-1)}, \overline{P}^{(<p)}, H_t^{(M)}, \overline{H}_t, a_{ij})$  ▷ Generate user's response to assistant question with Listing 38
15:       $t \leftarrow t \cup \{u_{ij}\}$  ▷ Add user's response to current dialogues turn
16:       $a_{ij} \leftarrow G_{\text{assistant}}(S, p_{1:(i-1)}, H_t^{(M)}, \overline{H}_t, \overline{P}^{(<p)})$  ▷ Generate assistant's response
17:       $t \leftarrow t \cup \{a_{ij}\}$  ▷ Add assistant's response to current dialogues turn
18:       $count \leftarrow count + 1$ 
19:       $isQ \leftarrow \phi(a_{ij}, H_t^{(M)}, \overline{H}_t)$ 
20:    end while
21:     $needFU \leftarrow \psi(a_{ij}, H_t^{(M)}, \overline{H}_t, S)$  ▷ Checks if user need to ask followup question with Listing 36
22:     $fu\_count \leftarrow 0$ 
23:    while  $needFU$  and  $fu\_count < \delta_2$  do
24:       $u_{ij} \leftarrow G_{\text{user}}(S, p_i, p_{1:(i-1)}, \overline{P}^{(<p)}, H_t^{(M)}, \overline{H}_t, a_{ij})$  ▷ Generate user's followup question with Listing 39
25:       $t \leftarrow t \cup \{u_{ij}\}$ 
26:       $a_{ij} \leftarrow G_{\text{assistant}}(S, p_{1:(i-1)}, H_t^{(M)}, \overline{H}_t, \overline{P}^{(<p)})$  ▷ Generate assistant's response to user's followup question
27:       $t \leftarrow t \cup \{a_{ij}\}$ 
28:       $fu\_count \leftarrow fu\_count + 1$ 
29:       $needFU \leftarrow \psi(a_{ij}, H_t^{(M)}, \overline{H}_t, S)$ 
30:    end while
31:     $\mathcal{T} \leftarrow \mathcal{T} \cup \{t\}$ 
32:  end for
33: end for
34: return  $T$ 
```
